



VC9101

Split-type Camera System

5MP, H.265, 30fps, Face Check, 3DNR, SNV

Technical Specifications

Specifications - Video Core

Model	VC9101
System Information	
CPU	Multimedia SoC (System-on-Chip)
Flash	8 GB
RAM	2 GB
On-board Storage	Seamless Recording to MicroSD/SDHC/SDXC card (1TB capacity supported) and recording to network-attached storage (NAS)
Video	
Compression	H.265, H.264, MJPEG
Video Source	1 VIVOTEK camera unit
Maximum Streams	3 video streams (Up to 8 configurable profiles)
Video Streaming	Adjustable resolution, quality and constant bit rate control, Smart Stream III
Image Settings	General settings: video title and time stamp overlay, video orientation (flip, mirror, rotation (CU9171-H(F) only)); Image settings: white balance, image adjustment (brightness, contrast, saturation, sharpness, gamma curve (CU9171-H(F) only)), defog, 3DNR, HLM, scene mode (auto, deblur); Exposure: BLC, HLC, exposure control (exposure level, exposure time, gain control) AE speed adjustment, WDR; Privacy mask; Pixel calculator
Display Mode	Client dewarping (CU9183-H(F) only) Ceiling mounted: 1O Fisheye, 1P Panoramic, 2P Two Panoramic, 1R One Region, 4R Four Regions, 1O3R One Fisheye Three Regions, 1O8R One Fisheye Eight Regions Wall mounted: 1O Fisheye, 1P Panoramic, 1R One Region, 4R Four Regions, 1P2R One Panoramic Two Regions, 1P3R One Panoramic Three Regions, 1O3R, One Fisheye Three Regions Local dewarping (CU9183-H(F) only) Ceiling mounted: 1O Fisheye, 1P Panoramic, 2P Two Panoramic, 1R One Region, 4R Four Regions Wall mounted: 1O Fisheye, 1P Panoramic, 1R One Region, 4R Four Regions
Audio	
Audio Capability	Two-Way Audio (full duplex)



Compression	G.711, G.726
Interface	External microphone input External line output

Network

Users	Live viewing for up to 10 clients
Security	Access list, digest authentication, HTTPS, IEEE 802.1x, Password protection, secure boot, signed firmware, Trend Micro IoT Security (brute force attack event, cyberattack event, quarantine event), user access log, user account management, CSRF protection
Protocols	802.1X, ARP, Bonjour, CIFS/SMB, CoS, DDNS, DHCP, DNS, FTP/SFTP, HTTP, HTTPS, ICMP, IGMPv3, IPv4, IPv6, NTP, PPPoE, QoS, RTSP/RTP/RTCP, SMTP, SNMP, SSL, TCP/IP, TLS, UDP, UPnP
Interface	10 Base-T/100 Base-TX Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard.
ONVIF	Profile G, S, T supported, specification available at www.onvif.org

Solution Integration

Smart Motion Detection	Five-window video motion detection, face detection, time filter
------------------------	---

Alarm and Event

Alarm Triggers	Audio detection, camera tampering detection, cybersecurity events (brute force attack event, cyberattack event, quarantine event), digital input, manual trigger, motion detection, periodical trigger, recording notification, SD card life expectancy, system boot
Alarm Events	Event notification via audio clip, camera link, digital output, email, HTTP, FTP/SFTP, NAS server, SD card, push notification File upload via email, HTTP, FTP/SFTP, NAS server, SD card

General

Connectors	RJ-45 cable connector for 10/100Mbps Network/PoE connection Audio line input Audio line output DC 12V power input Digital input *1 Digital output *1 (DO+: 12V, 50mA; DO-: 30V, Open Drain, 1A)
LED Indicator	System power and status indicator
Power Input	DC 12V, IEEE 802.3af PoE Class 0 Simultaneous Power Redundancy Supported
Power Consumption	Max. 8.5 W
Dimensions	105 (W) x 84 (D) x 30 (H) mm
Weight	190 g
Safety Certifications	EMC: CE (EN55032, EN55024 Class B), FCC (FCC Part 15 Subpart B Class B), RCM (AS/NZS CISPR32 Class B), VCCI (VCCI-CISPR 32 Class B); Safety: UL (UL62368-1), CB (IEC/EN 62368-1); Environment: IA: BSMI (EMC: CNS 13438, Safety: CNS 14336-1)
Operating Temperature	Starting Temperature: 0°C ~ 50°C (32°F ~ 122°F) Working Temperature: -10°C ~ 50°C (14°F ~ 122°F)
Humidity	90% RH (non-condensing)

System Requirements

Operating System	Microsoft Windows 10/8/7 Mac 10.12 (Chrome only)
Web Browser	Chrome 58.0 or above Internet Explorer 10/11
Other Players	VLC: 1.1.11 or above

Included Accessories

Packing Contents	Quick installation guide, installation kit
------------------	--

Specifications - Camera Unit

Model	CU9171-H(F): Pinhole
Image Sensor	1/2.7" Progressive CMOS
Maximum Resolution	30 fps @ 2688x1520
Focal Length	f = 3.7 mm



Aperture	F2.5
Field of View	93° (Horizontal) 48° (Vertical) 117° (Diagonal)
Shutter Time	1/5 sec. to 1/32,000 sec.
WDR Technology	WDR Pro
Minimum Illumination	0.045 lux @ F2.5 (Color)
Pan/Tilt/Zoom Functionalities	ePTZ: 48x digital zoom (4x on IE plug-in, 12x built-in)
S/N Ratio	55.9 dB
Dynamic Range	120 dB
Dimensions	CU9171-H: Ø 24 x 30 mm (Without cable) CU9171-HF: 33 x 32 x 20 mm (Without cable)
Weight	CU9171-H: 19g CU9171-HF: 43g
Operating Temperature	Starting Temperature: 0°C ~ 50°C (32°F ~ 122°F) Working Temperature: -10°C ~ 50°C (14°F ~ 122°F)
Humidity	90% RH (non-condensing)

Specifications - Camera Unit

Model	CU9183-H(F): Fisheye Camera
Image Sensor	1/2.7" Progressive CMOS
Maximum Resolution	30 fps @ 1920x1920
Focal Length	f = 1.22 mm
Aperture	F2.0
Field of View	180° (Horizontal) 180° (Vertical) 180° (Diagonal)
Shutter Time	1/5 sec. to 1/32,000 sec.
WDR Technology	WDR Pro
Minimum Illumination	0.035 lux @ F2.0 (Color)
Pan/Tilt/Zoom Functionalities	ePTZ: 48x digital zoom (4x on IE plug-in, 12x built in)
S/N Ratio	56.3 dB
Dynamic Range	120 dB
Dimensions	CU9183-H: Ø 24 x 37 mm (Without cable) CU9183-HF: 33 x 32 x 28 mm (Without cable)
Weight	CU9183-H: 28g CU9183-HF: 52g
Operating Temperature	Starting Temperature: 0°C ~ 50°C (32°F ~ 122°F) Working Temperature: -10°C ~ 50°C (14°F ~ 122°F)
Humidity	90% RH (non-condensing)

DORI (EN 62676-4 Standard)

Detect (25PPM/ 8PPF)	CU9171-H(F): 77 m (252.6 ft) CU9183-H(F): 24.3 m (79.7 ft)
Observe (63PPM/ 19PPF)	CU9171-H(F): 30.5 m (100.1 ft) CU9183-H(F): 9.6 m (31.5 ft)
Recognize (125PPM/ 38PPF)	CU9171-H(F): 15.4 m (50.5 ft) CU9183-H(F): 4.8 m (15.7 ft)
Identify (250PPM/ 76PPF)	CU9171-H(F): 7.7 m (25.3 ft) CU9183-H(F): 2.4 m (7.9 ft)

