

## CE EMC Test Report

**Report No.:** CE181017D21

**Test Model:** FD9187-H

**Series Model:** FD9187-HT

**Received Date:** Oct. 17, 2018

**Test Date:** Oct. 19 ~ Nov. 15, 2018

**Issued Date:** Nov. 16, 2018

**Applicant:** VIVOTEK INC.

**Address:** 6F, No.192, Lien-Cheng Rd., Chung-Ho , New Taipei City, 235, Taiwan, R.O.C.

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the U.S. government. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

<b>Release Control Record</b> .....	<b>5</b>
<b>1 Certificate of Conformity</b> .....	<b>6</b>
<b>2 Summary of Test Results</b> .....	<b>7</b>
2.1 Measurement Uncertainty.....	8
2.2 Modification Record.....	8
<b>3 General Information</b> .....	<b>9</b>
3.1 Description of EUT.....	9
3.2 Features of EUT.....	9
3.3 Operating Modes of EUT and Determination of Worst Case Operating Mode.....	10
3.4 Test Program Used and Operation Descriptions.....	11
3.5 Primary Clock Frequencies of Internal Source.....	11
<b>4 Configuration and Connections with EUT</b> .....	<b>12</b>
4.1 Connection Diagram of EUT and Peripheral Devices.....	12
4.2 Configuration of Peripheral Devices and Cable Connections.....	14
<b>5 Conducted Emission from the AC Mains Power Port</b> .....	<b>15</b>
5.1 Limits.....	15
<b>6 Test Instruments</b> .....	<b>15</b>
6.1 Test Arrangement.....	16
6.2 Test Results.....	17
<b>7 Asymmetric Mode Conducted Emission at Telecommunication Ports</b> .....	<b>21</b>
7.1 Limits.....	21
7.2 Test Instruments.....	22
7.3 Test Arrangement.....	23
7.4 Test Results.....	24
<b>8 Radiated Emission at Frequencies up to 1GHz</b> .....	<b>26</b>
8.1 Limits.....	26
8.2 Test Instruments.....	27
8.3 Test Arrangement.....	28
8.4 Test Results.....	29
<b>9 Radiated Emission at Frequencies above 1GHz</b> .....	<b>33</b>
9.1 Limits.....	33
9.2 Test Instruments.....	34
9.3 Test Arrangement.....	35
9.4 Test Results.....	36
<b>10 Harmonics Current Measurement</b> .....	<b>40</b>
10.1 Limits.....	40
10.2 Classification of Equipment.....	40
10.3 Test Instruments.....	41
10.4 Test Arrangement.....	41
10.5 Test Results.....	41

<b>11</b>	<b>Voltage Fluctuations and Flicker Measurement .....</b>	<b>42</b>
11.1	Limits .....	42
11.2	Test Instruments .....	42
11.3	Test Arrangement .....	42
11.4	Test Results .....	43
<b>12</b>	<b>General Immunity Requirements.....</b>	<b>44</b>
12.1	Performance Criteria .....	45
<b>13</b>	<b>Electrostatic Discharge Immunity Test (ESD).....</b>	<b>46</b>
13.1	Test Specification.....	46
13.2	Test Instruments .....	46
13.3	Test Arrangement .....	46
13.4	Test Results .....	48
<b>14</b>	<b>Radiated, Radio-frequency, Electromagnetic Field Immunity Test (RS) .....</b>	<b>55</b>
14.1	Test Specification.....	55
14.2	Test Instruments .....	55
14.3	Test Arrangement .....	56
14.4	Test Results .....	57
<b>15</b>	<b>Electrical Fast Transient/Burst Immunity Test (EFT).....</b>	<b>58</b>
15.1	Test Specification.....	58
15.2	Test Instruments .....	58
15.3	Test Arrangement .....	59
15.4	Test Results .....	60
<b>16</b>	<b>Surge Immunity Test.....</b>	<b>61</b>
16.1	Test Specification.....	61
16.2	Test Instruments .....	61
16.3	Test Arrangement .....	62
16.4	Test Results .....	63
<b>17</b>	<b>Immunity to Conducted Disturbances Induced by RF Fields (CS).....</b>	<b>64</b>
17.1	Test Specification.....	64
17.2	Test Instruments .....	64
17.3	Test Arrangement .....	65
17.4	Test Results .....	66
<b>18</b>	<b>Power Frequency Magnetic Field Immunity Test.....</b>	<b>67</b>
18.1	Test Specification.....	67
18.2	Test Instruments .....	67
18.3	Test Arrangement .....	67
18.4	Test Results .....	68
<b>19</b>	<b>Voltage Dips and Interruptions .....</b>	<b>69</b>
19.1	Test Specification.....	69
19.2	Test Instruments .....	69
19.3	Test Arrangement .....	69
19.4	Test Results .....	70

<b>20 Pictures of Test Arrangements .....</b>	<b>71</b>
20.1 Conducted Emission from the AC Mains Power Port.....	71
20.2 Asymmetric Mode Conducted Emission at Telecommunication Ports .....	72
20.3 Radiated Emission at Frequencies up to 1GHz .....	74
20.4 Radiated Emission at Frequencies above 1GHz .....	76
20.5 Harmonics Current, Voltage Fluctuations and Flicker Measurement.....	78
20.6 Electrostatic Discharge Immunity Test (ESD) .....	79
20.7 Radio-frequency, Electromagnetic Field Immunity Test (RS).....	80
20.8 Electrical Fast Transient/Burst Immunity Test (EFT) .....	82
20.9 Surge Immunity Test.....	84
20.10 Conducted Disturbances Induced by RF Fields (CS) .....	85
20.11 Power Frequency Magnetic Field Immunity Test (PFMF) .....	87
20.12 Voltage Dips and Interruptions .....	88
<b>Appendix – Information on the Testing Laboratories .....</b>	<b>89</b>

### Release Control Record

Issue No.	Description	Date Issued
CE181017D21	Original release.	Nov. 16, 2018

## 1 Certificate of Conformity

**Product:** Network Camera  
**Brand:** VIVOTEK  
**Test Model:** FD9187-H  
**Series Model:** FD9187-HT  
**Sample Status:** ENGINEERING SAMPLE  
**Applicant:** VIVOTEK INC.  
**Test Date:** Oct. 19 ~ Nov. 15, 2018  
**Standards:** **EN 55032:2015 +AC:2016, Class B**  
**CISPR 32:2015 +Cor 1:2016, Class B**  
**AS/NZS CISPR 32:2015, Class B**  
**EN 61000-3-2:2014**  
**EN 61000-3-3:2013**  
**EN 55024:2010 / EN55024:2010 +A1:2015**  
EN 61000-4-2:2009 / IEC 61000-4-2:2008 ED. 2.0  
EN 61000-4-3:2006 +A1:2008 +A2:2010 / IEC 61000-4-3:2010 ED. 3.2  
EN 61000-4-4:2012 / IEC 61000-4-4:2012 ED. 3.0  
EN 61000-4-5:2014 / IEC 61000-4-5:2014 ED. 3.0  
EN 61000-4-6:2014 / IEC 61000-4-6:2013 ED. 4.0  
EN 61000-4-8:2010 / IEC 61000-4-8:2009 ED. 2.0  
EN 61000-4-11:2004 / IEC 61000-4-11:2004 ED. 2.0

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :** Sandra Lin , **Date:** Nov. 16, 2018  
Sandra Lin / Specialist

**Approved by :** Jim Hsiang , **Date:** Nov. 16, 2018  
Jim Hsiang / Associate Technical Manager

## 2 Summary of Test Results

Emission			
Standard	Test Item	Result/Remarks	Verdict
EN 55032:2015 +AC:2016/ CISPR 32:2015 +Cor 1:2016/ AS/NZS CISPR 32:2015	Conducted emission from the AC mains power port	Minimum passing Class B margin is -14.85 dB at 0.37287 MHz	Pass
	Asymmetric mode conducted emission at telecommunication ports	Minimum passing Class B margin is -3.22 dB at 1.48923 MHz	Pass
	Radiated emission 30-1000 MHz	Minimum passing Class B margin is -3.72 dB at 168.01 MHz	Pass
	Radiated emission above 1GHz	Minimum passing Class B margin is -12.24 dB at 2159.98 MHz	Pass
EN 61000-3-2:2014	Harmonic current emissions	The power consumption of EUT is less than 75W and no limits apply.	Pass
EN 61000-3-3:2013	Voltage fluctuations and flicker	$P_{st} \leq 1.0$ $d_{max} \leq 4\%$ $P_{lt} \leq 0.65$ $d_c \leq 3.3\%$ $T_{max} \leq 500ms$	Pass

Immunity				
EN 55024 Clause	Basic standard	Test Item	Result/Remarks	Verdict
4.2.1	EN 61000-4-2:2009 / IEC 61000-4-2:2008 ED. 2.0	Electrostatic discharges (ESD)	Performance Criterion B	Pass
4.2.3.2	EN 61000-4-3:2006 +A1:2008 +A2:2010 / IEC 61000-4-3:2010 ED. 3.2	Continuous radiated disturbances (RS)	Performance Criterion A	Pass
4.2.2	EN 61000-4-4:2012 / IEC 61000-4-4:2012 ED. 3.0	Electrical fast transients (EFT)	Performance Criterion B	Pass
4.2.5	EN 61000-4-5:2014 / IEC 61000-4-5:2014 ED. 3.0	Surges	Performance Criterion A	Pass
4.2.3.3	EN 61000-4-6:2014 / IEC 61000-4-6:2013 ED. 4.0	Continuous conducted disturbances (CS)	Performance Criterion A	Pass
4.2.4	EN 61000-4-8:2010 / IEC 61000-4-8:2009 ED. 2.0	Power-frequency magnetic fields (PFMF)	Performance Criterion A	Pass
4.2.6	EN 61000-4-11:2004 / IEC 61000-4-11:2004 ED. 2.0	Voltage dips and interruptions	Voltage Dips: >95% reduction – 0.5 period, Performance Criterion A 30% reduction – 25 periods, Performance Criterion A Voltage Interruptions: >95% reduction – 250 periods, Performance Criterion B	Pass

**Note:**

1. There is no deviation to the applied test methods and requirements covered by the scope of this report.
2. The above EN/IEC basic standards are applied with latest version if customer has no special requirement.

## 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement	Expanded Uncertainty (k=2) ( $\pm$ )	Maximum allowable uncertainty ( $\pm$ )
Conducted emission from AC mains power port using AMN, 150kHz ~ 30MHz	2.79 dB	3.4 dB ( $U_{\text{cispr}}$ )
Asymmetric mode conducted emission using AAN, 150kHz ~ 30MHz	3.94 dB	5.0 dB ( $U_{\text{cispr}}$ )
Radiated emission, 30MHz ~ 1GHz	3.97 dB	6.3 dB ( $U_{\text{cispr}}$ )
Radiated emission, 1GHz ~ 6GHz	5.08 dB	5.2 dB ( $U_{\text{cispr}}$ )

## 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 Description of EUT

Product	Network Camera
Brand	VIVOTEK
Test Model	FD9187-H
Series Model	FD9187-HT
Model Difference	Refer to note as below
Sample Status	Engineering sample
Operating Software	N/A
Power Supply Rating	Brand: HONOTO Model: ADS-26FSG-12 12018EPCU Input Power: 100-240Vac, 50/60Hz, 0.7A Output Power: 12V, 1A Power cord: AC 2 Pin Non- Shielding DC cable (3.0m)
Accessory Device	Adapter
Data Cable Supplied	N/A

**Note:**

The EUT is a Network Camera and it has two models, which are identical to each other except for zoom focus only, as follows:

Model	Difference
FD9187-H	Without Zoom Focus
FD9187-HT	With Zoom Focus

During the test, the Model: **FD9187-H** was selected as the representative one for the test and therefore only its test data were recorded in this report.

### 3.2 Features of EUT

The tests reported herein were performed according to the method specified by VIVOTEK INC., for detailed feature description, please refer to the manufacturer's specifications or user's manual.

### 3.3 Operating Modes of EUT and Determination of Worst Case Operating Mode

1. The EUT was pre-tested under operating and standby condition and the worst emission level was found under **operating condition**.
2. The EUT consumes power from Adapter, which designed with AC power supply of rating 100-240Vac, 50/60Hz. For radiated emission evaluation, 230Vac/50Hz (for EN 55032 & AS/NZS CISPR 32), 120Vac/60Hz (for FCC Part 15), 100Vac/50Hz & 100Vac/60Hz (for VCCI) had been covered during the pre-test. The worst radiated emission data was found at **230Vac/50Hz** and recorded in the applied test report.
3. EUT has been pre-tested under following test modes, and test **mode 1** was the worst case for final test.

Mode	Test Condition
1	LAN 100Mbps + Adapter
2	LAN 10Mbps + Adapter
3	LAN 100Mbps + PoE

4. Test modes are presented in the report as below.

Mode	Test Condition	Input power
<b>Conducted emission test</b>		
1	Power from Adapter	230Vac/50Hz & 110Vac/60Hz
<b>Asymmetric Mode Conducted Emission at Telecommunication Ports test</b>		
1	Power from Adapter (LAN Speed: 100Mbps)	230Vac/50Hz
2	Power from PoE Adapter (LAN Speed: 100Mbps)	48Vdc

The idle mode of conducted emission test at telecom port was pre-tested based on the worst case of link mode. Due to emissions of idle mode being very low compared to link mode, only the link mode data were presented in the test report.

<b>Radiated emission test</b>		
1	Power from Adapter	230Vac/50Hz
2	Power from PoE Adapter	48Vdc
<b>Harmonics, Flicker, DIP &amp; Surge tests</b>		
1	Power from Adapter	230Vac/ 50Hz
<b>Immunity tests &lt;DIP &amp; Surge tests excluded&gt;</b>		
1	Power from Adapter	230Vac/ 50Hz
2	Power from PoE Switch	

### 3.4 Test Program Used and Operation Descriptions

#### ◆ For Emission tests:

- a. Connected the EUT with Adapter or PoE adapter.
- b. Turned on the power of all equipment.
- c. EUT captured video / audio signal to notebook (kept in a remote area) via an UTP LAN cable, then it displayed messages on its screen. **<For Power from Adapter>**
- d. EUT captured video / audio signal to notebook (kept in a remote area) via PoE by an UTP LAN cable, then it displayed messages on its screen. **<For Power from PoE Adapter>**
- e. EUT Save images to SD card.
- f. EUT sent 1kHz audio signal to earphone.
- g. Steps c-f were repeated.

#### ◆ For Harmonics, Flicker, Immunity tests:

- a. Connected the EUT with Adapter or PoE switch.
- b. Turned on the power of all equipment.
- c. EUT captured video / audio signal to notebook (kept in a remote area) via an UTP LAN cable, then it displayed messages on its screen simultaneously. **<For Power from Adapter>**
- d. EUT captured video / audio signal to notebook (kept in a remote area) via PoE switch with an UTP LAN cable, then it displayed messages on its screen simultaneously. **<For Power from PoE Switch >**
- e. EUT sent audio signal to speaker.
- f. EUT Save images to SD card.
- g. Steps c-f were repeated.



### 3.5 Primary Clock Frequencies of Internal Source

The highest frequency generated or used within the EUT or on which the EUT operates or tunes is 1866MHz, provided by VIVOTEK INC, for detailed internal source, please refer to the manufacturer's specifications.



#### 4 Configuration and Connections with EUT

##### 4.1 Connection Diagram of EUT and Peripheral Devices

Emission tests:



Harmonics, Flicker, Immunity tests:



## 4.2 Configuration of Peripheral Devices and Cable Connections

### Emission tests:

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Earphone	PHILIPS	SBC HL150	H2010149	N/A	Provided by Lab
B.	Microphone	Labtec	mic-333	N/A	N/A	Provided by Lab
C.	SD Card	Apacer	8GN	N/A	N/A	Provided by Lab
D.	Notebook	DELL	PP27L	8SNZ12S	FCC DoC Approved	Provided by Lab
E.	PoE Adapter	PSE	PSE151	N/A	FCC DoC Approved	Provided by Lab

### Note:

- All power cords of the above support units are non-shielded (1.8m).
- Items D-E acted as communication partners to transfer data.
- Rating of item E was listed as below:  
AC I/P: 100-240V, 50/60Hz, 0.4A  
DC O/P: 48V, 16W

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	DC power cable	1	3.0	N	0	Supplied by client
2.	Audio cable	1	1.2	N	0	Provided by Lab
3.	Audio cable	1	1.8	N	0	Provided by Lab
4.	LAN cable (Cat.5e)	1	10	N	0	Provided by Lab
5.	LAN cable (Cat.5e)	1	1.5	N	0	Provided by Lab
6.	I/O cable	4	1.0	N	0	Supplied by client

Note: The core(s) is(are) originally attached to the cable(s).

### Harmonics, Flicker, Immunity tests:

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Speaker	N/A	N/A	N/A	N/A	Provided by Lab
B.	Microphone	N/A	N/A	N/A	N/A	Provided by Lab
C.	SD Card	Apacer	8GN	N/A	N/A	Provided by Lab
D.	Notebook PC	LENOVO	TP00057A	R9-0JMLFS16/01	N/A	Provided by Lab
E.	PoE Switch	ASUS	GP-108	N/A	N/A	Provided by Lab

### Note:

- All power cords of the above support units are non-shielded (1.8m).
- Items D-E acted as communication partners to transfer data.

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	DC power cable	1	3.0	N	0	Supplied by client
2.	Audio cable	1	1.2	N	0	Provided by Lab
3.	Audio cable	1	1.1	N	0	Provided by Lab
4.	LAN cable (Cat.5e)	1	10	N	0	Provided by Lab
5.	LAN cable (Cat.5e)	1	10	N	0	Provided by Lab
6.	I/O cable	4	1.0	N	0	Supplied by client

Note: The core(s) is(are) originally attached to the cable(s).

## 5 Conducted Emission from the AC Mains Power Port

### 5.1 Limits

Frequency range (MHz)	Coupling device	Detector type / bandwidth	Class A limits (dBuV)
0.15 - 0.5	AMN	Quasi-peak / 9kHz	79
0.5 - 30.0			73
0.15 - 0.5		Average / 9kHz	66
0.5 - 30.0			60

Frequency range (MHz)	Coupling device	Detector type / bandwidth	Class B limits (dBuV)
0.15 - 0.5	AMN	Quasi-peak / 9kHz	66 - 56
0.5 - 5			56
5 - 30.0			60
0.15 - 0.5		Average / 9kHz	56 - 46
0.5 - 5			46
5 - 30.0			50

## 6 Test Instruments


Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
ROHDE & SCHWARZ TEST RECEIVER	ESR3	102413	Feb. 8, 2018	Feb. 7, 2019
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH2-Z5	100104	Dec. 6, 2017	Dec. 5, 2018
LISN With Adapter (for EUT)	AD10	C09Ada-001	Dec. 6, 2017	Dec. 5, 2018
ROHDE & SCHWARZ Artificial Mains Network (for peripherals)	ESH3-Z5	847265/023	Nov. 3, 2017	Nov. 2, 2018
SCHWARZBECK Artificial Mains Network (For EUT)	NNLK8129	8129229	May 3, 2018	May 2, 2019
SCHWARZBECK Artificial Mains Network (For EUT)	NNLK 8121	8121-808	Mar. 5, 2018	Mar. 4, 2019
Software	Cond_V7.3.7.4	NA	NA	NA
RF cable (JYEBAO) With 10dB PAD	5D-FB	Cable-C09.01	Feb. 21, 2018	Feb. 20, 2019
SUHNER Terminator (For ROHDE & SCHWARZ LISN)	65BNC-5001	E1-010789	May 8, 2018	May 7, 2019

- Notes:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in Shielded Room No. 9.
  3. The VCCI Site Registration No. C-1312.
  4. Tested Date: Oct. 20, 2018

## 6.1 Test Arrangement

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through an Artificial Mains Network (AMN). Other support units were connected to the power mains through another AMN. The two AMNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The test results of conducted emissions at mains ports are recorded of six worst margins for quasi-peak (mandatory) [and average (if necessary)] values against the limits at frequencies of interest unless the margin is 20 dB or greater.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.



- Note:**
- Support units were connected to second AMN.
  - The distance specified between EUT/AE and other metallic objects is  $\geq 0.8$  m in the measurement arrangement for table-top EUT.
  - Cable on the RGP must be insulated.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.


## 6.2 Test Results

Frequency Range	150kHz ~ 30MHz	Detector Function & Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	110Vac, 60Hz	Environmental Conditions	24°C, 72%RH, 1010mbar
Tested by	Adam Chen		
Test Mode	Mode 1		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.14	35.83	20.12	45.97	30.26	66.00	56.00	-20.03	-25.74
2	0.16564	10.15	34.82	18.46	44.97	28.61	65.18	55.18	-20.21	-26.57
3	0.18075	10.16	31.16	17.27	41.32	27.43	64.45	54.45	-23.13	-27.02
4	0.36816	10.21	33.15	22.56	43.36	32.77	58.54	48.54	-15.18	-15.77
5	0.55865	10.25	15.27	9.44	25.52	19.69	56.00	46.00	-30.48	-26.31
6	7.06839	10.77	7.45	1.88	18.22	12.65	60.00	50.00	-41.78	-37.35

### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




<b>Frequency Range</b>	150kHz ~ 30MHz	<b>Detector Function &amp; Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9kHz
<b>Input Power</b>	110Vac, 60Hz	<b>Environmental Conditions</b>	24°C, 72%RH, 1010mbar
<b>Tested by</b>	Adam Chen		
<b>Test Mode</b>	Mode 1		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15782	10.15	33.27	19.23	43.42	29.38	65.58	55.58	-22.16	-26.20
2	0.19254	10.17	30.23	15.26	40.40	25.43	63.93	53.93	-23.53	-28.50
3	0.20865	10.18	26.61	14.18	36.79	24.36	63.26	53.26	-26.47	-28.90
4	0.36048	10.20	29.82	19.44	40.02	29.64	58.72	48.72	-18.70	-19.08
5	0.55474	10.25	14.66	9.98	24.91	20.23	56.00	46.00	-31.09	-25.77
6	7.33427	10.80	13.18	6.04	23.98	16.84	60.00	50.00	-36.02	-33.16

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




<b>Frequency Range</b>	150kHz ~ 30MHz	<b>Detector Function &amp; Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9kHz
<b>Input Power</b>	230Vac, 50Hz	<b>Environmental Conditions</b>	24°C, 72%RH, 1010mbar
<b>Tested by</b>	Adam Chen		
<b>Test Mode</b>	Mode 1		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.14	33.50	20.11	43.64	30.25	66.00	56.00	-22.36	-25.75
2	0.18508	10.17	30.84	19.82	41.01	29.99	64.25	54.25	-23.24	-24.26
3	0.23585	10.19	30.99	20.89	41.18	31.08	62.24	52.24	-21.06	-21.16
<b>4</b>	<b>0.37287</b>	<b>10.21</b>	<b>33.38</b>	<b>21.27</b>	<b>43.59</b>	<b>31.48</b>	<b>58.44</b>	<b>48.44</b>	<b>-14.85</b>	<b>-16.96</b>
5	0.56647	10.26	17.17	10.73	27.43	20.99	56.00	46.00	-28.57	-25.01
6	13.41823	11.07	15.27	13.03	26.34	24.10	60.00	50.00	-33.66	-25.90

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




<b>Frequency Range</b>	150kHz ~ 30MHz	<b>Detector Function &amp; Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9kHz
<b>Input Power</b>	230Vac, 50Hz	<b>Environmental Conditions</b>	24°C, 72%RH, 1010mbar
<b>Tested by</b>	Adam Chen		
<b>Test Mode</b>	Mode 1		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	10.14	35.09	19.81	45.23	29.95	65.79	55.79	-20.56	-25.84
2	0.16955	10.16	32.58	17.40	42.74	27.56	64.98	54.98	-22.24	-27.42
3	0.20083	10.18	30.47	18.38	40.65	28.56	63.58	53.58	-22.93	-25.02
4	0.37287	10.21	28.72	16.31	38.93	26.52	58.44	48.44	-19.51	-21.92
5	0.56256	10.25	15.04	9.32	25.29	19.57	56.00	46.00	-30.71	-26.43
6	6.93936	10.78	15.03	7.39	25.81	18.17	60.00	50.00	-34.19	-31.83

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



## 7 Asymmetric Mode Conducted Emission at Telecommunication Ports

### 7.1 Limits

For Class A Equipment

Frequency range (MHz)	Coupling device	Detector type / bandwidth	Voltage limits (dBuV)	Current limits (dBuA)
0.15 - 0.5	AAN	Quasi-peak / 9kHz	97 – 87	N/A
0.5 - 30.0			87	
0.15 - 0.5	AAN	Average / 9kHz	84-74	
0.5 - 30.0			74	
0.15 - 0.5	CVP and current probe	Quasi-peak / 9kHz	97 – 87	53 – 43
0.5 - 30.0			87	43
0.15 - 0.5	CVP and current probe	Average / 9kHz	84-74	40 – 30
0.5 - 30.0			74	30
0.15 - 0.5	Current Probe	Quasi-peak / 9kHz	N/A	53 – 43
0.5 - 30.0				43
0.15 - 0.5	Current Probe	Average / 9kHz		40 – 30
0.5 - 30.0				30

For Class B Equipment

Frequency range (MHz)	Coupling device	Detector type / bandwidth	Voltage limits (dBuV)	Current limits (dBuA)
0.15 - 0.5	AAN	Quasi-peak / 9kHz	84 – 74	N/A
0.5 - 30.0			74	
0.15 - 0.5	AAN	Average / 9kHz	74-64	
0.5 - 30.0			64	
0.15 - 0.5	CVP and current probe	Quasi-peak / 9kHz	84 – 74	40 – 30
0.5 - 30.0			74	30
0.15 - 0.5	CVP and current probe	Average / 9kHz	74-64	30 – 20
0.5 - 30.0			64	20
0.15 - 0.5	Current Probe	Quasi-peak / 9kHz	N/A	40 – 30
0.5 - 30.0				30
0.15 - 0.5	Current Probe	Average / 9kHz		30 – 20
0.5 - 30.0				20

## 7.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
ROHDE & SCHWARZ TEST RECEIVER	ESR3	102413	Feb. 08, 2018	Feb. 07, 2019
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH2-Z5	100104	Dec. 06, 2017	Dec. 05, 2018
LISN With Adapter (for EUT)	AD10	C09Ada-001	Dec. 06, 2017	Dec. 05, 2018
ROHDE & SCHWARZ Artificial Mains Network (for peripherals)	ESH3-Z5	847265/023	Nov. 03, 2017	Nov. 02, 2018
SCHWARZBECK Artificial Mains Network (For EUT)	NNLK8129	8129229	May 3, 2018	May 2, 2019
SCHWARZBECK Artificial Mains Network (For EUT)	NNLK 8121	8121-808	Mar. 5, 2018	Mar. 4, 2019
Software	Cond_V7.3.7.4	NA	NA	NA
Software	ISN_V7.3.7.4	NA	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C09.01	Feb. 21, 2018	Feb. 20, 2019
SUHNER Terminator (For ROHDE & SCHWARZ LISN)	65BNC-5001	E1-010789	May 8, 2018	May 7, 2019
FCC ISN	F-071115-1057-1	20651	Feb. 12, 2018	Feb. 11, 2019


- Notes:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in Shielded Room No. 9.
  3. The VCCI Site Registration No. T-11587
  4. Tested Date: Oct. 20, 2018

### 7.3 Test Arrangement

#### Method of Using AANs:

- a. The EUT is placed 0.4 meters from the conducting wall of the shielded room and connected to AAN directly to reference ground plane.
- b. If voltage measurement is used, measure voltage at the measurement port of the AAN, correct the reading by adding the AAN voltage division factor, and compare to the voltage limit.
- c. It is not necessary to apply the voltage and the current limit if a AAN is used.
- d. The test results of disturbance at telecommunication ports are recorded of six worst margins for quasi-peak (mandatory) [and average (if necessary)] values against the limits at frequencies of interest unless the margin is 20 dB or greater.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.



1) Distance to the reference groundplane (vertical or horizontal).

2) Distance to the reference groundplane is not critical.

**Note: Cable on the RGP must be insulated.**

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.


#### 7.4 Test Results

<b>Frequency Range</b>	150kHz ~ 30MHz	<b>Detector Function &amp; Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9kHz
<b>Input Power</b>	230Vac, 50Hz	<b>Environmental Conditions</b>	24°C, 72%RH, 1010mbar
<b>Tested by</b>	Adam Chen		
<b>Test Mode</b>	Mode 1 - RJ45 TELECOM PORT (100Mbps) (TFGEN + PING)		

No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18508	9.73	48.08	37.83	57.81	47.56	82.25	72.25	-24.44	-24.69
2	0.22820	9.68	49.50	38.77	59.18	48.45	80.51	70.51	-21.33	-22.06
3	0.38460	9.55	50.38	43.75	59.93	53.30	76.18	66.18	-16.25	-12.88
4	7.92468	9.38	41.28	40.00	50.66	49.38	74.00	64.00	-23.34	-14.62
5	16.22952	9.72	40.77	39.50	50.49	49.22	74.00	64.00	-23.51	-14.78
6	29.23418	10.44	41.90	41.88	52.34	52.32	74.00	64.00	-21.66	-11.68

#### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




<b>Frequency Range</b>	150kHz ~ 30MHz	<b>Detector Function &amp; Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9kHz
<b>Input Power</b>	48Vdc	<b>Environmental Conditions</b>	24°C, 72%RH, 1010mbar
<b>Tested by</b>	Adam Chen		
<b>Test Mode</b>	Mode 2 - RJ45 TELECOM PORT (100Mbps) (TFGEN + PING)		

No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	1.48923	9.38	52.17	51.40	61.55	60.78	74.00	64.00	-12.45	-3.22
2	1.73947	9.36	51.81	51.03	61.17	60.39	74.00	64.00	-12.83	-3.61
3	1.98580	9.34	50.30	46.57	59.64	55.91	74.00	64.00	-14.36	-8.09
4	2.23604	9.34	50.95	49.94	60.29	59.28	74.00	64.00	-13.71	-4.72
5	17.38688	9.77	48.23	45.44	58.00	55.21	74.00	64.00	-16.00	-8.79
6	21.85861	10.00	51.77	50.09	61.77	60.09	74.00	64.00	-12.23	-3.91

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



## 8 Radiated Emission at Frequencies up to 1GHz

### 8.1 Limits

For Class A Equipment

Frequency range (MHz)	Distance (m)	Limits (dBuV/m)
30 - 230	10	40
230 - 1000		47
30 - 230	3	50
230 - 1000		57

For Class B Equipment

Frequency range (MHz)	Distance (m)	Limits (dBuV/m)
30 - 230	10	30
230 - 1000		37
30 - 230	3	40
230 - 1000		47

## 8.2 Test Instruments

### Mode 1

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
ROHDE & SCHWARZ TEST RECEIVER	ESCS 30	100027	Dec. 4, 2017	Dec. 3, 2018
Schwarzbeck Bilog Antenna	VULB9168	9168-303	Nov. 29, 2017	Nov. 28, 2018
Agilent Preamplifier	8447D	2944A08119	Feb. 21, 2018	Feb. 20, 2019
ADT. Turn Table	TT100	0205	NA	NA
ADT. Tower	AT100	0205	NA	NA
Software	Radiated_V7.6.15.9.5	NA	NA	NA
ADT RF Switches BOX	EMH-011	1001	Oct. 25, 2017	Oct. 24, 2018
Pacific RF cable With 5dB PAD	8D	CABLE-ST2-01	Oct. 25, 2017	Oct. 24, 2018

- Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
 2. The test was performed in Open Site No. 2.  
 3. The VCCI Site Registration No. R-237.  
 4. Tested Date: Oct. 19, 2018

### Mode 2

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
ROHDE & SCHWARZ TEST RECEIVER	ESCS 30	100027	Dec. 4, 2017	Dec. 3, 2018
Schwarzbeck Bilog Antenna	VULB9168	9168-303	Nov. 29, 2017	Nov. 28, 2018
Agilent Preamplifier	8447D	2944A08119	Feb. 21, 2018	Feb. 20, 2019
ADT. Turn Table	TT100	0205	NA	NA
ADT. Tower	AT100	0205	NA	NA
Software	Radiated_V7.6.15.9.5	NA	NA	NA
ADT RF Switches BOX	EMH-011	1001	Oct. 25, 2018	Oct. 24, 2019
Pacific RF cable With 5dB PAD	8D	CABLE-ST2-01	Oct. 25, 2018	Oct. 24, 2019


- Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
 2. The test was performed in Open Site No. 2.  
 3. The VCCI Site Registration No. R-237.  
 4. Tested Date: Nov. 15, 2018

### 8.3 Test Arrangement

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited test facility. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is up to 1 GHz.

#### Note:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for quasi-peak detection (QP) at frequency up to 1GHz.
- The measurement distance is the shortest horizontal distance between an imaginary circular periphery just encompassing this arrangement and the calibration point of the antenna.



**Note: Cable on the RGP must to be insulated.**

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.


#### 8.4 Test Results

<b>Frequency Range</b>	30MHz ~ 1GHz	<b>Detector Function &amp; Bandwidth</b>	Quasi-Peak (QP), 120kHz
<b>Tested by</b>	Vic Lin	<b>Environmental Conditions</b>	22°C, 78%RH, 1010mbar
<b>Test Mode</b>	Mode 1		

Antenna Polarity & Test Distance : Horizontal at 10 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	168.00	22.80 QP	30.00	-7.20	4.00 H	72	31.95	-9.15
2	216.60	24.80 QP	30.00	-5.20	4.00 H	169	36.88	-12.08
3	249.97	28.47 QP	37.00	-8.53	3.00 H	251	38.84	-10.37
4	360.05	28.66 QP	37.00	-8.34	2.00 H	169	35.56	-6.90
5	527.50	28.43 QP	37.00	-8.57	1.98 H	223	31.50	-3.07
6	1000.00	31.14 QP	37.00	-5.86	1.00 H	57	27.01	4.13

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




<b>Frequency Range</b>	30MHz ~ 1GHz	<b>Detector Function &amp; Bandwidth</b>	Quasi-Peak (QP), 120kHz
<b>Tested by</b>	Vic Lin	<b>Environmental Conditions</b>	22°C, 78%RH, 1010mbar
<b>Test Mode</b>	Mode 1		

Antenna Polarity & Test Distance : Vertical at 10 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	74.06	24.74 QP	30.00	-5.26	1.00 V	180	36.63	-11.89
2	167.90	23.82 QP	30.00	-6.18	1.00 V	153	32.96	-9.14
3	216.28	24.71 QP	30.00	-5.29	1.00 V	230	36.79	-12.08
4	249.97	29.88 QP	37.00	-7.12	1.00 V	119	40.25	-10.37
5	284.82	30.59 QP	37.00	-6.41	1.00 V	217	39.43	-8.84
6	643.75	29.53 QP	37.00	-7.47	1.99 V	248	30.32	-0.79

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)  
– Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




<b>Frequency Range</b>	30MHz ~ 1GHz	<b>Detector Function &amp; Bandwidth</b>	Quasi-Peak (QP), 120kHz
<b>Tested by</b>	Vincent Lin	<b>Environmental Conditions</b>	22°C, 72%RH, 1009mbar
<b>Test Mode</b>	Mode 2		

Antenna Polarity & Test Distance : Horizontal at 10 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	48.62	22.53 QP	30.00	-7.47	4.00 H	75	31.30	-8.77
2	118.65	21.86 QP	30.00	-8.14	4.00 H	173	33.08	-11.22
3	132.52	23.67 QP	30.00	-6.33	4.00 H	315	33.54	-9.87
<b>4</b>	<b>168.01</b>	<b>26.28 QP</b>	<b>30.00</b>	<b>-3.72</b>	<b>4.00 H</b>	<b>69</b>	<b>35.38</b>	<b>-9.10</b>
5	215.99	26.19 QP	30.00	-3.81	4.00 H	43	38.31	-12.12
6	240.10	27.90 QP	37.00	-9.10	3.15 H	206	38.38	-10.48
7	720.01	32.52 QP	37.00	-4.48	1.37 H	192	31.87	0.65

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)  
– Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




<b>Frequency Range</b>	30MHz ~ 1GHz	<b>Detector Function &amp; Bandwidth</b>	Quasi-Peak (QP), 120kHz
<b>Tested by</b>	Vincent Lin	<b>Environmental Conditions</b>	22°C, 72%RH, 1009mbar
<b>Test Mode</b>	Mode 2		

Antenna Polarity & Test Distance : Vertical at 10 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	47.52	23.95 QP	30.00	-6.05	1.00 V	5	32.72	-8.77
2	80.69	24.38 QP	30.00	-5.62	1.00 V	92	38.09	-13.71
3	122.84	23.55 QP	30.00	-6.45	1.00 V	351	34.28	-10.73
4	133.15	22.76 QP	30.00	-7.24	1.00 V	204	32.59	-9.83
5	168.00	25.86 QP	30.00	-4.14	1.00 V	152	34.96	-9.10
6	191.99	25.80 QP	30.00	-4.20	1.00 V	17	37.56	-11.76
7	720.01	33.12 QP	37.00	-3.88	2.61 V	61	32.47	0.65

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value



## 9 Radiated Emission at Frequencies above 1GHz

### 9.1 Limits

For Class A Equipment

Frequency range (MHz)	Distance (m)	Detector type	Limits (dBuV/m)
1000 - 3000	3	Average	56
3000 - 6000			60
1000 - 3000		Peak	76
3000 - 6000			80

For Class B Equipment

Frequency range (MHz)	Distance (m)	Detector type	Limits (dBuV/m)
1000 - 3000	3	Average	50
3000 - 6000			54
1000 - 3000		Peak	70
3000 - 6000			74

#### Required highest frequency for radiated measurement

Highest internal frequency ( $F_x$ )	Highest measured frequency
$F_x \leq 108$ MHz	1 GHz
108 MHz < $F_x \leq 500$ MHz	2 GHz
500 MHz < $F_x \leq 1$ GHz	5 GHz
$F_x > 1$ GHz	5 x $F_x$ up to a maximum of 6 GHz

NOTE 1 For FM and TV broadcast receivers,  $F_x$  is determined from the highest frequency generated or used excluding the local oscillator and tuned frequencies.

NOTE 2  $F_x$  is highest fundamental frequency generated or used within the EUT or highest frequency at which it operates.

Where  $F_x$  is unknown, the radiated emission measurements shall be performed up to 6 GHz.

## 9.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Agilent Spectrum	E4446A	MY51100009	Jun. 4, 2018	Jun. 3, 2019
Agilent Test Receiver	N9038A	MY51210137	Jun. 19, 2018	Jun. 18, 2019
Agilent Preamplifier	8449B	3008A01292	Feb. 22, 2018	Feb. 21, 2019
MITEQ Preamplifier	AMF-6F-260400-33-8P	892164	Feb. 21, 2018	Feb. 20, 2019
EMCI Preamplifier	EMC184045B	980235	Feb. 22, 2018	Feb. 21, 2019
Schwarzbeck Horn Antenna	BBHA-9170	212	Dec. 1, 2017	Nov. 30, 2018
EMCO Horn Antenna	3115	6714	Dec. 12, 2017	Dec. 11, 2018
Max Full. Turn Table	MF7802	MF780208216	NA	NA
Software	Radiated_V8.7.08	NA	NA	NA
SUHNER RF cable With 3/4dB PAD	SF102	Cable-CH10-3.6m	Aug. 13, 2018	Aug. 12, 2019
MICRO-TRONICS Notch filter	BRC50703-01	010	May 31, 2018	May 30, 2019
MICRO-TRONICS Band Pass Filter	BRM17690	005	May 31, 2018	May 30, 2019


- Notes:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The 3dB beamwidth of the horn antenna is minimum 41degree (or  $w = 2.24m$  at 3m distance) for 1~6 GHz.
  3. The test was performed in Chamber No. 10.
  4. The Industry Canada Reference No. IC 7450E-11.
  5. The VCCI Site Registration No. G-10427
  6. Tested Date: Oct. 20 ~ Nov. 15, 2018

### 9.3 Test Arrangement

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna can be varied from one meter to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The spectrum analyzer system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.

#### Note:

- The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection (PK) at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz for Average detection (AV) at frequency above 1GHz.
- The measurement distance is the shortest horizontal distance between an imaginary circular periphery just encompassing this arrangement and the calibration point of the antenna.



**Note: Cable on the RGP must to be insulated.**

\* :depends on the EUT height and the antenna 3dB beamwidth both.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.


#### 9.4 Test Results

<b>Frequency Range</b>	1GHz ~ 6GHz	<b>Detector Function &amp; Bandwidth</b>	Peak (PK) / Average (AV), 1MHz
<b>Tested by</b>	Vincent Chen	<b>Environmental Conditions</b>	23°C, 77%RH, 1010mbar
<b>Test Mode</b>	Mode 1		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1573.12	42.93 PK	70.00	-27.07	1.63 H	256	45.76	-2.83
2	1573.12	29.68 AV	50.00	-20.32	1.63 H	256	32.51	-2.83
3	2338.12	45.31 PK	70.00	-24.69	1.54 H	279	45.28	0.03
4	2338.12	31.69 AV	50.00	-18.31	1.54 H	279	31.66	0.03
5	2976.75	46.68 PK	70.00	-23.32	2.23 H	125	44.88	1.80
6	2976.75	33.25 AV	50.00	-16.75	2.23 H	125	31.45	1.80
7	3775.75	47.30 PK	74.00	-26.70	1.89 H	67	42.48	4.82
8	3775.75	34.16 AV	54.00	-19.84	1.89 H	67	29.34	4.82
9	5259.75	49.45 PK	74.00	-24.55	1.22 H	297	42.27	7.18
10	5259.75	35.43 AV	54.00	-18.57	1.22 H	297	28.25	7.18
11	5557.50	49.00 PK	74.00	-25.00	1.05 H	306	41.54	7.46
12	5557.50	35.12 AV	54.00	-18.88	1.05 H	306	27.66	7.46

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




<b>Frequency Range</b>	1GHz ~ 6GHz	<b>Detector Function &amp; Bandwidth</b>	Peak (PK) / Average (AV), 1MHz
<b>Tested by</b>	Vincent Chen	<b>Environmental Conditions</b>	23°C, 77%RH, 1010mbar
<b>Test Mode</b>	Mode 1		

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1586.62	43.45 PK	70.00	-26.55	1.32 V	297	46.20	-2.75
2	1586.62	30.08 AV	50.00	-19.92	1.32 V	297	32.83	-2.75
3	2421.00	44.80 PK	70.00	-25.20	1.06 V	155	44.74	0.06
4	2421.00	31.23 AV	50.00	-18.77	1.06 V	155	31.17	0.06
5	3066.25	48.49 PK	74.00	-25.51	1.85 V	175	46.11	2.38
6	3066.25	34.12 AV	54.00	-19.88	1.85 V	175	31.74	2.38
7	3600.11	41.73 PK	74.00	-32.27	1.66 V	209	37.85	3.88
8	3600.11	32.32 AV	54.00	-21.68	1.66 V	209	28.44	3.88
9	4711.50	47.74 PK	74.00	-26.26	2.32 V	19	42.18	5.56
10	4711.50	34.04 AV	54.00	-19.96	2.32 V	19	28.48	5.56
11	5414.75	48.89 PK	74.00	-25.11	1.74 V	124	41.49	7.40
12	5414.75	35.68 AV	54.00	-18.32	1.74 V	124	28.28	7.40

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




<b>Frequency Range</b>	1GHz ~ 6GHz	<b>Detector Function &amp; Bandwidth</b>	Peak (PK) / Average (AV), 1MHz
<b>Tested by</b>	Chin-Wen Wang	<b>Environmental Conditions</b>	19°C, 70%RH, 1009mbar
<b>Test Mode</b>	Mode 2		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2028.37	43.86 PK	70.00	-26.14	2.41 H	342	44.99	-1.13
2	2028.37	30.06 AV	50.00	-19.94	2.41 H	342	31.19	-1.13
3	2299.25	44.98 PK	70.00	-25.02	1.95 H	263	45.13	-0.15
4	2299.25	32.14 AV	50.00	-17.86	1.95 H	263	32.29	-0.15
5	2959.37	46.35 PK	70.00	-23.65	1.32 H	26	44.74	1.61
6	2959.37	33.48 AV	50.00	-16.52	1.32 H	26	31.87	1.61
7	3822.37	47.90 PK	74.00	-26.10	2.10 H	160	42.80	5.10
8	3822.37	34.59 AV	54.00	-19.41	2.10 H	160	29.49	5.10
9	4931.00	49.28 PK	74.00	-24.72	1.05 H	360	42.98	6.30
10	4931.00	34.36 AV	54.00	-19.64	1.05 H	360	28.06	6.30
11	5592.37	49.94 PK	74.00	-24.06	1.00 H	158	42.50	7.44
12	5592.37	35.50 AV	54.00	-18.50	1.00 H	158	28.06	7.44

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




<b>Frequency Range</b>	1GHz ~ 6GHz	<b>Detector Function &amp; Bandwidth</b>	Peak (PK) / Average (AV), 1MHz
<b>Tested by</b>	Chin-Wen Wang	<b>Environmental Conditions</b>	19°C, 70%RH, 1009mbar
<b>Test Mode</b>	Mode 2		

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2159.98	47.46 PK	70.00	-22.54	1.57 V	68	48.28	-0.82
2	<b>2159.98</b>	<b>37.76 AV</b>	<b>50.00</b>	<b>-12.24</b>	<b>1.57 V</b>	<b>68</b>	<b>38.58</b>	<b>-0.82</b>
3	2369.87	45.05 PK	70.00	-24.95	1.02 V	8	44.95	0.10
4	2369.87	32.17 AV	50.00	-17.83	1.02 V	8	32.07	0.10
5	2840.87	45.93 PK	70.00	-24.07	1.86 V	296	45.08	0.85
6	2840.87	32.32 AV	50.00	-17.68	1.86 V	296	31.47	0.85
7	3866.87	48.50 PK	74.00	-25.50	2.37 V	317	43.02	5.48
8	3866.87	34.70 AV	54.00	-19.30	2.37 V	317	29.22	5.48
9	5497.00	49.73 PK	74.00	-24.27	1.20 V	360	42.35	7.38
10	5497.00	35.74 AV	54.00	-18.26	1.20 V	360	28.36	7.38
11	5913.37	49.81 PK	74.00	-24.19	1.00 V	79	42.29	7.52
12	5913.37	35.90 AV	54.00	-18.10	1.00 V	79	28.38	7.52

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value



## 10 Harmonics Current Measurement

### 10.1 Limits

Limits for Class A equipment		Limits for Class D equipment		
Harmonic Order n	Max. permissible harmonics current A	Harmonic Order n	Max. permissible harmonics current per watt mA/W	Max. permissible harmonics current A
Odd harmonics		Odd Harmonics only		
3	2.30	3	3.4	2.30
5	1.14	5	1.9	1.14
7	0.77	7	1.0	0.77
9	0.40	9	0.5	0.40
11	0.33	11	0.35	0.33
13	0.21	13	0.30	0.21
$15 \leq n \leq 39$	$0.15 \times 15/n$	$15 \leq n \leq 39$	$3.85/n$	$0.15 \times 15/n$
Even harmonics				
2	1.08			
4	0.43			
6	0.30			
$8 \leq n \leq 40$	$0.23 \times 8/n$			

Notes: 1. Class A and Class D are classified according to section 5 of EN 61000-3-2.

2. According to section 7 of EN 61000-3-2, the above limits for all equipment except for lighting equipment having an active input power > 75 W and no limits apply for equipment with an active input power up to and including 75 W.

### 10.2 Classification of Equipment

Class A	Class B	Class C	Class D
Balanced three-phase equipment; Household appliances excluding equipment as Class D; Tools excluding portable tools; Dimmers for incandescent lamps; Audio equipment; Equipment not specified in one of the three other classes.	Portable tools; Arc welding equipment which is not professional equipment.	Lighting equipment.	Equipment having a specified power less than or equal to 600 W of the following types: Personal computers and personal computer monitors; Television receivers; Refrigerators and freezers having one or more variable-speed drives to control compressor motor(s).

### 10.3 Test Instruments


Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Teseq Harmonics - Flicker Test System	Proflin 2105	32A00983 & 1639A01863	Sep. 27, 2018	Sep. 26, 2019
Software	CTS 4	NA	NA	NA

Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in EMS Room No. 1.
3. According to IEC 61000-4-7: 2002, the time window shall be synchronized with each group of 10 or 12 cycles (200 ms) for power frequency of 50 or 60Hz.
4. Tested Date: Oct. 27, 2018.

### 10.4 Test Arrangement

- a. The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the maximum harmonic components under normal operating conditions for each successive harmonic component in turn.
- b. The correspondent test program of test instrument to measure the current harmonics emanated from EUT is chosen. The measure time shall be not less than the time necessary for the EUT to be exercised.



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

### 10.5 Test Results

Fundamental Voltage/Ampere	230.17Vrms/ 0.058Arms	Power Frequency	50.00Hz
Power Consumption	3.5W	Power Factor	0.264
Environmental Conditions	25deg. C, 75%RH	Tested by	Todd Chang
Test Mode	Mode 1		

Note: 1. Limits are not specified for equipment with a rated power of 75W or less (other than lighting equipment).

2. According to EN 61000-3-2 the manufacturer shall specify the power of the apparatus. This value shall be used for establishing limits. The specified power shall be within +/-10% of the measured power.

## 11 Voltage Fluctuations and Flicker Measurement

### 11.1 Limits

Test item	Limit	Note
$P_{st}$	1.0	$P_{st}$ : short-term flicker severity.
$P_{lt}$	0.65	$P_{lt}$ : long-term flicker severity.
$T_{max}$ (ms)	500	$T_{max}$ : maximum time duration during the observation period that the voltage deviation $d(t)$ exceeds the limit for $d_c$ .
$d_{max}$ (%)	4	$d_{max}$ : maximum absolute voltage change during an observation period.
$d_c$ (%)	3.3	$d_c$ : maximum steady state voltage change during an observation period.

### 11.2 Test Instruments


Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Teseq Harmonics - Flicker Test System	Proflin 2105	32A00983 & 1639A01863	Sep. 27, 2018	Sep. 26, 2019
Software	CTS 4	NA	NA	NA

Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in EMS Room No. 1.
3. Tested Date: Oct. 27, 2018.

### 11.3 Test Arrangement

- a. The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the most unfavorable sequence of voltage changes under normal operating conditions.
- b. During the flick measurement, the measure time shall include that part of whole operation cycle in which the EUT produce the most unfavorable sequence of voltage changes. The observation period for short-term flicker indicator is 10 minutes and the observation period for long-term flicker indicator is 2 hours.



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 11.4 Test Results

Fundamental Voltage/Ampere	230.17Vrms/ 0.058Arms	Power Frequency	50.00Hz
Observation ( $T_p$ )	10 min.	Power Factor	0.264
Environmental Conditions	25deg. C, 75%RH	Tested by	Todd Chang
Test Mode	Mode 1		

Test Parameter	Measurement Value	Limit	Remarks
$P_{st}$	0.064	1.00	Pass
$P_{lt}$	0.028	0.65	Pass
$T_{max}$ (ms)	0	500	Pass
$d_{max}$ (%)	0	4	Pass
$d_c$ (%)	0	3.3	Pass

- Note: (1)  $P_{st}$  means short-term flicker indicator.  
 (2)  $P_{lt}$  means long-term flicker indicator.  
 (3)  $T_{max}$  means accumulated time value of  $d(t)$  with a deviation exceeding 3.3 %.  
 (4)  $d_{max}$  means maximum relative voltage change.  
 (5)  $d_c$  means maximum relative steady-state voltage change.

## 12 General Immunity Requirements

### EN 55024:2010 / EN55024:2010 +A1:2015, Immunity requirements

Clause	Reference standard	Table	Test specification	Performance Criterion
4.2.1	EN/IEC 61000-4-2 ESD	1.3	Enclosure port: ±8kV Air discharge, ±4kV Contact discharge	B
4.2.3.2	EN/IEC 61000-4-3 RS	1.2	Enclosure port: 80-1000 MHz, 3V/m, 80% AM (1kHz)	A
4.2.2	EN/IEC 61000-4-4 EFT	2.3	Signal ports and telecommunication ports: xDSL equipment: ±0.5kV, 5/50 (T <sub>r</sub> /T <sub>h</sub> ) ns, 100kHz others: ±0.5kV, 5/50 (T <sub>r</sub> /T <sub>h</sub> ) ns, 5kHz	B
		3.3	Input DC power port: ±0.5kV, 5/50 (T <sub>r</sub> /T <sub>h</sub> ) ns, 5kHz	
		4.5	Input AC Power ports: ±1kV, 5/50 (T <sub>r</sub> /T <sub>h</sub> ) ns, 5kHz	
4.2.5	EN/IEC 61000-4-5 Surge	2.2	Signal and telecommunication ports (direct to outdoor cables): 10/700 (5/320) (T <sub>r</sub> /T <sub>h</sub> ) μs w/o primary protectors: ±1kV, or with primary protectors fitted: ±4kV	C
		3.2	Input DC power port (direct to outdoor cables): 1.2/50 (8/20) (T <sub>r</sub> /T <sub>h</sub> ) μs Line to earth: ±0.5kV	B
		4.4	Input AC Power ports: 1.2/50 (8/20) (T <sub>r</sub> /T <sub>h</sub> ) μs, Line to line: ±1kV Line to earth: ±2kV	
4.2.3.3	EN/IEC 61000-4-6 CS	2.1	Signal and telecommunication ports(cable length > 3m): 0.15-80 MHz, 3V, 80% AM (1kHz)	A
		3.1	Input DC power port: 0.15-80 MHz, 3V, 80% AM (1kHz)	
		4.1	Input AC Power ports: 0.15-80 MHz, 3V, 80% AM (1kHz)	
4.2.4	EN/IEC 61000-4-8 PFMF	1.1	Enclosure port: 50 or 60 Hz, 1A/m	A
4.2.6	EN/IEC 61000-4-11 Dips & Interruptions	4.2	Input AC Power ports: Voltage Dips: >95% reduction – 0.5 period 30% reduction – 25 periods	B C
		4.3	Input AC Power ports: Voltage Interruptions: >95% reduction – 250 periods	C

## 12.1 Performance Criteria

### General Performance Criteria

#### Performance criterion A

The equipment shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.

#### Performance criterion B

After the test, the equipment shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed, after the application of the phenomena below a performance level specified by the manufacturer, when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is allowed. However, no change of operating state or stored data is allowed to persist after the test. If the minimum performance level (or the permissible performance loss) is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.

#### Performance criterion C

Loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls by the user in accordance with the manufacturer's instructions. Functions, and/or information stored in non-volatile memory, or protected by a battery backup, shall not be lost.

### Particular performance criteria

The particular performance criteria which are specified in the normative annexes of EN 55024 take precedence over the corresponding parts of the general performance criteria. Where particular performance criteria for specific functions are not given, then the general performance criteria shall apply.

### 13 Electrostatic Discharge Immunity Test (ESD)

#### 13.1 Test Specification

<b>Basic Standard:</b>	EN/IEC 61000-4-2
<b>Discharge Impedance:</b>	330 ohm / 150 pF
<b>Discharge Voltage:</b>	Air Discharge: $\pm 2, \pm 4, \pm 8$ kV (Direct) Contact Discharge: $\pm 2, \pm 4$ kV (Direct & Indirect)
<b>Number of Discharge:</b>	Air – Direct: 10 discharges per location (each polarity) Contact – Direct & Indirect: 25 discharges per location (each polarity) and min. 200 times in total
<b>Discharge Mode:</b>	Single Discharge
<b>Discharge Period:</b>	1-second minimum

#### 13.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
KeyTek, ESD Simulator	MZ-15/EC	1203252	Sep. 20, 2018	Sep. 19, 2019

- Notes:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in ESD Room No. 2.
  3. Tested Date: Oct. 30, 2018

#### 13.3 Test Arrangement

The discharges shall be applied in two ways:

a. Contact discharges to the conductive surfaces and coupling planes:


The EUT shall be exposed to at least 200 discharges, 100 each at negative and positive polarity, at a minimum of four test points. One of the test points shall be subjected to at least 50 indirect discharges to the center of the front edge of the horizontal coupling plane. The remaining three test points shall each receive at least 50 direct contact discharges. If no direct contact test points are available, then at least 200 indirect discharges shall be applied in the indirect mode. Test shall be performed at a maximum repetition rate of one discharge per second.

b. Air discharges at slots and apertures and insulating surfaces:

On those parts of the EUT where it is not possible to perform contact discharge testing, the equipment should be investigated to identify user accessible points where breakdown may occur. Such points are tested using the air discharge method. This investigation should be restricted to those area normally handled by the user. A minimum of 10 single air discharges shall be applied to the selected test point for each such area.

The basic test procedure was in accordance with EN/IEC 61000-4-2:

- a. Electrostatic discharges were applied only to those points and surfaces of the EUT that are accessible to users during normal operation.
- b. The test was performed with at least ten single discharges on the pre-selected points in the most sensitive polarity.
- c. The time interval between two successive single discharges was at least 1 second.
- d. The ESD generator was held perpendicularly to the surface to which the discharge was applied and the return cable was at least 0.2 meters from the EUT.
- e. Contact discharges were applied to the non-insulating coating, with the pointed tip of the generator penetrating the coating and contacting the conducting substrate.
- f. Air discharges were applied with the round discharge tip of the discharge electrode approaching the EUT as fast as possible (without causing mechanical damage) to touch the EUT. After each discharge, the ESD generator was removed from the EUT and re-triggered for a new single discharge. The test was repeated until all discharges were complete.
- g. At least ten single discharges (in the most sensitive polarity) were applied to the **Horizontal Coupling Plane** at points on each side of the EUT. The ESD generator was positioned at a distance of 0.1 meters from the EUT with the discharge electrode touching the **HCP**.
- h. At least ten single discharges (in the most sensitive polarity) were applied to the center of one vertical edge of the **Vertical Coupling Plane** in sufficiently different positions that the four faces of the EUT were completely illuminated. The **VCP** (dimensions 0.5m x 0.5m) was placed vertically to and 0.1 meters from the EUT.



#### TABLE-TOP EQUIPMENT

The configuration consisted of a wooden table 0.8 meters high standing on the **Ground Reference Plane**. The **GRP** consisted of a sheet of aluminum at least 0.25mm thick, and 2.5 meters square connected to the protective grounding system. A **Horizontal Coupling Plane** (1.6m x 0.8m) was placed on the table and attached to the **GRP** by means of a cable with 940kΩ total impedance. The equipment under test, was installed in a representative system as described in section 7 of EN/IEC 61000-4-2, and its cables were placed on the **HCP** and isolated by an insulating support of 0.5mm thickness. A distance of 1-meter minimum was provided between the EUT and the walls of the laboratory and any other metallic structure.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

### 13.4 Test Results

Test mode	Mode 1	Input Power	230Vac, 50Hz
Environmental Conditions	24 °C, 53% RH 1007 mbar	Tested by	Xun Lee

#### Test Results of Direct Application

Discharge Level (kV)	Polarity (+/-)	Test Point	Contact Discharge	Air Discharge	Performance Criterion
2, 4, 8	+/-	1-6	NA	Note 1	A

Description of test points of direct application: Please refer to following page for representative mark only.

#### Test Results of Indirect Application



Discharge Level (kV)	Polarity (+/-)	Test Point	Horizontal Coupling Plane	Vertical Coupling Plane	Performance Criterion
2	+/-	Four Sides	Note 1	Note 1	A
4	+/-	Four Sides	Note 2	Note 2	B


Description of test points of indirect application:

1. Front side                      2. Rear side                      3. Right side                      4. Left side

- Note: 1. The EUT function was correct during the test.  
 2. There was noise sound on speaker during the test, but self-recoverable after the test.

### Description of Test Points







Test mode	Mode 2	Input Power	230Vac, 50Hz
Environmental Conditions	24 °C, 53% RH 1007 mbar	Tested by	Xun Lee

Test Results of Direct Application					
Discharge Level (kV)	Polarity (+/-)	Test Point	Contact Discharge	Air Discharge	Performance Criterion
2	+/-	1	Note 1	NA	A
4	+/-	1	Note 2	NA	B
2, 4, 8	+/-	2-5	NA	Note 1	A

Description of test points of direct application: Please refer to following page for representative mark only.

Test Results of Indirect Application					
Discharge Level (kV)	Polarity (+/-)	Test Point	Horizontal Coupling Plane	Vertical Coupling Plane	Performance Criterion
2	+/-	Four Sides	Note 1	Note 1	A
4	+/-	Four Sides	Note 2	Note 2	B

Description of test points of indirect application:


1. Front side                      2. Rear side                      3. Right side                      4. Left side

Note: 1. The EUT function was correct during the test.

2. There was noise sound on speaker during the test, but self-recoverable after the test.

### Description of Test Points





## 14 Radiated, Radio-frequency, Electromagnetic Field Immunity Test (RS)

### 14.1 Test Specification

Basic Standard:	EN/IEC 61000-4-3
Frequency Range:	80 MHz - 1000 MHz
Field Strength:	3 V/m
Modulation:	1kHz Sine Wave, 80%, AM Modulation
Frequency Step:	1 % of preceding frequency value
Polarity of Antenna:	Horizontal and Vertical
Antenna Height:	1.5m
Dwell Time:	3 seconds

### 14.2 Test Instruments


Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
BOONTON Power Meter	4232A	94901	Jun. 5, 2018	Jun. 4, 2019
BOONTON Power Sensor	51011-EMC	32807	Sep. 10, 2018	Sep. 9, 2019
BOONTON Power Sensor	51011-EMC	32832	Jun. 4, 2018	Jun. 3, 2019
TESEQ RF Generator	ITS 6006	37543	May 9, 2018	May 8, 2019
ETS Electric Field Sensor	HI-6105	00217912	Nov. 27, 2017	Nov. 26, 2018
TESEQ RF Amplifier	CBA1G-150	T44220	NA	NA
TESTQ Amplifier	CBA 3G-050	T44345	NA	NA
TESTQ Amplifier	CBA 1G-275	T44344	NA	NA
AR Log-Periodic Antenna	AT5080	312115	NA	NA
AR High Gain Horn Antenna	AT4010	0329800	NA	NA
CHANCE MOST Compact Full Anechoic Chamber (7x3x3 m)	N/A	N/A	Mar. 28, 2018	Mar. 27, 2019
Software	RS_V7.6	NA	NA	NA

- Notes:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in RS Room No.1.
  3. The transmit antenna was located at a distance of 3 meters from the EUT.
  4. Tested Date: Oct. 24 ~ 29, 2018

### 14.3 Test Arrangement

The test procedure was in accordance with EN/IEC 61000-4-3.

- The testing was performed in a fully anechoic chamber.
- The frequency range is swept from 80 MHz to 1000 MHz, with the signal 80% amplitude modulated with a 1kHz sine wave.
- The field strength level was 3 V/m.
- The test was performed with the EUT exposed to both vertically and horizontally polarized fields on each of the four sides.



#### Table-top Equipment

The EUT installed in a representative system as described in section 7 of EN/IEC 61000-4-3 was placed on a non-conductive table 0.8 meters in height. The system under test was connected to the power and signal wire according to relevant installation instructions.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 14.4 Test Results

Test mode	Mode 1	Input Power	230Vac, 50Hz
Environmental Conditions	26 °C, 70% RH	Tested by	Aga Lin

Frequency (MHz)	Polarity	Azimuth(°)	Applied Field Strength		Observation	Performance Criterion
			(V/m)	Modulation		
80 -1000	V&H	0	3	80% AM (1kHz)	Note	A
80 -1000	V&H	90	3	80% AM (1kHz)	Note	A
80 -1000	V&H	180	3	80% AM (1kHz)	Note	A
80 -1000	V&H	270	3	80% AM (1kHz)	Note	A

Note: The EUT function was correct during the test.

Test mode	Mode 2	Input Power	230Vac, 50Hz
Environmental Conditions	25 °C, 62% RH	Tested by	Michael Cheng

Frequency (MHz)	Polarity	Azimuth(°)	Applied Field Strength		Observation	Performance Criterion
			(V/m)	Modulation		
80 -1000	V&H	0	3	80% AM (1kHz)	Note	A
80 -1000	V&H	90	3	80% AM (1kHz)	Note	A
80 -1000	V&H	180	3	80% AM (1kHz)	Note	A
80 -1000	V&H	270	3	80% AM (1kHz)	Note	A

Note: The EUT function was correct during the test.

## 15 Electrical Fast Transient/Burst Immunity Test (EFT)

### 15.1 Test Specification

Basic Standard:	EN/IEC 61000-4-4
Test Voltage:	Signal / telecommunication port: $\pm 0.5\text{kV}$ Input DC power port: N/A Input AC power port: $\pm 1\text{kV}$
Impulse Repetition Frequency:	xDSL telecommunication port: 100kHz others: 5kHz
Impulse Wave Shape:	5/50 ns
Burst Duration:	0.75 ms for 100kHz Repetition Frequency 15 ms for 5kHz Repetition Frequency
Burst Period:	300 ms
Test Duration:	1 min.

### 15.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Haefely, EFT Generator	PEFT 4010	154954	Apr. 25, 2018	Apr. 24, 2019
Haefely, Capacitive Clamp	IP4A	155173	Apr. 25, 2018	Apr. 24, 2019

- Notes:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in EFT Room.
  3. Tested Date: Oct. 27, 2018



#### 15.4 Test Results

Test mode	Mode 1	Input Power	230Vac, 50Hz
Environmental Conditions	26 °C, 63% RH	Tested by	Todd Chang

##### Input AC power port

Voltage (kV)	Test Point	Polarity (+/-)	Observation	Performance Criterion
1	L1	+/-	Note	B
1	L2	+/-	Note	B
1	L1-L2	+/-	Note	B

##### Signal port

Voltage (kV)	Test Point	Polarity (+/-)	Observation	Performance Criterion
0.5	Cat. 5 Line	+/-	Note	B

Note: There is noise sound on the speaker of Notebook PC during the test, but self-recoverable after the test.

Test mode	Mode 2	Input Power	230Vac, 50Hz
Environmental Conditions	26 °C, 63% RH	Tested by	Todd Chang

##### Signal port

Voltage (kV)	Test Point	Polarity (+/-)	Observation	Performance Criterion
0.5	Cat. 5 Line	+/-	Note	B

Note: There is noise sound on the speaker of Notebook PC during the test, but self-recoverable after the test.

## 16 Surge Immunity Test

### 16.1 Test Specification

Basic Standard:	EN/IEC 61000-4-5
Wave-Shape:	Signal / telecommunication port (direct to outdoor cables*): 10/700 $\mu$ s Open Circuit Voltage 5/320 $\mu$ s Short Circuit Current  Input DC power port (direct to outdoor cables*): 1.2/50 $\mu$ s Open Circuit Voltage 8/20 $\mu$ s Short Circuit Current  Input AC power port: 1.2/50 $\mu$ s Open Circuit Voltage 8/20 $\mu$ s Short Circuit Current
Test Voltage:	Signal and telecommunication ports**: w/o primary protectors: N/A with primary protectors fitted: N/A  Input DC power port: N/A  Input AC power ports: Line to line: $\pm 0.5$ kV, $\pm 1$ kV Line to earth or ground: N/A
AC Phase Angle (degree):	0°, 90°, 180°, 270°
Pulse Repetition Rate:	1 time / 20 sec.
Number of Tests:	5 positive and 5 negative at selected points

\* This test is only applicable only to ports, which according to the manufacturer's specification, may connect directly to outdoor cables.

\*\* For ports where primary protection is intended, surges are applied at voltages up to 4 kV with the primary protectors fitted. Otherwise the 1 kV test level is applied without primary protection in place.

### 16.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
TESEQ, Surge Simulator	NSG 3060	1572	May 28, 2018	May 27, 2019
Coupling Decoupling Network	CDN-UTP8	045	Aug. 27, 2018	Aug. 26, 2019
TESEQ Coupling Decoupling Network	CDN HSS-2	41009	May 23, 2018	May 22, 2019
TESEQ Coupling Decoupling Network	CDN 118-T8	40386	Sep. 20, 2018	Sep. 19, 2019
TESEQ CDN for Unshielded Unsymmetrical Signal & Data Lines	CDN117	40144	Sep. 20, 2018	Sep. 19, 2019

- Notes:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in EMS Room No. 2.
  3. Tested Date: Oct. 31, 2018

### 16.3 Test Arrangement

a. Input AC/DC Power ports:

The surge is to be applied to the EUT power supply terminals via the capacitive coupling network. Decoupling networks are required in order to avoid possible adverse effects on equipment not under test that may be powered by the same lines, and to provide sufficient decoupling impedance to the surge wave. The power cord between the EUT and the coupling/decoupling networks shall be 2 meters in length (or shorter).

For double-insulated products without PE or external earth connections, the test shall be done in a similar way as for grounded products but without adding any additional external grounded connections. If there are no other possible connections to earth, line-to-ground tests may be omitted.

b. Signal and telecommunication ports,

- Unshielded unsymmetrical interconnection lines:

The surge is applied to the lines via the capacitive coupling. The coupling / decoupling networks shall not influence the specified functional conditions of the EUT. The interconnection line between the EUT and the coupling/decoupling networks shall be 2 meters in length.

- Unshielded symmetrical interconnections communication lines:

The surge is applied to the lines via gas arrestors coupling. Test levels below the ignition point of the coupling arrestor cannot be specified. The interconnection line between the EUT and the coupling/decoupling networks shall be 2 meters in length.

- High speed communications lines

Prior to the test, the correct operation of the port shall be verified; the external connection shall then be removed and the surge applied directly to the port's terminals with no coupling /decoupling network. After the surge, the correct operation of the port shall again be verified.

- Shielded lines:

- Direct application,

The EUT is isolated from ground and the surge is applied to its metallic enclosure; the termination (or auxiliary equipment) at the port(s) under test is grounded. This test applies to equipment with single or multiple shielded cables.

Rules for application of the surge to shielded lines:

a) Shields grounded at both ends

- The surge injection on the shield.


b) Shields grounded at one end

- If in the installation the shield is connected only at the auxiliary equipment, test shall be done in that configuration but with the generator still connected to the EUT side. If cable lengths allow, the cables shall be on insulated supports 0,1 m above the ground plane or cable tray.

For products which do not have metallic enclosures, the surge is applied directly to the shielded cable.

- Alternative coupling method for testing single cables in a multi-shield configuration,

Surges are applied in close proximity to the interconnection cable under test by a wire. The length of the cable between the port(s) under test and the device attached to the other end of the cable shall be the lesser of: the maximum length permitted by the EUT's specification, or 20 m. Where the length exceeds 1 m, excess lengths of cables shall be bundled at the approximate centre of the cables with the bundles 30 cm to 40 cm in length.



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 16.4 Test Results

Test mode	Mode 1	Input Power	230Vac, 50Hz
Environmental conditions	24 °C, 69% RH	Tested by	Aga Lin

Input AC power port

Voltage (kV)	Test Point	Polarity (+/-)	Observation	Performance Criterion
0.5, 1	L1-L2	+/-	Note	A

Note: The EUT function was correct during the test.

## 17 Immunity to Conducted Disturbances Induced by RF Fields (CS)

### 17.1 Test Specification

Basic Standard:	EN/IEC 61000-4-6
Frequency Range:	0.15 MHz - 80 MHz
Voltage Level:	3 V
Modulation:	1kHz Sine Wave, 80%, AM Modulation
Frequency Step:	1 % of preceding frequency value
Dwell Time	3 seconds


### 17.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
ROHDE & SCHWARZ Signal Generator	SML03	101801	Jan. 8, 2018	Jan. 7, 2019
Digital Sweep Function Generator	8120	984801	NA	NA
AR Power Amplifier	75A250AM1	306331	NA	NA
FCC Coupling Decoupling Network	FCC-801-M2-16A	01047	Jun. 20, 2018	Jun. 19, 2019
FISCHER CUSTOM COMMUNICATIONS EM Injection Clamp	F-203I-23mm	455	NA	NA
FISCHER CUSTOM COMMUNICATIONS Current Injection Clamp	F-120-9A	361	Jul. 24, 2018	Jul. 23, 2019
B&K Ear Simulator	4185	2553594	NA	NA
EM TEST Coupling Decoupling Network	CDN M1/32A	306508	Jun. 20, 2018	Jun. 19, 2019
TESEQ Coupling Decoupling Network	CDN T800	34428	Jun. 20, 2018	Jun. 19, 2019
FCC Coupling Decoupling Network	FCC-801-T4	02031	Jun. 20, 2018	Jun. 19, 2019
EM TEST Coupling Decoupling Network	CDN T2	306509	Jun. 20, 2018	Jun. 19, 2019
TESEQ Coupling Decoupling Network	CDN M232	37702	Jun. 20, 2018	Jun. 19, 2019
TESEQ Coupling Decoupling Network	CDN M332	41258	Jun. 20, 2018	Jun. 19, 2019
TESEQ Coupling Decoupling Network	CDN M332	41256	Jun. 20, 2018	Jun. 19, 2019
TESEQ Coupling Decoupling Network	CDN T400A	28569	Jun. 20, 2018	Jun. 19, 2019
TESEQ Coupling Decoupling Network	CDN T8-10	40376	Jun. 20, 2018	Jun. 19, 2019
TESEQ Coupling Decoupling Network	ISN ST08	41212	Jun. 20, 2018	Jun. 19, 2019
FCC Coupling Decoupling Network	FCC-801-M5-50A	100018	Jan. 24, 2018	Jan. 23, 2019
Software	CS_V7.4.2	NA	NA	NA

- Notes:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in CS Room No. 1.
  3. Tested Date: Oct. 26, 2018

### 17.3 Test Arrangement

- The EUT shall be tested within its intended operating and climatic conditions.
- An artificial hand was placed on the hand-held accessory and connected to the ground reference plane.
- One of the CDNs not used for injection was terminated with 50 ohm, providing only one return path. All other CDNs were coupled as decoupling networks.
- The frequency range is swept from 150 kHz to 80 MHz, using the signal level established during the setting process and with a disturbance signal of 80 % amplitude. The signal is modulated with a 1 kHz sine wave, pausing to adjust the RF signal level or the switch coupling devices as necessary. Where the frequency is swept incrementally, the step size shall not exceed 1 % of the preceding frequency value.
- Attempts should be made to fully exercise the EUT during testing, and to fully interrogate all exercise modes selected for susceptibility.



- Note:**
- The EUT clearance from any metallic obstacles shall be at least 0,5 m.
  - Interconnecting cables ( $\leq 1$  m) belonging to the EUT shall remain on the insulating support.
  - The equipment to be tested is placed on an insulating support of 0.1 meters height above a ground reference plane. All relevant cables shall be provided with the appropriate coupling and decoupling devices at a distance between 0.1 meters and 0.3 meters from the projected geometry of the EUT on the ground reference plane.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 17.4 Test Results

Test mode	Mode 1	Input Power	230Vac, 50Hz
Environmental Conditions	25 °C, 72% RH	Tested by	Aga Lin

Frequency (MHz)	Level (Vrms)	Tested Line	Injection Method	Return Path	Observation	Performance Criterion
0.15 – 80	3	AC Power	CDN-M2	CDN-T8	Note	A
0.15 – 80	3	RJ45	CDN-T8	CDN-M2	Note	A

Note: The EUT function was correct during the test.

Test mode	Mode 2	Input Power	230Vac, 50Hz
Environmental Conditions	25 °C, 72% RH	Tested by	Aga Lin

Frequency (MHz)	Level (Vrms)	Tested Line	Injection Method	Return Path	Observation	Performance Criterion
0.15 – 80	3	RJ45	CDN-T8	N/A	Note	A

Note: The EUT function was correct during the test.

## 18 Power Frequency Magnetic Field Immunity Test

### 18.1 Test Specification

Basic Standard:	EN/IEC 61000-4-8
Frequency Range:	50Hz
Field Strength:	1 A/m
Observation Time:	1 minute
Inductance Coil:	Rectangular type, 1 m x 1 m


### 18.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
HAEFELY Magnetic Field Tester	MAG 100	083794-06	NA	NA
COMBINOVA Magnetic Field Meter	MFM10	224	Apr. 24, 2018	Apr. 23, 2019
F.W.BELL 4190 Gaussmeter	4190	0743043	Mar. 12, 2018	Mar. 11, 2019

- Notes:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in EMS Room No. 1
  3. Tested Date: Oct. 24, 2018

### 18.3 Test Arrangement

- a. The equipment is configured and connected to satisfy its functional requirements.
- b. The power supply, input and output circuits shall be connected to the sources of power supply, control and signal.
- c. The cables supplied or recommended by the equipment manufacturer shall be used. 1 meter of all cables used shall be exposed to the magnetic field.



#### TABLETOP EQUIPMENT

The equipment shall be subjected to the test magnetic field by using the induction coil of standard dimension (1 m x 1 m). The induction coil shall then be rotated by 90 degrees in order to expose the EUT to the test field with different orientations.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 18.4 Test Results

Test mode	Mode 1 & Mode 2	Input Power	230Vac, 50Hz
Environmental Conditions	24 °C, 69% RH	Tested by	Aga Lin

Application	Frequency (Hz)	Field Strength (A/m)	Observation	Performance Criterion
X - Axis	50	1	Note	A
Y - Axis	50	1	Note	A
Z - Axis	50	1	Note	A

Note: The EUT function was correct during the test.

## 19 Voltage Dips and Interruptions

### 19.1 Test Specification

Basic Standard:	EN/IEC 61000-4-11
Test levels:	Voltage Dips: >95% reduction – 0.5 period 30% reduction – 25 periods Voltage Interruptions: >95% reduction – 250 periods
Interval between Event:	Minimum ten seconds
Sync Angle (degrees):	0° / 180°
Test Cycle:	3 times

### 19.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Teseq Immunity Test System	Proflin 2105	1632A00983 & 1639A01863	Sep. 27, 2018	Sep. 26, 2019
Software	WIN2120	NA	NA	NA


Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in EMS Room No. 1.

3. Tested Date: Oct. 27, 2018.

### 19.3 Test Arrangement

The EUT shall be tested for each selected combination of test levels and duration with a sequence of 3 dips/interruptions with intervals of 10 s minimum (between each test event). Each representative mode of operation shall be tested. Abrupt changes in supply voltage shall occur at 0 degree crossover point of the voltage waveform.



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 19.4 Test Results

Test mode	Mode 1	Input Power	230 Vac, 50 Hz/ 240 Vac, 50 Hz/ 100 Vac, 50 Hz
Environmental Conditions	25 °C, 61% RH	Tested by	Todd Chang

Input Power for testing: 230 Vac, 50 Hz (Nominal input Voltage)					
Voltage Reduction (%)	Duration (period)	Interval (sec)	Times	Observation	Performance Criterion
>95	0.5	10	3	Note 1	A
30	25	10	3	Note 1	A
>95	250	10	3	Note 2	B

Input Power for testing: 240 Vac, 50 Hz (Maximum rated input voltage)					
Voltage Reduction (%)	Duration (period)	Interval (sec)	Times	Observation	Performance Criterion
>95	0.5	10	3	Note 1	A
30	25	10	3	Note 1	A
>95	250	10	3	Note 2	B

Input Power for testing: 100 Vac, 50 Hz (Minimum rated input voltage)					
Voltage Reduction (%)	Duration (period)	Interval (sec)	Times	Observation	Performance Criterion
>95	0.5	10	3	Note 1	A
30	25	10	3	Note 1	A
>95	250	10	3	Note 2	B

Note: 1. The EUT function was correct during the test.  
2. The EUT reset during the test.

## 20 Pictures of Test Arrangements

### 20.1 Conducted Emission from the AC Mains Power Port



## 20.2 Asymmetric Mode Conducted Emission at Telecommunication Ports

For Mode 1




For Mode 2



### 20.3 Radiated Emission at Frequencies up to 1GHz

Mode 1



Mode 2



## 20.4 Radiated Emission at Frequencies above 1GHz

Mode 1



Mode 2



## 20.5 Harmonics Current, Voltage Fluctuations and Flicker Measurement



## 20.6 Electrostatic Discharge Immunity Test (ESD)

Mode 1





Mode 2





## 20.7 Radio-frequency, Electromagnetic Field Immunity Test (RS)

Mode 1



Mode 2



## 20.8 Electrical Fast Transient/Burst Immunity Test (EFT)

Mode 1 - Mains ports



Mode 1 - LAN



Mode 2 - LAN




## 20.9 Surge Immunity Test



## 20.10 Conducted Disturbances Induced by RF Fields (CS)


Mode 1 - Mains ports



Mode 1 - LAN



Mode 2 - LAN




## 20.11 Power Frequency Magnetic Field Immunity Test (PFMF)

Mode 1



Mode 2



## 20.12 Voltage Dips and Interruptions



## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauVeritas.com](mailto:service.adt@tw.bureauVeritas.com)

**Web Site:** [www.bureauVeritas-adt.com](http://www.bureauVeritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---