

# FE9191 FE9391-EV Fisheye Fixed Dome Network Camera User's Manual

12MP • Vandal-proof • 360° Surround View • 20M IR • Smart IR II Smart Stream II • Pixel Calculator • PoE





Rev. 1.1



## Table of Contents

Overview	
Revision History	4
Read Before Use	5
Package Contents	
Symbols and Statements in this Document	
Physical Description - FE9191 (Indoor Camera)	
Physical Description - FE9391-EV (Outdoor Camera)	
LED Definition - both models Hardware Installation - FE9191	
Hardware Installation - FE9391-EV	
Software Installation	
Ready to Use	
Network Deployment	
Setting up the Network Camera over the Internet	
Accessing the Network Camera	
Using Web Browsers	
Using RTSP Players	
Using 3GPP-compatible Mobile Devices	
Using VIVOTEK Recording Software	
Main Page	
Client Settings	
H.265/H.264 Media Options	
H.265/H.264 Protocol Options	
MP4 Saving Options	
Local streaming buffer time	
Configuration	
System > General settings	
System > Homepage layout	
System > Logs	
System > Parameters	
System > Maintenance Media > Image	
General settings	
Media > IR control	
IR illuminators	
Smart IR	
IR zone adjustment	
Image settings	
Exposure	
Privacy mask	81

Pixel Calculator	
Media > Video	
Stream settings	
Media > Audio	91
Audio Settings	91
Network > General settings	92
Network > Streaming protocols	
Network > QoS (Quality of Service)	108
Network > SNMP (Simple Network Management Protocol)	110
Network > FTP	
Security > User accounts	112
Security > HTTPS (Hypertext Transfer Protocol Secure)	114
Security > Access List	
Security > IEEE 802.1x	
PTZ > PTZ settings	
Event > Event settings	129
Event	129
Add server	133
Add media	137
Applications > Motion detection	143
Applications > DI and DO	146
Applications > Tampering detection	147
Applications > Audio detection	148
Applications > Package management - a.k.a., VADP (VIVOTEK Application Development Platform)	
Recording > Recording settings	
Local storage > SD card management	
Local storage > Content management	159
Appendix	162
URL Commands for the Network Camera	162
1. Overview	162
2. Style Convention	162
Technical Specifications	378
Technology License Notice	
Electromagnetic Compatibility (EMC)	382

## **Overview**

VIVOTEK's FE9191 and FE9391-EV are the next generation of market-leading 12-Megapixel 360° panamorph network cameras, both featuring a detailed 12-Megapixel CMOS sensor which guarantees superb image quality. Utilizing the latest in panamorph lens technology for 180° panoramic view (wall mount) or 360° surround view (ceiling/wall/foor mount) with zero blind spots, these cameras are able to provide comprehensive coverage of open areas such as airports, shopping malls, parking lots, retail stores, offces and more.

The FE9191 and FE9391-EV (IP66, IK10 rated) are the successors to FE8191 and FE8391-V in the VIVOTEK 360° surround view family. Both new models are equipped with a removable IR-cut filter and WDR Enhancement technology, allowing the cameras to maintain optimal image quality around the clock for unparalleled visibility under high-contrast lighting environments. 3D Noise Reduction technology enables the cameras to capture clear, polished video under low-light conditions. The FE9191 and FE9391-EV's use of the latest in panamorph lens technology has led to much improved image quality with a huge drop in edge distortion. The FE9391-EV is also updated with the latest in IR illumination, VIVOTEK's Smart IR II technology with Adaptive IR. Adaptive IR enables the FE9391-EV's IR illuminators to adjust to the scene together or individually to provide the best possible IR image, reducing glaring hotspots and/or underexposed dark spots.

The FE9191 and FE9391-EV will also be the frst to include a new wave of advanced Video Content Analyses (VCA). Available in 4Q 2017, these will include better object detection in order to reduce false alarms. Through advanced human detection and crowd detection features the FE9191 and FE9391-EV are the next steps in elevating surveillance cameras from image capturing devices to advanced notification instruments, allowing users to see more in smarter ways.

**Revision History** 

Rev. 1.0: Initial release. Rev. 1.1: Corrected DI/DO pin related description.

## **Read Before Use**

The use of surveillance devices may be prohibited by law in your country. The Network Camera is not only a high-performance web-ready camera but can also be part of a flexible surveillance system. It is the user's responsibility to ensure that the operation of such devices is legal before installing this unit for its intended use.

It is important to first verify that all contents received are complete according to the Package Contents listed below. Take note of the warnings in the Quick Installation Guide before the Network Camera is installed; then carefully read and follow the instructions in the Installation chapter to avoid damage due to faulty assembly and installation. This also ensures the product is used properly as intended.

The Network Camera is a network device and its use should be straightforward for those who have basic networking knowledge. It is designed for various applications including video sharing, general security/ surveillance, etc. The Configuration chapter suggests ways to best utilize the Network Camera and ensure proper operations. For creative and professional developers, the URL Commands of the Network Camera section serves as a helpful reference to customizing existing homepages or integrating with the current web server.

### **Package Contents**

- FE9391-EV or FE9191
- Mounting bracket
- Screws / desiccant bag / double-side tape / rubber seal plug / rubber washer (some only for outdoor model)
- Quick Installation Guide
- Mounting plate / star driver (ourdoor model)
- Power & I/O combo cable (sold separately in US and Canada)

Alignment stickers


## Symbols and Statements in this Document




**INFORMATION:** provides important messages or advices that might help prevent inconvenient or problem situations.

**NOTE**: Notices provide guidance or advices that are related to the functional integrity of the machine.


**Tips**: Tips are useful information that helps enhance or facilitae an installation, function, or process.






## Physical Description - FE9191 (Indoor Camera)


#### **Inner View**






## Physical Description - FE9391-EV (Outdoor Camera)

#### **Inner View**



MicroSD/SDHC/SDXC Card Slot




## **LED Definition - both models**

Item	LED Status	Description
1	Steady Red	Power on and system booting
	Red LED off	Powered off
2	Steady Red + blinking Green every 1 sec. (Green LED on for 1 sec and off for another)	Network heartbeat
	Steady Red + Green LED off	Network disconnected
3	Blinking Red every 0.15 sec. + Blinking Green every 1 sec. (Red LED on for 0.15 sec. and Green LED on for 1 sec. and off for another)	
4	Blinking Red every 0.15 sec. + blinking Green every 0.15 sec	Restoring defaults

#### **Mounting Positions**

Refer to the diagram on the right for the mounting hole positions and the dimensions of the base plate.



.13°


## Hardware Installation - FE9191

#### **Opening Dome Cover**

1. Jot down the camera's MAC address for later reference. It is especially important if you install multiple cameras at one site.




2. Open the dome cover by pressing the release button. You may squeeze the opposite edge of the dome cover if the dome cover does not come off easily. Then, follow the steps below to install the camera to either a ceiling or a wall.




It is not recommended to use an Ethernet cable with a strain relief boot. If it does, remove the boot.

3. Install an SD card if edge recording is preferred.




4. Connect the power, audio, and I/O combo cable. Connect the white header connectors to J7 and J12 connectors on the camera. The camera can also be powered by a DC12V power source.



#### **Connecting Cables**


- 5. Connect the Ethernet cable. The Ethernet cable is user-supplied.
- 6. Use an included cable tie to secure the Ethernet cable to the vertical mounting tab located on the edge of the cabling cutout.
- 7. Cut the extra length from the cable tie.




If you route cables through a drill hole on a wall/ceiling, you can simply route cables through the cabling cutout.

#### **Ceiling or Wall Mount**

- 8 Attach the supplied alignment sticker for the camera base to the a ceiling or wall.
- 9. Drill pilot holes into the ceiling. Then hammer the supplied plastic anchors into the holes. If preferred, drill a cabling hole on the ceiling/wall, and feed the cables through the hole.




10. Secure the camera the ceiling/wall using the supplied screws.




## NOTE:

You may also install the camera to a U.S. standard 4 in. junction box. You can align the camera's curved slots with the mounting holes on a junction box. Use diagonal mounting positions on the camera to match those on a junction box.




10. Arrange the cables neatly. Make sure there is a 1 cm clearance between I/O cables and the mounting tab so that cables will not get in the way when installing the dome cover.



#### Attach the Dome Cover

11. Install the plastic dome cover by aligning the snap-fit tabs on the dome cover with the slotted tabs on the camera base. Install the dome cover by pressing it evenly to the camera base.

Make sure the dome cover and the base plate are flush-aligned before pressing down. The dome cover is secured using a snap-fit mechanism.



Refer to page 29 for the rest of the configuration procedure.


## Hardware Installation - FE9391-EV

#### **Opening Dome Cover**


1. Jot down the camera's MAC address for later reference. This is especially important if you install many cameras in your surveillance deployment.




2. Use the supplied screwdriver to loosen the four screws and detach the dome cover from the camera base. Then, follow the steps below to install the camera to either a ceiling or a wall.




3. If edge recording is preferred, install a microSD card to the camera.



Prepare the wiring, and drill a cabling hole with the aid of the included alignment sticker.



4. Remove the stoppers and route cables through the openings.



#### **Connecting RJ45 Ethernet Cable**


#### RJ45 Cable Dimension (unit: mm)

Recommended cable gauge: 5 to 8mm


#### Rubber Seal Plug

#### Assembly Steps


5. Drill a hole on the rubber seal plug and insert an Ethernet cable through the opening. Strip part of the sheath from the Ethernet cable.




6. You will need an RJ45 crimping tool to attach the Ethernet wires to a connector. When done, connect the cable to the camera's Ethernet RJ45 socket.




7. Feed the Ethernet cable from the bottom of the camera and through the hole. Attach the rubber seal plug for water proofing.



8. Use the included cable tie to fasten the top of the rubber seal so that the position of the Ethernet cable will not alter. When done, cut the excessive part of the cable tie.




9. If the DI/DO combo cable is preferred, install the supplied rubber washer to the cable as shown in the picture. Feed the cable from the bottom of the camera and tighten the plastic nut for waterproofing.



If you are not powering the camera over a PoE switch, use the DC 12V connector on the DI/DO

10. Replace the desiccant bag on the camera. This is very important to reduce the moisture level inside the camera. Replace it whenever you open the camera dome cover.






There are two installation options:

A. Direct installation

- B. Using the mount bracket.
- A-1. Attach the supplied alignment sticker for camera base to the ceiling/wall. Using the three circles on the sticker, drill three pilot holes into the ceiling. Then hammer the three supplied plastic anchors into the holes.


If preferred, drill a cabling hole on the ceiling or wall, and feed the cables through the hole.




A-2. Secure the camera base to the ceiling/wall with three supplied screws.



A-3. Connect the white headers of the DI/DO combo cable to the J3 and J7 headers on the camera.




A-4. Attach the dome cover. Secure the four screws using the supplied T10 stardriver. Make sure all camera parts are securely installed.



#### MIMPORTANT:

Arrange the cables neatly to avoid getting in the way when the dome cover is attached.


If you are not using the mount bracket, skip to step 11.






Installation Type B: Using the mount bracket.

B-1. Attach the supplied alignment sticker for the supplied mounting plate to the ceiling or wall. Note that there are two different alignment stickers.




Using the three circles on the sticker, drill three holes into the ceiling. Then hammer the three supplied plastic anchors into the holes.


B-2. Arrange and feed the cables through the side of the mount bracket. Secure the mount bracket to the ceiling or wall using the supplied screws.




B-3. Install the camera to the mount bracket. Align the double-sided keyhole slot with the largest rivet head on the mount bracket. Turn the camera counter-clockwise as shown below.




B-4. A small mount hole will be revealed through the keyhole slot. Secure the camera by tightening a flat-head screw.




B-5. Install the dome cover using the T10 star driver.



#### Skip to step 11.






U.S. standard 4" junction box.

You may also use the diagonal holes on the mounting plate, marked as A, B, or C, to install the camera to a U.S. standard 4 in. junction box.

#### **General Connection (without PoE)**

- 11. If using the DI/DO combo cable.
- 11-1. Connect RJ45 Ethernet cable to a switch.
- 11-2. Connect the power cable from the Network Camera to a power outlet.
- 11-3. If you have external devices such as sensors and alarms, make the connection from the general I/O terminal block.



#### M IMPORTANT:

If DC power is preferred, it should comply with: O/P: 12VDC, 2A min., L.P.S. per IEC 60950-1.

## **Software Installation**

12. Install the **Shepherd** utility, which helps you locate and configure your Network Camera in the local network. If your camera comes without the CD, go to VIVOTEK's website, and locate the utility in the Downloads > Software page.



12-1. Run the Shepherd utility.

12-2.	The program	will conduct ar	analysis of v	your network	environment.
					•••••••••••••••••••••••••••••••••••••••

а,			16	Al devices 2010
Batus	Michel	2	MAG	Fernance
	APP OF DATA	182,108.4,123	00-03-01-28-81-50	2+50
	3494167	(0):00000000000000000000000000000000000	00.01.01.00.56.00	010036
	101010-01	1942718-0428	. 09.62423-024581	010083
	1210101-014	102,108,4148	10-61-01-49-85-62	0100
	308122-0	101103-4147	0040-014840-10	\$1,000,0
	124343-414	192,152-4,105	00.02/01-05494.03	0105+
	PRICE CELENS	752.100.06.7	00.00.01.48.00.14	4000
	944.57	101214.214247	manage inter	1723.0
	WALT.	192108-0778	1040-004+33.W	111343.2
	widt	Pat. 108.4 191	1144-0211-02146	LIEUR
	wald.	PRINT ALC: L	14-01-02-04-20-05	11110



- 12-3. The program will search for all VIVOTEK network devices on the same LAN.
- 12-4. After a brief search, the installer window will prompt. Click on the MAC and model name that matches the one printed on the product label. You can then double-click on the address to open a management session with the Network Camera.



(4)		6	E	NR I
Inte	Mudel		UNC .	Destaura
	FE9191	192.168.4.151	00-02-D1-73-02-02	
	625067-691	152,158-8,148		04027
	HURLITY'N	182.168.4,147	0002D1730202	-0100e,8
	Scittoria-bris.	192,558,4,105	10-22-07-02-08-88	11234
	eut.	103,254,8,13	00-00-00-00-01	1.12.1.8
	what	112.114.4.112	2048-00-14 32-14	1.13.0.2
	10.07	102,164,4,131	224836-843233	1,121.0
	1937	102/1454 119	54.53 425 (1) 491-10	10103
	VALUE	112,156,4,130	34.42-55.00.11.18	1.12.1.6
	(TTHE O	140.034.010.729	11.45-10.3625-00	11110
	1000	1019,254,102,144	44-05-64-01-85-10	1.16.1.8

#### **Forceful Password Configuration**

- 13. The first time you log in to the camera, the firmware will prompt for a password configuration for security concerns.
- 13-1. Since your camera is used for the first time, there is no password. Enter "root" as the user name, and nothting for the password.

Windows Security	×
The server 169.254.205.239 is asking for your user name and password. The server reports that it is from streaming_server.	
Warning: Your user name and password will be sent using basic authentication on a connection that isn't secure.	
root Remember my credentials	
確定 取消	

13-2. Enter the combination of alphabetic and numeric characters to fulfill the password strength. requirement. The default name for the camera administrator is "root", and can not be changed.

		Language
Configure password At least 8 characters with no space, one character(uppercase or lowercase), and character		
User name :	root	
User password :	•••••• Medium	
Confirm user password :	•••••••	
	<ul> <li>Enable https connection to secure the configuration for password</li> </ul>	
*The new password will be applied to al	Il connections	
	Save Cancel	]

Some, but not all special ASCII characters are supported: !,  $, %, -, ., @, ^, _, and ~$ . You can use them in the password combination.


網頁訊息		×
<u>^</u>	You have used invalid characters. These characters are valid:A-Z, a-z, 0-9 and !\$%@^_~	
	確定	

13-3. Another prompt will request for the password you just configured. Enter the password and then you can start configure your camera and see the live view.

Windows Security	
The server 169.254.205.239 is asking password. The server reports that it	
Warning: Your user name and passy authentication on a connection that	-
root  Foot  Remember my cr	• • • • • •
	確定 取消

## **Ready to Use**

- 1. A browser console with the Network Camera should prompt as shown below.
- 2. You should be able to see live video from your camera. You may also install the 32-channel recording software, VAST, in a deployment consisting of multiple cameras. For its installation details, please refer to its related documents.



#### Hardware Reset

The reset button is used to reset the system or restore the factory default settings. Sometimes resetting the system can return the camera to normal operation. If the system problems remain after reset, press the reset button longer to restore the factory settings and install again.

<u>Reset</u>: Press and release the recessed reset button with a straightened paper clip. Wait for the Network Camera to reboot.


<u>Restore</u>: Press and hold the recessed reset button for at least several seconds to restore. Note that all settings will be restored to factory defaults.

#### SD/SDHC/SDXC Card Capacity


This network camera is compliant with **SD/SDHC/SDXC 32GB, 64GB**, and other preceding standard SD cards.

#### **DI/DO Diagram**

Dry contact with external DC power source to supply a relay. Dry contact is the safest connection to protect devices.




Wet contact with external DC power source to supply a relay.



- 1. The DO+ pin (5V) provides 5V±10% output voltages, and the max. load is 50mA.
- The max. voltage for the DO- pins is 30VDC (External power). In order to control AC devices, the above diagram can be taken in consideration. The diagram uses a relay to control the ON/OFF condition of the AC device.
- 3. An external relay can be triggered by using DO+ or by an external power source, depending on the type of relay you use.
- 4. In case of using an individual relay (instead of using a relay module), for protection against voltage or current spikes, a transient voltage suppression diode must be connected in parallel with the inductive load.

Dry contact and using camera's DO+ to supply a relay.



## **Network Deployment**

Setting up the Network Camera over the Internet


There are several ways to set up the Network Camera over the Internet. The first way is to set up the Network Camera behind a router. The second way is to utilize a static IP. The third way is to use PPPoE.

#### Internet connection via a router

Before enabling the access to the Network Camera over the Internet, make sure you have a router and follow the steps below.

- 1. Connect your Network Camera behind a router, the Internet environment is illustrated below. Regarding how to obtain your IP address, please refer to Software Installation on page 27 for details.
- 2. In this case, if the Local Area Network (LAN) IP address of your Network Camera is 192.168.0.3, please forward the following ports for the Network Camera on the router.
  - Secondary HTTP port: 8080
  - RTSP port: 554
  - RTP port for audio: 5558
  - RTCP port for audio: 5559
  - RTP port for video: 5556
  - RTCP port for video: 5557

If you have changed the port numbers on the Network page, please open the ports accordingly on your router. For information on how to forward ports on the router, please refer to your router's user's manual.  Find out the public IP address of your router provided by your ISP (Internet Service Provider). Use the public IP and the secondary HTTP port to access the Network Camera from the Internet. Please refer to Network Type on page 92 for details.



For example, your router and IP settings may look like this:

Device	IP Address: internal port	IP Address: External Port (Mapped port on the router)
Public IP of router	122.146.57.120	
LAN IP of router	192.168.2.1	
Camera 1	192.168.2.10:80	122.146.57.120:8000
Camera 2	192.168.2.11:80	122.146.57.120:8001

Configure the router, virtual server or firewall, so that the router can forward any data coming into a preconfigured port number to a network camera on the private network, and allow data from the camera to be transmitted to the outside of the network over the same path.

From	Forward to
122.146.57.120:8000	192.168.2.10:80
122.146.57.120:8001	192.168.2.11:80

When properly configured, you can access a camera behind the router using the HTTP request as follows: http://122.146.57.120:8000

If you change the port numbers on the Network configuration page, please open the ports accordingly on your router. For example, you can open a management session with your router to configure access through the router to the camera within your local network. Please consult your network administrator for router configuration if you have troubles with the configuration.

For more information with network configuration options (such as that of streaming ports), please refer to Configuration > Network Settings. VIVOTEK also provides the automatic port forwarding feature as an NAT traversal function with the precondition that your router must support the UPnP port forwarding feature.

	Network > General settings
System	Network type Port
Media	* LAN
Network	Get P address automatically
General settings	Use fixed P address
Streaming protocols	Enable UPnP presentation
DOMS	P Enable UPnP port forwarding
QoS	O PPPoE
SNMP	Enable Pv6
Security	The device is configuring now. Your browser will reconnect IPv6 information to http://192.168.4.140.60/
PTZ	Manually If the connection fails, please manually enter the above P address in your browser.
Event	Save

#### Internet connection with static IP

Choose this connection type if you are required to use a static IP for the Network Camera. Please refer to LAN configuration on page 92 for details.


#### Internet connection via PPPoE (Point-to-Point over Ethernet)

Choose this connection type if you are connected to the Internet via a DSL Line. Please refer to PPPoE on page 115 for details.

## Set up the Network Camera through Power over Ethernet (PoE)

### When using a PoE-enabled switch


The Network Camera is PoE-compliant, allowing transmission of power and data via a single Ethernet cable. Follow the below illustration to connect the Network Camera to a PoE-enabled switch via an Ethernet cable.



- 1. The camera is only to be connected to PoE networks without routing to outside plants.
- 2. For PoE connection, use only UL listed I.T.E. with PoE output.

#### When using a non-PoE switch

If your switch/router does not support PoE, use a PoE power injector (optional) to connect between the Network Camera and a non-PoE switch.





If you encounter problems with displaying live view or the onscreen plug-in control, you may try to remove the plug-ins that might have been installed on your computer. Remove the following folder: C:\Program Files (x86)\Camera Stream Controller\.

- 2. If you forget the root (administrator) password for the camera, you can restore the camera defaults by pressing the reset button for longer than 5 seconds.
- 3. If DHCP is enabled in your network, and the camera cannot be accessed, run the Shepherd utility to search the network. If the camera has been configured with fixed IP that does not comply with your local network, you may see its default IP 169.254.x.x. If you still cannot find the camera, you can restore the camera to its factory defaults.
- 4. If you change your network parameters, e.g., added a connection to a LAN card, re-start the Shepherd utility.

# **Accessing the Network Camera**

This chapter explains how to access the Network Camera through web browsers, RTSP players, 3GPP-compatible mobile devices, and VIVOTEK recording software.


## **Using Web Browsers**

## 

- Currently the Network Camera utilizes 32-bit ActiveX plugin. You CAN NOT open a management/view session with the camera using a 64-bit IE browser.
- If you encounter this problem, try execute the lexplore.exe program from C:\Windows\ SysWOW64. A 32-bit version of IE browser will be installed.
- On Windows 7, the 32-bit explorer browser can be accessed from here: C:\Program Files (x86)\Internet Explorer\iexplore.exe

Use the Shepherd utility to access the Network Cameras on the LAN.


- If your network environment is not a LAN, follow these steps to access the Network Camera:
- 1. Launch your web browser (e.g., Microsoft<sup>®</sup> Internet Explorer, Mozilla Firefox, or Netscape).
- 2. Enter the IP address of the Network Camera in the address field. Press Enter.
- 3. The live video will be displayed in your web browser.
- 4. If it is the first time installing the VIVOTEK network camera, an information bar will prompt as shown below. Follow the instructions to install the required plug-in on your computer.



# NOTE:

For **Mozilla Firefox** users, your browser will use **Quick Time** to stream live video. If you do not have QuickTime on your computer, please download QuickTime from Apple Inc's website, and then launch your web browser.






# -ˈo͡ː- Tips:


- 1. The onscreen Java control can malfunction under the following situations: A PC connects to different cameras that are using the same IP address (or the same camera running different firmware versions). Removing your browser cookies will solve this problem.
- 2. If you encounter problems with displaying the configuration menus or UI items, try disable the Compatibility View on IE8 or IE9.



You may also press the F12 key to open the developer tools utility, and then change the Browser Mode to the genuine IE8 or IE9 mode.



 In the event of plug-in compatibility issues, you may try to uninstall the plug-in that was previously installed.



**?** 🗙

# 

- 1. By default, your Network Camera is not password-protected. To prevent unauthorized access, it is highly recommended to configure a password for your camera later. *For more information about how to enable password protection, please refer to Security on page 112.*
- 2. If you see a dialogue box indicating that your security settings prohibit running ActiveX Controls®, please enable ActiveX Controls for your browser.

Internet Options

To enable the ActiveX<sup>®</sup> Controls for your browser:

2-1. Choose Tools > Internet Options > Security > Custom Level.


2-2. Look for Download signed ActiveX<sup>®</sup> controls; select Enable or Prompt. Click **OK**.

General Security Privacy Content Connections Programs Advanced
Select a Web content zone to specify its security settings.
Internet Local intranet Trusted sites
Internet This zone contains all Web sites you haven't placed in other zones Sites
Security level for this zone
<b>Custom</b> Custom settings. - To change the settings, click Custom Level. - To use the recommended settings, click Default Level.
Custom Level Default Level
Security Settings
Settings:
Settings: ActiveX controls and plug-ins Download signed ActiveX controls Disable
Settings:
Settings: ActiveX controls and plug-ins Download signed ActiveX controls Disable
Settings: ActiveX controls and plug-ins Download signed ActiveX controls Disable Enable Prompt Download unsigned ActiveX controls Disable
Settings: ActiveX controls and plug-ins Download signed ActiveX controls Disable Enable Prompt Download unsigned ActiveX controls Disable Enable Enable Disable Enable
Settings: ActiveX controls and plug-ins Download signed ActiveX controls Disable Enable Prompt Download unsigned ActiveX controls Disable Enable Prompt
Settings: ActiveX controls and plug-ins Download signed ActiveX controls Disable Enable Prompt Download unsigned ActiveX controls Disable Enable Prompt Disable Initialize and script ActiveX controls not marked as safe Disable
Settings: ActiveX controls and plug-ins Download signed ActiveX controls Disable Enable Prompt Download unsigned ActiveX controls Disable Enable Prompt Jinitialize and script ActiveX controls not marked as safe Disable Enable Prompt Settings:
Settings: ActiveX controls and plug-ins Download signed ActiveX controls Disable Enable Prompt Download unsigned ActiveX controls Disable Enable Prompt Initialize and script ActiveX controls not marked as safe Disable Enable Prompt Market ActiveX controls not marked as safe Disable Enable Prompt Market ActiveX controls not marked as safe Disable Enable Prompt Market ActiveX controls not market as safe Disable Prompt Prompt Prompt
Settings:
Settings: ActiveX controls and plug-ins Download signed ActiveX controls Disable Enable Prompt Download unsigned ActiveX controls Disable Enable Prompt Initialize and script ActiveX controls not marked as safe Disable Enable Prompt Market and script ActiveX controls not marked as safe Disable Enable Prompt Market and script ActiveX controls not market as safe Disable Enable Prompt Market and script ActiveX controls not market as safe Disable Enable Prompt Market and script ActiveX controls not market as safe Disable Enable Prompt Prompt
Settings: ActiveX controls and plug-ins Download signed ActiveX controls Disable Enable Prompt Download unsigned ActiveX controls Disable Enable Prompt Initialize and script ActiveX controls not marked as safe Disable Enable Prompt Initialize and script ActiveX controls not marked as safe

2-3. Refresh your web browser, then install the ActiveX<sup>®</sup> control. Follow the instructions to complete installation.

## **Using RTSP Players**

To view the H.265 or H.264 streaming media using RTSP players, you can use one of the following players that support RTSP streaming.



- 1. Launch the RTSP player.
- 2. Choose File > Open URL. A URL dialog box will prompt.
- 3. The address format is rtsp://<ip address>:<rtsp port>/<RTSP streaming access name for stream1 to stream4>

As most ISPs and players only allow RTSP streaming through port number 554, please set the RTSP port to 554. For more information, please refer to RTSP Streaming on page 99. For example:

Open URL			
Enter an Internet URL to op	en:		
rtsp://192.168.5.151:554/	live.sdp		~
		OK	Cancel

4. The live video will be displayed in your player. For more information on how to configure the RTSP access name, please refer to RTSP Streaming on page 99 for details.



## NOTE:

Quick Time player only supports the playback of H.264 stream, and not the MJPEG stream. In terms of audio codec, Quick Time only supports AAC. Since this camera supports G.711 codec, audio is not available on Quick Time.

VLC player supports H.264/MPEG-4/ MJPEG, and all audio codecs supported by VIVOTEK's cameras.

The RTSP players will show the original circular-shape image. You can access the Regional views via the ST7501 or VAST software. See page 100 for an example.

## **Using 3GPP-compatible Mobile Devices**

To view the streaming media through 3GPP-compatible mobile devices, make sure the Network Camera can be accessed over the Internet. For more information on how to set up the Network Camera over the Internet, please refer to Setup the Network Camera over the Internet on page 35.

To utilize this feature, please check the following settings on your Network Camera:

- 1. Because most players on 3GPP mobile phones do not support RTSP authentication, make sure the authentication mode of RTSP streaming is set to disable. For more information, please refer to RTSP Streaming on page 99.
- 2. As the the bandwidth on 3G networks is limited, you will not be able to use a large video size. Please set the video and audio streaming parameters as listed below. For more information, please refer to Stream settings on page 84.

Video Mode	MPEG-4
Frame size	176 x 144
Maximum frame rate	5 fps
Intra frame period	1S
Video quality (Constant bit rate)	40kbps
Audio type (GSM-AMR)	12.2kbps

- 3. As most ISPs and players only allow RTSP streaming through port number 554, please set the RTSP port to 554. For more information, please refer to RTSP Streaming on page 99.
- 4. Launch the player on the 3GPP-compatible mobile devices (e.g., Real Player).
- 5. Type the following URL commands in the URL field.

The address format is rtsp://<public ip address of your camera>:<rtsp port>/<RTSP streaming access name for stream 3>.

For example:

Open URL				
Enter an Internet URL to op	en:			
rtsp://192.168.5.151:554/live.sdp				
		OK Cancel		

## NOTE:

Quick Time player only supports the playback of H.265 or H.264 stream, and not the MJPEG stream. In terms of audio codec, Quick Time only supports AAC. Since this camera supports G.711 codec, audio is not available on Quick Time.

VLC player supports H.265/H.264/MPEG-4/MJPEG, and all audio codecs supported by VIVOTEK's cameras.

# Using VIVOTEK Recording Software

You can download a VAST recording software from VIVOTEKs website. The VAST software allows simultaneous monitoring and video recording for multiple Network Cameras. Please install the recording software; then launch the program to add the Network Camera to the Channel list. For detailed information about how to use the recording software, please refer to the user's manual of the software or download it from http://www.vivotek.com.



# Main Page

This chapter explains the screen elements on the main page. It is composed of the following sections: VIVOTEK INC. Logo, Host Name, Camera Control Area, Configuration Area, and Live Video Window.



## **VIVOTEK INC. Logo**


Click this logo to visit the VIVOTEK website.

#### **Host Name**

The host name can be customized to fit your needs. For more information, please refer to System > General Settings on page 58.

### **Camera Control Area**

**Display mode:** This is a brand new configuration menu exclusively designed for Fisheye cameras. Due to the fisheye lens' wide coverage of 180° hemispheric and 360° panoramic views and to manipulate the details within, the following display modes are provided:



108R - One Original and eight Regional views

\* Most display modes are available in the Ceiling mount type.


\* See following discussions for detailed explanation of these modes. If selected, the Wall mount type provides another two distinctive modes.

## 10 (Original) Display mode:

When mounted on a ceiling, the fisheye camera can cover an approximate of 64 m<sup>2</sup> surveillance area (installed at a height of approximately 3 meters), while still keeping details in videos with recognizable facial features of people trafficking through the area.

The 1O view is especially adequate for taking an overview glimpse of the surveillance area when mounted on the ceiling.

# 10 View (Original View)



#### **1P** (Single Panoramic) Display mode:

With image correction algorithms in firmware, the hemispheric image is transformed into a rectilinear stripe in the 1P display mode. Viewers can use the PTZ panel or simply use mouse swipe to quickly move through the 360° panoramic view. (Mouse control on the Panoramic view is available with the Ceiling mount type.)

When mounted on a wall, this mode can cover a 180° overview from side to side, e.g., on the entrance of a building or a corridor.

Life View


 Mega Fixel Network Camera

 Swipe to scroll horizontally

Note that the 1P view is apt for an overview, the Zoom in/out function does not apply in this mode.

### **1R** (Single Regional) Display mode:


The 1R mode provides access to one image section within the hemisphere. You can zoom in or out (using the mouse wheel or PTZ panel) or travel to other areas in the hemisphere using mouse clicks and swipes. A single click on a particular object can bring the object to the center of your view window. Click and hold down the left mouse button, and you can swipe the view in all directions.




### 2P (Dual Panoramic View) Display mode:

Similar to 1P, the 2P display mode provides simultaneous access to both the left and right sections of a hemisphere. Both panoramic views are corrected into a more viewable dewarped image. Viewers can use a mouse click and swipe to quickly scroll horizontally through the surveillance area.

\* Note that the dividing line falls approximately on the center of the VIVOTEK logo on the camera.



Converted to rectilinear view (Dewarp)




### **103R** (One Original & Three Regional) Display mode:

The 1O3R mode provides access to multiple live view sections within the hemisphere and the reference to their relative positions on an Original circular view. The FOV indicators (#1  $\sim$  #3) interact with your current operation as you may zoom in/out or move the live view window to a different place.

You can zoom in or out or travel to other areas within the hemisphere using identical methods as previously described in the 1R mode.

You can also change the locations of Regional views by dragging the FOV indicators on the "Original" circular view.




#### 103R (Original & Regional) Mode Screen Control

# -ˈo͡ː- Tips:

In a Regional view displaying 100% of video feed (via the Resize buttons - see page 51), your mouse wheel can be used to scroll the view window vertically before you click on a live image. After you click on the live image, the mouse wheel becomes the zoom in/out tool.

#### 4R (Four Regional) Display mode:

The view control and look and feel are identical to that as described in the 1O3R mode except that the Original circular view is absent from this mode.




### 4R PRO (Four Regional Proactive) Display mode:

The 4R PRO mode is similar to the 4R mode except that the quad view windows consecutively rotate in correspondence to the change of view area in one window. Note that zoom in/out and tilt control is not available in this mode.

#### **108R** (One Original and Eight Regional) Display mode:

The view control and look and feel are identical to that as described in the 1O3R mode.

Note that if you change the position of a view in hemisphere, e.g., the #3 window, you may lose the configuration change by switching to another display mode. The live view window does not automatically save your view section layout.



<u>Video Stream</u>: This Network Camera supports multiple streams (stream  $#1 \sim #4$ ) simultaneously. You can select any one of them for live viewing. For more information about multiple streams, please refer to page 84 for detailed information.

<u>Manual Trigger</u>: Click to manually enable or disable an event trigger. Please configure an event setting before enabling this function. A total of 3 or 4 event settings can be configured. For more information about event setting, please refer to page 129. If you want to hide this item on the homepage, please go to the **System > Homepage Layout > General settings > Customized button** to deselect the "show manual trigger button" checkbox.

Digital Output: Click to turn the digital output device on or off.

#### **PTZ Control Panel:** Up **Return to Home Position** Right Left Down Zoom In Zoom Out Zoom + Start the Panoramic Rotate Pano. Stop Rotate rotation Stop Auto Pano or Rotate

Pano.: Click this button to start the automatic horizontal pan (360° continuous rotation).

Stop: Click this button to stop the Auto Pano and Auto Rotate functions.

<u>Rotate</u>: Once the Administrator has configured the list of preset positions (including the zoom-in action on a particular position), click this button to command the camera to display the preset positions in a consecutive order. The Network Camera will display those positions continuously. For more information, please refer to PTZ control on page 126.

No was		ANA VIE	All A			
	A Home		1		n speed	0
( <b>1</b>		111160	a			Ċ.
•	Zoom	•		Zo Pa	om speed noramic speed to: - Selectione	0
Proset and ro	Zoon tata settings eefitication	•	1	Zo Pa Go	om speed noramic speed to - Selectione Rotale speed	0
Preset and ro Name Add pre	Zoon tata settings eefitication			Zo Pa Go S Z Rotate locate	om speed noramic speed to - Selectione Rotale speed	0
Proset and ro Name Add pro	Zoon tata settings eefitication	•	1	Zo Pa Go ⊽ Rotate locato ⊽ 1	om speed noramic speed to - Selectione Rotale speed	0
Preset and ro Name Add pro	Zoon tata settings eefitication	•		Zo Pa Go V Rotate locato V 1 V 2 2	om speed noramic speed to - Selectione Rotale speed	0
Proset and ro Name Add pro	Zoon tata settings eefitication	•		20 Pa 00 ≶ 7 Rotate locatio © 1 © 2 2 2 3	om speed noramic speed to - Selectione Rotale speed	0
Preset and ro Name Add pro	Zoon tata settings eefitication	•		Zo Pa Go V Rotate locato V 1 V 2 2	om speed noramic speed to - Selectione Rotale speed	0

Pan speed	Tilt speed	Zoom speed	Panoramic speed	
-5	-5	-5	-	Slower
-4	-4	-4	-	
-3	-3	-3	-	
-2	-2	-2	-	
-1	-1	-1	-	
0	0	0	0	
1	1	1	1	
2	2	2	2	
3	3	3	3	
4	4	4	4	
5	5	5	5	Faster

Pan /Tilt /Zoom speed: Adjust the speed of these controls when exerted:

#### **Configuration Area**

<u>Client Settings</u>: Click this button to access the client setting page. For more information, please refer to Client Settings on page 55.

<u>Configuration</u>: Click this button to access more of the configuration options provided with the Network Camera. It is suggested that a password is applied to the Network Camera so that only the administrator can configure the Network Camera. For more information, please refer to the description for the Configuration menus on page 57.

Language: Click this button to choose a language for the user interface. Language options are available in: English, Deutsch, Español, Français, Italiano, 日本語, Português, 簡体中文, and 繁體中文. You can also change a language on the Configuration page; please refer to page 57.

#### **Hide Button**

You can click the hide button to hide the control panel or display the control panel.

#### **Resize Buttons**

ET Auto ET 100% ET 50% ET 25% .

Click the Auto button, the video cell will resize automatically to fit the monitor. Click 100% is to display the original homepage size. Click 50% is to resize the homepage to 50% of its original size.

Click 25% is to resize the homepage to 25% of its original size.

■ The following window is displayed when the video mode is set to MJPEG:



<u>Video Title</u>: The video title can be configured. For more information, please refer to Media > Image on page 69.

<u>Time</u>: Display the current time. For more information, please refer to Media > Image on page 69.

<u>Title and Time</u>: Video title and time can be stamped on the streaming video. For more information, please refer to Media > Image on page 69.

## 2.0x Title 2014/03/05 10:39:08

<u>Video Control Buttons</u>: Depending on the camera model and your current configuration, some buttons may not be available.

Snapshot: Click this button to capture and save still images. The captured images will be displayed in a pop-up window. Right-click the image and choose **Save Picture As** to save it in JPEG (\*.jpg) or BMP (\*.bmp) format.

Start MP4 Recording: Click this button to record video clips in MP4 file format to your computer. Press the Stop MP4 Recording button to end recording. When you exit the web browser, video recording stops accordingly. To specify the storage destination and file name, please refer to MP4 Saving Options on page 56 for details.

Full Screen: Click this button to switch to full screen mode. Press the "Esc" key to switch back to normal mode.

Please refer to page 126 for PTZ settings.

#### **Live Video Window**

■ The following window is displayed when the video mode is set to H.265 or H.264:



<u>Video Title</u>: The video title can be configured. For more information, please refer to Video settings on page 84.

<u>H.264 Protocol and Media Options</u>: The transmission protocol (TCP or UDP, etc.)and media options for H.264 video streaming. For further configuration, please refer to Client Settings on page 55.

<u>Time</u>: Display the current time. For further configuration, please refer to Media > Image > Genral settings on page 69.

<u>Title and Time</u>: The video title and time can be stamped on the streaming video. For further configuration, please refer to Media > Image > Genral settings on page 69.

<u>Video and Audio Control Buttons</u>: Depending on the Network Camera model and Network Camera configuration, some buttons may not be available.

Snapshot: Click this button to capture and save still images. The captured images will be displayed in a pop-up window. Right-click the image and choose **Save Picture As** to save it in JPEG (\*.jpg) or BMP (\*.bmp) format.

Pause: Pause the transmission of the streaming media. The button becomes the	Resume button
er clicking the Pause button.	

Stop: Stop the transmission of the streaming media. Click the Resume button to continue transmission.

Start MP4 Recording: Click this button to record video clips in MP4 file format to your computer. Press the Stop MP4 Recording button to end recording. When you exit the web browser, video recording stops accordingly. To specify the storage destination and file name, please refer to MP4 Saving Options on page 56 for details.


Volume: When the Mute function is not activated, move the slider bar to adjust the volume on the local computer.

Mute: Turn off the volume on the local computer. The button becomes the Audio On button after clicking the Mute button.

**Talk:** Click this button to talk to people around the Network Camera. Audio will project from the external speaker connected to the Network Camera. Click this button again to end talking transmission.

Mic Volume: When the W Mute function is not activated, move the slider bar to adjust the microphone volume on the local computer.

**Full Screen**: Click this button to switch to full screen mode. Press the "Esc" key to switch back to normal mode.



# **Client Settings**

This chapter explains how to select the stream transmission mode and saving options on the local computer. When completed with the settings on this page, click **Save** on the page bottom to enable the settings.

#### H.265/H.264 Media Options

 H.264 media opt	ions
Video and audio Video only	
Audio only	

Select to stream video or audio data or both. This is enabled only when the video mode is set to H.264.

#### H.265/H.264 Protocol Options

[	UDP Unicast UDP Multicast	otions
	TCP	
	HTTP	

Depending on your network environment, there are four options with the transmission protocols with the H.264 streaming:

<u>UDP unicast</u>: This protocol allows for more real-time audio and video streams. However, network packets may be lost due to network burst traffic and images may be broken. Activate UDP connection when occasions require time-sensitive responses and the video quality is less important. Note that each unicast client connecting to the server takes up additional bandwidth and the Network Camera allows up to ten simultaneous accesses.

<u>UDP multicast</u>: This protocol allows multicast-enabled routers to forward network packets to all clients requesting streaming media. This helps to reduce the network transmission load of the Network Camera while serving multiple clients at the same time. Note that to utilize this feature, the Network Camera must be configured to enable multicast streaming at the same time. For more information, please refer to RTSP Streaming on page 99.

<u>TCP</u>: This protocol guarantees the complete delivery of streaming data and thus provides better video quality. The downside of this protocol is that its real-time effect is not as good as that of using the UDP protocol.

<u>HTTP</u>: This protocol allows the same quality as TCP protocol without needing to open specific ports for streaming under some network environments. Users behind a firewall can utilize this protocol to allow camera's streaming data to pass through.

#### Two way audio

Two way audio	 
Half-duplex	
Full-duplex	

<u>Half duplex</u>: Audio is transmitted from one direction at a time, e.g., from a PC holding a web console with the camera.

Full duplex: Audio is transmitted in both directions simultaneously.

#### **MP4 Saving Options**

MP4 saving options								
Folder:	D:\Record3	Browse						
File name prefix:	CLIP							
V Add date and	ate and time suffix to file name							

Users can record live video as they are watching it by clicking the estimation and file name. "Start MP4 Recording" button on the main page. Here, you can specify the storage destination and file name.

Folder: Specify a storage destination for the recorded video files.

File name prefix: Enter the text that will be appended to the front of the video file name.

Add date and time suffix to the file name: Select this option to append the date and time to the end of the file name.



#### Local streaming buffer time

Γ	Local	Streaming Buffer Time
	0	Millisecond
	Save	

Due to possible occurrences of unsteady network transmission, live streaming may lag and not be very smoothly. If you enable this option, the live streaming will be stored on the client PC's cache memory for a few seconds before being played on the client computer's live view window. This helps produce a smoothlier live streaming. If you enter a vlue of 3,000 milliseconds, the streaming will delay for 3 seconds.

# Configuration

Click **Configuration** on the main page to enter the camera setting pages. Note that only Administrators can access the configuration page.

VIVOTEK provides an easy-to-use user interface that helps you set up your network camera with minimal effort. In order to simplify the user interface, detailed information will be hidden unless you click on the function item. When you click on the first sub-item, the detailed information for the first sub-item will be displayed; when you click on the second sub-item, the detailed information for the second sub-item will be displayed and that of the first sub-item will be hidden.

The following is the interface of the main page:

<b>VIVOTEK</b>							
WWW.VIVOTER.COM		Home	Client settings	Configuration	Language		
	System > General settings						
System	System		1	I Navigation Area	1		
General settings	Host name:	Mega-Pixel Network Camera					
Homepage layout Logs	Turn off the LED indicator						
Parameters	System time						
Maintenance	Time zone: GMT+08:00 Beijing, Chongqing,	Hong Kong, I	Kuala Lumpur, Sinqap	ore, Taipei 💌			
Media Network	Note: You can upload your daylight saving time rules on <u>Maintenance</u> page or use the camera default value.						
network	Keep current date and time						
Security	Synchronize with computer time						
РТΖ	Manual						
Event	Automatic						
Applications	-Configuration List			S	ave		
Recording							
Local storage							
Version: 0100a	- Firmware Version						

Each function on the configuration list will be explained in the following sections.

The Navigation Area provides access to all different views from the **Home** page (for live viewing), **Configuration** page, and multi-language selection.

System

## System > General settings

This section explains how to configure the basic settings for the Network Camera, such as the host name and system time. It is composed of the following two columns: System and System Time.

System	
Host name:	Mega-Pixel Network Camera
Turn off the LED indicator	

Host name: Enter a desired name for the Network Camera. The name will be displayed at the top center of the main page.

Turn off the LED indicator: Click to disable the onboard LEDs.

#### System time

ime zone:	GMT+08:00 Beijing, Chongqing, Hong Kong, Kuala Lumpur, Singapore, Taipei 💌
Note: You default va	can upload your daylight saving time rules on <u>Maintenance</u> page or use the camera lue.
Keep cu	rrent date and time
Synchro	nize with computer time
🖱 Manual	
Automat	ic

<u>Time zone</u> : Select the appropriate time zone from the list. If you want to upload Daylight Savings Time rules, please refer to **System > Maintenance > Import/ Export files** on page 66 for details.

<u>Keep current date and time</u>: Select this option to preserve the current date and time of the Network Camera. The Network Camera's internal real-time clock maintains the date and time even when the power of the system is turned off.

<u>Synchronize with computer time</u>: Select this option to synchronize the date and time of the Network Camera with the local computer. The read-only date and time of the PC is displayed as updated.

<u>Manual</u>: The administrator can enter the date and time manually. Note that the date and time format are [yyyy/mm/dd] and [hh:mm:ss].

<u>Automatic</u>: The Network Time Protocol is a protocol which synchronizes computer clocks by periodically querying an NTP Server.

<u>NTP server</u>: Assign the IP address or domain name of the time-server. Leaving the text box blank connects the Network Camera to the default time servers.

<u>Update interval</u>: Select to update the time using the NTP server on an hourly, daily, weekly, or monthly basis.

When finished with the settings on this page, click **Save** at the bottom of the page to enable the settings.

## System > Homepage layout

This section explains how to set up your own customized homepage layout.

#### **General settings**

This column shows the settings of your hompage layout. You can manually select the background and font colors in Theme Options (the second tab on this page). The settings will be displayed automatically in this Preview field. The following shows the homepage using the default settings:



■ Hide Powered by VIVOTEK: If you check this item, it will be removed from the homepage.

#### Logo graph

Here you can change the logo at the top of your homepage.

— Logo graph								
	A customized logo (Gif, JPG or PNG) can be uploaded for main page. It will be resized to 160x50 pixels to replace the previous logo.							
O Default	⊙ Custom	Browse						
Logo link: http://www.vivotek.	com							

Follow the steps below to upload a new logo:

- 1. Click **Custom** and the Browse field will appear.
- 2. Select a logo from your files.
- 3. Click **Upload** to replace the existing logo with a new one.
- 4. Enter a website link if necessary.
- 5. Click **Save** to enable the settings.


#### Customized button

If you want to hide the manual trigger buttons on the homepage, please uncheck this item. This item is selected by default.


Customized button	
🔽 Show manual trigger button	
	Save

#### **Theme Options**

Here you can change the color of your homepage layout. There are three types of preset patterns for you to choose from. The new layout will simultaneously appear in the **Preview** filed. Click **Save** to enable the settings.



- Follow the steps below to set up a custom homepage:
- 1. Click **Custom** on the left column.
- 2. Click to select a color on on the right column.



3. The palette window will pop up as shown below.

Hex:	#000000		02	Hex:	#23538A
Red:	0			Red:	35
Green:	0			Green:	83
Blue:	0			Blue:	138
Hue:	0			Hue:	212
Saturation:	0			Saturation:	74.6
Value:	0			Value:	54.1
Se	elect			4 Se	lect

- 4. Drag the slider bar and click on the left square to select a desired color.
- 5. The selected color will be displayed in the corresponding fields and in the **Preview** column.
- 6. Click **Save** to enable the settings.

## System > Logs

This section explains how to configure the Network Camera to backup system log to a remote server.

#### Log server settings

Log server settings		
Enable remote log		
IP address:		
port:	514	
	Save	

Follow the steps below to set up the remote log:

- 1. Select Enable remote log.
- 2. In the IP address text box, enter the IP address of the remote server.
- 2. In the port text box, enter the port number of the remote server.
- 3. When completed, click **Save** to enable the setting.

You can configure the Network Camera to send the system log file to a remote server as a log backup. Before utilizing this feature, it is suggested that the user install a log-recording tool to receive system log messages from the Network Camera. An example is Kiwi Syslog Daemon. Visit http://www.kiwisyslog. com/kiwi-syslog-daemon-overview/.


10.101	view the	rage team			
0 1 10	4.45.0	Display 00 (Da	e illest	21 Deputat in evolution	
Gutte	Terr	Printy	Hadester	Mensage	
0527.2011	17.08.48	Trikigide	¥80.188.4.103	springel 1.5.0. revisat.	
06-27-2011	12:59:57	Shen hele	\$32.168.4.103	(11547 SERVER): Step one accelor, IP-132,158 4,101	
86.37.2811	17.06.57	Elses July	897,1884.109	fast service registered 2 blaces	
06-27-2411	17:06:13	Clear Sets	882.168.4.103	(FEP SEPVER) Start are sension, IP-152 168.4.101	
06-27-2001	17.0612	User.Earer	19211884103	[115P 111WDI], and exampling function of SS, XM, SP area, TransAt File Analysis assumption in the PH	
06-27-2011	17:06:12	Uner.left	192.168.4.103	(TTSP LEIVER) XHLSP and: and also descent element at Inn 6'H	
06-27-2911	17:06:12	User.W/c	132.168.4.103	THEP LEMMER Step are access, IP-IN: 108.4.121	
06-27-2011	17.06.12	Blue hals	812 188 4 103	PTEP SERVERS Searce services, IP-192 168 8 111	
06-27-2011	17.06.10	User Notice	187.168.4.103	APRIP DEVICE Present and	
06-27-2011	17.06.00	Here Notice	192,168 4 103	(DFM Service) Stating OfM service	
06-27-2011	17.06.07	Giver July	152.168.4.103	Jeastholing Roady to watch httpd	
100-27-2001	120606	Dogwoo Notice	192,168 4,103	officare: then 1102 164.01 10 1522 168 (0.20)	
06-27-2011	17.06.06	Domain Holice	110,188.4.103	offenget makes TRI 168.4.1	
06-27-2011	17.0615	Distance Notice	1321084103	officer IF 102 160 4 102 million 25 256 255 0	
06-27-2611	1706.03	Ban Waning	810 108 4 103	(VENT HER) the process of event \$1 is shipped because of her printly 0	
06-27 2001	17:06:01	Doesen Notice	192.108.4.103	adhope: mates 192,168,4,1	
06-27-2011	17:06:08	Document Notice	192.1084.103	offspe: 17 192 162.4 163 enhant 256 256 256	
AL. 10. 100.1	1206.00	Property Martice		uthouse descentes	

#### System log

This column displays the system log in chronological order. The system log is stored in the Network Camera's buffer and dated events will be overwritten when the number of events reaches a limit.

System log	Access log		
Jul 4 09:45	T syslogd 1.5	D: restart	
Jul 4 09:45	(@ [swatchdog]	Ready to watch httpd.	- 01
Jul 4 09:45	19 JEVENT MGR	Q Starting eventings with support for EcTun	
Jul 4 09:45	19 JEVENT MGR	R): Task confitie: there is no valid event in recording_task.xml, skip it	- 11
Jul 4 09:45	19 JEVENT MGP	] Task confille: there is no valid event in event_task.xml, skip if	
Jul 4 09:45:5	1 [DRM Servic	e) Starting DRM service.	
Jul 4 09:48.0	1 [UPnPIGDCI	P): Search IGD failed	
Jul 4 09:461	)1 [swatchdog]	Reduplicate registration from configer.	
Jul 4 09:46:	1 [swatchdog]	Ready to watch configer.	
Jul 4 09:48.0	2 automount[7	23] >> mount: mounting /dev/mmcbik0p1 on /mnt/auto/CF failed: No	
such device	or address		
Jul 4 09:46:0	2 automount[7	23] mount(generic): failed to mount /devimmcbik0p1 (type vfat)	
on /mnt/auto	ICF .		
Jul 4 09:46.0	2 automount[7	32]. >> mount: mounting /dev/mmcblk0p1 on /mnt/auto/CF failed: No	
such device	or address		
Jul 4 09:46:	2 automount[7	32): mount(generic): failed to mount /devimmcblk0p1 (type vfat)	
on /mnt/auto	VCF		
Jul 4 09:461	2 [ThermalD]	Can not access thermal sensor	
Jul 4 09:46:0	3 [SYS]: Serial	number = 0002D112C715	
Jul 4 09.46.	3 [SY3]: System	m starts at Mon Jul 4 09:46:03 UTC 2011	
Jul 4 09:46:0	3 (NET): === N	ET INFO ===	1.

You can install the included VAST recording software, which provides an Event Management function group for delivering event messages via emails, GSM short messages, onscreen event panel, or to trigger an alarm, etc. For more information, refer to the VAST User Manual.



### **Access log**

Access log displays the access time and IP address of all viewers (including operators and administrators) in a chronological order. The access log is stored in the Network Camera's buffer and older events will be overwritten when the number of events reaches a limit.

System log Access log	
May 4 19:00:17 [RTSP SERVER]: Start one session, IP=192.168.4.101	
May 4 19:00:39 [RTSP SERVER]: Stop one session, IP=192.168.4.101	
May 4 19:00:59 [RTSP SERVER]: Start one session, IP=192.168.4.101	
May 4 19:14:42 [RTSP SERVER]: Stop one session, IP=192.168.4.101	
May 4 19:16:11 [RTSP SERVER]: Start one session, IP=192.168.4.101	
May 4 19:16:20 [RTSP SERVER]: Stop one session, IP=192.168.4.101	-

## System > Parameters

The View Parameters page lists the entire system's parameters in an alphabetical order. If you need technical assistance, use a text-editor program to copy and save the parameters listed on this page. Send the parameter text file to VIVOTEK's technical support.

arameters	
system hostname='FE9191'	,
system ledoff='0'	
system lowlight='1'	
system date='2017/05/17'	
system time='17:36:28'	
system datetime='051717352017.38'	
system ntp=''	
system timezoneindex='320'	
system davlight enable='0'	
system daylight dstactualmode='1'	
system daylight auto begintime='NONE'	
system daylight auto endtime='NONE'	
system daylight timezones=',-360,-320,-280,-240,-241,-	200,-201,-160
system updateinterval='0'	
system info modelname='FE9191'	
system info extendedmodelname='FE9191'	
system info serialnumber='0002D15AD1BF'	
system_info_firmwareversion='FE8191_v2-VVTK-0100a_FE9x	91'
system_info_language_count='10'	
system_info_language_i0='English'	
system_info_language_i1='Deutsch'	
system_info_language_i2='Español'	
system_info_language_i3='Français'	
system_info_language_i4='Italiano'	
system_info_language_i5='日本語'	
system_info_language_i6='Português'	
system_info_language_i7='简体中文'	
system info language i8='繁體中文'	
system info language i9='Русский'	
system_info_language_i10=''	
watam infa languaga i11-11	

## System > Maintenance

This chapter explains how to restore the Network Camera to factory default, upgrade firmware version, etc.

#### **General settings > Upgrade firmware**

Upgrade firmware —		
Select firmware file:	Browse	Upgrade

This feature allows you to upgrade the firmware of your Network Camera. It takes a few minutes to complete the process.

#### Note: Do not power off the Network Camera during the upgrade!

Follow the steps below to upgrade the firmware:

- 1. Download the latest firmware file from the VIVOTEK website. The file is in .pkg file format.
- 2. Click **Browse...** and specify the firmware file.
- 3. Click **Upgrade**. The Network Camera starts to upgrade and will reboot automatically when the upgrade completes.

If the upgrade is successful, you will see "Reboot system now!! This connection will close". After that, reaccess the Network Camera.

The following message is displayed when the upgrade has succeeded.

Reboot system now!! This connection will close.

The following message is displayed when you have selected an incorrect firmware file.

Starting firmware upgrade Do not power down the server during the upgrade. The server will restart automatically after the upgrade is

#### **General settings > Reboot**

Reboot	
[	Reboot

This feature allows you to reboot the Network Camera, which takes about one minute to complete. When completed, the live video page will be displayed in your browser. The following message will be displayed during the reboot process.

The device is rebooting now. Your browser will reconnect to http://192.168.5.151:80/ If the connection fails, please manually enter the above IP address in your browser.

If the connection fails after rebooting, manually enter the IP address of the Network Camera in the address field to resume the connection.

#### **General settings > Restore**

- Restor	е —			
Restore	all se	ettings to factory default exc	ept settings in	
🗌 Net	work	Daylight saving time	🗌 Custom language 🗌 VADP	Restore

This feature allows you to restore the Network Camera to factory default settings.

<u>Network</u>: Select this option to retain the Network Type settings (please refer to Network Type on page 92).

<u>Daylight Saving Time</u>: Select this option to retain the Daylight Saving Time settings (please refer to Import/Export files below on this page).

<u>Custom Language</u>: Select this option to retain the Custom Language settings.

<u>VADP</u>: Retain the VADP modules (3rd-party software stored on the SD card) and related settings.

If none of the options is selected, all settings will be restored to factory default. The following message is displayed during the restoring process.

The device is rebooting now. Your browser will reconnect to http://192.168.5.151:80/ If the connection fails, please manually enter the above IP address in your browser.

#### Import/Export files


This feature allows you to Export / Update daylight saving time rules, custom language file, and configuration file.

Export files	
Export daylight saving time configuration file	Export
Export language file	Export
Export configuration file	Export
Export server status report	Export
Upload files	
Update daylight saving time rules:	Browse Upload
Update custom language file:	Browse Upload
Upload configuration file:	Browse Upload

Export daylight saving time configuration file: Click to set the start and end time of DST.

Follow the steps below to export:

- 1. In the Export files column, click **Export** to export the daylight saving time configuration file from the Network Camera.
- 2. A file download dialog will pop up as shown below. Click **Open** to review the XML file or click **Save** to store the file for editing.



3. Open the file with Microsoft<sup>®</sup> Notepad and locate your time zone; set the start and end time of DST. When completed, save the file.

In the example below, DST begins each year at 2:00 a.m. on the second Sunday in March and ends at 2:00 a.m. on the first Sunday in November.

D e	onfig	_dst - I	Notep	ad			
File	Edk	Format	View	Help			
		<timez <s <!--</td--><td>EndT Zone: one ' csl dM cD Start start csl csl co co EndT</td><td>&gt; Id="- rime&gt; nft&gt; nth&gt; xy&gt;<!--<br-->:Time ne&gt; nft&gt; nth&gt; yy&gt;<!--<br-->ime&gt;</td><td><pre>cweekinMonth&gt;First <dayofweek>Sunday</dayofweek> <hour>2</hour> 240" name="(GMT-06:00) Central Time (US and Canada)"; 60 3 Day&gt; <weekinmonth>Second</weekinmonth> <dayofweek>Sunday</dayofweek> <hour>2</hour> &gt; -60 11 11 </pre></td><td>&gt;</td><td></td></s </timez 	EndT Zone: one ' csl dM cD Start start csl csl co co EndT	> Id="- rime> nft> nth> xy> <br :Time ne> nft> nth> yy> <br ime>	<pre>cweekinMonth&gt;First <dayofweek>Sunday</dayofweek> <hour>2</hour> 240" name="(GMT-06:00) Central Time (US and Canada)"; 60 3 Day&gt; <weekinmonth>Second</weekinmonth> <dayofweek>Sunday</dayofweek> <hour>2</hour> &gt; -60 11 11 </pre>	>	
					241" name="(GMT-06:00) Mexico City">		~
<							>

Update daylight saving time rules: Click Browse... and specify the XML file to update.

If incorrect date and time are assigned, you will see the following warning message when uploading the file to the Network Camera.

🗈 config_dst - Notepad 📃 🗖 🔀	🗿 http://197.168.5.121/cgi-bin/admin/upload.cgi - Microsoft Int 📰 🗖 🔀
File Edit Format View Help	
File Edit Format Wew Help <pre></pre>	Invalid «Month» value in TimeZone 1d: -240
<pre></pre>	

The following message is displayed when attempting to upload an incorrect file format.



Export language file: Click to export language strings. VIVOTEK provides nine languages: English, Deutsch, Español, Français, Italiano, 日本語, Português, 簡体中文, and 繁體中文.

Update custom language file: Click Browse... and specify your own custom language file to upload.

Export configuration file: Click to export all parameters for the device and user-defined scripts.

<u>Export daylight saving time configuration file</u>: Click **Browse...** to update a configuration file. Please note that the model and firmware version of the device should be the same as the configuration file. If you have set up a fixed IP or other special settings for your device, it is not suggested to update a configuration file.

Export server staus report: Click to export the current server status report, such as time, logs, parameters, process status, memory status, file system status, network status, kernel message..., and so on.



• If a firmware upgrade is accidentally disrupted, say, by a power outage, you still have a last resort method to restore normal operation. See the following for how to bring the camera back to work:

Applicable scenario:

- (1) Power disconnected during firmware upgrade.
- (2) Unknown reason causing abnormal LED status, and a Restore cannot recover normal working condition.

You can use the following methods to activate the camera with its backup firmware:

- (1) Press and hold down the reset button for at least one minute.
- (2) Power on the camera until the Red LED blinks rapidly.
- (3) After boot up, the firmware should return to the previous version before the camera hanged. (The procedure should take 5 to 10 minutes, longer than the normal boot-up process). When tthis process is completed, the LED status should return to normal.

## Media > Image

This section explains how to configure the image settings of the Network Camera. It is composed of the following tabbed windows: General settings, Image settings, Exposure, and Privacy mask, and Pixel Calculator.

	General settings	IR control	Image settings	Exposure	Privacy mask	Ptert calculator	
General settings	- Video settings						
	Video title						
	Show timesta	imp and vide	to the in video and	snapshots			
	Position of timestamp and video title on image:			7	Top		
	Timestamp and video title font-size. Video font (.ttf):			3	30~		
					Default 🔍	Upload	
	Mount type:				Ceiling () Wall	() Floor	
	Color:				O B/W @ Color		
	Power line frequency:			0	○ 50 Hz		
	Video orientation:						
	- Day/Night setti	ings					
	Switch to B/	V in night m	ode				
	IR cut filter:				uto mode	v	
	Sensitivity of IR cut filter: Normal						
	Select auto mode will disable profile of exposure settings.						
					1	Save	

<u>Video title</u>: Enter a name that will be displayed on the title bar of the live video as well as the view cell on the ST7501 and VAST recording software.

Show timestamp and video title in videos and snapshots: Enter a name that will be displayed on the title bar of the live video as the picture shown below.

<u>Position of timestamp and video title on image</u>: Select to display time stamp and video title on the top or at the bottom of the video stream.

<u>Timestamp and video title font size</u>: Select the font size for the time stamp and title.

<u>Video font (.ttf)</u>: You can select a True Type font file for the display of textual messages on video.

Mount type: There are 3 Mount types - Ceiling, Wall, and Floor.

**Ceiling**: The Ceiling mount type automatically delivers upside-down images. The Ceiling mode supports the following Display modes - 10, 1P, 1R, 2P, 103R, 4R, 4R PRO, and 108R.

**Wall**: The Wall mount type applies to the monitoring of long, side-to-side surveillance areas, such as when mounted on a wall facing a corridor. Different Mount types have different options with the Display mode settings. For example, the **1P2R** (1 Panoramic & 2 Regional) and **1P3R** (1 Panoramic & 3 Regional) display modes are only available when the "Wall" Mount type is applied.

**Floor:** The Display modes with the Floor mount type are identical to those for the Ceiling mount except that the images are not vertically flipped.

Color: Select to display color or black/white video streams.

<u>Power line frequency</u>: Set the power line frequency consistent with local utility settings to eliminate image flickering associated with fluorescent lights.

<u>Video orientation</u>: Flip - vertically reflect the display of the live video; Mirror - horizontally reflect the display of the live video. Select both options if the Network Camera is installed upside-down (e.g., on the ceiling) to correct the image orientation. Please note that the preset locations will be cleared after you configure the flip/mirror option.

#### Day/Night settings

Day/Night settings	
Switch to B/W in night mode	
IR cut filter:	Auto mode
Sensitivity of IR cut filter:	Normal
Select auto mode will disable profile of exposure settings	3.

#### Switch to B/W in night mode

Select this checkbox to enable the Network Camera to automatically switch to Black & White display during the night mode.



The IR (Infrared lilght) related functions are available for the FE9391-EV.

IR cut filter

With a removable IR-cut filter, this Network Camera can automatically remove the filter to let Infrared light pass into the sensor during low light conditions.

Auto mode (The Day/Night Exposure Profile will not be available if Auto mode is selected) The Network Camera automatically removes the filter by judging the level of ambient light.

Day mode

In day mode, the Network Camera switches on the IR cut filter at all times to block infrared light from reaching the sensor so that the colors will not be distorted.

Night mode

In night mode, the Network Camera switches off the IR cut filter at all times for the sensor to accept infrared light, thus helping to improve low light sensitivity.

#### Synchronize with digital input

The Network Camera automatically removes the IR cut filter when a digital input is triggered, for example, when the camera is accompanied by an external IR light that comes with its own sensor and provides a signal to the camera. Some camera housings come with such mechanism.

#### Schedule mode

The Network Camera switches between day mode and night mode based on a specified schedule. Enter the start and end time for day mode. Note that the time format is [hh:mm] and is expressed in 24-hour clock time. By default, the start and end time of a day mode are set to 07:00 and 18:00.

#### **Sensitivity**

Tune the responsiveness of the IR filter to lighting conditions as Low, Normal, or High.

When completed with the settings on this page, click **Save** to enable the settings.

If you want to configure another sensor setting for a specific lighting condition in day/night/schedule mode, please click **Profile** to open the Profile settings page as shown below.

Please follow the steps below to setup a profile:

#### 1. Check Enable and apply this profile.

- 2. Select the applied mode: **Day mode**, **Night mode**, or **Schedule mode**. Please manually enter a range of time through which you want the Schedule mode to apply.
- 3. Configure Exposure control settings in the following columns. Please refer to page 78 for detailed information.
- 4. Click **Save** to enable the setting and click **Close** to exit the window.

## Media > IR control

The IR (Infrared lilght) related functions are available for the FE9391-EV.

#### **IR illuminators**

#### Turn on built-in IR illuminator in night mode

Select this to turn on the camera's onboard IR illuminator when the camera detects low light condition and enters the night mode.

#### Turn on external IR illuminator in night mode

If your camera is installed with an IR illuminator and the digital output signals are connected to it, you can let system firmware turn on the supplementary illuminator during low-light conditions.

#### Anti-overexposure

When enabled, the camera automatically adjusts the IR projection to adjacent objects in order to avoid over-exposure in the night mode.

The function is more beneficial when the spot of intrusions or an object of your interest is close to the lens and the IR lights. For example, if an intruder has a chance of getting near the range of 3 meters, Smart IR can effectively reduce the over-exposure. For a surveillance area at a greater distance, e.g., 5 meters, the Smart IR function may not bring as significant benefits as in close range.

Anti-overexposure disabled; distance: 5M Anti-overexposure enabled; distance: 5M





Anti-overexposure disabled; distance: 3M

Anti-overexposure enabled; distance: 3M






# -ˈo͡ː- Tips:

If there is an object in close proximity, the IR lights reflected back from it can mislead the Antioverexposure's calculation of light level. To solve this problem, you can place an "Exposure Exclude" window on an unavoidable object in the Exposure setting window. See page 79 for how to do it.

You can also configure the "Exposure Exclude" window in a night mode "Profile" setting so that your day time setting is not affected.


FD8363(TCP-V)	2013/2/4 10:46:08
Exclude	Add exclusive window
ctivated period	
Enable and apply this profile to	
<ul> <li>Dwy mode</li> <li>Night mode</li> </ul>	
Schedule mode	
Measurement window	
© Fall view	
Custom	
OBC	





### **Smart IR**

Smart IR is designed for applications where the IR fisheye camera is installed at a less-than-ideal position. For example, the fisheye can be installed next to a wall or column, which in turn may reflect the IR lights at night, causing over-exposure and blurring part of the image.



## 

It is a must making the Smart IR adjustment in the night mode.

### IR zone adjustment

The IR zone adjustment divides image planes to multiple sections, each single section is equipped with an independent IR control lighting devices for local region illumination. This keeps the comprehensive details of an approaching subject and preserves visibility for the background.

For an installation site with an unavoidable limitation, say, a wall that causes IR reflection, you can manually reduce the light level on specific area(s). This can apply when an IR fisheye camera is installed on a wall with a part of its field of view covering a wall.

Media > Image	
General settings     IR control     Image settings     Exposure     Privacy mask     Pixel calculator	Zone 2 is the default front, indicated by the VIVOTEK camera logo on the dome cover.
Zone s Zone 1 Zone 3 Zone 4	Smart IR  Anth-overexposure  IR adjustment  O Auto IR adjust
- IR illuminators	Manual IR adjust     Che time adjust
✓ Turn on built-in IR illuminator in night mode	Note. Before setup one time adjust, must be set to night mode
Turn on external IR illuminator in night mode	IR LED1 () 100%
- Smart IR	IR LED2 100%
✓ Anti-overexposure	IR LED3 100%
IR adjustment:	IR LED4 100%
Auto IR adjust	IR LEDS 100%
Restore Save	Restore Save

#### IR adjustment

Auto IR adjust - This lets camera firmware automatically calculate and adjust light levels and come up with the best balance for all illumination zones.

Manual IR adjust -

- One time adjust: Before you manually tune the IR light levels for different zones, press this button for the camera to begin the initial calculation. After you manually adjust the light levels for zones, the lighting levels will no longer be adjusted by the camera unless an object approaches near the camera.

Observe the imaging results on the live view and pull the adjustment tabs to increase or decrease the light levels in different zones. For example, when some unavoidable objects stand in one area, and you observe signs of overexposure, you can lower the lighting level for it.

#### **Image settings**

On this page, you can tune the White balance, Image adjustment and related parameters. You can configure two sets of preferred settings: one for normal situations, the other for special situations, such as a schedule mode. Quality: select from the pull-down menu the image quality of the current live view.

	ontrol Image setting		r the state	Ploter concure	
TRACE BEING					
a management		A PARTY	WILL DO		
		2			
Normal light mode	Profile mode	di di			
- White balance		1			^
White balance	]	19			<
White balance Auto	]	ALL OF		5.289411	^
White balance	]	er Pite		50%	~
White balance Auto	]			50%	~
White balance Auto	]				^
White balance Auto	]			- 50%	~
White belance Auto	]			= 50% = 50%	•
White balance Auto	] ent			= 50% = 50%	< >

<u>White balance</u>: Adjust the value for the best color temperature.

Auto: This will automatically adjust the color temperature of the light in response to different light sources.

You may follow the steps below to adjust the white balance to the best color temperature.

- 1. Set the White balance to Auto.
- 2. Place a sheet of white paper (or a color of a cool color temperature, such as blue) in front of the lens, then allow the Network Camera to automatically adjust the color temperature.
- 3. Check the **Fix current value** to confirm the setting when the camera automatically measured and adjusted the white balance.
- Manual: This item allows users to manually input the R gain & B gain ratios.

#### Image Adjustment

- Brightness: Adjust the image brightness level, which ranges from 0% to 100%.
- Contrast: Adjust the image contrast level, which ranges from 0% to 100%.
- Saturation: Adjust the image saturation level, which ranges from 0% to 100%. You can also select **Customize** and manually enter a value.

- Sharpness: Adjust the image sharpness level, which ranges from 0% to 100%.
- Gamma curve: Adjust the image sharpness level, which ranges from 0.45 to 1, from Detailed to Contrast. You may let firmware **Optimize** your display or select the **Manual** mode, and pull the slide bar pointer to change the preferred level of Gamma correction towards higher contrast or towards the higher luminance for detailed expression for both dark and lighted areas of an image.

This option is disabled when the WDR feature is enabled.

<u>Defog</u>: Defog helps improve the visibility quality of captured image in poor weather conditions such as smog, fog, or smoke.

- Noise reduction
- Enable 3D noise reduction: Check to enable noise reduction in order to reduce noises and flickers in image. This applies to the onboard 3D Noise Reduction feature. Use the pull-down menu to adjust the reduction strength. Note that applying this function to the video channel will consume system computing power.

3D Noise Reduction is mostly applied in low-light conditions. When enabled in a low-light condition with fast moving objects, trails of after-images may occur. You may then select a lower strength level or disable the function.

You can click **Restore** to recall the original settings without incorporating the changes. When completed with the settings on this page, click **Save** to enable the setting. You can also click on the **Profile mode** to adjust all settings above in a tabbed window for special lighting conditions at a specific period of time.

_	Normal light mode	Profile mode		
	<ul> <li>Enable to apply</li> </ul>	these settings at		^
	<ul> <li>Schedule m</li> </ul>	ode : From 18:00	to 06:00 [hh:mm]	

<u>Enable to apply these settings at</u>: Select the mode this profile to apply to: Schedule mode. Please manually enter a range of time if you choose Schedule mode. Then check **Save** to take effect.

#### **Exposure**

On this page, you can configure the Exposure measurement window, Exposure level, Exposure mode, Exposure time, Gain control, and Day/Night mode settings. Quality: select the pull-down menu to configure the image quality of the current display.

\$11.00 \$1.10%	III control	image writings			
			and a state	City City	
	ode   ruma	e profile of exposur		we window	<u>^</u>
	<ul> <li>Custom</li> </ul>				
Exposure to Exposure to Exposure 10 Exposure 10	ess	0 💌			- 1/20

<u>Measurement Window</u>: This function allows users to configure measurement window(s) for low light compensation. For example, where low-light objects are posed against an extremely bright background. You may want to exclude the bright sunlight shining through a building's corridor.


- Full view: Calculate the full range of view and offer appropriate light compensation.
- Custom: This option allows you to manually add customized windows as inclusive or exclusive regions. A total of 10 windows can be configured. Please refer to the next page for detailed illustration.



- The Profile mode setting in the Exposure window will be disabled when the IR cut filter is set to the Auto mode (Media > Image > General settings window).
- Note that, in the Custom mode, the title bar area is not included as the effective measurement area.



The inclusive window refers to the "weighted window"; the exclusive window refers to the "ignored window." It adopts the weighted averages method to calculate the value. The inclusive windows have a higher priority. You can overlap these windows, and, if you place an exclusive window within a larger inclusive window, the exclusive part of the overlapped windows will be deducted from the inclusive window. An exposure value will then be calculated out of the remaining of the inclusive window.



BLC (Back Light Compensation): This option will automatically add a "weighted region" in the middle of the window and give the necessary light compensation.

#### Exposure control:

- Exposure level: You can manually set the Exposure level, which ranges from -0.7 to +0.7 (dark to bright).
- Flickerless: Under some circumstances when there is a difference between the video capture frequency and local AC power frequency (NTSC or PAL), the mismatch causes color shifts or flickering images. If the above mismatch occurs, select the Flickerless checkbox, and the range of Exposure time (the shutter time) will be limited to a range in order to match the AC power frequency. When selected, the exposure time will be forced to stay longer than 1/120 second. For cameras that come with fixed iris lens, setting the exposure time to longer than 1/120 second may introduce too much lights to the lens. Users can use this option to observe whether the result of long exposure time is satisfactory.

You can click and drag the semi-circular pointers on the **Exposure time** and **Gain control** slide bars to specify a range of shutter time and Gain control values within which the camera can automatically tune to an optimal imaging result. For example, you may prefer a shorter shutter time to better capture moving objects, while a faster shutter reduces light and needs to be compensated by electrical brightness gains.

Exposure time: (Note that this option is not available when WDR Pro is enabled!)

You can split the round pointers on the **Exposure time** and **Gain control** slide bars into two halves and drag them on the bars to designate a range of values in which firmware can automatically adapt to. Note that Firmware will then automatically tune the Gain, Exposure time, and Iris opening within the ranges you specified. For example, in low-light condition, you may prefer a longer exposure time and more electronic gains. However, the noises in the image will also increase. Gain control: Tune the slide bar to set the Gain Control to the best image quality. Higher gain control value will generate a certain amount of noises, and that the gain control, lighting levels, and picture performance are closely related.

Click the **Save** button to preserve your configuration.

Note that when the WDR function is enabled, the exposure time and gain control are not available.

#### AE Speed Adjustment:

This function applies when you need to monitor fast changing lighting conditions. For example, the camera may need to monitor a highway lane or entrance of a parking area at night where cars passing by with their lights on can bring fast changes in light levels. The same applies if the camera is installed on a vehicle, and when it needs to adapt to fast changes of light when entering and leaving a tunnel.

AE speed adjustment				
✓ Enable AE speed adjustment				
Speed level:	Slow		Fast	
Sensitivity:	Low		High	I

<u>Enable WDR enhanced</u>: This function allows users to identify more image details with an extreme contrast from an object of interest with one shadowed side against a bright background, e.g., at an entrance. You may select the **Enable WDR enhanced** checkbox, and then adjust the strength (low, medium, high) to reach the best image quality.

You can click **Restore** to recall the original settings without incorporating the changes. When completed with the settings on this page, click **Save** to enable the settings.

If you want to configure another sensor setting for a specific lighting condition for a specific period of time in a day, please click **Profile mode** to open the Profile of exposure settings page as shown below.

<u>Enable to apply these settings at</u>: Manually enter a range of time during which this profile will take effect, and then click **Save** for the configuration to take effect.

Please follow the steps below to configure a profile:

- 1. Select the **Profile mode** tab.
- 2. Select the applicable mode: Please manually enter a range of time if you choose the Schedule mode.
- 3. Configure Exposure control settings in the folowing columns. Please refer to previous dicussions for detailed information.
- 4. Click **Save** to enable the setting and click **Close** to exit the page.

Normal light mode Pr	offie mode	
2 Enable to apply the	se settings at	^
Schedule mode	From 18:00 to 06:00 [httmm]	
- Measurement w	indow	
Full view      O	ustom OBLC	
Exposure contro	0	
Exposure level:	0 🔽	
Flickeness		
		~
who		

#### **Privacy mask**

Click **Privacy Mask** to open the configuration page. On this page, you can block out certain sensitive zones to address privacy concerns.

General settings	IR control	Image settings	Exposure	Privacy mask	Pixel calculator
Enable privac	y mask				
	162	<b>a</b> 1		Window name	
	1	Sel .		areaA	×
1 mm	AL.	C. S.	A.	areaB	×
			21		
-1-1-	154	2		New	Save
- 5 -	2.1			ò	
and the	TA.				Ý
T PL	5 /ACS	San C			
		<b>4</b> x	In		
	Lp.				
	-				

- To configure the privacy mask windows, follow the steps below:
- 1. Click **New** to add a new window. A text box will appear allowing you to enter a name for the mask.
- 2. Use four mouse clicks to mark a square area, which is recommended to be at least twice the size of the object (height and width) you want to cover.
- 3. Enter a Window Name and click **Save** to enable the setting.
- 4. Check Enable privacy mask to enable this function.

## NOTE:

- ▶ Up to 5 privacy mask windows can be configured on the same screen.
- ► To delete a mask, use the red cross button and then click on the **Save** button.

#### **Pixel Calculator**

Click the **Add** button at the lower screen to create a pixel calculator window. Place your cursor on the window to move it to an area of your interest, and change the size of window to fit the area of interest.

Once they are drawn, the numbers of pixels on the sides of windows will appear. This allows you to calculate if your current configuration fulfills a requirement, for instance, for recognizing the faces of persons passing through a location. A facial recognition usually requires around 130 pixels per meter or higher.

The pixels thus calculated are listed at the lower screen on a per-stream basis depending on the frame size you configured for each video stream.



Pixel Calculator	
Window1 (H)x(V)	Window2 (H)x(V)
Stream1: 551x373	Stream1: 555x370
Stream2: 55x37	Stream2: 55x37
Stream3: 551x373	Stream3: 555x370

Take the following into consideration when using this feature:

- 1. Operational requirement: Identify a human or a human face.
- 2. Why human face? There are less variances in the size of a face than that for limbs and body. Human face is normally 16cm wide.
- 3. The recommended pixel number is, 40 to 80 for facial identification; or 100 pixels per foot (30.48cm) 3-1. One example is a human face in retail.
  - 3-2. Another example is a doorway:

If the requirement is 100 pixels per foot, to detect a person passing through a door, the camera will have to cover 700 pixels throughout the length of a doorway. This application aims to identify a subject passing through a specific area.

- 4. Other factors may include that a person will move in your area of interest: The face may not always face the camera.
- 5. Details can be affected by weak lighting or the view angle. Therefore, higher the pixels, higher the chance you can identify the subject.
  - Ceneral settings
     Tappsare
     Privacy mask
     Pade Calculator
- 6. The pixel calculator visual tool looks like the following.

With the visual tool, you can estimate a coverage area, the distance from the subject, and place a ruler or an object of known size. You can then draw a calculator frame to cover the subject of your interest.

The calculated numbers will be listed at the lower screen. You will then understand if the current setting fulfills your requests for the number of pixels.

## Media > Video

### **Stream settings**



Please follow the steps below to set up those settings for an individual stream:

- 1. Select a stream to configure its viewing region.
- 2. Choose a proper **Frame Size** from the drop-down list according to the size of monitored device.
- 3. Select the Maximum frame rate.
- The parameters of a fixed-focal lens' multiple streams:

	Region of Interest
Stream 1	3000 X 3000 ~ 256 x 256
Stream 2	2560 X 2560 (default) ~ 256 x 256
Stream 3	512 X 512 (default) ~ 256 x 256
Stream 4	3000 X 3000 ~ 256 x 256

To begin the configuration, first select a video channel.

To change the frame size, frame rate, and other related settings, click on video settings for a video stream to its individual configuration panel.



When operating with a fluorescene light in the field of view, which is rare for a fisheye installation, and the power line frequency is set to 50Hz, the edges of such light may appear flickering. In the event of this occurrence, you can turn on the flickerless mode (Configuration > Media > Image > Exposure), and the frame rate will be automatically configured to 16.6fps. This will get around the flickering issue.

Click the stream item to display the detailed information.

- Video aattrijs for atteant 1.	
0420	
@ H 204	
Farmann	[ 1000-0005 ]
Nation fame and	Ditte VI
inter Tarte pailod	11 4
amer america	
Dysame interferenziation	Chief .
🔁 Smart same	Automotion (Automotion (Automotio) (Automotio) (Automotio) (Automotio) (Automotio) (Automo
Hote	Committee To
Guality priority' (Help)	* -0
Stars (star)	
· Constanted on hele	
Telget survive	(Celeiet ~)
Maximum or rare-	i Vispo 👻
Rokey .	Plana ara pronty 🔍
Free surry	
0.411	
<ul> <li>Video antitige for stream 2</li> </ul>	
CH281	
(# H 20+	
Forme Last	(Intercent) w)
Maximum harma rates	(32 %+ w)
intra theme period	18 -
Anat search 0	
2 Dysamic interframe period	(fair)
(2) Direct socies	80 3 M S P
linia	(Automatiking with
Guality privily their	2 - 1 - 2
the set of the set of the	- 0 -
· Constanted at late	
Tepenaty	(Sealer w)
Recover of rate	T Vites w
Fator	Frame are priority will
O Frei suffy	The second s
0.90	
0.449	

This Network Camera offers real-time H.265, H.264 and MJPEG compression standards (triple Codec) for real-time viewing.

If the H.265 or H.264 mode is selected, the video is streamed via RTSP protocol. There are several parameters for you to adjust the video performance:

(i) H 265	
Frame size	3000×3000 🗸
Maximum frame rate:	20 tos 🗸
Intra frame period.	18 🗸
Smart stream II	
[2] Dynamic intra frame period (	Help)
[2] Smart codes:	
Mode.	Auto tracking 🐱
Quality priority: (Help)	à:
Bit rate control	
<ul> <li>Constrained bit rate:</li> </ul>	
Target quality	Detailed 🗸
Maximum bit rate	6 Mops 🗸
Policy:	Frame rate priority
<ul> <li>Fixed quality:</li> </ul>	
OH.264	
_ JPEG	

Frame size

You can set up different video resolutions for different viewing devices. For example, set a smaller frame size and lower bit rate for remote viewing on mobile phones and a larger video size and a higher bit rate for live viewing on web browsers. Note that a larger frame size takes up more bandwidth.

Maximum frame rate

This limits the maximum refresh frame rate per second. Set the frame rate higher for smoother video quality and for recognizing moving objects in the field of view.

If the power line frequency is set to 50Hz, the frame rates are selectable at 1fps, 2fps, 3fps, 5fps, 8fps, 10fps, 15fps, and 20fps. If the power line frequency is set to 60Hz, the frame rates are selectable at 1fps, 2fps, 3fps, 5fps, 8fps, 10fps, 15fps, and 20fps. You can also select **Customize** and manually enter a value.

#### ■ Intra frame period


Determine how often to plant an I frame. The shorter the duration, the more likely you will get better video quality, but at the cost of higher network bandwidth consumption. Select the intra frame period from the following durations: 1/4 second, 1/2 second, 1 second, 2 seconds, 3 seconds, and 4 seconds.

#### **Smart stream II**

#### Dynamic Intra frame period

High quality motion codecs, such as H.265 and H.264, utilize the redundancies between video frames to deliver video streams at a balance of quality and bit rate.


The encoding parameters are summarized and illustrated below. The **I-frames** are completely selfreferential and they are largest in size. The **P-frames** are predicted frames. The encoder refers to the previous I- or P-frames for redundant image information.



H.264 Frame Types

By dynamically prolonging the intervals for I-frames insertion to up to 10 seconds, the bit rates required for streaming a video can be tremendously reduced. When streaming a video of a static scene, the Dynamic Intra frame feature can save up to 53% of bandwidth. The amount of bandwidth thus saved is also determined by the activities in the field of view. If activities occur in the scene, firmware automatically shortens the I-frame insertion intervals in order to maintain image quality. In the low light or night conditions, the P-frames can have a larger size due to the noises, and hence the bandwidth saving effect is also reduced.

Streaming a typical 2MP scene normally requires 3~4Mb/s of bandwidth. With the Dynamic Intra frame function, the bandwidth for streaming a medium-traffic scene can be reduced to 2~3Mb/s, and during the no-traffic period of time, down to 500kb/s.



With the H.264 codec in an optimal scenario and when Dynamic Intra frame is combined with the Smart Stream function, an 80% of bandwidth saving can be achieved compared with using H.264 without enabling these bandwidth-saving features.

Smart codec effectively reduces the quality of the whole FOV or the non-interested areas on a scene and therefore reduces the bandwidth consumed.

You can manually specify the video quality for the foreground and the background areas.





- Slide bar to the right higher quality in the ROI areas.
- Slide bar to the left higher quality in the non-ROI areas.


Select an operation mode if Smart codec is preferred.

- Auto tracking: The Auto mode configures the whole screen into the non-interested area. The video quality of part of the screen returns to normal when one or more objects move in that area. The remainder of the screen where there are no moving objects (no pixel changes) will still be transmitted in low-quality format.
- Manual: The Manual mode allows you to configure 3 ROI windows (Region of Interest, with Foreground quality) on the screen. Areas not included in any ROI windows will be considered as the non-interested areas. The details in the ROI areas will be transmitted in a higher-quality video format.

As illustrated below, the upper screen may contain little details of your interest, while the sidewalk on the lower screen is included in an ROI window.



As the result, the lower screen is constantly displayed in high details, while the upper half is transmitted using a lower-quality format. Although the upper half is transmitted using a lower quality format, you still have an awareness of what is happening on the whole screen.



- **Hybrid**: The major difference between the "Manual" mode and the "Hybrid" mode is that:

In the "**Hybrid**" mode, any objects entering the non-interested area will restore the video quality of the moving objects and the area around them. The video quality of the associated non-interested area is immediately restored to normal to cover the moving objects.

In the "**Manual**" mode, the non-interested area is always transmitted using a low-quality format regardless of the activities occurring inside.

Quality priority: (Help)

- **Quality priority**: Use the slide bar to tune the quality contrast between the ROI and non-interested areas.

14

The farther the slide bar button is to the right, the higher the image quality of the ROI areas. On the contrary, the farther the slide bar button to the left, the higher the image quality of the non-interested area.

In this way, you may set up an ROI window as a privacy mask by covering a protected area using an ROI window, while the rest of the screen becomes the non-interested area. You may then configure the non-interested area to have a high image quality, or vice versa.

You should also select the Maximum bit rate from the pull-down menu as the threshold to contain the bandwidth consumption for both the high- and low-quality video sections in a smart stream.

### Bit rate control

Constrained bit rate:

A complex scene generally produces a larger file size, meaning that higher bandwidth will be needed for data transmission. The bandwidth utilization is configurable to match a selected level, resulting in mutable video quality performance. The bit rates are selectable at the following rates: 20Kbps, 30Kbps, 40Kbps, 50Kbps, 64Kbps, 128Kbps, 256Kbps, 512Kbps, 768Kbps, 1Mbps, 2Mbps, 3Mbps, 4Mbps, 6Mbps, 8Mbps, 10Mbps, 12Mbps, 14Mbps, ~ to 40Mbps. You can also select **Customize** and manually enter a value up to 40Mbps.

- Target quality: Select a desired quality ranging from Medium to Excellent.

- Maximum bit rate: select a bit rate from the pull-down menu. The bit rate ranges from 20kbps to a maximum of 40Mbps. The bit rate then becomes the Average or Upper bound bit rate number. The Network Camera will strive to deliver video streams around or within the bit rate limitation you impose.

- Policy: If Frame Rate Priority is selected, the Network Camera will try to maintain the frame rate per second performance, while the image quality will be compromised. If Image quality priority is selected, the Network Camera may drop some video frames in order to maintain image quality.

### Fixed quality:

On the other hand, if **Fixed quality** is selected, all frames are transmitted with the same quality; bandwidth utilization is therefore unpredictable. The video quality can be adjusted to the following settings: Medium, Standard, Good, Detailed, and Excellent. You can also select **Customize** and manually enter a value.

Maximum bit rate: With the guaranteed image quality, you might still want to place a bit rate limitation to control the size of video streams for bandwidth and storage concerns. The configurable bit rate starts from 1Mbps to 40Mbps.

The Maximum bit rate setting in the Fixed quality configuration can ensure a reasonable and limited use of network bandwidth. For example, in low light conditions where a Fixed quality setting is applied, video packet sizes can tremendously increase when noises are produced with electrical gains.

You may also manually enter a bit rate number by selecting the **Customized** option.

If **JPEG** mode is selected, the Network Camera continuously sends JPEG images to the client, producing a moving effect similar to a filmstrip. Every single JPEG image transmitted guarantees the same image quality, which in turn comes at the expense of variable bandwidth usage. Because the media contents are a combination of JPEG images, no audio data is transmitted to the client. There are three parameters provided in MJPEG mode to control the video performance:

JPEG			
Frame	size:	1920x1080	$\sim$
Maxim	um frame rate:	10 fps	$\checkmark$
Video	quality		
0	Constant bit rate:		
۲	Fixed quality:		
	Quality:	Good	$\sim$
	Maximum bit rate:	40 Mbps	$\checkmark$

Frame size

You can set up different video resolution for different viewing devices. For example, set a smaller frame size and lower bit rate for remote viewing on mobile phones and a larger video size and a higher bit rate for live viewing on web browsers. Note that a larger frame size takes up more bandwidth.

Maximum frame rate

This limits the maximum refresh frame rate per second. Set the frame rate higher for smoother video quality.

If the power line frequency is set to 50Hz, the frame rates are selectable at 1fps, 2fps, 3fps, 5fps, 8fps, 10fps, 15fps, and 20fps. If the power line frequency is set to 60Hz, the frame rates are selectable at 1fps, 2fps, 3fps, 5fps, 8fps, 10fps, 15fps, and 20fps. You can also select **Customize** and manually enter a value.

■ Video quality

Refer to the previous page to configure an average or upper bound threshold for controlling the bandwidth consumed for transmitting motion jpegs. The configuration method is identical to that for H.264 and H.265.



- Video quality and fixed quality refer to the compression rate. If you select to enter a Customized value in the Fixed quality menu, a lower value will produce higher quality.
- Converting high-quality video may significantly increase the CPU load, and you may encounter streaming disconnection or video loss while capturing a complicated scene. In the event of occurrence, we suggest you customize a lower video resolution or reduce the frame rate to obtain a smooth video.

## Media > Audio

### **Audio Settings**

Audio settings		
Mute		
Microphone source:	Internal 🗸	
Internal microphone input gain:	0	70%
External microphone input gain:	0O	100%
Audio type	0	100%
● G.711:	pcmu 🔽	
⊖ G.726 bit rate:	32 Kbps 🔽	
		Save

<u>Mute</u>: Select this option to disable audio transmission from the Network Camera to all clients. Note that if mute mode is turned on, no audio data will be transmitted even if audio transmission is enabled on the Client Settings page. In that case, the following message is displayed:

Warning
The media type has been changed to video only because the media from server contains no audio
ОК

<u>Microphone source</u>: Select to stream the video with either the audio input from the internal or an external microphone.

Internal microphone input gain: Select the gain of the internal audio input according to ambient conditions. Adjust the gain from 0% (least) to 100% (most).

<u>Enternal microphone input gain:</u> Select the gain of the internal audio input according to ambient conditions. Adjust the gain from 0% (least) to 100% (most).

Audio type: Select audio codec as G.711 or G.726 and the bit rate.

- G.711 provides good sound quality and requires about 64Kbps. Select pcmu (µ-Law) or pcma (A-Law) mode.
- G.726 is a speech codec standard covering voice transmission at rates of 16, 24, 32, and 40kbit/s.

When completed with the settings on this page, click **Save** to enable the settings.

## **Network > General settings**

This section explains how to configure a wired network connection for the Network Camera.

Network Type	Network type
	LAN     LAN
	<ul> <li>Get IP address automatically</li> </ul>
	Use fixed IP address
	Enable UPnP presentation
	Enable UPnP port forwarding
	O PPPoE
	Enable IPv6
	Save

#### LAN

Select this option when the Network Camera is deployed on a local area network (LAN) and is intended to be accessed by local computers. The default setting for the Network Type is LAN. Rememer to click **Save** when you complete the Network setting.

<u>Get IP address automatically</u>: Select this option to obtain an available dynamic IP address assigned by the DHCP server each time the camera is connected to the LAN.

Use fixed IP address: Select this option to manually assign a static IP address to the Network Camera.

Get IP address automatically		
Our Use fixed IP address		
IP address:	192.168.4.108	
Subnet mask:	255.255.255.0	
Default router:	192.168.4.1	
Primary DNS:	192.168.0.10	
Secondary DNS:	192.168.0.20	
Primary WINS server:	192.168.0.10	
Secondary WINS server:	192.168.0.20	
Enable UPnP presentation		
Enable UPnP port forwarding		
PPPoE		
Enable IPv6		

- 1. You can make use of VIVOTEK Installation Wizard 2 on the software CD to easily set up the Network Camera on LAN. Please refer to Software Installation on page 30 for details.
- 2. Enter the Static IP, Subnet mask, Default router, and Primary DNS provided by your ISP.

<u>Subnet mask</u>: This is used to determine if the destination is in the same subnet. The default value is "255.255.255.0".

<u>Default router</u>: This is the gateway used to forward frames to destinations in a different subnet. Invalid router setting will fail the transmission to destinations in different subnet.


<u>Primary DNS</u>: The primary domain name server that translates hostnames into IP addresses.

<u>Secondary DNS</u>: Secondary domain name server that backups the Primary DNS.

<u>Primary WINS server</u>: The primary WINS server that maintains the database of computer name and IP address.

<u>Secondary WINS server</u>: The secondary WINS server that maintains the database of computer name and IP address.

<u>Enable UPnP presentation</u>: Select this option to enable UPnP<sup>™</sup> presentation for your Network Camera so that whenever a Network Camera is presented to the LAN, shortcuts of connected Network Cameras will be listed in My Network Places. You can click the shortcut to link to the web browser. Currently, UPnP<sup>™</sup> is supported by Windows XP or later. Note that to utilize this feature, please make sure the UPnP<sup>™</sup> component is installed on your computer.



<u>Enable UPnP port forwarding</u>: To access the Network Camera from the Internet, select this option to allow the Network Camera to open ports on the router automatically so that video streams can be sent out from a LAN. To utilize of this feature, make sure that your router supports UPnP<sup>TM</sup> and it is activated.

#### PPPoE (Point-to-point over Ethernet)

Select this option to configure your Network Camera to make it accessible from anywhere as long as there is an Internet connection. Note that to utilize this feature, it requires an account provided by your ISP.

Follow the steps below to acquire your Network Camera's public IP address.

- 1. Set up the Network Camera on the LAN.
- 2. Go to Configuration > Event > Event settings > Add server (please refer to Add server on page 133) to add a new email or FTP server.
- 3. Go to Configuration > Event > Event settings > Add media (please refer to Add media on page 137). Select System log so that you will receive the system log in TXT file format which contains the Network Camera's public IP address in your email or on the FTP server.
- 4. Go to Configuration > Network > General settings > Network type. Select PPPoE and enter the user name and password provided by your ISP. Click **Save** to enable the setting.

C LAN	
PPPoE	
User name:	
Password:	
Confirm password:	
Enable IPv6	
	Save


- 5. The Network Camera will reboot.
- 6. Disconnect the power to the Network Camera; remove it from the LAN environment.




- If the default ports are already used by other devices connected to the same router, the Network Camera will select other ports for the Network Camera.
- If UPnP<sup>™</sup> is not supported by your router, you will see the following message: Error: Router does not support UPnP port forwarding.
- ► Below are steps to enable the UPnP<sup>TM</sup> user interface on your computer: Note that you must log on to the computer as a system administrator to install the UPnP<sup>TM</sup> components.
  - 1. Go to Start, click Control Panel, then click Add or Remove Programs.

B Gardeni Ranni		12 H 12
the sum and family had		
0.030	and Colores The	
O Destad	No. 1	- 0 -
Constant 1	Pick a category	
Direction in a	5 August 10 August 1	
e valoritation O laterature O laterature	🚽	-) 🥶
(	<b>1</b>	nin and a second second second
	.()	- &


2. In the Add or Remove Programs dialog box, click Add/Remove Windows Components.



3. In the Windows Components Wizard dialog box, select Networking Services and click Details.



4. In the Networking Services dialog box, select Universal Plug and Play and click OK.



5. Click Next in the following window.

ndows Components You can add or remove components of Windows XP.	
To add a remove a component, click the checkbox. An part of the component will be installed. To see what's inc	
Details Components	
Staff Message Queuing	DOME -
2 Min Expose	13.5 MB
P - Newaking Lemmas	0.2 MB
C Contrast Network File and Piret Services	0.0 ME
Se Fait Indete Broot Certificates	nowe 🗧
Description: Contains a variety of specialized, network or	elated services and protocols
Description: Contains a vallery of specialetic, nervolation	
Total del: space required: 0.0 MB	and the second se

- 6. Click **Finish**. UPn $P^{TM}$  is enabled.
- ► How does  $UPnP^{TM}$  work?

UPnP<sup>™</sup> networking technology provides automatic IP configuration and dynamic discovery of devices added to a network. Services and capabilities offered by networked devices, such as printing and file sharing, are available among each other without the need for cumbersome network configuration. In the case of Network Cameras, you will see Network Camera shortcuts under My Network Places.

Enabling UPnP port forwarding allows the Network Camera to open a secondary HTTP port on the router-not HTTP port-meaning that you have to add the secondary HTTP port number to the Network Camera's public address in order to access the Network Camera from the Internet. For example, when the HTTP port is set to 80 and the secondary HTTP port is set to 8080, refer to the list below for the Network Camera's IP address.

From the Internet	In LAN
http://203.67.124.123:8080	http://192.168.4.160 or http://192.168.4.160:8080

If the PPPoE settings are incorrectly configured or the Internet access is not working, restore the Network Camera to factory default; please refer to **Restore** on page 66 for details. After the Network Camera is reset to factory default, it will be accessible on the LAN.

#### Enable IPv6

Select this option and click **Save** to enable IPv6 settings.

Please note that this only works if your network environment and hardware equipment support IPv6. The browser should be Microsoft<sup>®</sup> Internet Explorer 6.5, Mozilla Firefox 3.0 or above.

Network type		
© LAN		
PPPoE		
User name:	]	
Password:	]	
Confirm password:	]	
🖉 Enable IPv6		
IPv6 information		
Manually setup the IP address		
		Save

When IPv6 is enabled, by default, the network camera will listen to router advertisements and be assigned with a link-local IPv6 address accordingly.

IPv6 Information: Click this button to obtain the IPv6 information as shown below.

	<u>close</u>
[eth0 address] fe80:0000:0000:0000:0202:d1ff:fe0e:d4c8/64@Link [Gateway] IPv6 address list of gateway [DNS] IPv6 address list of DNS	]

If your IPv6 settings are successful, the IPv6 address list will be listed in the pop-up window. The IPv6 address will be displayed as follows:

#### **Refers to Ethernet**

	ink-global IPv6 address/network mask ink-local IPv6 address/network mask
	ink-local IPv6 address/network mask
[Gateway]	
[outona)]	
fe80::211:d8ff:fea2:1a2b	
[DNS]	
2010:05:0:978d::	

Please follow the steps below to link to an IPv6 address:

- 1. Open your web browser.
- 2. Enter the link-global or link-local IPv6 address in the address bar of your web browser.
- 3. The format should be:



4. Press **Enter** on the keyboard or click **Refresh** button to refresh the webpage. For example:

Network Camera - Microsoft Internet Explorer File Edit View Favorites Tools Help	
🔇 Back • 🕥 · 🖹 🖻 🏠 🔎 Search 👷 Favorites 🥝	🖉 - 🍃 🗃 🎕
Address Address http://[2001:0c08:2500:0002:0202:d1ff:fe04:65f4]/	
VIVOTEK	

## NOTE:

If you have a Secondary HTTP port (the default value is 8080), you can also link to the webpage in the following address format: (Please refer to HTTP streaming on page 98 for detailed information.)



► If you choose PPPoE as the Network Type, the [PPP0 address] will be displayed in the IPv6 information column as shown below.

[eth0 address] fe80.0000.0000.0000.0202.d1ff:fe11.2299/64@Link
[ppp0 address] fe80.0000.0000.0000.0202.d1ff:fe11:2299/10@Link
2001:b100:01c0:0002:0202:d1ff:fe11:2299/64@Global
[Gateway]
fe80::90:1a00:4142:8ced
[DNS]
2001:6000::1

<u>Manually setup the IP address</u>: Select this option to manually set up IPv6 settings if your network environment does not have DHCPv6 server and router advertisements-enabled routers. If you check this item, the following blanks will be displayed for you to enter the corresponding information:

Enable IPv6		
IPv6 information		
Manually setup the IP address		
Optional IP address / Prefix length	/	64
Optional default router		
Optional primary DNS		

## **Network > Streaming protocols**

#### **HTTP streaming**

To utilize HTTP authentication, make sure that your have set a password for the Network Camera first; please refer to Security > User account on page 112 for details.

HTTP RTSP SIP	
Authentication:	basic 🗸
HTTP port:	80
Secondary HTTP port:	8080
Access name for stream 1:	video.mjpg
Access name for stream 2:	video2.mjpg
Access name for stream 3:	video3.mjpg
Access name for stream 4:	video4.mjpg
	Save

<u>Authentication</u>: Depending on your network security requirements, the Network Camera provides two types of security settings for an HTTP transaction: basic and digest.

If **basic** authentication is selected, the password is sent in plain text format and there can be potential risks of being intercepted. If **digest** authentication is selected, user credentials are encrypted using MD5 algorithm and thus provide better protection against unauthorized access.

<u>HTTP port / Secondary HTTP port</u>: By default, the HTTP port is set to **80** and the secondary HTTP port is set to **8080**. They can also be assigned to another port number between 1025 and 65535. If the ports are incorrectly assigned, the following warning messages will be displayed:

Microsoft Internet Explorer	Microsoft Internet Explorer
HTTP port must be 80 or from 1025 to 65535	Secondary HTTP port must be from 1025 to 65535
ОК	ОК

To access the Network Camera on the LAN, both the HTTP port and secondary HTTP port can be used to access the Network Camera. For example, when the HTTP port is set to 80 and the secondary HTTP port is set to 8080, refer to the list below for the Network Camera's IP address.


On the LAN http://192.168.4.160 or http://192.168.4.160:8080

<u>Access name for Channel # and stream #</u>: This Network camera supports multiple streams simultaneously. The access name is used to differentiate the streaming source. Users can click **Media > Video > Stream settings** to set up the video quality of linked streams. For more information about how to set up the video quality, please refer to Stream settings on page 84.

When using Mozilla Firefox or Netscape to access the Network Camera and the video mode is set to **JPEG**, users will receive video comprised of continuous JPEG images. This technology, known as "server push", allows the Network Camera to feed live pictures to Mozilla Firefox and Netscape.

URL command -- http://<ip address>:<http port>/<access name for stream 1 ~ 4> For example, when the Access name for stream 2 is set to video2.mjpg:

- 1. Launch Mozilla Firefox or Netscape.
- 2. Type the above URL command in the address bar. Press Enter.
- 3. The JPEG images will be displayed in your web browser.



- Microsoft<sup>®</sup> Internet Explorer does not support server push technology; therefore, using http://<ip address>:<http port>/<access name for stream 1 ~ 4> will fail to access the Network Camera.
- ► Users can only use URL commands to request the stream 5. For more information about URL commands, please refer to page 163.

#### **RTSP Streaming**

To utilize RTSP streaming authentication, make sure that you have set a password for the Network Camera first; please refer to **Security > User account** on page 112 for details.

HTTP RTSP SIP	
Authentication:	basic 🗸
Access name for stream 1:	live.sdp
Access name for stream 2:	live2.sdp
Access name for stream 3:	live3.sdp
Access name for stream 4:	live4.sdp
RTSP port:	554
RTP port for video:	5556
RTCP port for video:	5557
RTP port for metadata:	6556
RTCP port for metadata:	6557
RTP port for audio:	5558
RTCP port for audio:	5559
Multicast settings for stream 1	
Multicast settings symbol 2	
Multicast settings for stream 3	
Multicast settings for stream 4	
	Save

<u>Authentication</u>: Depending on your network security requirements, the Network Camera provides three types of security settings for streaming via RTSP protocol: disable, basic, and digest.

If **basic** authentication is selected, the password is sent in plain text format, but there can be potential risks of it being intercepted. If **digest** authentication is selected, user credentials are encrypted using MD5 algorithm, thus provide better protection against unauthorized access.

The availability of the RTSP streaming for the three authentication modes is listed in the following table:

	Quick Time player	VLC Player
Disable	0	0
Basic	0	0
Digest	0	Х

<u>Access name for Channel # and stream #</u>: This Network camera supports multiple streams simultaneously. The access name is used to differentiate the streaming source.

If you want to use an RTSP player to access the Network Camera, you **HAVE TO** set the video mode to H.264 and use the following RTSP URL command to request transmission of the streaming data.

rtsp://<ip address>:<rtsp port>/<access name for stream1 ~ 4>

For example, when the access name for stream 1 is set to live.sdp:

- 1. Launch an RTSP player.
- 2. Choose File > Open URL. A URL dialog box will pop up.
- 3. Type the above URL command in the address field.
- 4. The live video will be displayed in your player as shown below.



Open URL	
Enter an Internet URL to open	
rtsp://192.168.5.151:554/live.sdp	×
	OK Cancel

RTSP port /RTP port for video, audio/ RTCP port for video, audio

- RTSP (Real-Time Streaming Protocol) controls the delivery of streaming media. By default, the port number is set to 554.
- The RTP (Real-time Transport Protocol) is used to deliver video and audio data to the clients. By default, the RTP port for video is set to 5556 and the RTP port for audio is set to 5558.
- The RTCP (Real-time Transport Control Protocol) allows the Network Camera to transmit the data by monitoring the Internet traffic volume. By default, the RTCP port for video is set to 5557 and the RTCP port for audio is set to 5559.

The ports can be changed to values between 1025 and 65535. The RTP port must be an even number and the RTCP port is the RTP port number plus one, and thus is always an odd number. When the RTP port changes, the RTCP port will change accordingly.

If the RTP ports are incorrectly assigned, the following warning message will be displayed:

Microsoft Internet Explorer		
⚠	Invalid port number. RTP video port must be an even numbe	
	ОК	

<u>Multicast settings for stream #1 ~ #4</u>: Click the items to display the detailed configuration information. Select the Always multicast option to enable multicast for streams #1 ~ #4.

#### w Multicast settings for stream 1 Always multicast 239.128.1.99 Multicast group address: 5560 Multicast video port: Multicast RTCP video port: 6560 Multicast metadata port: Multicast RTCP metadata port: 5562 Multicast audio port: Multicast RTCP audio port: Multicast TTL [1~255]: 15 \* Multicast settings for stream 2 Always multicast 239.128.1.100 Multicast group address: 5564 Multicast video port: Multicast RTCP video port: 6564 Multicast metadata port: Multicast RTCP metadata port: 5566 Multicast audio port: Multicast RTCP audio port: 15 Multicast TTL [1~255]:

Unicast video transmission delivers a stream through point-to-point transmission; multicast, on the other hand, sends a stream to the multicast group address and allows multiple clients to acquire the stream at the same time by requesting a copy from the multicast group address. Therefore, enabling multicast can effectively save Internet bandwith.

The ports can be changed to values between 1025 and 65535. The multicast RTP port must be an even number and the multicast RTCP port number is the multicast RTP port number plus one, and thus is always odd. When the multicast RTP port changes, the multicast RTCP port will change accordingly.

If the multicast RTP video ports are incorrectly assigned, the following warning message will be displayed:



<u>Multicast TTL [1~255]</u>: The multicast TTL (Time To Live) is the value that tells the router the range a packet can be forwarded.

Initial TTL	Scope	
0	Restricted to the same host	
1	Restricted to the same subnetwork	
32	Restricted to the same site	
64	Restricted to the same region	
128	Restricted to the same continent	
255	Unrestricted in scope	



### IMPORTANT:

The Multicast metadata port is utilized by VIVOTEK VADP modules to transfer video analytics results, PTZ stream, textual data, and event messages between the camera and the client side running and observing the video analysis. If your client side computer is located outside the local network, you may need to open the associated TCP port on routers and firewall.


#### SIP


SIP is short for Session Initiation Protocol. If necessary, you can change the default port number, 5060, to one between 1025 and 65535.

<u>Two way audio port</u>: By default, the two way audio port is set to 5060. Also, it can also be assigned to another port number between 1025 and 65535.

The Network Camera supports two way audio communication so that operators can transmit and receive audio simultaneously. By using the Network Camera's built-in or external microphone and an external speaker, you can communicate with people around the Network Camera.

Note that as JPEG only transmits a series of JPEG images to the client, to enable the two-way audio function, make sure the video mode is set to H.264 on the Media > Video > Stream settings page and the media option is set to "Media > Video > Stream settings" on the Client Settings page. Please refer to Client Settings on page 55 and Stream settings on page 84.





Audio is being transmitted to the Network Camera

Click 💽 to enable audio transmission to the Network Camera; click 🔛 to adjust the volume of microphone; click 👽 to turn off the audio. To stop talking, click 🕞 again.

## Network > DDNS

This section explains how to configure the dynamic domain name service for the Network Camera. DDNS is a service that allows your Network Camera, especially when assigned with a dynamic IP address, to have a fixed host and domain name.

### Manual setup

DDNS: Dynamic domain name service

DDNS: Dynamic domain name service		
Enable DDNS:		
Provider:	Dyndns.org(Dynamic) 🗸	
Host name:		
User name:		
Password:		

Enable DDNS: Select this option to enable the DDNS setting.

Provider: Select a DDNS provider from the provider drop-down list.

VIVOTEK offers **Safe100.net**, a free dynamic domain name service, to VIVOTEK customers. It is recommended that you register **Safe100.net** to access VIVOTEK's Network Cameras from the Internet. Additionally, we offer other DDNS providers, such as Dyndns.org(Dynamic), Dyndns.org(Custom), Safe100.net, and CustomSafe100.

Note that before utilizing this function, please apply for a dynamic domain account first.

#### ■ Safe100.net

- 1. In the DDNS column, select **Safe100.net** from the drop-down list. Click **I accept** after reviewing the terms of the Service Agreement.
- 2. In the Register column, fill in the Host name (xxxx.safe100.net), Email, Key, and Confirm Key, and click **Register**. After a host name has been successfully created, a success message will be displayed in the DDNS Registration Result column.

- Degister			
Γ	Register		
	Host name:	VVTK. <mark>safe100.net</mark>	
	Email:	wtk@vivotek.com	
	Key:	••••	Forget key
	Confirm key:	••••	]
To apply for a domain name for the camera, or to modify the previously registered information, fill in		ously registered information, fill in	
	the following fields and then click "Register".		
	Register		
DDNS Registration Result:			
l	[Register] Successfully Your account information has been mailed to registered e-mail address		
	Upon successful registration, you can click copy to automatically upload relevant information to the		
DDNS form or you can manually fill it in. Then, click "Save" to save new settings.			new settings.

3. Click **Copy** and all the registered information will automatically be uploaded to the corresponding fields in the DDNS column at the top of the page as seen in the picture.

DDNS: Dynamic domain name s	ervice	
Enable DDNS:		
Provider:	Safe100.net	
Host name:	VVTK.safe100.net	[*.safe100.net]
Email:	wtk@vivotek.com	
Key:	••••	
Save Register		
Register		
Host name:	VVTK.safe100.net	
Email:	wtk@vivotek.com	
Key:	•••• Forget	t key
Confirm key:	••••	
To apply for a domain name for the can	nera, or to modify the previously registe	red information, fill in
the following fields and then click "Regi	ster".	
Register		
DDNS Registration Result:		
[Register] Successfully Your account been mailed to registered e-mail add		
Upon successful registration, you can o DDNS form or you can manually fill it in		

4. Select Enable DDNS and click **Save** to enable the setting.

### CustomSafe100

VIVOTEK offers documents to establish a CustomSafe100 DDNS server for distributors and system integrators. You can use CustomSafe100 to register a dynamic domain name if your distributor or system integrators offer such services.

- 1. In the DDNS column, select CustomSafe100 from the drop-down list.
- 2. In the Register column, fill in the Host name, Email, Key, and Confirm Key; then click **Register**. After a host name has been successfully created, you will see a success message in the DDNS Registration Result column.
- 3. Click **Copy** and all for the registered information will be uploaded to the corresponding fields in the DDNS column.
- 4. Select Enable DDNS and click **Save** to enable the setting.

<u>Forget key</u>: Click this button if you have forgotten the key to Safe100.net or CustomSafe100. Your account information will be sent to your email address.

Refer to the following links to apply for a dynamic domain account when selecting other DDNS providers:

Dyndns.org(Dynamic) / Dyndns.org(Custom): visit http://www.dyndns.com/

#### **Express link**

Express Link is a free service provided by VIVOTEK server, which allows users to register a domain name for a network device. One URL can only be mapped to one MAC address. This service will examine if the host name is valid and automatically open a port on your router. If using DDNS, the user has to manually configure UPnP port forwarding. Express Link is more convenient and easier to set up.

Manual setup	Express link			
Enable expression	ess link			
http://		.2bthere.net	<u>Help</u>	Save
	k, all users need mera from interne	name for the ca	amera. I	t will generate the link to

Please follow the steps below to enable Express Link:

- 1. Make sure that your router supports UPnP port forwarding and it is activated.
- 2. Check Enable express link.
- 3. Enter a host name for the network device and click **Save**. If the host name has been used by another device, a warning message will show up. If the host name is valid, it will display a message as shown below.

Z Enable express link			
ttp:// vivotek_test3454	.2bthere.net Help	Save	



## Network > QoS (Quality of Service)

Quality of Service refers to a resource reservation control mechanism, which guarantees a certain quality to different services on the network. Quality of service guarantees are important if the network capacity is insufficient, especially for real-time streaming multimedia applications. Quality can be defined as, for instance, a maintained level of bit rate, low latency, no packet dropping, etc.

The following are the main benefits of a QoS-aware network:

- The ability to prioritize traffic and guarantee a certain level of performance to the data flow.
- The ability to control the amount of bandwidth each application may use, and thus provide higher reliability and stability on the network.

#### **Requirements for QoS**

To utilize QoS in a network environment, the following requirements must be met:

- All network switches and routers in the network must include support for QoS.
- The network video devices used in the network must be QoS-enabled.

#### **QoS models**

#### CoS (the VLAN 802.1p model)

IEEE802.1p defines a QoS model at OSI Layer 2 (Data Link Layer), which is called CoS, Class of Service. It adds a 3-bit value to the VLAN MAC header, which indicates the frame priority level from 0 (lowest) to 7 (highest). The priority is set up on the network switches, which then use different queuing disciplines to forward the packets.

Below is the setting column for CoS. Enter the **VLAN ID** of your switch ( $0\sim4095$ ) and choose the priority for each application ( $0\sim7$ ).

CoS	
📝 Enable CoS	
VLAN ID:	1
Live video:	0 🗸
Live audio:	0 🗸
Event/Alarm:	0 🗸
Management:	0 🔻

If you assign Video the highest priority level, your network switch will handle video packets first.



- A VLAN-capable switch (802.1p) is required. Web browsing may fail if the CoS setting is incorrect.
- Class of Service technologies do not guarantee a level of service in terms of bandwidth and delivery time; they offer a "best-effort." Users can think of CoS as a "coarsely-grained" traffic control and QoS as a "finely-grained" traffic control.
- Although CoS is simple to manage, it lacks scalability and does not offer end-to-end guarantees since it is based on L2 protocol.

### QoS/DSCP (the DiffServ model)

DSCP-ECN defines QoS at Layer 3 (Network Layer). The Differentiated Services (DiffServ) model is based on packet marking and router queuing disciplines. The marking is done by adding a field to the IP header, called the DSCP (Differentiated Services Codepoint). This is a 6-bit field that provides 64 different class IDs. It gives an indication of how a given packet is to be forwarded, known as the Per Hop Behavior (PHB). The PHB describes a particular service level in terms of bandwidth, queueing theory, and dropping (discarding the packet) decisions. Routers at each network node classify packets according to their DSCP value and give them a particular forwarding treatment; for example, how much bandwidth to reserve for it.

Below are the setting options of DSCP (DiffServ Codepoint). Specify the DSCP value for each application (0~63).

Live video:	0	
Live audio:	0	
Event/Alarm:	0	
Management:	0	

Note that different vendors of network devices might have different methodologies and unique implementations. Shown below is a sample corresponding information from a Cisco switch. You should enter a DSCP tag value according to the information provided by the network devices.

Ingress DSCP	Output Queue	Ingress DSCP   Out	put Queue	Ingress DSCP Out	put Queue	Ingress DSCP Out	put Queue
0(BE)	1.1	16(CS2)	2.*	32(CS4)	3 *	48(CS6)	3 *
4	5.4	17	2 *	30	3.*	49	3 *
2	5.*	18(AF21)	2.*	34(AF41)	3.*	50	3 •
3	1 -	19	2 *	35	3.	51	3 *
4	3.4	20(AF22)	2 *	36(AF42)	3 *	52	3 *
5	1.*	21	2 *	37	3 *	53	3 *
6	1.*	22(AF23)	2 *	38(AF43)	3.*	54	3 *
7	5.*	23	2.*	39	3 *	55	3 -
8(CS1)	1.*	24(CS3)	3 *	40(C85)	4.*	56(CS7)	3 .
9	3.4	25	3.1	41	4 7	57	3 *
10(AF11)	1.1	26(AF31)	3.*	42	4.7	58	3 *
11	1.*	27	3 *	43	4.*	59	3 *
12(AF12)	5.*	28(AF32)	3.*	44	4.7	60	3 *
13	1 *	29	3 *	45	4.*	61	3 *
14(AF13)	3.4	30(AF33)	3.*	46(EP)	4 7	62	3 *
15	1.7	31	3 7	47	4.7	63	3 *
Queue 1 has t	he lowest priority.	queue 4 has the high	est priority.				

 QoS/DSCP

 ✓ Enable GoO/DSCP

 Live video.

 1 rice audio:

 FwentNatame:

 Management.

QoS Baseline/Technic	al Marketir	ng Classification	and Marking I	Recommenda	tions		
Application	Layer3 Cl	Layer3 Classification			Layer 2 CoS/MPLS EXP		
	IPP	PHB	DSCP				
IP Routing	6	CS6	48	6			
Voice	5	EF	46	5			
Interactive Video	4	AF41	34	4	QoS B		
Streaming-Video	4	CS4	32	4			
Locally-defined Mission- Critical Data	3	-	25	3			
Call-signaling	3	AF31/CS3	26/24	3			
Transactional Data	2	AF21	18	2			
Network Management	2	CS2	16	2			
Bulk Data	1	AF11	10	1			

# **Network > SNMP (Simple Network Management Protocol)**

This section explains how to use the SNMP on the network camera. The Simple Network Management Protocol is an application layer protocol that facilitates the exchange of management information between network devices. It helps network administrators to remotely manage network devices and find, solve network problems with ease.

- The SNMP consists of the following three key components:
- 1. Manager: Network-management station (NMS), a server which executes applications that monitor and control managed devices.
- 2. Agent: A network-management software module on a managed device which transfers the status of managed devices to the NMS.
- 3. Managed device: A network node on a managed network. For example: routers, switches, bridges, hubs, computer hosts, printers, IP telephones, network cameras, web server, and database.

Before configuring SNMP settings on the this page, please enable your NMS first.

### **SNMP** Configuration

#### Enable SNMPv1, SNMPv2c

Select this option and enter the names of Read/Write community and Read Only community according to your NMS settings.

Enable SNMPv1, SNMPv2c

SNMPv1, SNMPv2c Settin	ngs	
Read/Write community:	Private	
Read only community:	Public	

#### Enable SNMPv3

This option contains cryptographic security, a higher security level, which allows you to set the Authentication password and the Encryption password.

- Security name: According to your NMS settings, choose Read/Write or Read Only and enter the community name.
- Authentication type: Select MD5 or SHA as the authentication method.
- Authentication password: Enter the password for authentication (at least 8 characters).
- Encryption password: Enter a password for encryption (at least 8 characters).

Enable SNMPv3

SNMPv3 Settings		
Read/Write Security name:	Private	
Authentication Type:	MD5 💌	
Authentication Password:		
Encryption Password:		
Read only Security name:	Public	
Authentication Type:	MD5 💌	
Authentication Password:		
Encryption Password:		

# Network > FTP

The newer firmware may disable the FTP port for security concerns. You can manually enable the FTP server service to enable the FTP function.

<u>FTP port</u>: The FTP server allows the user to save recorded video clips. You can utilize VIVOTEK's Installation Wizard 2 to upgrade the firmware via FTP server. By default, the FTP port is set to 21. It can also be assigned to another port number between 1025 and 65535.



You can FTP the camera's IP address to download videos recorded in the SD card, or use the "http://ip/ cgi-bin/admin/lsctrl.cgi?cmd=search" command to examine the recorded files on your SD card.

# Security > User accounts

This section explains how to enable password protection and create multiple accounts.

# Account management

Security > User accounts		
Account management Privilege management	nent	
New user V		
User name:	front_guard	
User password:	•••••	Medium
* At least 8 characters with no space, one alphabet	character and one numeric characte	er
Confirm user password:	•••••	
Privilege:	Operator 🗸	
	Delete Add	Update

The administrator account name is "root", which is permanent and can not be deleted. If you want to add more accounts in the Account management window, please apply the password for the "root" account first.

The administrator can create up to 20 user accounts.

To create a new user,

- 1. Click to unfold the pull-down menu. Select New user.
- 2. Enter the new user's name and password. Type the password identically in both text boxes.

Some, but not all special ASCII characters are supported: !, \$, %, -, ., @, ^, \_, and ~. You can use them in the password combination.

The strength of your password combination is shown on the right, use the combination of alphabetic, numeric, upper case, and lower case characters until the password strength is good enough.

3. Select the privilege level for the new user account. Click **Add** to enable the setting. The privilege levels are listed below:

Administrator	Full control
Operator	Control DO, white-light illuminator, snapshot, and PTZ;
	unable to enter the camera Configuration page.
Viewer	Control DO, white-light illuminator, view, listen, PTZ, and talk through the camera
	interface.

Access rights are sorted by user privilege (Administrator, Operator, and Viewer). Only administrators can access the Configuration page. Although operators cannot access the Configuration page, they can use the URL Commands to get and set the value of parameters. For more information, please refer to URL Commands of the Network Camera on page 163. Viewers can only access the main page for live viewing.

Here you also can change a user's access rights or delete user accounts.

- 1. Select an existing account to modify.
- 2. Make necessary changes and click **Update** or **Delete** to enable the setting.

### **Privilege management**

Account mana	agement	Privilege man	agement			
Allow anor	nymous vie	wing				
Operator:	🗸 Di	gital output	✓	PTZ control		
Viewer:	🗌 Di	gital output	✓	PTZ control		
					Save	]

<u>Digital Output & PTZ control</u>: You can modify the management privilege as operators or viewers. Select or de-select the checkboxes, and then click **Save** to enable the settings. If you give Viewers the privilege, Operators will also have the ability to control the Network Camera through the main page. (Please refer to Configuration on page 57).

<u>Allow anonymous viewing</u>: If you select this item, any client can access the live stream without entering a User ID and Password.

# Security > HTTPS (Hypertext Transfer Protocol Secure)

This section explains how to enable authentication and encrypted communication. It helps protect streaming data transmission over the Internet on higher security level.

### **Create and Install Certificate Method**

Before using HTTPS for communication with the Network Camera, a **Certificate** must be created first. There are three ways to create and install a certificate:

**Create self-signed certificate** 

- 1. Select the first option.
- 2. Check **Enable HTTPS secure connection**, then select a connection option: "HTTP & HTTPS" or "HTTPS only".
- 3. Click **Create certificate** to generate a certificate.

HTTPS							
Enable HTTPS secure connection							
🐭 Mode:							
● HTTP & HTTPS ◎ HTTPS only							
Certificate inform	Certificate:						
Certificate inform	ation						
Status:		Not instal	ed				
Method:		Create se	If-signed certificate	-			
Country:		TW					
State or province:		Asia					
Locality:		Asia					
Organization:		VIVOTEK	Inc.				
Organization unit:		VIVOTEK	Inc.				
Common name:		www.viv	otek.com				
Validity:		3650	days				
	Diaman 1 1			Create cert	ificate		
	Please wait whil generated	le the certif	icate is being				
	generated						

4. The Certificate mornation will automatically be also ayea in the lower screen as shown below. You can click **Certificate properties** to view detailed information about the certificate.

Certificate information	
Status:	Active
Method:	Create self-signed certificate
Country:	TW
State or province:	Asia
Locality:	Asia
Organization:	VIVOTEK Inc.
Organization unit:	VIVOTEK Inc.
Common name:	www.vivotek.com
	Certificate properties Remove certificate
	Save

- 5. Click **Save** to preserve your configuration, and your current session with the camera will change to the encrypted connection.
- 6. If your web session does not automatically change to an encrypted HTTPS session, click Home to return to the main page. Change the URL address from "<u>http://</u>" to "<u>https://</u>" in the address bar and press Enter on your keyboard. Some Security Alert dialogs will pop up. Click OK or Yes to enable HTTPS.

# https://

	Mega-Pixel Network Camera
Video stream 1 M Marual trigger Digital output I I III Marual trigger Digital output I IIII Marual trigger Digital output I IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	Security Atert
irity Alert	Security Information
Information you exchange with this sit changed by others. However, there is security certificate.	ite cannot be viewed or is a problem with the site's ued by a company you have
Information you exchange with this sit changed by others. However, there is security certificate.	ite cannot be viewed or is a problem with the site's ued by a company you have ertificate to determine whether authority.

#### Create certificate request and install

- 1. Select the option from the **Method** pull-down menu.
- 2. Click Create certificate to proceed.
- 3. The following information will show up in a pop-up window after clicking **Create**. Then click **Save** to generate the certificate request.

💙 Ce	rtificate:	
	Certificate information	
	Status:	Notinstalled
	Method:	Create certificate request and install
	Country:	TW
	State or province:	Asia
	Locality:	Asia
	Organization:	VIVOTEK Inc.
	Organization unit:	VIVOTEK Inc.
	Common name:	www.vivotek.com
	Please wait while the certific generated	Create certificate

4. The Certificate request window will prompt.

e	http://192168 + 163/perup/security/certificate_request.html + Windows Intern.	1.3
ľ	Create certificate request completed	
	Copy the PEM formal request below and send it to a CA for identity validation. After that, you have to install it by clicking the "Upload" bullon on HTTPS page.	
	Certificate request (PEM format)	
	MITH #SOCABUCAQIVERETABLE REQUEST	
	30cmrfluov== END CERTIFICATE REQUEST	

If you see the following Information bar, click **OK** and click on the Information bar at the top of the page to allow pop-ups.



5. Look for a trusted certificate authority, such as Symantec's VeriSign Authentication Services, that issues digital certificates. Sign in and purchase the secure certification service. Copy the certificate request from your request prompt and paste it in the CA's signing request window. Proceed with the rest of the process as CA's instructions on their webpage.

ee Trial >> Occurred	► 21 Notwice Care	ant > 3 CSR > 1 Summary	Chet With Us
Enter Certificate Signing P	lequest (CSR)		
Server platform: 🕥 Selectione	×	Sample CSI - Base CE FIG. 1 Report - Bas	Order details Symwater ** SSL Test Cettlicate • Vasity proof 30 aign
BACTORT25//E-FTATbg SyBAmitAME-wFG/TD/ AAX08/DAWgFYRg/TEA2 515-WFBgD028/FCDL2 305-D029-m076-AA26 AaAAM000C392582D T752-W502-T0224E3	MARGA LEBRACVE AVEAUTOR 2 AVEAU 1960 EN C34300 JM 1960 EN C34300 JM 1973 AVEAU 1980 EN C36 1980 2080 EN C36 1980 1980 EN C36	csCTA_BigHVHsgTBEFSWHjSTALBigHV 33 TusgDWEBLZVHERNAATUSCSHENAATUSC TBGVHSULL/HLINNAATUSCSHENAATUSC TBGVHSULL/HLINNABHUGHVBSAEE TBGVHSULL/HLINNABHUGHVBSAEE TBGVHSULL/HLINNABHUGHVBSAE TBGVHSULL/HLINNABHUGHVBSAE TBGVHSULL/HLINNABHUGHVBSAE ColleGaveEts/TwiteFood/TDSAE ColleGaveEts/TwiteFood/TDSAE	What is a CSR? What is a CSR? A CSR is generated from your samer and your samer's unique "ingerprint". The CB motubes upon another print and the set working a series and the set and consistence of the second second benefitige on the second second second benefitige on the second second second benefitige on the second second benefitige of the second secon
			Geer

 Once completed, your certificate should be delivered to you via an email or other means. Copy the contents of the certificate in the email and paste it in a text/HTML/hex editor/converter, such as IDM Computer Solutions' UltraEdit.

immediately, please dial 866.893.6565 or 650.426.5112 option 3 or send an email to internet-sales@verisign.com
Thank you for your interest in Symanter!
<pre>HEGII: CERTIFICATE HITFHCCA:+yyAdTBagiQFAICAD: JeE8110MQDOBI:#ARBgaghkiGP+08AQUFADCB ysE10AKGAUUENMCVNer=AVBgAVABCTIII:mit*AbduGVDSmethafTakGyUVVQC yydr511CPQCKANGNUC;PSEnacS.LLAgTbgQTDBLcKADmethadLagUVVQC BafT0VII.mitTCDmLTNTe25BbgCBedEBerzervL3d5dy52ZX3pc21nh15b2DVY3Bs L3BLCBSYIXAVYskvTE:HDS6AUUEAMCVNYyVMp224VUDyDVvqUVy3KX1TTTII ccliclBQCASTED;054X4UEJBAGCBEdEBerzervL3d5dy52ZX3pc21nh15b2DVY3Bs L3BLCBSYIXAVYskvTE:HDS6AUUEAMCVNYyVMp224VUDyDVvqUVy3KX1TTTII ccliclBQCASTED;054X4UEJBAGCBEAMCMCVCVTVVQUFFABE21h60DVEVTD VQUFFAMH9V2FVEVLIELuty4wFTAT5gNV5acDVCVVTVVQUFFABE21h60DVEVTD VQUFFAMH9V2FVEVLIELuTy4wFTAT5gNV5acDVCVVTVVQUFFABE21h60DVEVTD VQUFFAMH9V2FVEVLIELUTy4wFTAT5gNV5acDVCVVTVVQUFFABE21h60DVEVTD VQUFFAMH9V2FVEVLIELUTy4wFTAT5gNV5acDVCVVTVVQUFFABE21h60DVEVTD VQUFFAMH9V2FVEVLIELUTy4wFTAT5gNV5acDVCVVTVVQUFFABE21h60DVEVTD VQUFFAMH9V2FVEVLIELUTy4wFTAT5gNV5acDVCVVTVVQUFFABE21h60DVEVTD VQUFFAMH9V2FVEVLIELUTy4wFTAT5gNV5acDVCVVTVQUFFABE21h60DVEVTD VQUFFAMH9V2FVEVLIELUTy4wFTAT5gNV5acDVCVVTVQUFFABE21h60DVEVTD VQUFFAMH9VEFAUHEAMCVSACDVCVTVVQUFFABE21h60DVEVTD VQUFFAMH9VEFVUFFALIELUTy4wFTAT5gNV5acDVCVVTVQUFFABE21h60DAB1 gVAML67Ar6BABLIECGCUFFABE21AOGUNAS2VEFABE20AGUNAGAB2X00N0hag4FABABABABABABABABABABABABABABABABABABAB</pre>

7. Open a new edit, paste the certificate contents, and press ENTER at the end of the contents to add an empty line.

	KARATARANA KARATARAN JORRENGARARA	
+ a × Protect Open Explorer Lists	See Edit x	* a ×
ter:		×
C:	Concession and the second seco	
		1

8. Convert file format from DOS to UNIX. Open **File** menu > **Conversions** > **DOS to Unix**.

-	Edit I*] - UltraEdit Edit Search Insert Prov	of Very Fran	r Column Macro Scripting Advanced Window Help
	New Sector Street Prop	Chi+N	
0	Open	CHI+O	
	Quick Open	Corl+Q	* 0 X
	goce		N X
ŝ,	Close All Elles	Cori+Shift+F4	
٥	Close All Files Except This		
	F]P/Tekset		10 20 40 50 50 50 50 50 50 50 50 50 50 50 50 50
•	Revent to Saved		L2Nwcy90ZXNOY2EwHQYDVR01BBYwFAYIKwYBBQUHAwEGCCsGAQUFBwHCHB0G
	Save	Ctrl+S	dIwQYMBaAFCgXE4q91qK13AYst7a02hBmYG71MHQGCCsGAQUFBwEBBGgwZjAk
	Save As	F12	rBgrFBQevAYYYAHROcDovL29jc)AudmVyaXNp224uY29tHD4GCCaGAQUFBzAC cdHRw0i8vU12SVHJpYWwtRzItYW1hLn21cm1zaWduLmNvbS9TV1JUcm1hbEcy
a	Save Al	AR+F12	lcjANBgkqhk1G9w0BAQUFALOCAQEATxuH7FnIme/X7T6z/zzr9zEKhLKSEQSp
	Seve Selection Ac	121022	c0swixSc129PpJkzERvp6TCLPSMbr0PGjPa1LFxAEUITrJW1SCoXWR1AjWp12
ä	Make Copy/Backup		bDfxgVHVx9T7rd2oURzjms6ifcH5Tcub3Qc2Tu3pVeANDAH/U+x+ojG0EvB3z Shn/qcapKcqOXvHycwHeCWNSRQgsGei368qkPzssv7oErbnLhupjdxDE3GExu
-	Encryption		Shn/qcapKcqOXvNycwHeCWNSRQysGci368qkPizsv70ErbnLhupjdxUE3GExu OCXrAtQZv1RadifJQYSTgSONq2mA9ghdEuKTnbCHUwwqOxNBuceII63ITFFK70 SYnstbicmErxy1ExwIUdc6YZIms2E5gc55gc12ABPH/gi//ZeGgs=
	Rename Fée		a share after a break a second a second a second a second
-			END CERTIFICATE
ę.	Cogpare	At+F11	-
	Soft		
	Conversions Special Functions		Land Constantia Consta
			TO DO TO SHE
Ħ	But	Ot/HP	
1	Print All Files		
54	Print Preview		Accil to Electric and a constraint and a
	Print Setup/Configuration		🕂 OEM to AlgSt 🥵 🖓
0	Fagorite Files	Ctrl+Shift+F	Power User
	Recent Files		- ASCII to Urecode
	Recent Projects/WorkSpace		2 UTHE to Decoor
	Est		U Transfer to ASCII

and a second s	Save As					2 ×
ect Open Explorer Lists	Save	Desktop		202	• 🖬 •	
A: C: C: C: C: C: F: F: F: F: F: F: Network FIP Accounts Name Date modified	Ny Pacent Documents Declarp My Documents My Documents	My Documents My Computer My Network P Adobe Reade Friezilis Clerk Google Chrom Tristalation W UveClerk Mickfee Secur Mickfee Sec	laces 9 e cord 2 ty Scan Has tect Smart Client	UltraCompare  UltraEdt		0M /6 m3 c1
	Mu Madaman	Fienane	CAcet cit			Al Save
	My Network Places	Save at type:	All Files. (".")		and the second se	ancel
		Line Terminator:	Default			
dt Witteljee		Format:	Default	r norod use, or charge if eggent	•	
		ADS Stream:	-	esteel Arter Descriptioner	-	

9. Save the edit using the ".crt" extension, using a file name like "CAcert.crt."

10. Return to the original firmware session, use the **Browse** button to locate the crt certificate file, and click **Upload** to enable the certification.

	Security > HTTPS	
System	E HTTPS	
Media	F Enable HTTPS secure conne	ction
Network	🤝 Modu:	
Security	IF HITP & HTTPS C F	ITTPS only
User accounts	👻 Certificate	
HTTPS	Certificate information	
Access list	Statue:	Waiting for certificated
BEE 802.1x	Select certificate file:	C Documents and Se Drowse Upload
PTZ	Method:	Create certificate request and install
Event	Country.	TW
Applications	State or province:	Asia
	Locality	Asia
Recording	Organization:	VIVOTEK Inc.
Local storage	Organization unit	VIVOTEK Inc.
	Common name;	www.vivolek.com
(Basic mode )		Remove certificate

-

11. When the certifice file is successfully loaded, its status will be stated as **Active**. Note that a certificate must have been created and installed before you can click on the "**Save**" button for the configuration to take effect.

Enable HTTPS secure connect	
Mode:	
C HTTP&HTTPS C HT	TPS only
Certificate:	
Certificate information	
Status	Active
Method	Create certificate request and install
Country	TW
State or province:	Asia
Locality.	Asia
Organization	VIVOTEK Inc.
Organization unit	VIVOTEK Inc.
Common name:	www.wvotek.com
	Certificate properties Remove certificat

12. To begin an encrypted HTTPS session, click **Home** to return to the main page. Change the URL address from "<u>http://</u>" to "<u>https://</u>" in the address bar and press **Enter** on your keyboard. Some Security Alert dialogs will pop up. Click **OK** or **Yes** to enable HTTPS.

Security A	lert				Security	Information
۲ ۲	You are about to vie Any information you viewed by anyone e In the future, do r	exchange with Ise on the Wel	b.		ß	This page contains both secure and nonsecure items. Do you want to display the nonsecure items? Yes No More Info
		Securit	Information you e changed by other security certificate The security not chosen you want to The security The name of The name of	y certificate was issued by to trust. View the certifical trust the certifying authori y certificate date is valid. on the security certificate is name of the site roceed?	blem with the a company y e to determin ty.	ou have e whether es not

# Security > Access List

This section explains how to control access permission by verifying the client PC's IP address.

# General Settings

General settings			
Maximum number of concur	rent streaming: 10 💌	Connection management	

<u>Maximum number of concurrent streaming connection(s) limited to</u>: Simultaneous live viewing for 1~10 clients (including stream #1, #2, and #3). The default value is 10. If you modify the value and click **Save**, all current connections will be disconnected and automatically attempt to re-link (IE Explorer or Quick Time Player).

<u>Connection management</u>: Click this button to display the connection status window showing a list of the current connections. For example:

	IP address	Elapsed time	User ID			
	192.168.1.147	12:20:34	root			
	61.22.15.3	00:10:09				
	192.168.3.25	45:00:34	greg			
Re	Refresh Add to deny list Disconnect Close					

- IP address: Current connections to the Network Camera.
- Elapsed time: How much time the client has been at the webpage.
- User ID: If the administrator has set a password for the webpage, the clients have to enter a user name and password to access the live video. The user name will be displayed in the User ID column. If the administrator allows clients to link to the webpage without a user name and password, the User ID column will be empty.

There are some situations which allow clients access to the live video without a user name and password:

- 1. The administrator does not set up a root password. For more information about how to set up a root password and manage user accounts, please refer to Security > User account on page 112.
- 2. The administrator has set up a root password, but set **RTSP Authentication** to "disable". For more information about **RTSP Authentication**, please refer to RTSP Streaming on page 99.
- 3. The administrator has set up a root password, but allows anonymous viewing. For more information about **Allow Anonymous Viewing**, please refer to page 112.
- Refresh: Click this button to refresh all current connections.
- Add to deny list: You can select entries from the Connection Status list and add them to the Deny List to deny access. Please note that those checked connections will only be disconnected temporarily and will automatically try to re-link again (IE Explore or Quick Time Player). If you want to enable the denied list, please check Enable access list filtering and click Save in the first column.

Disconnect: If you want to break off the current connections, please select them and click this button. Please note that those checked connections will only be disconnected temporarily and will automatically try to re-link again (IE Explorer or Quick Time Player).

<u>Enable access list filtering</u>: Check this item and click **Save** if you want to enable the access list filtering function.

#### Filter

<u>Filter type</u>: Select **Allow** or **Deny** as the filter type. If you choose **Allow Type**, only those clients whose IP addresses are on the Access List below can access the Network Camera, and the others cannot access. On the contrary, if you choose **Deny Type**, those clients whose IP addresses are on the Access List below will not be allowed to access the Network Camera, and the others can access.

Then you can **Add** a rule to the following Access List. Please note that the IPv6 access list column will not be displayed unless you enable IPv6 on the Network page. For more information about **IPv6 Settings**, please refer to Network > Enable IPv6 on page 96 for detailed information.

Г	Filter
	Enable access list filtering
	Filter type: 🔘 Allow 💿 Deny
	IPv4 access list
	Add Delete
	IPv6 access list
	Add Delete

There are three types of rules:

<u>Single</u>: This rule allows the user to add an IP address to the Allowed/Denied list. For example:

Filter address	
Rule: Single 💌	
IP address:	
OK Cancel	

<u>Network</u>: This rule allows the user to assign a network address and corresponding subnet mask to the Allow/Deny List. The routing prefix is written in CIDR (Classless Inter-Domain Routing) notation. For example:

Filter address			
Rule: Network			
Network address / Network mask:	192.168.2.0	/ 24	
OK Cancel			

accesses from IP address 192.168.2.x will be bolcked.

For example:

- 192.168.100.14/24 represents the IPv4 address 192.168.100.14 and its associated routing prefix 192.168.100.0, or equivalently, its subnet mask 255.255.255.0 has 24 leading 1-bits.
- The IPv4 block 192.168.100.0/22 represents the 1024 IPv4 addresses from 192.168.100.0 to 192.168.103.255.

If IPv6 filter is preferred, you will be prompted by the following window. Enter the IPv6 address and the two-digit prefix length to specify the range of IP addresses in your configuration.

ilter address	
ule: Network	
etwork address / Network mask:	1

<u>Range</u>: This rule allows the user to assign a range of IP addresses to the Allow/Deny List. Note: This rule is only applied to IPv4. For example:

Filter address			
Rule: Range 💌			
IP address - IP address:	192.168.2.0	- 192.168.2.255	

### Administrator IP address

<u>Always allow the IP address to access this device</u>: You can check this item and add the Administrator's IP address in this field to make sure the Administrator can always connect to the device.

Administrator IP address	
Always allow the IP address to access this device	
	Save

# Security > IEEE 802.1x

Enable this function if your network environment uses IEEE 802.1x, which is a port-based network access control. The network devices, intermediary switch/access point/hub, and RADIUS server must support and enable 802.1x settings.

The 802.1x standard is designed to enhance the security of local area networks, which provides authentication to network devices (clients) attached to a network port (wired or wireless). If all certificates between client and server are verified, a point-to-point connection will be enabled; if authentication fails, access on that port will be prohibited. 802.1x utilizes an existing protocol, the Extensible Authentication Protocol (EAP), to facilitate communication.

■ The components of a protected network with 802.1x authentication:



- 1. Supplicant: A client end user (camera), which requests authentication.
- 2. Authenticator (an access point or a switch): A "go between" which restricts unauthorized end users from communicating with the authentication server.
- 3. Authentication server (usually a RADIUS server): Checks the client certificate and decides whether to accept the end user's access request.
- VIVOTEK Network Cameras support two types of EAP methods to perform authentication: EAP-PEAP and EAP-TLS.

Please follow the steps below to enable 802.1x settings:

- 1. Before connecting the Network Camera to the protected network with 802.1x, please apply a digital certificate from a Certificate Authority (i.e., MIS of your company) which can be validated by a RADIUS server.
- Connect the Network Camera to a PC or notebook outside of the protected LAN. Open the configuration page of the Network Camera as shown below. Select EAP-PEAP or EAP-TLS as the EAP method. In the following blanks, enter your ID and password issued by the CA, then upload related certificate(s).


IEEE 802.1x				
Enable IEEE 802.1x		г	 The maximum length	of password is 200
EAP method:	EAP-PEAP 💙		symbols.	
Identity:		-		
Password:				
CA certificate:		Browse	Upload	
Status: no file	Remove			

- IEEE 802.1x			
Enable IEEE 802.1x			
EAP method:	EAP-TLS 🗸		
Identity:			
Private key password:			
CA certificate:		Browse	Upload
Status: no file	Remove		
Client certificate:		Browse	Upload
Status: no file	Remove		
Client private key:		Browse	Upload
Status: no file	Remove		
			Save

3. When all settings are complete, move the Network Camera to the protected LAN by connecting it to an 802.1x enabled switch. The devices will then start the authentication automatically.




- ► The authentication process for 802.1x:
- 1. The Certificate Authority (CA) provides the required signed certificates to the Network Camera (the supplicant) and the RADIUS Server (the authentication server).
- 2. A Network Camera requests access to the protected LAN using 802.1X via a switch (the authenticator). The client offers its identity and client certificate, which is then forwarded by the switch to the RADIUS Server, which uses an algorithm to authenticate the Network Camera and returns an acceptance or rejection back to the switch.
- 3. The switch also forwards the RADIUS Server's certificate to the Network Camera.
- 4. Assuming all certificates are validated, the switch then changes the Network Camera's state to authorized and is allowed access to the protected network via a pre-configured port.




# PTZ > PTZ settings

This section explains how to control the Network Camera's Pan/Tilt/Zoom operation.

The fisheye PTZ function allows users to move among regional views for close-up viewing. The PTZ view takes effect when the current field of view is not the circular Original view or the Panoramic view. Users can then move the view in different directions or zoom in or zoom out on the screen.



## **PTZ Settings**



Preset positions and rotation settings

In the PTZ settings page, you can create preset positions in the hemisphere covered by the fisheye lens. A total of 20 preset positions can be configured.

Please follow the steps below to configure preset positions and arrange them in a rotational tour through different positions.

- 1. First select a video stream on which the PTZ settings will take place.
- 2. Adjust the shooting area to the desired position using the PTZ keypad, the FOV indicators, or mouse clicks on the live screen. To begin the mouse control, click on the two interactive windows. Due to the highly-sensitive mouse control, the PTZ control buttons can help fine-tune to an optimal location.
- 3. After you selected an area of interest, enter a name for the new position, which can contain up to 40 alphabetic and numeric characters.

- 4. Click **Add** to enable the settings. The preset positions will be listed on the **User preset locations**. (To add more positions you wish, please repeat steps 1~3.)
- 5. Select the preset positions by their checkboxes.
- 6. Click on the move button (>>)  $\ge$  to move positions to the Patrol locations window.
- 7. You may select some or all of the imported positions as the stop points during the tour.
- 8. Select a preset position when you need to move to a specific place on screen.

Select a preferred **Rotate speed** or **move the preset positions** for consecutively displaying views of multiple positions. The speeds for rotating through each position on a Regional view window are shown below.

9. Click on the **Save** button to preserve your configuration.

To remove a preset position from the list, select it and click **Remove**. You can re-arrange the order of the position hop on the list using the **I u** buttons.

# **Event > Event settings**

This section explains how to configure the Network Camera to respond to particular situations (event). A typical application is that when a motion is detected, the Network Camera sends buffered images to an FTP server or e-mail address as notifications. Click on **Help**, there is an illustration shown in the pop-up window explaining that an event can be triggered by many sources, such as motion detection or external digital input devices. When an event is triggered, you can specify what type of action that will be performed.

Name	Status Sun M	on Tue We	d Thu Fri Sat	Time Trigger
Add	Help			close of Esc K
		Motion detect Digital input,	tion, Periodically, System boot Media (What to send)	Server (Where to send)
			Ex.	Ex.

### **Event**

An event is an action initiated by a user-defined trigger source. In the **Event** column, click **Add** to open the event settings window.

	Lvent	Chatus Cup Man Tup Wind Thu Fri Cat Time Triange
	Name	Status Sun Mon Tue Wed Thu Fri Sat Time Trigger
	Add	Help
F	Event name: Enable this even Priority: Normal Detect next motion de 1. Schedule 2. Trigger 3. Action	
		Save event Close

- Event name: Enter a name for the event setting.
- Enable this event: Select this checkbox to enable the event setting.
- Priority: Select the relative importance of this event (High, Normal, or Low). Events with a higher priority setting will be executed first.
- Detect next motion detection or digital input after seconds: Enter the duration in seconds to pause motion detection after a motion is detected. This prevents too many events to be triggered within a short time.

Follow the steps 1~3 to arrange the three elements -- Schedule, Trigger, and Action to set an event. A total of 3 event settings can be configured.

#### 1. Schedule

Specify the period for the event. Please select the days of the week and the time in a day (in 24-hr time format) to specify when will the event-triggering conditions take effect.

#### 2. Trigger

This is the cause or stimulus which defines what will trigger the event. The trigger source can be configured to use the Network Camera's built-in motion detection mechanism or external digital inputs.

There are several choices of trigger sources as shown below. Select each item to display its related options.


#### Video motion detection

This option makes use of the built-in motion detection mechanism as a trigger source. To enable this function, you need to configure a Motion Detection Window first. For more information, please refer to Motion Detection on page 143 for details.

Video motion detection		
Normal: 🔲 door		
Profile: 📄 hallway		
Note: Please configure	Motion detection	irst

#### Periodically

This option allows the Network Camera to trigger periodically for every other defined minute. Up to 999 minutes are allowed.



Trigger every other 1 minutes

#### Digital input

This option allows the Network Camera to use an external digital input device or sensor as a trigger source. Depending on your application, there are many choices with digital input devices on the market which help detect changes in temperature, vibration, sound, light, etc.

#### System boot

This option triggers the Network Camera when the power to the Network Camera is disconnected.

#### Recording notify

This option allows the Network Camera to trigger when the recording disk is full or when recording starts to overwrite older data.

Audio detection

A preset threshold can be configured with an external microphone as the trigger to system event. The triggering condition can be an input exceeding or falling below a threshold. Audio detection can take place as a complement to motion detection or as a method to detect activities not covered by the camera's view.

Camera tampering detection

This option allows the Network Camera to trigger when the camera detects that is being tampered with. To enable this function, you need to configure the Tampering Detection option first. Please refer to page 146 for detailed information.

Camera tampering detection

Note: Please configure Camera tampering detection first

Manual Trigger

This option allows user to enable event triggers manually by clicking the on/off button on the homepage. Please configure 1 ~ 3 events before using this function.





VADP

It is presumed that you already uploaded and enabled the VADP modules before you can associatee VADP triggers with an Event setting.

Click on the Set VADP Trigger button to open the VADP setup menu. The triggering conditions available with 3rd-party software modules known as VADP will be listed. Use the arrow buttons to select these triggers. Users may implant these modules for different purposes such as triggering motion detection, or applications related to video analysis, etc. Please refer to page 150 for the configuration options with VADP modules.

et VADP Trigger	
VADP Triggers	Triggers for Event Settings
ManualTrigger TriggerA TriggerB TriggerC TriggerD	>>
	Close Save

### Once the triggers are configured, they will be listed under the VADP option.

VADP		
TriggerD		
TriggerA		
TriggerB		
TriggerC		
Set VADP Trigger		
ManualTrigger	>> TriggerD TriggerA TriggerB TriggerC	
	Close	Save

#### 3. Action

Define the actions to be performed by the Network Camera when a trigger is activated.

iority: Normal 👻			
and the second second			
tect next motion deteo	ction or digital input after 10 second	1(S).	
	Action		
1. Schedule	Trigger digital output for 1	seconds	
1. Schedule	do (second		
	Backup media if the network is	disconnected	
+	Server Media	Extra parameter	
2. Trigger			
	SD snapshot 💌 SI	) test <u>View</u>	
	♥ NAS snapshot ▼	] Create folders by date time and hour automati ew	cally
3. Action	Add server 💟 Add media	0	

- Trigger digital output for seconds Select this option to turn on the digital output signals (via the DO connectors on the main assembly) when a trigger is activated. Specify the length of the trigger interval in the text box.
- Backup media if the network is disconnected Select this option to backup media file on SD card if the network is disconnected. Please note that this function will only apply after you set up the connection to network attched storage (NAS). For more information about how to set up network storage, please refer to page 155.

To configure an event with video recording or snapshots, it is necessary to configure/provide servers and storage media settings so that the Network Camera will know where to send the media files to when a trigger is activated.

### Add server

Click **Add server** to unfold the server setting window. You can specify how the notification messages are delivered when a trigger is activated. A total of 5 server settings can be configured.

There are four choices of server types available: Email, FTP, HTTP, and Network storage. Select the item to display the detailed configuration options. You can configure either one or all of them.

Add server Add media 오				
Server name: Email				
Server type				
Email				
Sender email address:	Camera@vivotek.com			
Recipient email address:	VIVOTEK@vivotek.com			
Server address:	Ms.vivotek.tw			
User name:				
Password:				
Server port	25			
This server requires a serv	ecure connection			
◎ FTP				
◎ HTTP				
Network storage				
Test	Close Save server			

#### Server type - Email

Select to send the media files via email when a trigger is activated.

- Server name: Enter a name for the server setting.
- Sender email address: Enter a valid email address as the sender address.
- Recipient email address: Enter a valid email address as the recipient address.
- Server address: Enter the domain name or IP address of the email server.
- User name: Enter the user name of the email account if necessary.
- Password: Enter the password of the email account if necessary.
- Server port: The default mail server port is set to 25. You can also manually set another port.

If your SMTP server requires a secure connection, check **This server requires a secure connection**.

To verify if the email settings are correctly configured, click **Test**. The result will be shown in a pop-up window. If successful, you will also receive an email indicating the result.

🗟 hay 17197 1585 1725 ya bala sada tarafa taraya ya 📖 💽 🗖 🔯	🗿 hey 1997 i 101 5-121 hey-biologian (between ees - 👘 📰 🔯
The email has been out raccessfully.	Erose in sending email.
-	

Click **Save server** to enable the settings, then click **Close** to exit the Add server page.

After you set up the first event server, a new item for event server will automatically appear on the Server list. If you wish to add more server options, click **Add server**.

Server	Media			Extra parameter
SD	None 💌	<u>SD test</u>	<u>View</u>	
🔳 Email	None 💌			
Add serv	er 💟 Add med	lia 🔽		

#### Server type - FTP

Select to send the media files to an FTP server when a trigger is activated.

Add server	Add media 💟								
Server name:	FTP								
Server type									
Email	Email								
FTP									
Server a	ddress:	ftp.vivotek	vom						
Server p	ort:	21	]						
User nar	me:	vivotek							
Passwoi	rd:	•••••							
FTP fold	er name:								
🔽 Pass	sive mode								
HTTP									
Network sto	rage								
	Test		Close	Save server					

- Server name: Enter a name for the server setting.
- Server address: Enter the domain name or IP address of the FTP server.
- Server port: By default, the FTP server port is set to 21. It can also be assigned to another port number between 1025 and 65535.
- User name: Enter the login name of the FTP account.
- Password: Enter the password of the FTP account.
- FTP folder name

Enter the folder where the media file will be placed. If the folder name does not exist, the Network Camera will create one on the FTP server.

Passive mode

Most firewalls do not accept new connections initiated from external requests. If the FTP server supports passive mode, select this option to enable passive mode FTP and allow data transmission to pass through the firewall.

To verify if the FTP settings are correctly configured, click **Test**. The result will be shown in a pop-up window as shown below. If successful, you will also receive a test.txt file on the FTP server.

🗿 http://192.160.5.121/cgi-hin/admin/hestverver.cgi 💼 🛅 🔀
ftp transmission failed.

Click **Save server** to enable the settings, then click **Close** to exit the Add server page.

#### Server type - HTTP

Select to send the media files to an HTTP server when a trigger is activated.

Add server	Add media 💟			
Server name:	HTTP			
Server type				
Email				
◎ FTP				
HTTP				
URL:		http://192	2.168.5.10/cgi-bi	n/upload.cgi
Usernan	ne:			
Passwor	d:			
Network stor	age			
	Test		Close	Save server

- Server name: Enter a name for the server setting.
- URL: Enter the URL of the HTTP server.
- User name: Enter the user name if necessary.
- Password: Enter the password if necessary.

To verify if the HTTP settings are correctly configured, click **Test**. The result will be shown in a pop-up window as below. If successful, you will receive a test.txt file on the HTTP server.

🗿 http://192.168.5.121/cgi-bin/admin/testserver.cgi 🔳 🗖 🗙	🗿 http://192.168.5.121/cgi-bin/admin/testserver.cgi 🔳 🗖 🛿
HTTP Transmission successfully. Thanks	HTTP Transmission failed.

Click **Save server** to enable the settings and click **Close** to exit the Add server page.

Network storage:

Select to send the media files to a network storage location when a trigger is activated. Please refer to **NAS server** on page 155 for details.

Click Save server to enable the settings, then click Close to exit the Add server page.

Action —							
Trigger digital output for:							
Backup	media if the networ	k is disco	nnected				
Server	Media			Extra paramete	r		
SD	None	<u>SD test</u>	<u>View</u>				
📃 Email	Snapshot Video clip						
FTP	System log						
HTTP	None 💌						
NAS	None 💌	Crea	te folders	by date time and	hour automatically		
Add serve	er 🔍 Add med	lia 🔽					
				Close	Save event		

SD Test: Click to test your SD card. The system will display a message indicating success or failure. If you want to use your SD card for local storage, please format it before use. Please refer to page 158 for detailed information.

### Add media

Click **Add media** to open the media setting window. You can specify the type of media that will be sent when a trigger is activated. A total of 5 media settings can be configured. There are three choices of media types available: Snapshot, Video Clip, and System log. Select the item to display the detailed configuration options. You can configure either one or all of them.

Add server 💟 Add media
Media name: Snapshot
Media type
Attached media:
Snapshot
Channel: 1 💌 Stream: 1 💌
Send 1 pre-event image(s) [0~7]
Send 1 post-event image(s) [0~7]
File name prefix: Snapshot_
Add date and time suffix to file name
Video clip
System log
Close Save media

#### Media type - Snapshot

Select to send snapshots when a trigger is activated.

- Media name: Enter a name for the media setting.
- Source: Select the stream number from which the snapshots will be taken.
- Send □ pre-event images

The Network Camera has a buffer area; it temporarily holds data up to a certain limit. Enter a number to decide how many images to capture before a trigger is activated. Up to 7 images can be generated.

■ Send □ post-event images

Enter a number to decide how many images to capture after a trigger is activated. Up to 7 images can be generated.

For example, if both the Send pre-event images and Send post-event images are set to 7, a total of 15 images are generated after a trigger is activated.

1	pic.	2 pic.	3 pic.	4 pic.	5 pic.	6 pic.	7 pic.	8 pic.	9 pic.	10 pic.	11 pic.	10 pic.	12 pic.	13 pic.	14 pic.	15 pic.
	▲															
						1	ſrigge	r Act	ivatic	n						

File name prefix

Enter the text that will be appended to the front of the file name.

Add date and time suffix to the file name. Select this option to add a date/time suffix to the file name. For example:



Click **Save media** to enable the settings, then click **Close** to exit the Add media page.

After you set up the first media server, a new column for media server will automatically display on the Media list. If you wish to add more media options, click **Add media**.

	Server	Media	Extra parameter
	SD	None	<u>SD test</u> <u>View</u>
	NAS	Snapshot None 💌	Create folders by date time and hour automatically <u>View</u>
<u>A</u>	dd serve	er 👽 <u>Add med</u>	

#### Media type - Video clip

Select to send video clips when a trigger is activated.


Add server 💟 Add media
Media name: Video Clip
Media type
Attached media:
Snapshot
<ul> <li>Video clip</li> </ul>
Source: Stream 1 🔽
Pre-event recording: 0 seconds (0~9)
Maximum duration: 5 seconds [1~20]
Maximum file size: 500 Kbytes [50~8192]
File name prefix: Channel1s1_
System log
Save media Close

- Media name: Enter a name for the media setting.
- Source: Select the source of video clip from the stream number.
- Pre-event recording

The Network Camera has a buffer area; it temporarily holds data up to a certain limit. Enter a number to decide the duration of recording before a trigger is activated. Up to 9 seconds of video can be recorded.

Maximum duration

Specify the maximum recording duration in seconds. Up to 10 seconds of video can be recorded. For example, if pre-event recording is set to 5 seconds and the maximum duration is set to 10 seconds, the Network Camera continues to record for another 4 seconds after a trigger is activated.



 Maximum file size Specify the maximum file size allowed.

File name prefix Enter the text that will be appended to the front of the file name. For example:

Video_20160720_100341				
1	↑			
File name prefix	Date and time suffix The format is: YYYYMMDD_HHMMSS			

Click **Save media** to enable the settings, then click **Close** to exit the Add media page.

#### Media type - System log

Select to send a system log when a trigger is activated.

Add server 🔍 Add media	
Media name:	
Media type	
Attached media:	
Snapshot	
Video clip	
System log	
	Save media Close

Click **Save media** to enable the settings, then click **Close** to exit the Add media page.

Action —					
👂 Trigger d	ligital output for:				
Backup	media if the networ	k is disco	nnected		
Server	Media			Extra parameter	
SD SD	None 💌	SD test	View		
_	None				
Email	Snapshot				
	Video clip System log				
FTP	Systeming				
HTTP	None 💌				
		Cros	to folders	by date time and ho	ur automatically
NAS	None 💌		te folders	s by date time and no	our autornatically
	None	View			
		_			
Add serve	er 💟 🛛 Add med	lia 🔽			
				Close	Save event
				01036	oave event

- View: Click this button to open a file list window. This function is only for SD card and Network Storage. If you click View button of SD card, a Local storage page will pop up for you to manage recorded files on SD card. For more information about Local storage, please refer to page 158. If you click View button of Network storage, a file directory window will pop up for you to view recorded data on Network storage.
- Create folders by date, time, and hour automatically: If you check this item, the system will generate folders automatically by date.

The following is an example of a file destination with video clips:



Click to delete selected items

Click 20160320 to open the directory:

#### The format is: HH (24r)

Click to open the file list for that hour

< 0	7 <u>08 09 10 11</u>	<u>12 13 14 1</u>	<u>5 16 17 &gt;</u>			
	file name	size	date	time		
Uideo Clip_58.mp4 2526004			2016/03/20	07 <mark>:</mark> 58:28		
Video Clip_59.mp4		2563536	2016/03/20	07. <mark>59</mark> .28		
Delete Delete all Back						
	to delete ted items	Click to go back to the previous level of the directory				
Click to delete all recorded data						

<	< 07 <u>08 09 10 11 12 13 14 15 16 17 &gt;</u>					
	file name	size	date	time		
	Video Clip_58. np4	2526004	2016/03/20	07:58:28		
	Video Clip_59. np4	2563536	2016/03/20	07:59:28		
	Delete     Delete all     Back					

The format is: File name prefix + Minute (mm) You can set up the file name prefix on Add media page. Here is an example of the Event setting:

Event name: intru_alarm		
2 Enable this event		
nority: Normal +		
Detect next motion detection	on or digital input after 10 second(s).	
	Action	
1. Schedule	<ul> <li>Trigger digital output for</li> <li>Backup media if the network is disconnected</li> </ul>	
	Server Media Extra parameter	
-	SD	
2. Trigger 3. Action	Image: Create folders by date time and hour       Image: False_NAS     snapshots       Image: Create folders by date time and hour       Image: Create folders by date timage: Create folders by date time and hour  <	
	Media name:	
	<ul> <li>Media type</li> </ul>	
	Attached media:	
	Snapshot	
	<ul> <li>Video clip</li> </ul>	
	<ul> <li>System log</li> </ul>	
	Save media Ciose	
	Save event Close	

When completed the settings with steps 1~3 to arrange Schedule, Trigger, and Action of an event, click **Save event** to enable the settings and click **Close** to exit the page.

The following is an example of the Event setting page:

Event —											
Name	Status	Sun	Mon	Tue	Wed	Thu	Fri	Sat	Time	Trigger	
<u>intru alarm</u>	ON	V	V	V	۷	V	V	V	00:00~24:00	motion	Delete
motiondetect	<u>ON</u>	۷	۷	V	۷	۷	۷	۷	00:00~24:00	motion	Delete
Add	Hel	D									
Server setting	js —										
Name	Туре	•				Addr	ess/l	Locat	ion		
False NAS	ns				\UC	CHE	N-PC	\Fals	e_NAS		Delete
Add											
Media Available memo Name	ory spac										
snapshots	9	Type napsi									Delete
Add		napor	101								Delete
- Customized	script										
Name		Date	;		Tim	e					
Add											

When the Event Status is <u>ON</u>, once an event is triggered by motion detection, the Network Camera will automatically send snapshots via e-mail.

If you want to stop the event trigger, you can click <u>ON</u> to turn it to <u>OFF</u> status or click **Delete** to remove a previously-configured event setting.

To remove a server setting from the list, select a server name and click **Delete**. Note that only when the server setting is not being applied to an event setting can it be deleted.

To remove a media setting from the list, select a media name and click **Delete**. Note that only when the media setting is not being applied to an event setting can it be deleted.


#### **Customized Script**

This function allows you to upload a sample script (.xml file) to the webpage, which will save your time on configuring the settings. Please note that there is a limited number of customized scripts you can upload; if the current amount of customized scripts has reached the limit, an alert message will prompt. If you need more information, please contact VIVOTEK's technical support.



# **Applications > Motion detection**

This section explains how to configure the Network Camera to enable motion detection. A total of 5 motion detection windows can be configured.



Follow the steps below to enable motion detection:

- 1. Click New to add a new motion detection window.
- 2. In the Window Name text box, enter a name for the motion detection window.
  - Use 4 mouse clicks to designate a detection window. You can change the window shape by dragging the corner marks to a preferred location.
  - Drag the item size tab to change the minimum size of item to trigger an alarm. An item size box will appear in the center of screen for your reference (in semi-transparent red). An intruding object must be larger than the Item size to trigger an alarm. Change the item size according to the live view.
  - To delete a window, click the X mark on the right of the window name.
- 3. Define the sensitivity to moving objects by moving the Sensitivity slide bar. Note that a high sensitivity is prone to produce false alarms such as the fast changes of light (such as day/night mode switch, turning lights on/off). A movement must persist longer than 0.3 second for the motion to be detected.
- 4. Click **Save** to enable the settings.
- 5. Select Enable motion detection to enable this function.

2 Enable motion detection


For example:

rmal light mode				
111==	STATISTICS.	Window name Motion 1		1.35
	06B	DEC Rem size 17		4
-				
1	2			
	The			
est.	a	10		
Bensituity 60%				
			New	Save

The Percentage Indicator will rise or fall depending on the variation between sequential images. When motions are detected by the Network Camera and are considered to exceed the preset threshold, the red bar rises. Meanwhile, the motion detection window will be outlined in red.

Photos or videos can be captured instantly and configured to be sent to a remote server (via an Email or FTP server). For more information on how to configure an event setting, please refer to Event settings on page 129.

A green bar indicates that even though motions have been detected, the event has not been triggered because the image variations still fall under the preset threshold.



If you want to configure other motion detection settings for day/night/schedule mode (e.g., for a different lighting condition during a specific period of time), please click **Profile mode** to open the Motion Detection Profile Settings page as shown below. Another three motion detection windows can be configured on this page.

		Window name Motion1	88
	06B	06C Item size: 15	
		Enable to apply the	nese settinos at
		Initiation of appendix     Night mode	
1 and the second		O Schedule mode	e [hh:mm]
Sensitivity: 80%	<u> </u>		


Please follow the steps beolw to set up a profile:

- 1. Create a new motion detection window, and configure the minimum item size.
- 2. Click the **Profile mode** tab.
- 3. Select the applicable Schedule mode. Please manually enter a time range.
- 4. Click **Save** to enable the settings and click **Close** to exit the page.

This motion detection window will also be displayed on the Event Settings page. You can go to **Event** > **Event settings** > **Trigger** to select it as a trigger source. Please refer to page 129 for detailed information.

# NOTE:

How does motion detection work?



There are two motion detection parameters: Sensitivity and Min. Item Size. As illustrated above, frame A and frame B are two sequential images. Pixel differences between the two frames are detected and highlighted in gray in which the sensitivity setting will take effect. Sensitivity is a value that expresses the sensitivity to moving objects. A higher sensitivity setting allows camera to detect slight movements while a lower sensitivity setting will neglect them.

The minimum item size is a threshold value that determines how many "alerted pixels" can trigger an event. When the size of an intruding object is larger than the minimum size, and its movement persist for 0.3 second, the motion is judged to exceed the defined threshold; and the motion window will be outlined in red. With a large minimum item size, the size of moving object in frame C is considered as smaller than the minimum item size, no motion alarm is triggered. With a smaller minimum item size, the same moving object in frame D triggers the alarm.

For applications that require a high level of security management, it is suggested to use **higher** sensitivity settings. However, a higher sensitivity level can also produce false alarms due to fast light changes when switching between the day and night modes, AE switch, turning the light on or off, etc.

## Applications > DI and DO

Digital input		
Normal status:	● High ○ Low	
Current status:	High	
Digital output		
Normal status:	Open      Grounded	
Current status:	Open	

<u>Digital input</u>: Select High or Low as the Normal status for the digital input. Connect the digital input pin of the Network Camera to an external device to detect the current connection status.

<u>Digital output</u>: Select Grounded or Open to define the normal status for the digital output. Connect the digital output pin of the Network Camera to an external device to determine the current status.

Set up the event source as DI on **Event > Event settings > Trigger.** Please refer to page 130 for detailed information.

## **Applications > Tampering detection**

This section explains how to set up camera tamper detection. With tamper detection, the camera is capable of detecting incidents such as **redirection**, **blocking or defocusing**, or even the **spray paint**.

Camera tampering detection	
Tampering detection	
Trigger duration 10 seconds [10~600]	
Trigger threshold 12 [0~100]	
Image too dark detection	
Trigger duration 2 seconds [1~10]	
Trigger threshold 15 [0~100]	
Image too bright detection	
Trigger duration 2 seconds [1~10]	
Trigger threshold 15 [0~100]	
Image too blurry detection	
Trigger duration 7 seconds [1~10]	
Trigger threshold 12 [0~100]	
	Save
	Jave

Please follow the steps below to set up the camera tamper detection function:

 Click to select the checkbox before tampering conditions: Tampering detection, Image too dark, Image too bright, and Image too blurry. Enter the tamper trigger duration. (10 sec. ~ 10 min.). The duraction specifies the set of time before the tampering is considered as a real alarm. This helps avoid false alarms by short-lived changes.

The tamper alarm will be triggered only when the tampering factor (the difference between current frame and pre-saved background) exceeds the trigger threshold. Conditions such as image too dark, too bright, or too blurry (defocused) can also be configured as tampering conditions. The Trigger threshold determines how sensitive is your tamper detection setting. Lower the threshold number, easier to trigger.

Too bright: shining a flash light. The average lighting level of the scene is taken into consideration.

Too dark: covering the objective or spraying paint.

Too blurry: blurry scene can be the result of strong interference on the device, such as EMI interference.

2. You can configure Tampering Detection as a trigger element to the proactive event configurations in Event -> Event settings -> Trigger. For example, when the camera is tampered with, camera can be configured to send the pre- and post-event video clips to a networked storage device. Please refer to page 130 for detailed information.

## Applications > Audio detection

Audio detection, along with video motion detection, is applicable in the following scenarios:

- 1. Detection of activities not covered by camera view, e.g., a loud input by gun shots or breaking a door/ window.
- 2. A usually noisy environment, such as a factory, suddenly becomes quiet due to a breakdown of machines.
- 3. A PTZ camera can be directed to turn to a preset point by the occurrence of audio events.
- 4. Dark environments where video motion detection may not function well.



The red circles indicate where the audio alarms can be triggered when breaching or falling below the preset threshold.

How to configure Audio detection:

- 1. Once the Audio detection window is opened, the current sound input will be interactively indicated by a fluctuating yellow wave diagram.
- 2. Use a mouse click to drag the Alarm level tab to a preferred location on the slide bar.
- 3. Select the "Enable audio detection" checkbox and click Save to enable the feature.

### NOTE:

- 1. Note that the volume numbers (0~100) on the side of wave diagram does not represent decibel (dB). Sound intensity level has already been mapped to preset values. You can, however, use the realworld inputs at your installation site that are shown on the wave diagram to configure an alarm level.
- 2. To configure this feature, you must not mute the audio in **Configuration > Media > Audio**. The default of the camera can be muted due to the lack of an internal microphone. An external microphone is provided by users.

You can use the **Profile** window to configure a different Audio detection setting. For example, a place can be noisy in the day time and become very quiet in the night.

- 1. Click on the **Enable this profile** checkbox. Once the Audio detection window is opened, the current sound input will be interactively indicated by a fluctuating yellow wave diagram.
- 2. Use a mouse click to drag the Alarm level tab to a preferred location on the slide bar.
- 3. Select the **Day**, **Night**, or **Schedule** mode check circles. You may also manually configure a period of time during which this profile will take effect.
- 4. Click **Save** and then click **Close** to complete your configuration.

90		Alarm Level
		Volume
80		
70		
60		
50		
40		
30		
20		
10		
0		
General settings		
Z Enable this profile		
his profile is applied to:		
his profile is applied to:		
his profile is applied to: Day mode		



- If the Alarm level and the received volume are set within a range of 20% on the wave diagram, frequent alarms will be triggered. It is recommended to set the Alarm level farther apart from the detected sound level.
- To configure and enable this feature, you must not configure video stream #1 into Motion JPEG. If an external microphone input is connected and recording of audio stream is preferred, audio stream is transmitted between camera and viewer/recording station along with stream #1.
- Refer to page 91 for Audio settings, and page 84 for video streaming settings.

## Applications > Package management - a.k.a., VADP (VIVOTEK Application Development Platform)

Upload package					
Save to SD card	t				
Select file				Browse U	pload
Resource status					
* Storage status:					
storage_siz	e: 10240 Ki	Bytes	Free size:	10240 KB)	tes
* SD card status:	Detached				
Total size:	0 KBytes	Fi	ee size:	0 KBytes	
Used size:	0 KBytes	U	se (%):	0 %	
🐭 Memory status:					
Total size:	24576 KByte	s F	ree size:	24576 KByt	es
— Package list					
Module	e name	Vendor	Vers	ion Status	License
Backup	Reload	Restore	Start	Sto	q

Users can store and execute VIVOTEK's or 3rd-party software modules onto the camera's flash memory or SD card. These software modules can apply in video analysis for intelligent video applications such as license plate recognition, object counting, or as an agent for edge recording, etc.

- Once the software package is successfully uploaded, the module configuration (vadp.xml) information is displayed. When uploading a module, the camera will examine whether the module fits the predefined VADP requirements. Please contact our technical support or the vendor of your 3rd-party module for the parameters contained within.
- Users can also run VIVOTEK's VADP packages as a means to access updated functionality instead of replacing the entire firmware.
- Note that for some cameras the flash is too small to hold VADP packages. These cameras will have its "Save to SD card" checkbox selected and grayed-out for all time.
- The file system of SD card (FAT32) does not support soft (symbolic) link. It will return failure if your module tries to create soft links on SD card.

To utilize a software module, acquire the software package and click **Browse** and **Upload** buttons. The screen message for a successful upload is shown below:




To start a module, select the checkcircle in front, and click the **Start** button.

	rackage its	-						
	Module	name	Vendor	Version	Status	License	Ł	
0	Hello \	<u>Norld</u>	ABC	1.0.0	ON	yes		88
	Backup	Reload	Restore	Sta	art	Stop		]

If you should need to remove a module, select the checkcircle in front and then click the **Stop** button. By then the module status will become **OFF**, and the **X** button will appear at the end of the row. Click on the **X** button to remove an existing module.

	Module	name	Vendor	Version	Status	License	±	
۲	Hello W	<u>/orld</u>	ABC	1.0.0	ON	no		23
B	ackup	Reload	Restore	Sta	art	Stop		1

When prompted by a confirm message, Click **Yes** to proceed.



Note that the actual memory consumed while operating the module will be indicated on the **Memory status** field. This helps determine whether a running module has consumed too much of system resources.

On the License page, register and activate the license for using VIVOTEK's VADP modules.



## **Recording > Recording settings**

This section explains how to configure the recording settings for the Network Camera.

#### **Recording Settings**

			Ē		I	nser	t you	r SD card a	and click	here to test	•
Record	ding set	ttings	+								
Name	Status	Sun I	M <mark>o</mark> n	Tue	Wed Th	ı Fri	Sat	Time	Source	Destination	Delete
Ad	ld	<u>SD</u> 1	est								

## NOTE:

- 1. Each Recording setting records a video stream from one channel, i.e., from a single lens module.
- 2. Please remember to format your SD card when used for the first time. Please refer to page 158 for detailed information.

#### **Recording Settings**


Click **Add** to open the recording setting window. On this page, you can define the adaptive recording, recording source, recording schedule, and recording capacity. A total of 2 recording settings can be configured.

Recording name: Video		^
<ul> <li>Enable this recording</li> </ul>		
✓ With adaptive recording (	<u>Help</u> )	
Pre-event recording:	5 seconds [0~9]	
Post-event recording:	5 seconds [0~10]	
Priority: Normal 🗸		
Source: Stream 1 🗸		
	Trigger	
1. Trigger	Schedule	
	Sun V Mon V Tue V Wed V Thu V Fri V Sat	
	Time	
+	Always	
2. Destination	O From 00:00 to 24:00 [hh:mm]	
	O Network fail	
Note: To enable recording no	tification please configure <u>Event</u> first	
	Save Close	~

- Recording name: Enter a name for the recording setting.
- Enable this recording: Select this option to enable video recording.
- With adaptive recording:

Select this option will activate the frame rate control according to alarm trigger. The frame control means that when there is a triggered alarm/event, the frame rate will raise up to the value you've set on the Stream setting page. Please refer to page 84 for more information.

If you enable adaptive recording on Camera A, only when an event is triggered on Camera A will the server record the streaming data in full frame rate; otherwise, it will only request the I frame data during normal monitoring, thus effectively save lots of bandwidths and storage.



The alarm trigger includes: motion detection and DI detection. Please refer to Event settings on page 129.

- Pre-event recording and post-event recording The Network Camera has a buffer area; it temporarily holds data up to a certain limit. Enter a number to decide the duration of recording before and after a trigger is activated.
- Priority: Select the relative importance of this recording (High, Normal, or Low). Recording with a higher priority setting will be executed first.
- Channel # Stream #: Select a channel and a stream under it as the recording source.

## D NOTE:

- To enable adaptive recording, please also enable time shift caching stream and select a caching stream on Media > Video > Stream settings. Please refer to page 84 for detailed instruction.
- ▶ To enable recording notification please configure *Event settings* first. Please refer to page 129.

Please follow steps 1~2 below to set up the recording:

<u>1. Trigger</u>	Trigger —
Select a trigger source.	Schedule
	🖉 Sun 🖉 Mon 👽 Tue 👽 Wed 👽 Thu 👽 Fri 🖉 Sat
	Time
	<ul> <li>Always</li> </ul>
	From 00:00 to 24:00 [hh:mm]
	Network fail

- Schedule: The server will start to record files on the local storage or network attached storage (NAS).
- Network fail: Since network fail, the server will start to record files onto the local storage (SD card).

#### 2. Destination

You can select the SD card or network storage (NAS) for the recorded video files.

Recording name: \\deo				
C Enable this recording				1
[2] Writh adaptive recording	o Otteda:			1
Pre-event recordin	2 5 seconds (2-9)			
Post-event records	rg: 5 seconds ⊒-10			
Priority Normal V				
Source: Stream 1 V				
	Destination			
1. Trigger	Destination: DD v			
	Recording file management			
	Miximum duration 1 minutes [1-60]			
	Maximum file size: 100 MB (100-2000)			
2. Destination	File name prefix			
	Add NAS server			
Note: To enable recording	notification please configure Event first.			
	1	Save	Cittee	

#### NAS server

Click **Add NAS server** to open the server setting window and follow the steps below to set up: 1. Fill in the information for the access to the shared networked storage.


For example:

	Add NAS server					
			vork storage ver name c		s\folder name)	
1	Network stor: Network s	age torage location:	\\192.160.5	.122\nas		
	(For example: \\my_nas\disk\folder)					
	Workgrou User nam		vivotek ritali		er name and sword for your	
	Password	t	•••••	ser	· · · · · · · · · · · · · · · · · · ·	
		Test	Sav	ve server	Close	

2. Click **Test** to check the setting. The result will be shown in the pop-up window.

🗿 http://192.168.5.151/cgi-bin/admin/testserver 🔲 🗖 🔀	🖆 http://192.168.5.151/cgi-bin/admin/testserver 🔲 🗖 🔀
Mount succeeded.	Mount failed.
🗃 Done 👘 👘 Internet	🕘 Done 🛛 🔮 Internet 🦪

If successful, you will receive a test.txt file on the networked storage server.



- 3. Enter a server name.
- 4. Click **Save** to complete the settings and click **Close** to exit the page.

Enable this recording		*
With adaptive recording	(Help)	
Priority: Normal 💌 Source: Stream 1 🗸		
	Destination	
1. Trigger	Destination: NAS 💌	
	Capacity:	
	Entire free space	
	Reserved space: 100 Mbytes	
2. Destination	Enable cyclic recording	E
	Recording file management	
	Maximum duration: 1 minutes [1~60]	
	Maximum file size: 100 MB [100~2000]	
	File name prefix: Bahasa	
Note: To enable recording n	otification please configure <u>Event</u> first	
	Save Close	
		-

- Capacity: You can either choose the entire available space or impose a reserved space. The **Reserved** space should be of the size of at least **15MBytes**. The reserved space can be used as a safe buffer especially when the cyclic recording function is enabled, during the transaction stage when a storage space is full and the incoming streaming data is about to overwrite the previously saved videos.
- File name prefix: Enter the text that will be appended to the front of the file name.

Enable cyclic recording: If you check this item, when the maximum capacity is reached, the oldest file will be overwritten by the latest one.

#### **Recording file management**

- Maximum duration: This determines the length of each recorded video, applicable from 1 to 60 minutes.
- Maximum file size: This determines the file size of each concluded recording. The applicable sizes range from 100 to 2000 Megabytes.
- File name prefix: Enter a name for each recorded video.

If you want to enable recording notification, please click **<u>Event</u>** to set up. Please refer to **Event > Event** settings on page 129 for more details.

When completed, select **Enable this recording**. Click **Save** to enable the setting and click **Close** to exit this page. When the system begins recording, it will send the recorded files to the network storage or SD card. The new recording name will appear on the recording page as shown below.

To remove an existing recording setting from the list, single-click to select it and click **Delete**.

- 1	Record	ling set	ting	s —									
N	lame	Status	Sun	Mon	Tue	Wed	Thu	Fri	Sat	Time	Source	Destination	Delete
N	/ideo	<u>ON</u>	V	۷	V	۷	۷	۷	۷	00:00~24:00	stream1	<u>SD</u>	Delete
	Ad	d	<u>s</u>	) test									

- Video (Name): Click to open the Recording settings page to modify.
- ON (Status): Click to manually adjust the Status. (ON: start recording; OFF: stop recording)
- NAS or SD (Destination): Click to open the file list of recordings as shown below. For more information about folder naming rules, please refer to page 140 for details.

### Local storage > SD card management

### NOTE:

- It is recommended to turn OFF the recording activity before you remove an SD card from the camera.
- The lifespan of an SD card is limited. Regular replacement of the SD card can be necessary.
- Camera filesystem takes up several megabytes of memory space. The storage space cannot be used for recording.
- Using an SD card that already contains data recorded by another device should not be used in this camera.
- Please do not modify or change the folder names in the SD card. That may result in camera malfunctions.

This section explains how to manage the local storage on the Network Camera. Here you can view SD card status, and implement SD card control.

#### **SD card staus**

This column shows the status and reserved space of your SD card. Please remember to format the SD card when using for the first time.

SD card status							
SD card status: Detach	ned ned	o SD card					
Total size: 0 KBytesFree	Total size: 0 KBytesFree size:0 KBytes						
Used size:0 KBytesUse	(%): 0 %						
			Format				
- SD card status							
SD card status: Ready							
File system: FAT32							
Total size:	15323496 KBytes	Free size:	15087976 KBytes				
Used size:	235520 KBytes	Use (%):	1.537 %				

#### SD card format

The Linux kernel EXT4 file system format applies to SD card larger than 32GB. However, if EXT4 is applied, the computers running Windows will not be able to access the contents on the SD card unless using some 3rd-party software. If the SD card capacity is larger than 8GB, you should format the card using the Ext4 standard.

Г	SD card format	
	Ext4	
	Ext4	Format
	FAT32	Tomat

#### **SD card control**

SD card control			
Enable cyclic storage			
Enable automatic disk cleanup			
Maximum duration for keeping files:	7	days	
			Save

- Enable cyclic storage: Check this item if you want to enable cyclic recording. When the maximum capacity is reached, the oldest file will be overwritten by the latest one.
- Enable automatic disk cleanup: Check this item and enter the number of days you wish to retain a file. For example, if you enter "7 days", the recorded files will be stored on the SD card for 7 days.

Click Save to enable your settings.

### Local storage > Content management

This section explains how to manage the content of recorded videos on the Network Camera. Here you can search and view the records and view the searched results.

#### **Searching and Viewing the Records**

This column allows the user to set up search criteria for recorded data. If you do not select any criteria and click **Search** button, all recorded data will be listed in the **Search Results** column.

Search							
Trigger type							
Backup		System	boot		🗌 Digi	tal input	
Motion		Network	fail		🗌 Rec	ording notify	/
Periodically		Tamperi	ng detecti	ion	U VAD	)P	
Manual trigge	rs	🗌 Audio de	etection				
Media type							
<ul> <li>Video clip</li> </ul>		<ul> <li>Snapsho</li> </ul>	ot		⊖ Text	t	
Time							
Search for last	1 minute	e(s) hours	days	weeks			
From:	2015/05/18	1	i [	02	36	PM	
to:	2015/05/25		i [	02	36	PM	
							Q Search
	Trigger type Backup Motion Periodically Manual trigger Media type Video clip Time Search for last From:	Trigger type         Backup         Motion         Periodically         Manual triggers         Media type         Video clip         Time         Search for last       1         From:       2015/05/18	Trigger type         Backup       System         Motion       Network         Periodically       Tamperi         Manual triggers       Audio de         Media type       Snapsho         Video clip       Snapsho         Time       Search for last       minute(s)         From:       2015/05/18       minute(s)	Trigger type         Backup       System boot         Motion       Network fail         Periodically       Tampering detect         Manual triggers       Audio detection         Media type       Snapshot         Time       Search for last       1       minute(s)       hours       days         From:       2015/05/18       Image: Construction of the second sec	Trigger type         Backup       System boot         Motion       Network fail         Periodically       Tampering detection         Manual triggers       Audio detection         Media type       Snapshot         Time       Search for last       1       minute(s)       hours       days       weeks         From:       2015/05/18       02       1	Trigger type         Backup       System boot       Digiter of the system boot         Motion       Network fail       Rec         Periodically       Tampering detection       VAD         Manual triggers       Audio detection       VAD         Media type       Snapshot       Text         Time       Search for last       1       minute(s)       hours       days       weeks         From:       2015/05/18       1       2       36       1	Trigger type         Backup       System boot       Digital input         Motion       Network fail       Recording notify         Periodically       Tampering detection       VADP         Manual triggers       Audio detection         Media type       Snapshot       Text         Time       Search for last       1       minute(s)       hours       days       weeks         From:       2015/05/18       102       36       PM

-ò́r- Tips:

You can also FTP the camera or use the "http://ip/cgi-bin/admin/ lsctrl.cgi?cmd=search" command to examine the recorded files on your SD card.

- File attributes: Select one or more items as your search criteria.
- Trigger time: Manually enter the time range you want to search for contents created at a specific point in time.

Click **Search** and the recorded data corresponding to the search criteria will be listed in **Search Results** window.

#### **Search Results**

The following is an example of search results. There are four columns: Trigger time, Media type, Trigger type, and Locked. Click 🖕 to sort the search results in either direction.

Searc	h results ——				
	Name	Trigger type	Starting time	Ending time	
	to SD	Periodically	Today at 3:45 PM	Today at 3:58 PM	— Click to open a live vie
	to SD	Periodically	Today at 3:58 PM		
	test	Motion	Today at 3:45 PM	Today at 3:45 PM	
	test	Motion	Today at 3:49 PM	Today at 3:49 PM	
	test	Motion	Today at 3:49 PM	Today at 3:49 PM	
	test	Motion	Today at 3:50 PM	Today at 3:50 PM	
	test	Motion	Today at 3:50 PM	Today at 3:50 PM	
10	wnload 🔒 Loo	k/Unlock 🗐 JF	PEGs to AVI		

Play: Click on a search result which will highlight the selected item. A Play window will appear on top for immediate review of the selected file.
For example:

For example:

1	tay
	Check to search
	2010/1/26164670
1	
1	
	H R H 20

- Download: Click on a search result to highlight the selected item in purple as shown above. Then click the **Download** button and a file download window will pop up for you to save the file.
- JPEGs to AVI: This functions only applies to "JPEG" format files such as snapshots. You can select several snapshots from the list, then click this button. Those snapshots will be converted into an AVI file.

Lock/Unlock: Select the checkbox in front of a desired search result, then click this button. The selected items will become Locked, which will not be deleted during cyclic recording. You can click again to unlock the selections. For example:

Search	results					
	Name	Trigger type	Starting time	Ending time		
	to SD	Periodically	Today at 3:45 PM	Today at 3:58 PM		
	to SD	Periodically	Today at 3:58 PM			
☑ 🔒	test	Motion	Today at 3:45 PM	Today at 3:45 PM		
	test	Motion	Today at 3:49 PM	Today at 3:49 PM		
☑ 🔒	test	Motion	Today at 3:49 PM	Today at 3:49 PM		
	test	Motion	Today at 3:50 PM	Today at 3:50 PM		
	test	Motion	Today at 3:50 PM	Today at 3:50 PM	-	
10	10     ✓     ✓     1     / 3     ✓     Click to switch pages       Lock/Unlock     ➡ JPEGs to AVI     m Remove					

■ Remove: Select the desired search results, then click this button to delete the files.

# Appendix

### **URL Commands for the Network Camera**

## 1. Overview

For some customers who already have their own web site or web control application, the Network Camera/Video Server can be easily integrated through URL syntax. This section specifies the external HTTP-based application programming interface. The HTTP-based camera interface provides the functionality to request a single image, control camera functions (PTZ, output relay etc.), and get and set internal parameter values. The image and CGI-requests are handled by the built-in Web server.

# 2. Style Convention

In URL syntax and in descriptions of CGI parameters, text within angle brackets denotes content that is to be replaced with either a value or a string. When replacing the text string, the angle brackets should also be replaced. An example of this is the description of the name for the server, denoted with <servername> in the URL syntax description below, that is replaced with the string myserver in the URL syntax example further down in the page.

URL syntax is denoted with the word "Syntax:" written in bold face followed by a box with the referenced syntax as shown below. For example, name of the server is written as <servername> and is intended to be replaced with the name of the actual server. This can either be a name, e.g., "mywebcam" or "thecam. adomain.net" or the associated IP number for the server, e.g., 192.168.0.220.

Syntax:

http://<servername>/cgi-bin/viewer/video.jpg

Description of returned data is written with "**Return:**" in bold face followed by the returned data in a box. All data is returned in HTTP format, i.e., each line is separated with a Carriage Return and Line Feed (CRLF) printed as \r\n.

Return:

HTTP/1.0 <HTTP code> <HTTP text>\r\n

URL syntax examples are written with "**Example:**" in bold face followed by a short description and a light grey box with the example.

Example: request a single snapshot image

http://mywebserver/cgi-bin/viewer/video.jpg

# **3. General CGI URL Syntax and Parameters**

CGI parameters are written in lower-case and as one word without any underscores or other separators. When the CGI request includes internal camera parameters, these parameters must be written exactly as they are named in the camera or video server. The CGIs are organized in functionally-related directories under the cgi-bin directory. The file extension .cgi is required.

Syntax:

```
http://<servername>/cgi-bin/<subdir>[/<subdir>...]/<cgi>.<ext>
[?<parameter>=<value>[&<parameter>=<value>...]]
```

**Example:** Set digital output #1 to active

http://mywebserver/cgi-bin/dido/setdo.cgi?do1=1

# 4. Security Level

SECURITY LEVEL	SUB-DIRECTORY	DESCRIPTION
0	anonymous	Unprotected.
1 [view]	anonymous, viewer,	1. Can view, listen, talk to camera.
	dido, camctrl	2. Can control DI/DO, PTZ of the camera.
4 [operator]	anonymous, viewer,	Operator access rights can modify most of the camera's
	dido, camctrl, operator	parameters except some privileges and network options.
6 [admin]	anonymous, viewer,	Administrator access rights can fully control the camera's
	dido, camctrl, operator,	operations.
	admin	
7	N/A	Internal parameters. Unable to be changed by any external
		interfaces.

# 5. Get Server Parameter Values

**Note:** The access right depends on the URL directory. **Method:** GET/POST

Syntax:
http://< <i>servername</i> >/cgi-bin/anonymous/getparam.cgi?[< <i>parameter</i> >]
[& <parameter>]</parameter>
http://< <i>servername</i> >/cgi-bin/viewer/getparam.cgi?[< <i>parameter</i> >]
[& <parameter>]</parameter>
http:// <servername>/cgi-bin/operator/getparam.cgi?[<parameter>]</parameter></servername>
[& <parameter>]</parameter>
http://< <i>servername</i> >/cgi-bin/admin/getparam.cgi?[< <i>parameter</i> >]
[& <parameter>]</parameter>

Where the *<parameter>* should be *<group>*[\_*<name>*] or *<group>*[.*<name>*]. If you do not specify any parameters, all the parameters on the server will be returned. If you specify only *<group>*, the parameters oftherelated group will be returned.

When querying parameter values, the current parameter values are returned.

A successful control request returns parameter pairs as follows:

Return:	
HTTP/1.0 200 OK\r\n	
Content-Type: text/html\r\n	
Context-Length: <length>\r\n</length>	
\r\n	
<parameter pair=""></parameter>	
where <parameter pair=""> is</parameter>	
<parameter>=<value>\r\n</value></parameter>	
[ <parameter pair="">]</parameter>	

<length> is the actual length of content.

#### Example: Request IP address and its response

Request:

http://192.168.0.123/cgi-bin/admin/getparam.cgi?network\_ipaddress Response: HTTP/1.0 200 OK\r\n Content-Type: text/html\r\n Context-Length: 33\r\n \r\n

network.ipaddress=192.168.0.123\r\n

# 6. Set Server Parameter Values

**Note:** The access right depends on the URL directory. **Method:** GET/POST

Syntax:

```
http://<servername>/cgi-bin/anonymous/setparam.cgi? <parameter>=<value>
[&<parameter>=<value>...][&update=<value>][&return=<return page>]
```

http://<*servername*>/cgi-bin/viewer/setparam.cgi? <*parameter*>=<*value*> [&<parameter>=<value>...][&update=<value>] [&return=<return page>]

http://<*servername*>/cgi-bin/operator/setparam.cgi? <*parameter*>=<*value*> [&<parameter>=<value>...][&update=<value>] [&return=<return page>]

http://<*servername*>/cgi-bin/admin/setparam.cgi? <*parameter*>=<*value*> [&<parameter>=<value>...][&update=<value>] [&return=<return page>]

PARAMETER	VALUE	DESCRIPTION
<group>_<name></name></group>	value to assigned	Assign < <i>value</i> > to the parameter < <i>group</i> >_< <i>name</i> >.
update	<boolean></boolean>	Set to 1 to update all fields (no need to update parameter in each group).
return	<return page=""></return>	Redirect to the page < <i>return page</i> >after the parameter is assigned. The < <i>return page</i> >can be a full URL path or relative path according to the current path. If you omit this parameter, it will redirect to an empty page. (Note: The return page can be a general HTML file(.htm, .html) or a VIVOTEK server script executable (.vspx) file. It cannot be a CGI commandor have any extra parameters.This parameter must be

#### placed at the end of the parameter list

#### Return:

HTTP/1.0 200 OK\r\n	
Content-Type: text/html\r\n	
Context-Length: <length>\r\n</length>	
\r\n	
<parameter pair=""></parameter>	
where <parameter pair=""> is</parameter>	

<parameter>=<value>\r\n

[<parameter pair>]

Only the parameters that you set and are readable will be returned.

**Example:** Set the IP address of server to 192.168.0.123:

#### Request:

http://myserver/cgi-bin/admin/setparam.cgi?network ipaddress=192.168.0.123

Response: HTTP/1.0 200 OK\r\n Content-Type: text/html\r\n Context-Length: 33\r\n \r\n network.ipaddress=192.168.0.123\r\n

# 7. Available parameters on the server

Valid values:

VALID VALUES	DESCRIPTION
string[ <n>]</n>	Text strings shorter than 'n' characters. The characters ",',<,>,& are invalid.
string[n~m]	Text strings longer than `n' characters and shorter than `m' characters. The
	characters ",',<,>,& are invalid.
password[ <n>]</n>	The same as string but displays'*' instead.
<integer></integer>	Any single integer number in 32-bits.
	The range is -2147483648~2147483647.
<positive integer=""></positive>	Any single positive integer number in 32-bits.
	The range is 1~ 4294967295.
<m> ~ <n></n></m>	Any number between 'm' and 'n'.
domain name[ <n>]</n>	A string limited to a domain name shorter than 'n' characters (eg. www.ibm.com).
email address [ <n>]</n>	A string limited to an email address shorter than 'n' characters (eg.
	joe@www.ibm.com).
<ip address=""></ip>	A string limited to an IP address (eg. 192.168.1.1).
<mac address=""></mac>	A string limited to contain a MAC address without hyphens or colons.
<boolean></boolean>	A boolean value of 1 or 0 represents [Yes or No], [True or False], [Enable or
	Disable].
<value1>,</value1>	Enumeration. Only given values are valid.
<value2>,</value2>	
<value3>,</value3>	
blank	A blank string.
everything inside <>	A description
integer primary key	SQLite data type. A 32-bit signed integer. The value is assigned a unique integer by
	the server.
<text></text>	SQLite data type. The value is a text string, stored using the database encoding
	(UTF-8, UTF-16BE or UTF-16-LE).
<coordinate></coordinate>	x, y coordinate (eg. 0,0)
<window size=""></window>	window width and height (eg. 800x600)
<w,h></w,h>	The format for coordinate in 2D.
	W is the pixel number of width.
	H is the pixel number of height.
	EX: (176,144)
<wxh></wxh>	The format for resolution.

	W is the pixel number of width.	
H is the pixel number of height.		
	Ex: 1920x1080, 2048x1536	
available	The API is listed in product WebAPIs.	
non-available	The API is not in product WebAPIs.	
valid	The API is listed in product WebAPIs, and is functional.	
non-valid	The API is listed in product WebAPIs, but is malfunction in this status.	
<decimal></decimal>	Any decimal number expressed in 32-bits ranging from 1.18e-38~3.40e+38.	

NOTE: The camera should not be restarted when parameters are changed.

# 7.1 system

#### Group: **system**

NAME	VALUE	SECURITY (get/set)	DESCRIPTION
hostname	string[64]	1/6	Host name of server
			(Network Camera,
			Wireless Network Camera,
			Video Server,
			Wireless Video Server).
ledoff	<boolean></boolean>	6/6	Turn on (0) or turn off (1) all led indicators.
date	<yyyy dd="" mm="">,</yyyy>	6/6	Current date of system. Set to 'keep' to keep
	keep,		date unchanged. Set to 'auto' to use NTP to
	auto		synchronize date.
time	<hh:mm:ss>,</hh:mm:ss>	6/6	Current time of the system. Set to 'keep' to
	keep,		keep time unchanged. Set to 'auto' to use NTP
	auto		to synchronize time.
datetime	<mmddhhmmyyyy< td=""><td>6/6</td><td>Another current time format of the system.</td></mmddhhmmyyyy<>	6/6	Another current time format of the system.
	.ss>		
ntp	<domain name="">,</domain>	6/6	NTP server.
	<ip address="">,</ip>		*Do not use "skip to invoke default server" for
	<blank></blank>		default value.
timezoneindex	-489 ~ 529	6/6	Indicate timezone and area.
			-480: GMT-12:00 Eniwetok, Kwajalein
			-440: GMT-11:00 Midway Island, Samoa
			-400: GMT-10:00 Hawaii
			-360: GMT-09:00 Alaska
			-320: GMT-08:00 Las Vegas, San_Francisco,
			Vancouver
			-280: GMT-07:00 Mountain Time, Denver
			-281: GMT-07:00 Arizona
			-240: GMT-06:00 Central America, Central
			Time, Mexico City, Saskatchewan
			-200: GMT-05:00 Eastern Time, New York,
			Toronto
			-201: GMT-05:00 Bogota, Lima, Quito, Indiana
			-180: GMT-04:30 Caracas
			-160: GMT-04:00 Atlantic Time, Canada, La
			Paz, Santiago

-140: GMT-03:30 Newfoundland
-120: GMT-03:00 Brasilia, Buenos Aires,
Georgetown, Greenland
-80: GMT-02:00 Mid-Atlantic
-40: GMT-01:00 Azores, Cape_Verde_IS.
0: GMT Casablanca, Greenwich Mean Time:
Dublin,
Edinburgh, Lisbon, London
40: GMT 01:00 Amsterdam, Berlin, Rome,
Stockholm, Vienna, Madrid, Paris
41: GMT 01:00 Warsaw, Budapest, Bern
80: GMT 02:00 Athens, Helsinki, Istanbul, Riga
81: GMT 02:00 Cairo
82: GMT 02:00 Lebanon, Minsk
83: GMT 02:00 Israel
120: GMT 03:00 Baghdad, Kuwait, Riyadh,
Moscow, St. Petersburg, Nairobi
121: GMT 03:00 Iraq
140: GMT 03:30 Tehran
160: GMT 04:00 Abu Dhabi, Muscat, Baku,
Tbilisi, Yerevan
180: GMT 04:30 Kabul
200: GMT 05:00 Ekaterinburg, Islamabad,
Karachi, Tashkent
220: GMT 05:30 Calcutta, Chennai, Mumbai,
New Delhi
230: GMT 05:45 Kathmandu
240: GMT 06:00 Almaty, Novosibirsk, Astana,
Dhaka, Sri Jayawardenepura
260: GMT 06:30 Rangoon
280: GMT 07:00 Bangkok, Hanoi, Jakarta,
Krasnoyarsk
320: GMT 08:00 Beijing, Chongging, Hong
Kong, Kuala Lumpur, Singapore, Taipei
360: GMT 09:00 Osaka, Sapporo, Tokyo,
Seoul, Yakutsk
380: GMT 09:30 Adelaide, Darwin
400: GMT 10:00 Brisbane, Canberra,
Melbourne, Sydney, Guam, Vladivostok
440: GMT 11:00 Magadan, Solomon Is., New

			Caledonia
			480: GMT 12:00 Aucklan, Wellington, Fiji,
			Kamchatka, Marshall Is.
			520: GMT 13:00 Nuku'Alofa
daylight_enable	<boolean></boolean>	6/6	Enable automaticdaylight saving time in time
duyiight_chubic		0,0	zone.
 daylight_dstactualmode	<positive integer=""></positive>	6/7	Check if current time is under daylight saving
ddyngnt_dstaetdannode		0, /	time.
			(Used internally)
	string[19]	6/7	Display the current daylight saving start time.
		-	
daylight_auto_endtime	string[19]	6/7	Display the current daylight saving end time.
daylight_timezones	string	6/6	List time zone index which support daylight
			saving time.
updateinterval	0,	6/6	0 to Disable automatic time adjustment,
	3600,		otherwise, it indicates the seconds between
	86400,		NTP automatic update intervals.
	604800,		
	2592000		
restore	0,	7/6	Restore the system parameters to default
	<positive integer=""></positive>		values after <value> seconds.</value>
reset	0,	7/6	Restart the server after <value> seconds if</value>
	<positive integer=""></positive>		<value> is non-negative.</value>
restoreexceptnet	0,	7/6	Restore the system parameters to default
	<positive integer=""></positive>		values except (ipaddress, subnet, router,
			dns1, dns2, pppoe).
			This command can cooperate with other
			"restoreexceptXYZ" commands. When
			cooperating with others, the system
			parameters will be restored to the default
			value except for a union of the combined
			results.
restoreexceptdst	0,	7/6	Restore the system parameters to default
	<positive integer=""></positive>		values except all daylight saving time settings.
	_		This command can cooperate with other
			"restoreexceptXYZ" commands. When
			cooperating with others, the system
			parameters will be restored to default values
			except for a union of combined results.
restoreexceptlang	0,	7/6	Restore the system parameters to default
	<pre> c, <positive integer=""> </positive></pre>	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	values except the custom language file the

			user has uploaded.
			This command can cooperate with other
			"restoreexceptXYZ" commands. When
			cooperating with others, the system
			parameters will be restored to the default
			value except for a union of the combined
			results.
restoreexceptvadp	0,	7/6	Restore the system parameters to default
	<positive integer=""></positive>		values except the vadp parameters and VADP
			modules that stored in the system.
			This command can cooperate with other
			"restoreexceptXYZ" commands. When
			cooperating with others, the system
			parameters will be restored to the default
			value except for a union of the combined
			results.
restoreexceptfocusvalue	0,	7/6	Restore the system parameters to default
	<positive integer=""></positive>		values except zoom and focus value.
			This command can cooperate with other
			"restoreexceptXYZ" commands. When
			cooperating with others, the system
			parameters will be restored to the default
			value except for a union of the combined
			results.
			* Only available when
			"capability_image_c<0~(n-1)>_remotefocus"
			!= 0.

## 7.1.1 system.info

NAME	VALUE	SECURITY (get/set)	DESCRIPTION
modelname	string[40]	0/7	Internal model name of the server
extendedmodelname	string[40]	0/7	ODM specific model name of server (eg.
			DCS-5610). If it is not an ODM model, this field
			will be equal to "modelname"
serialnumber	<mac address=""></mac>	0/7	12 characters MAC address (without hyphens).
firmwareversion	string[40]	0/7	Firmware version, including model, company,
			and version number in the
			format: <model-brand-version></model-brand-version>
language_count	<positive integer=""></positive>	0/7	Number of webpage languages available on
			the server.
language_i<0~(count-1)>	string[16]	0/7	Available language lists.
	language_i0 :		
	English		
	language_i1 :		
	Deutsch		
	language_i2 :		
	Español		
	language_i3 :		
	Français		
	language_i4:		
	Italiano		
	language_i5:日本		
	語		
	language_i6 :		
	Português		
	language_i7: 简体		
	中文		
	language_i8:繁體		
	中文		
customlanguage_maxcoun	0, <positive< td=""><td>0/6</td><td>Maximum number of custom languages</td></positive<>	0/6	Maximum number of custom languages
t	integer>		supported on the server.
customlanguage_count	0, <positive< td=""><td>0/6</td><td>Number of custom languages which have been</td></positive<>	0/6	Number of custom languages which have been
	integer>		uploaded to the server.
customlanguage_i<0~(ma	string	0/6	Custom language name.

Subgroup of **system**: **info** (The fields in this group are unchangeable.)

xcount-1)>		

# 7.2 status

#### Group: **status**

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
di_i<0~(capability_ndi-1)>	<boolean></boolean>	1/7	0 => Inactive, normal
<product dependent=""></product>			1 => Active, triggered
			(capability.ndi > 0)
do_i<0~(capability_ndo-1)>	<boolean></boolean>	1/7	0 => Inactive, normal
<product dependent=""></product>			1 => Active, triggered
			(capability.ndo > 0)
onlinenum_rtsp	0, <positive< td=""><td>6/7</td><td>Current number of RTSP connections.</td></positive<>	6/7	Current number of RTSP connections.
	integer>		
onlinenum_httppush	0, <positive< td=""><td>6/7</td><td>Current number of HTTP push server</td></positive<>	6/7	Current number of HTTP push server
	integer>		connections.
onlinenum_sip	0, <positive< td=""><td>6/7</td><td>Current number of SIP connections.</td></positive<>	6/7	Current number of SIP connections.
	integer>		
eth_i0	<string></string>	1/7	Get network information from mii-tool.
vi_i<0~(capability_nvi-1)>	<boolean></boolean>	1/7	Virtual input
<product dependent=""></product>			0 => Inactive
			1 => Active
			(capability.nvi > 0)

## 7.2.1 status per channel

Group: **status\_c<0~(n-1)>** for n channel products

n denotes the value of "capability\_nvideoin"

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
signal_detect	<boolean></boolean>	1/7	Indicates whether the video source is
			connected or not.
			* Only available when capability_videoin_type
			is 0 or 1.
signal_type	ntsc,pal	1/7	The actual modulation type.
			* Only available when capability_videoin_type
			is 0 or 1.

# 7.3 digital input behavior define

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
normalstate	high,	1/1	Indicates open circuit or closed circuit
	low		(inactive status)

Group: **di\_i<0~(n-1)>** for n is the value of "capability\_ndi" (capability.ndi > 0)

# 7.4 digital output behavior define

Group: **do\_i<0~(n-1)>** for n is the value of "capability\_ndo" (capability.ndo > 0)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
normalstate	open,	1/1	Indicate open circuit or closed circuit (inactive
	grounded		status)

# 7.5 security

#### Group: security

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
privilege_do	view, operator,	1/6	Indicate which privileges and above can
	admin		control digital output
			(capability.ndo > 0)
privilege_camctrl	view, operator,	1/6	Indicate which privileges and above can
	admin		control PTZ
			(capability.ptzenabled > 0 or capability.eptz >
			0)
user_i0_name	string[64]	6/7	User name of root
user_i<1~20>_name	string[64]	6/7	User name
user_i0_pass	password[64]	7/6	Root password
user_i<1~20>_pass	password[64]	7/6	User password
user_i0_privilege	view,	6/7	Root privilege
	operator,		
	admin		
user_i<1~20>_ privilege	view,	6/6	User privilege
	operator,		
	admin		

# 7.6 network

#### Group: network

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
preprocess	<positive integer=""></positive>	6/6	An 32-bit integer, each bit can be set
			separately as follows:
			Bit 0 => HTTP service;
			Bit 1=> HTTPS service;
			Bit 2=> FTP service;
			Bit 3 => Two way audio and RTSP Streaming
			service;
			To stop service before changing its port
			settings. It's <b>recommended</b> to set this
			parameter when change a service port to the
			port occupied by another service currently.
			Otherwise, the service may fail.
			Stopped service will auto-start after changing
			port settings.
			Ex:
			Change HTTP port from 80 to 5556, and
			change RTP port for video from 5556 to 20480.
			Then, set preprocess=9 to stop both service
			first.
			"/cgi-bin/admin/setparam.cgi?
			network_preprocess=9&network_http_port=
			5556& network_rtp_videoport=20480"
type	lan,	6/6	Network connection type.
	рррое		
resetip	<boolean></boolean>	6/6	1 => Get ipaddress, subnet, router, dns1,
			dns2 from DHCP server at next reboot.
			0 => Use preset ipaddress, subnet, rounter,
			dns1, and dns2.
ipaddress	<ip address=""></ip>	6/6	IP address of server.
subnet	<ip address=""></ip>	6/6	Subnet mask.
router	<ip address=""></ip>	6/6	Default gateway.
dns1	<ip address=""></ip>	6/6	Primary DNS server.
dns2	<ip address=""></ip>	6/6	Secondary DNS server.

wins1	<ip address=""></ip>	6/6	Primary WINS server.
wins2	<ip address=""></ip>	6/6	Secondary WINS server.

## 7.6.1 802.1x

#### Subgroup of **network: ieee8021x (**capability.protocol.ieee8021x > 0)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	6/6	Enable/disable IEEE 802.1x
eapmethod	eap-peap, eap-tls	6/6	Selected EAP method
identity_peap	string[64]	6/6	PEAP identity
identity_tls	string[64]	6/6	TLS identity
password	string[200]	7/6	Password for TLS
privatekeypassword	string[200]	7/6	Password for PEAP
ca_exist	<boolean></boolean>	6/6	CA installed flag
ca_time	0, <positive< td=""><td>6/7</td><td>CA installed time. Represented in EPOCH</td></positive<>	6/7	CA installed time. Represented in EPOCH
	integer>		
ca_size	0, <positive< td=""><td>6/7</td><td>CA file size (in bytes)</td></positive<>	6/7	CA file size (in bytes)
	integer>		
certificate_exist	<boolean></boolean>	6/6	Certificate installed flag (for TLS)
certificate_time	0, <positive< td=""><td>6/7</td><td>Certificate installed time. Represented in</td></positive<>	6/7	Certificate installed time. Represented in
	integer>		EPOCH
certificate_size	0, <positive< td=""><td>6/7</td><td>Certificate file size (in bytes)</td></positive<>	6/7	Certificate file size (in bytes)
	integer>		
privatekey_exist	<boolean></boolean>	6/6	Private key installed flag (for TLS)
privatekey_time	0, <positive< td=""><td>6/7</td><td>Private key installed time. Represented in</td></positive<>	6/7	Private key installed time. Represented in
	integer>		EPOCH
privatekey_size	0, <positive< td=""><td>6/7</td><td>Private key file size (in bytes)</td></positive<>	6/7	Private key file size (in bytes)
	integer>		

# 7.6.2 QOS

#### Subgroup of **network: qos\_cos** (capability.protocol.qos.cos > 0)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	6/6	Enable/disable CoS (IEEE 802.1p)
vlanid	1~4095	6/6	VLAN ID
video	0~7	6/6	Video channel for CoS
audio	0~7	6/6	Audio channel for CoS

<product dependent=""></product>			(capability.naudioin > 0)
eventalarm	0~7	6/6	Event/alarm channel for CoS
management	0~7	6/6	Management channel for CoS
eventtunnel	0~7	6/6	Event/Control channel for CoS

#### Subgroup of **network: qos\_dscp** (capability.protocol.qos.dscp > 0)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	6/6	Enable/disable DSCP
video	0~63	6/6	Video channel for DSCP
audio	0~63	6/6	Audio channel for DSCP
			(capability.naudioin > 0)
eventalarm	0~63	6/6	Event/alarm channel for DSCP
management	0~63	6/6	Management channel for DSCP
eventtunnel	0~63	6/6	Event/Control channel for DSCP

## 7.6.3 IPV6

Subgroup of **network**: **ipv6** (capability.protocol.ipv6 > 0)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	6/6	Enable IPv6.
addonipaddress	<ip address=""></ip>	6/6	IPv6 IP address.
addonprefixlen	0~128	6/6	IPv6 prefix length.
addonrouter	<ip address=""></ip>	6/6	IPv6 router address.
addondns	<ip address=""></ip>	6/6	IPv6 DNS address.
allowoptional	<boolean></boolean>	6/6	Allow manually setup of IP address setting.

## 7.6.4 FTP

#### Subgroup of **network**: **ftp**

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
port	21, 1025~65535	6/6	Local ftp server port.
enable	<boolean></boolean>	6/6	Enable ftp.

## 7.6.5 HTTP

#### Subgroup of network: http

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
port	80, 1025 ~ 65535	1/6	HTTP port.
alternateport	1025~65535	6/6	Alternate HTTP port.
authmode	basic,	1/6	HTTP authentication mode.
	digest		
s<0~(capability_nmediast	string[32]	1/6	Http server push access name for stream N,
ream-1)>_accessname			N= 1~ capability.nmediastream.
<product dependent=""></product>			(capability.protocol.spush_mjpeg =1 and
			capability.nmediastream > 0)
			The value are shown as
			video.mjpg = s0_accessname, (stream1)
			video2.mjpg = s1_accessname, (stream2)
			video3.mjpg = s2_accessname, (stream3)
			video4.mjpg = s3_accessname, (stream4)
			etc.
anonymousviewing	<boolean></boolean>	1/6	Enable anonymous streaming viewing.

## 7.6.6 HTTPS port

Subgroup of **network**: **https** (capability.protocol.https > 0)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
port	443, 1025 ~ 65535	1/6	HTTPS port.

## 7.6.7 RTSP

Subgroup of **network**: **rtsp** (capability.protocol.rtsp > 0)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
port	554, 1025 ~ 65535	1/6	RTSP port.
			(capability.protocol.rtsp=1)
anonymousviewing	<boolean></boolean>	1/6	Enable anoymous streaming viewing.
authmode	disable,	1/6	RTSP authentication mode.
	basic,		(capability.protocol.rtsp=1)
	digest		

s<0~(capability_nmediast	string[32]	1/6	RTSP access name for stream N, N= $1\sim$	
ream-1)>_accessname			capability.nmediastream.	
<product dependent=""></product>			(capability.protocol.spush_mjpeg =1 and	
			capability.nmediastream > 0)	
			The value are shown as	
			live.sdp = s0_accessname, (stream1)	
			live2.sdp = s1_accessname, (stream2)	
			live3.sdp = s2_accessname, (stream3)	
			live4.sdp = s3_accessname, (stream4)	
			etc.	

## 7.6.7.1 RTSP multicast

#### Subgroup of **network\_rtsp\_s<0~(n-1)>**: **multicast** n is stream count

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
alwaysmulticast	<boolean></boolean>	4/4	Enable always multicast.
ipaddress	<ip address=""></ip>	4/4	Multicast video IP address.
			* We replace
			"network_rtsp_s<0~(n-1)>_multicast_ipaddress"
			with "
			network_rtsp_s<0~(n-1)>_multicast_videoipaddre
			ss ".
			* Reserved for compatibility, and suggest don't use
			this since [httpversion] > 0304a
videoipaddress	<ip address=""></ip>	4/4	Multicast video IP address.
			* We support this parameter when the version
			number (httpversion) is equal or greater than 0304a.
audioipaddress	<ip address=""></ip>	4/4	Multicast audio IP address.
<product dependent=""></product>			* We support this parameter when the version
			number (httpversion) is equal or greater than 0304a.
			* Only available when capability_naudioin > 0
metadataipaddress	<ip address=""></ip>	4/4	Multicast metadata IP address.
			* We support this parameter when the version
			number (httpversion) is equal or greater than 0304a.
videoport	1025 ~ 65535	4/4	Multicast video port.
audioport	1025 ~ 65535	4/4	Multicast audio port.
<product dependent=""></product>			* Only available when capability_naudioin > 0
metadataport	1026~65534	4/4	Multicast metadata port.

ttl	1 ~ 255	4/4	Multicasttime to live value.
-----	---------	-----	------------------------------

## 7.6.8 SIP port

Subgroup of **network**: **sip** (capability.protocol.sip> 0)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
port	1025 ~ 65535	1/6	SIP port.

## 7.6.9 RTP port

Subgroup of **network**: **rtp** 

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
videoport	1025 ~ 65535	6/6	Video channel port for RTP.
			(capability.protocol.rtp_unicast=1)
audioport	1025 ~ 65535	6/6	Audio channel port for RTP.
			(capability.protocol.rtp_unicast=1)
metadataport	1025 ~ 65535	6/6	Metadata channel port for RTP.

#### 7.6.10 PPPoE

Subgroup of **network**: **pppoe** (capability.protocol.pppoe > 0)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
user	string[128]	6/6	PPPoE account user name.
pass	password[64]	7/6	PPPoE account password.

# 7.7 IP Filter

#### Group: ipfilter

NAME	VALUE	SECURITY (get/set)	DESCRIPTION
enable	<boolean></boolean>	6/6	Enable access list filtering.
admin_enable	<boolean></boolean>	6/6	Enable administrator IP address.
admin_ip	string[43]	6/6	Administrator IP address.
maxconnection	1~10	6/6	Maximum number of concurrent streaming connection(s).
type	0, 1	6/6	Ipfilter policy :
			$0 \Rightarrow allow$
			1 => deny
ipv4list_i<0~9>	Single address: <ip address&gt; Network address: <ip <br="" address="">network mask&gt; Range</ip></ip 	6/6	IPv4 address list.
	address: <start ip<br="">address - end ip address&gt;</start>		
ipv6list_i<0~9>	string[43]	6/6	IPv6 address list.

# 7.8 Video input

#### Group: videoin

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
cmosfreq	50, 60	4/4	CMOS frequency.
			* Only available when capability_videoin_type
			is 2.
whitebalance	auto,	4/4	Modes of white balance.
<product dependent=""></product>	manual,		"auto": Auto white balance
	rbgain,		"rbgain": Use rgain and bgain to set white
	widerange,		balance manually.
	outdoor,		"manual": 2 cases:
	indoor,		a. if "rbgain" is not supported, this means
	sodiumauto,		keep current white balance status.
	etc		b. if "rbgain" is supported, "rgain" and
			"bgain" are updated to the current values
	(Available values are		which is got from white balance module. Then,
	listed in		act as rbgain mode
	"capability_image_c		"widerange": Auto Tracing White balance
	<0~(n-1)>_wbmod		(2000K to 10000K).
	e")		"outdoor": auto white balance mode
			specifically for outdoor.
			"indoor": auto white balance mode
			specifically for indoor.
			"sodiumauto": sodium vapor lamps.
			* Only available when
			"capability_image_c<0~(n-1)>_wbmode" !="
			_"
exposurelevel	0~12	4/4	Exposure level
			"0,12": This range takes the concept from DC's
			exposure tuning options. The definition is:
			0: EV -2.0
			1: EV -1.7
			2: EV -1.3
			3: EV -1.0
			4: EV -0.7
			5: EV -0.3

			1 7
			6: EV 0
			7: EV +0.3
			8: EV +0.7
			9: EV +1.0
			10: EV +1.3
			11: EV +1.7
			12: EV +2.0
			* Only available when
			"capability_image_c<0~(n-1)>_exposure_m
			ode" !=0
irismode	fixed, indoor,	4/4	Control DC-Iris mode.
	outdoor		"outdoor": Auto-setting DC-Iris to get best
	<product< td=""><td></td><td>quality, but easy to meet rolling or flicker effect</td></product<>		quality, but easy to meet rolling or flicker effect
	independent>		in indoor environment.
			"indoor": Avoid rolling and flicker effect first.
			"fixed": Open the iris to maximum.
			* Only available when
			"capability_image_c<0~(n-1)>_iristype"=dci
			ris
enableblc	<boolean></boolean>	4/4	Enable backlight compensation.
<not anymore="" support=""></not>			* Not support this parameter anymore when
			the version number (httpversion) is equal or
			greater than 0301a.
			* It's recommanded to use
			"exposurewin_c<0~(n-1)>_mode" to switch
			on/off BLC.
color	0, 1	4/4	0 =>monochrome
			1 => color
flip	<boolean></boolean>	4/4	Flip the image.
mirror	<boolean></boolean>	4/4	Mirror the image.
rotate	0,90,180,270	1/4	The rotation angle of image.
		_, .	Support only in Rotation mode.
			* Only available when "
			capability_videoin_c<0~(n-1)>_rotation"=1
ptzstatus	0, <positive< td=""><td>1/7</td><td>A 32-bit integer, each bit can be set separately</td></positive<>	1/7	A 32-bit integer, each bit can be set separately
<not anymore="" support=""></not>	integer>	-, ,	as follows:
			Bit 0 => Support camera control function;
			0(not support), 1(support)
			Bit 1 => <b>Built-in</b> or <b>external</b> camera; 0

			(external), 1(built-in)
			Bit 2 => Support <b>pan</b> operation; 0(not
			support), 1(support)
			Bit 3 => Support <b>tilt</b> operation; 0(not
			support), 1(support)
			Bit 4 => Support <b>zoom</b> operation; 0(not
			support), 1(support)
			Bit 5 => Support <b>focus</b> operation; 0(not
			<pre>support), 1(support)(SD/PZ/IZ series only)</pre>
text	string[64]	1/4	Enclose caption.
imprinttimestamp	<boolean></boolean>	4/4	Overlay time stamp on video.
minexposure	<1~32000>,	4/4	Minimum exposure time
<product dependent=""></product>	<5~32000>,		1~32000 => 1s ~ 1/32000s
	<1~8000>,		5~32000 => 1/5s ~ 1/32000s
	<5~8000>,		1~8000 => 1s ~ 1/8000s
	etc.		5~8000 => 1/5s ~ 1/8000s
			etc.
	* Available value is		
	listed in		* Only available when
	"capability_image_c		"capability_image_c<0~(n-1)>_exposure_mi
	<0~(n-1)>_exposu		nrange" != "-"
	re_minrange"		* Only valid when "piris_mode"=manual or
			"irismode"=fixed
			* Only available when
			"capability_image_c<0~(n-1)>_exposure_ra
			ngetype" is "twovalues".
maxexposure	<1~32000>,	4/4	Maximum exposure time
<product dependent=""></product>	<5~32000>,		1~32000 => 1s ~ 1/32000s
	<1~8000>,		5~32000 => 1/5s ~ 1/32000s
	<5~8000>,		1~8000 => 1s ~ 1/8000s
	etc.		5~8000 => 1/5s ~ 1/8000s
			etc.
	* Available value is		
	listed in		* This parameter may also restrict image
	"capability_image_c		frame rate from sensor due to sensor
	<0~(n-1)>_exposu		generates a frame per exposure time. Ex: If
	re_maxrange"		this is set to $1/5s \sim 1/8000s$ and camera takes
1		1	
			1/5s on the night, then sensor only outputs 5

			<pre>* Only available when "capability_image_c&lt;0~(n-1)&gt;_exposure_m axrange" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Only available when "capability_image_c&lt;0~(n-1)&gt;_exposure_ra ngetype" is "twovalues".</pre>
enablepreview	<boolean></boolean>	1/4	Usage for UI of exposure settings. Preview settings of video profile. * Only available when "capability_image_c<0~(n-1)>_exposure_m ode" !=0

## 7.8.1 Video input setting per channel

Group: videoin\_c<0~(n-1)> for n channel products, and m is stream number

n denotes the value of "capability\_nvideoin", m denotes the value of "capability\_nmediastream"

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
cmosfreq	50, 60	4/4	CMOS frequency.
			* Only available when "
			capability_videoin_type " is 2
mode	0 ~	4/4	Indicate the video mode on use.
	"capability_videoin_c<0~(n-1)>_nm		
	ode"-1		
whitebalance	auto,	4/4	Modes of white balance.
<product< td=""><td>manual,</td><td></td><td>"auto": Auto white balance</td></product<>	manual,		"auto": Auto white balance
dependent>	rbgain,		"rbgain": Use rgain and bgain to set
	widerange,		white balance manually.
	outdoor,		"manual": 2 cases:
	indoor,		a. if "rbgain" is not supported, this
	sodiumauto,		means keep current white balance
	etc		status.
			b. if "rbgain" is supported, "rgain"
	(Available values are listed in		and "bgain" are updated to the current
	"capability_image_c<0~(n-1)>_wbm		values which is got from white balance
	ode")		module. Then, act as rbgain mode
			"widerange": Auto Tracing White

	1		
			balance (2000K to 10000K).
			"outdoor": auto white balance mode
			specifically for outdoor.
			"indoor": auto white balance mode
			specifically for indoor.
			"sodiumauto": sodium vapor lamps.
			* Only available when
			"capability_image_c<0~(n-1)>_wbm
			ode" !="-"
rgain	0~100	4/4	Manual set rgain value of gain control setting.
			0: Weak <-> 100: Strong
			* Only available when "rbgain" is listed
			in
			"capability_image_c<0~(n-1)>_wbm
			ode".
			* Only valid when
			videoin_c<0~(n-1)>_whitebalance"
			!= auto
			* Normalized range.
bgain	0~100	4/4	Manual set bgain value of gain control
-			setting.
			0: Weak <-> 100: Strong
			* Only available when "rbgain" is listed
			in
			"capability_image_c<0~(n-1)>_wbm
			ode".
			* Only valid when
			"videoin_c<0~(n-1)>_whitebalance"
			!= auto
			* Normalized range.
exposurelevel	0~12	4/4	Exposure level
			"0,12": This range takes the concept
			from DC's exposure tuning options.
			The definition is:
			0: EV -2.0
			0. 27 2.0

			2: EV -1.3
			3: EV -1.0
			4: EV -0.7
			5: EV -0.3
			6: EV 0
			7: EV +0.3
			8: EV +0.7
			9: EV +1.0
			10: EV +1.3
			11: EV +1.7
			12: EV +2.0
			* Only available when
			"capability_image_c<0~(n-1)>_expo
			sure_mode" !=0
exposuremode	auto,	4/4	Select exposure mode.
<product< td=""><td>shutterpriority,</td><td></td><td></td></product<>	shutterpriority,		
dependent>	irispriority,		"auto": Automatically adjust the Iris,
	qualitypriority,		Gain and Shutter Speed to fit the
	manual,		exposure level.
	etc		"shutterpriority": Manually adjust
			with variable Shutter Speed, and keep
	(Available options are list in		adjusting Iris, Gain automatically.
	"capability_image_c<0~(n-1)>_expo		"irispriority": Manually adjust with
	sure_modetype")		variable Iris, and keep adjusting Gain
			and Shutter speed automatically.
			"qualitypriority": Automatically
			adjust the Iris, Gain and Shutter Speed
			by VIVOTEK quality algorithm.
			"manual": Manually adjust with
			variable Shutter, Iris and Gain.
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0302a.
			* Only available when
			"capability_image_c<0~(n-1)>_expo
			sure_mode" !=0
irismode	fixed, indoor, outdoor	4/4	Control DC-Iris mode.
	<product dependent=""></product>		"outdoor": Auto-setting DC-Iris to
			get best quality, but easy to meet
			get sest quality, but easy to meet

enableblc <body>       void and set P-Iris         enableblc       1~100       1/4       Manual set P-Iris         piris_position       1~100       1/4       Manual set P-Iris         piris_position       1~100       1/4       Manual set P-Iris         sependent&gt;       1/4       Manual set P-Iris       1/4         control P-Iris mode.       "outdoor": Avoid rolling and flicker         effect first.       "outdoor": Avoid rolling and flicker         effect first.       "manual": Manual set P-Iris to get         best quality, but easy to meet rolling or flicker effect in indoor environment.       "indoor": Avoid rolling and flicker         "indoor": Avoid rolling and flicker       "ficker effect in indoor environment.       "indoor": Avoid rolling and flicker         "indoor": Avoid rolling and flicker       effect first.       "manual": Manual set P-Iris by       "piris_position".         "indoor": avoid rolling and flicker       "capability_image_c&lt;0~(n-1)&gt;_iristy       pe"=piris         piris_position       1~100       1/4       Manual set P-Iris         i: Open &lt;&gt; 100: Close       *       "only valiable when         "piris_mode"=manual or       "capability_image_c&lt;0~(n-1)&gt;_iristy         "piris_mode"=manual or       "capability_image_c&lt;0~(n-1)&gt;_iristy         "only valid when</body>				1
Image: second				rolling or flicker effect in indoor
effect first.       "fixed": Open the iris to maximum.         * Only available when       "capability_image_c<0~(n-1)>_iristy         piris_mode       manual, indoor, outdoor,-       1/4       Control P-Tris mode.         *product       dependent>       "outdoor": Auto-setting P-Iris to get best quality, but easy to meet rolling or filcker effect in indoor environment.         "indoor": Avoid rolling and filcker effect first.       "manual": Manual set P-Iris by "piris_position".       "": not support. (only available when "capability_image_c<0~(n-1)>_iristy pe"=piris         plris_position       1~100       1/4       Manual set P-Iris.         ependent>       1~100       1/4       Manual set P-Iris.         plris_position       1~100       1/4       Manual set P-Iris.         ependent>       1~100       1/4       Manual set P-Iris.         stronge_ec=0~(n-1)>_iristy pe"=piris       100 close       *         enablebic <boolean>       4/4       Enable backlight compensation * Not support         enablebic       <boolean>       4/4       Enable backlight compensation * Not support this parameter anymore when the version number         enablebic       <boolean>       4/4       Enable backlight compensation * It's recommanded to use "exposurewin_c&lt;0~(n-1)&gt;_mode" to</boolean></boolean></boolean>				environment.
enableblc <body>       *Only available when "capability_image_c&lt;0~(n-1)&gt;_iristy pe"=drins         piris_mode       manual, indoor, outdoor,-       1/4       Control P-Iris mode.         <product< td="">       dependent&gt;       *Only available when "capability_ibut easy to meet rolling or flicker effect in indoor environment.         'indoor': Avoid rolling and flicker effect first.       "manual": Manual set P-Iris by "piris_position".       "</product<></body>				"indoor": Avoid rolling and flicker
enableblc <body>       * Only available when</body>				effect first.
enableblc         "capability_image_c<0~(n-1)>_iristy pe"=dciris         piris_mode       manual, indoor, outdoor,-       1/4       Control P-Iris mode.       "outdoor": Auto-setting P-Iris to get best quality, but easy to meet rolling or flicker effect in indoor environment.         'indoor': Auto-setting P-Iris to get best quality, but easy to meet rolling or flicker effect in indoor environment.       "indoor": Auto-setting P-Iris to get best quality, but easy to meet rolling or flicker effect first.         ''manual': Manual set P-Iris by "piris_position".       ""				"fixed": Open the iris to maximum.
piris_mode       manual, indoor, outdoor,-       1/4       Control P-1ris mode. <product< td="">       "outdoor": Auto-setting P-Iris to get       best quality, but easy to meet rolling or flicker effect in indoor environment.         'indoor": Avoid rolling and flicker       effect first.       "manual": Manual set P-Iris by         ''piris_position       -       "'expability_image_c&lt;0~(n-1)&gt;_sens         ortype" is "smartsensor")       * Only available when       "capability_image_c&lt;0~(n-1)&gt;_iristy         peris_position       1~100       1/4       Manual set P-Iris.         i: Open &lt;-&gt; 100: Close       *         dependent&gt;       *       Only available when         ''capability_image_c&lt;0~(n-1)&gt;_iristy       pe"=piris         piris_position       1~100       1/4       Manual set P-Iris.         : Open &lt;-&gt; 100: Close       *       *         dependent&gt;       *       Only valid when       "piris_mode"=manual or         ''capability_image_c&lt;0~(n-1)&gt;_iristy       pe"=piris       *       Only available when         ''capability_image_c&lt;0~(n-1)&gt;_iristy       *       Only available when       "capability_image_c&lt;0~(n-1)&gt;_iristy         enableblc       <boolean>       4/4       Enable backlight compensation       *         <not support<="" td="">       anymore&gt;       *</not></boolean></product<>				* Only available when
piris_mode       manual, indoor, outdoor,-       1/4       Control P-Iris mode. <product< td="">       "outdoor": Auto-setting P-Iris to get best quality, but easy to meet rolling or flicker effect in indoor environment.         "indoor": Avoid rolling and flicker effect first.       "manual": Manual set P-Iris by "piris_position".        </product<>				"capability_image_c<0~(n-1)>_iristy
<product </product  dependent>"outdoor": Auto-setting P-Iris to get best quality, but easy to meet rolling or flicker effect in indoor environment. "indoor": Avoid rolling and flicker effect first. "manual": Manual set P-Iris by "piris_position". "-": not support. (only available when "capability_image_c<0~(n-1)>_sirsty pe"=pirisplris_position1~1001/4Manual set P-Iris. "capability_image_c<0~(n-1)>_iristy pe"=pirisplris_position1~1001/4Manual set P-Iris. "capability_image_c<0~(n-1)>_iristy pe"=piriseheendent>1~1001/4Manual set P-Iris. "capability_image_c<0~(n-1)>_iristy pe"=pirisenableblc <boolean>4/4Enable backlight compensation * Not support this parameter anymore when the version number (httpsersion) is equal or greater than 0301a. * It's recommanded to use "exposurewin_c&lt;0~(n-1)&gt;_mode" to</boolean>				pe"=dciris
dependent>best quality, but easy to meet rolling or flicker effect in indoor environment. "indoor": Avoid rolling and flicker effect first. "manual": Manual set P-Iris by "piris_position". "-": not support. (only available when "capability_image_c<0~(n-1)>_sens ortype" is "smartsensor") * Only available when "capability_image_c<0~(n-1)>_iristy pe"=pirispiris_position <pre>troduct dependent&gt;1~1001/4Manual set P-Iris. to Support. (n-1)&gt;_iristy pe"=pirispiris_position <pre>coduct dependent&gt;1~1001/4Manual set P-Iris. to Only available when "capability_image_c&lt;0~(n-1)&gt;_sens ortype" is "smartsensor" * Only valid when "piris_mode"=manual or "capability_image_c&lt;0~(n-1)&gt;_sens ortype" is "smartsensor" * Only valid when "capability_image_c&lt;0~(n-1)&gt;_sens ortype" is "smartsensor" * Only valid when "capability_image_c&lt;0~(n-1)&gt;_iristy pe"=pirisenableblc <not support<br=""></not>anymore&gt;4/4Enable backlight compensation * Not support this parameter anymore when the version number (httpversion) is equal or greater than 0301a. * It's recommanded to use "exposurewin_c&lt;0~(n-1)&gt;_mode" to</pre></pre>	piris_mode	manual, indoor, outdoor,-	1/4	Control P-Iris mode.
enableblc <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation</boolean></boolean></boolean></boolean></boolean></boolean></boolean></boolean></boolean></boolean></boolean>	<product< td=""><td></td><td></td><td>"outdoor": Auto-setting P-Iris to get</td></product<>			"outdoor": Auto-setting P-Iris to get
enableblc <not support<="" th="">       <br <="" td=""/><td>dependent&gt;</td><td></td><td></td><td>best quality, but easy to meet rolling or</td></not>	dependent>			best quality, but easy to meet rolling or
enableblc <not support<="" td="">       <br <="" td=""/><td></td><td></td><td></td><td>flicker effect in indoor environment.</td></br></not>				flicker effect in indoor environment.
enableblc < Not support anymore>  				"indoor": Avoid rolling and flicker
enableblc <not support<="" td=""><boolean>4/4Enable backlight compensationenableblc <not support<="" td=""><boolean>4/4Enable backlight compensation* Not support <boolean>*/4Enable backlight compensation* Not support <boolean>*/4*/15* prome * Not support <boolean>*/4*/15* prome * Not support <boolean>*/4*/15* prome * Not support <boolean>*/4*/15* prome * Not support <boolean>*/4*/15* prome * Not support <boolean>*/15* prome * Not support <boolean>*/15* prome * Not support <boolean>*/15* prome * Not support */15* prom */15* prome * Not support */15* prom */15* prom * Not support */15* prom */15* prom *</boolean></boolean></boolean></boolean></boolean></boolean></boolean></boolean></br></boolean></boolean></not></boolean></not>				effect first.
enablebic <not support<="" th="">       <br <="" td=""/><td></td><td></td><td></td><td>"manual": Manual set P-Iris by</td></not>				"manual": Manual set P-Iris by
enableblc < Not support anymore>  				"piris_position".
enableblc <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       4/4       Enable backlight compensation         enableblc       <boolean>       %ort support       %ort support         enableblc       <boolean>       "exposurewin_cov(-(n-1)&gt;_mode" to    </boolean></boolean></boolean></boolean></boolean></boolean></boolean></boolean></boolean></boolean></boolean></boolean></boolean></boolean></boolean>				"-": not support. (only available when
enableblc <boolean>       4/4       Enable backlight compensation         <not support<br="">anymore&gt;       <boolean>       4/4       Enable backlight compensation         * Not support anymore&gt;       <boolean>       4/4       Enable backlight compensation         * Not support anymore&gt;       <boolean>       4/4       Enable backlight compensation         * Not support anymore&gt;       <boolean>       4/4       Enable backlight compensation         * It's recommanded to use "exposurewin_c&lt;0~(n-1)&gt;_mode" to       301a. * It's recommanded to use "exposurewin_c&lt;0~(n-1)&gt;_mode" to</boolean></boolean></boolean></boolean></not></boolean>				"capability_image_c<0~(n-1)>_sens
enableblc <not support<br=""></not> anymore>        <td></td> <td></td> <td></td> <td>ortype" is "smartsensor")</td>				ortype" is "smartsensor")
enableblc <boolean>       4/4       Enable backlight compensation         <not support<br="">anymore&gt;       <boolean>       4/4       Enable backlight compensation         * Not support anymore&gt;       <boolean>       4/4       Enable backlight compensation         * Not support anymore&gt;       <boolean>       4/4       Enable backlight compensation         * Not support anymore&gt;       * Not support compensation       * Not support this parameter anymore when the version number (httpversion) is equal or greater than 0301a.       * It's recommanded to use "exposurewin_c&lt;0~(n-1)&gt;_mode" to</boolean></boolean></boolean></not></boolean>				* Only available when
piris_position       1~100       1/4       Manual set P-Iris. <product< td="">       1/4       Manual set P-Iris.       1: Open &lt;-&gt; 100: Close         dependent&gt;       * Only valid when       "piris_mode"=manual or         "capability_image_c&lt;0~(n-1)&gt;_sens       ortype" is "smartsensor"         ortype" is "smartsensor"       * Only available when         "capability_image_c&lt;0~(n-1)&gt;_iristy         pe"=piris         enableblc       <boolean> <not support<="" td="">         anymore&gt;          4/4         Enable backlight compensation         * Not support         anymore&gt;          Yot support         anymore&gt;       * It's recommanded to use         "exposurewin_c&lt;0~(n-1)&gt;_mode" to</not></boolean></product<>				"capability_image_c<0~(n-1)>_iristy
<product </product  dependent>1: Open <-> 100: Close& Only valid when "piris_mode"=manual or "capability_image_c<0~(n-1)>_sens ortype" is "smartsensor" * Only available when "capability_image_c<0~(n-1)>_iristy pe"=pirisenableblc <not support<br=""></not> anymore> <boolean>4/4Enable backlight compensation * Not support this parameter anymore when the version number (httpversion) is equal or greater than 0301a. * It's recommanded to use "exposurewin_c&lt;0~(n-1)&gt;_mode" to</boolean>				pe"=piris
dependent>* Only valid when "piris_mode"=manual or "capability_image_c<0~(n-1)>_sens ortype" is "smartsensor" * Only available when "capability_image_c<0~(n-1)>_iristy pe"=pirisenableblc <boolean>4/4Enable backlight compensation * Not support this parameter anymore when the version number (httpversion) is equal or greater than 0301a. * It's recommanded to use "exposurewin_c&lt;0~(n-1)&gt;_mode" to</boolean>	piris_position	1~100	1/4	Manual set P-Iris.
<pre>* Only valid when "piris_mode"=manual or "capability_image_c&lt;0~(n-1)&gt;_sens ortype" is "smartsensor" * Only available when "capability_image_c&lt;0~(n-1)&gt;_iristy pe"=piris enableblc </pre> <pre>* boolean&gt;</pre> <pre> 4/4</pre> Enable backlight compensation * Not support anymore>  #/4 * Not support his parameter anymore when the version number (httpversion) is equal or greater than 0301a. * It's recommanded to use "exposurewin_c<0~(n-1)>_mode" to	<product< td=""><td></td><td></td><td>1: Open &lt;-&gt; 100: Close</td></product<>			1: Open <-> 100: Close
enableblc <boolean>4/4Enable backlight compensation * Not support anymore&gt;anymore&gt;<boolean>4/4Enable backlight compensation * Not support this parameter anymore when the version number (httpversion) is equal or greater than 0301a. * It's recommanded to use "exposurewin_c&lt;0~(n-1)&gt;_mode" to</boolean></boolean>	dependent>			
enableblc <boolean>4/4Enable backlight compensation<not support<="" td="">* Not support this parameter anymoreanymore&gt;<td></td><td></td><td></td><td>* Only valid when</td></not></boolean>				* Only valid when
enableblc <boolean>       4/4       Enable backlight compensation         <not support<="" td="">       * Not support this parameter anymore         anymore&gt;       4/4       Enable backlight compensation         * Not support       * Not support this parameter anymore         anymore&gt;       * It's recommanded to use         * It's recommanded to use       * It's recommanded to use</not></boolean>				"piris_mode"=manual or
enableblc <boolean>       4/4       Enable backlight compensation         <not support<="" td="">       * Not support this parameter anymore         anymore&gt;        When the version number         (httpversion) is equal or greater than       0301a.         * It's recommanded to use       * It's recommanded to use</not></boolean>				"capability_image_c<0~(n-1)>_sens
Image: Constant"capability_image_c<0~(n-1)>_iristy pe"=pirisenableblc <boolean>4/4Enable backlight compensation<not support<="" td="">* Not support this parameter anymore when the version number (httpversion) is equal or greater than 0301a.0301a.<image: constant<br=""></image:>anymore* It's recommanded to use "exposurewin_c&lt;0~(n-1)&gt;_mode" to</not></boolean>				ortype" is "smartsensor"
enableblc <boolean>     4/4     Enable backlight compensation       <not support<="" td="">     * Not support this parameter anymore       anymore&gt;     //4     Kot support this parameter anymore       (httpversion) is equal or greater than     0301a.       * It's recommanded to use     "exposurewin_c&lt;0~(n-1)&gt;_mode" to</not></boolean>				* Only available when
enableblc <boolean>       4/4       Enable backlight compensation         <not support<="" td="">       * Not support this parameter anymore         anymore&gt;       when the version number         (httpversion) is equal or greater than         0301a.         * It's recommanded to use         "exposurewin_c&lt;0~(n-1)&gt;_mode" to</not></boolean>				"capability_image_c<0~(n-1)>_iristy
<pre><not anymore="" support="">  * Not support this parameter anymore  when the version number  (httpversion) is equal or greater than  0301a.  * It's recommanded to use  "exposurewin_c&lt;0~(n-1)&gt;_mode" to</not></pre>				pe"=piris
anymore> when the version number (httpversion) is equal or greater than 0301a. * It's recommanded to use "exposurewin_c<0~(n-1)>_mode" to	enableblc	<boolean></boolean>	4/4	Enable backlight compensation
(httpversion) is equal or greater than 0301a. * It's recommanded to use "exposurewin_c<0~(n-1)>_mode" to	<not support<="" td=""><td></td><td></td><td>* Not support this parameter anymore</td></not>			* Not support this parameter anymore
0301a. * It's recommanded to use "exposurewin_c<0~(n-1)>_mode" to	anymore>			when the version number
* It's recommanded to use "exposurewin_c<0~(n-1)>_mode" to				(httpversion) is equal or greater than
"exposurewin_c<0~(n-1)>_mode" to				0301a.
				* It's recommanded to use
				"exposurewin_c<0~(n-1)>_mode" to

			1
maxgain	0~100	4/4	Maximum gain value.
			0: Low <-> 100: High
			* Only available when
			"capability_image_c<0~(n-1)>_agc_
			maxgain" != "-"
			* Only valid when
			"piris_mode"=manual or
			"irismode"=fixed
			* Normalized range.
			* Only available when
			"capability_image_c<0~(n-1)>_expo
			sure_rangetype" is "twovalues".
mingain	0~100	4/4	Minimum gain value.
			0: Low <-> 100: High
			* Only available when
			"capability_image_c<0~(n-1)>_agc_
			mingain" != "-"
			* Only valid when
			"piris_mode"=manual or
			"irismode"=fixed
			* Normalized range.
			* Only available when
			"capability_image_c<0~(n-1)>_expo
			sure_rangetype" is "twovalues".
gainvalue	0~100	4/4	Gain value.
5			0: Low <-> 100: High
			* Only available when
			"capability_image_c<0~(n-1)>_agc_
			maxgain" != "-" and
			"capability_image_c<0~(n-1)>_expo
			sure_rangetype" is "onevalue".
			* Normalized range.
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0302a.
color	0, 1	4/4	0 =>monochrome
	0, 1	4/4	

			1 => color
flip	<boolean></boolean>	4/4	Flip the image.
mirror	<boolean></boolean>	4/4	Mirror the image.
rotate	0,90,180,270	1/4	The rotation angle of image.
			Support only in Rotation mode
			(capability_videoin_c<0~(n-1)>_rota
			tion=1)
ptzstatus	0, <positive integer=""></positive>	1/7	A 32-bit integer, each bit can be set
<not support<="" td=""><td></td><td></td><td>separately as follows:</td></not>			separately as follows:
anymore>			Bit 0 => Support camera control
,			function; 0(not support), 1(support)
			Bit 1 => <b>Built-in</b> or <b>external</b> camera;
			0 (external), 1(built-in)
			Bit 2 => Support <b>pan</b> operation;
			0(not support), 1(support)
			Bit 3 => Support <b>tilt</b> operation; 0(not
			support), 1(support)
			Bit 4 => Support <b>zoom</b> operation;
			0(not support), 1(support)
			Bit 5 => Support <b>focus</b> operation;
			0(not support), 1(support)(SD/PZ/IZ
			series only)
text	string[64]	1/4	Enclose caption.
imprinttimesta	<boolean></boolean>	4/4	Overlay time stamp on video.
mp			
textonvideo_po	top, bottom	4/4	Text on video string position
sition			
textonvideo_siz	20~40	4/4	Text on video font size
е			
textonvideo_fon	/usr/share/font/Default.ttf,	4/4	Choose camera default font file
tpath	/mnt/flash2/upload.ttf		(/usr/share/font/Default.ttf) or user
			uploaded font
			uploaded font file(/mnt/flash2/upload.ttf).
textonvideo_upl	Depends on the font file name	1/7	
textonvideo_upl oadfilename	Depends on the font file name uploaded by user	1/7	file(/mnt/flash2/upload.ttf).
-		1/7	file(/mnt/flash2/upload.ttf).
oadfilename minexposure	uploaded by user		file(/mnt/flash2/upload.ttf). Show the uploaded font file name.
oadfilename minexposure <product< td=""><td>uploaded by user &lt;1~32000&gt;, &lt;5~32000&gt;,</td><td></td><td>file(/mnt/flash2/upload.ttf).Show the uploaded font file name.Minimum exposure time1~32000 =&gt; 1s ~ 1/32000s</td></product<>	uploaded by user <1~32000>, <5~32000>,		file(/mnt/flash2/upload.ttf).Show the uploaded font file name.Minimum exposure time1~32000 => 1s ~ 1/32000s
oadfilename minexposure	uploaded by user		file(/mnt/flash2/upload.ttf). Show the uploaded font file name. Minimum exposure time

		1	1
			etc.
	* Available value is listed in		
	"capability_image_c<0~(n-1)>_expo		* Only available when
	sure_minrange"		"capability_image_c<0~(n-1)>_expo
			sure_minrange" != "-"
			* Only valid when
			"piris_mode"=manual or
			"irismode"=fixed
			* Only available when
			"capability_image_c<0~(n-1)>_expo
			sure_rangetype" is "twovalues".
maxexposure	<1~32000>,	4/4	Maximum exposure time
<pre>cproduct</pre>	<5~32000>,	., .	$1 \sim 32000 => 1s \sim 1/32000s$
dependent>	<1~8000>,		$5 \sim 32000 => 1/5 \approx 1/32000s$
acpendents	<5~8000>,		1~8000 => 1s ~ 1/8000s
	etc.		$5 \sim 8000 => 1/5s \sim 1/8000s$
			etc.
	* Available value is listed in		*
	"capability_image_c<0~(n-1)>_expo		* This parameter may also restrict
	sure_maxrange"		image frame rate from sensor due to
			sensor generates a frame per
			exposure time. Ex: If this is set to 1/5s
			$\sim$ 1/8000s and camera takes 1/5s on
			the night, then sensor only outputs 5
			frame/s.
			* Only available when
			"capability_image_c<0~(n-1)>_expo
			sure_maxrange" != "-"
			* Only valid when
			"piris_mode"=manual or
			"irismode"=fixed
			* Only available when
			"capability_image_c<0~(n-1)>_expo
<u> </u>	1 22000		sure_rangetype" is "twovalues".
shuttervalue	<1~32000>,	4/4	Exposure time
<product< td=""><td>&lt;5~32000&gt;,</td><td></td><td>1~32000 =&gt; 1s ~ 1/32000s</td></product<>	<5~32000>,		1~32000 => 1s ~ 1/32000s
dependent>	<1~8000>,		5~32000 => 1/5s ~ 1/32000s
	<5~8000>,		1~8000 => 1s ~ 1/8000s
	etc.		5~8000 => 1/5s ~ 1/8000s

		1	1
			etc.
	* Available value is listed in		
	"capability_image_c<0~(n-1)>_expo		* This parameter may also restrict
	sure_maxrange"		image frame rate from sensor due to
			sensor generates a frame per
			exposure time. Ex: If this is set to 1/5s
			$\sim 1/8000s$ and camera takes 1/5s on
			the night, then sensor only outputs 5
			frame/s.
			* Only available when
			"capability_image_c<0~(n-1)>_expo
			sure_maxrange" != "-" and
			"capability_image_c<0~(n-1)>_expo
			sure_rangetype" is "onevalue".
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0302a.
enablepreview	<boolean></boolean>	1/4	Usage for UI of exposure settings.
			Preview settings of video profile.
			* Only available when
			"capability_image_c<0~(n-1)>_expo
			sure_mode" !=0
crop_position	<coordinate></coordinate>	1/7	Crop left-top corner coordinate.
	(x,y)		
crop_size	<window size=""></window>	1/7	Crop width and height.
	(WxH)		(width must be 16x or 32x and height
			must be 8x)
zoomratiodispla	<boolean></boolean>	1/4	Indicates multiple of zoom in is
y			"on-screen display" or not.
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0302a.
s<0~(m-1)>_e	<boolean></boolean>	4/4	Indicate whether stream supprts eptz
nableeptz			or not
s<0~(m-1)>_c	Listed at "capability_videoin_codec"	1/4	Codec type for this stream
odectype	Possible values are: mjpeg,		
50000,00			<u> </u>

h264,h265 <pre>cprduct dependent&gt;I/4Video resolution in pixels.s&lt;0~(m-1)&gt;_re ("capability_videoin_c&lt;0~(n-1)&gt;_reso lution".1/4Video resolution in pixels.Besides, available options is referred to "capability_videoin_c&lt;0~(n-1)&gt;_min resolution" and "capability_videoin_c&lt;0~(n-1)&gt;_min resolution"Enable "Dynamic intra frame period". * Only available when * capability_videoin_c&lt;0~(n-1)&gt;_min resolution"s&lt;0~(m-1)&gt;_h 2.64_dintraperio d_enable.Enable "Dynamic intra frame period". * Only available when * capability_videoin_c&lt;0~(n-1)&gt;_min resolution"Enable "Dynamic intra frame period". * Only available when * capability_videoin_c&lt;0~(n-1)&gt;_min raperiod_support" is 1. * We support this parameter when the version number (httpversion) is equal or greater than 0301c.s&lt;0~(m-1)&gt;_h 2.64_intraperio250, 500, 1000, 2000, 3000, 40004/4The time interval between two 1-frames (Intra coded picture). The unit is milliscond (ms).s&lt;0~(m-1)&gt;_hs&lt;0~(m-1)&gt;_hs&lt;0~(m-1)&gt;_hs&lt;0~(m-1)&gt;_hs&lt;0~(m-1)&gt;_hs&lt;0~(m-1)&gt;_hs&lt;0~(m-1)&gt;_hs&lt;0~(m-1)&gt;_hs&lt;0~(m-1)&gt;_hs&lt;0~(m-1)&gt;_hs&lt;0~(m-1)&gt;_h.<td< th=""><th></th><th></th><th>1</th><th>1</th></td<></pre>			1	1
s<0~(m-1)>_re       Available options are list in       1/4       Video resolution in pixels.         solution       "capability_videoin_c<0~(n-1)>_reso       1/4       Video resolution in pixels.         Besides, available options is referred to       "capability_videoin_c<0~(n-1)>_ma       *         s<0~(m-1)>_h       cboolean>       4/4       Enable "Dynamic Intra frame period".         s<0~(m-1)>_h       cboolean>       4/4       Enable "Dynamic Intra frame period".         s<0~(m-1)>_h       cboolean>       4/4       Enable "Dynamic Intra frame period".         s<0~(m-1)>_h       cboolean>       4/4       The time interval between two         264_intraperiod       250, 500, 1000, 2000, 3000, 4000       4/4       The time interval between two         264_intraperiod       cbr, vbr       4/4       Cbr: Constant bit rate mode.         s<0~(m-1)>_h       cbr, vbr       4/4       Cbr: Constant bit rate mode.         s<0~(m-1)>_h       cbr, vbr       4/4       Set the pre-defined quality level:         s<0~(m-1)>_h       1~5,       99, 100       1: Medium         2: Standard       3: Good       3: Good       3: Good         3: Bood       Set the quality level in "qvalue"       "Qvalue"       "Qvalue"         s<0~(m-1)>_h       0~51       4/4 <td></td> <td>h264,h265</td> <td></td> <td></td>		h264,h265		
solution"capability_videoin_c<0~(n-1)>_reso lution".Image: solution is referred to "capability_videoin_c<0~(n-1)>_ma xresolution" and "capability_videoin_c<0~(n-1)>_min resolution"Enable "Dynamic intra frame period". * Only available when "capability_videoin_c<0~(n-1)>_min resolution"s<0~(m-1)>_h 264_dintraperiod d_enable 200 (an > 0 )4/4Enable "Dynamic intra frame period". * Only available when "capability_videoin_c<0~(n-1)>_dint raperiod_support" is 1. * We support this parameter when the version number (httpwersion) is equal or greater than 0301c.s<0~(m-1)>_h 264_intraperiod250, 500, 1000, 2000, 3000, 40004/4The time interval between two 1-frames (Intra coded picture). The unit is millisecond (ms).s<0~(m-1)>_h 264_ratecontrol modecbr, vbr4/4Cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_h 264_quant1~5, 99, 1004/4Set the pre-defined quality level: 1. Medium 2. Standard 3. Good 4. Detailed 5. Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qualue" 99: Use the quality level in "qualue"		<product dependent=""></product>		
Iution".Besides, available options is referred to "capability_videoin_c<0~(n-1)>_mai xresolution" and "capability_videoin_c<0~(n-1)>_min resolution"s<0~(m-1)>_h <boolean>4/4Enable "Dynamic intra frame period". * Only available when "capability_videoin_c&lt;0~(n-1)&gt;_dint raperiod_support" is 1. * We support this parameter when the version number (httpversion) is equal or greater than 0301c.s&lt;0~(m-1)&gt;_h250, 500, 1000, 2000, 3000, 40004/4The time interval between two I-frames (Intra coded picture). The unit is millisecond (ms).s&lt;0~(m-1)&gt;_hcbr, vbr4/4cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s&lt;0~(m-1)&gt;_h1~5,99, 1004/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qvalue" * vbr.s&lt;0~(m-1)&gt;_h0~514/4Manual video quality level in unit are vbr.</boolean>	s<0~(m-1)>_re	Available options are list in	1/4	Video resolution in pixels.
Besides, available options is referred to "capability_videoin_c<0~(n-1)>_ma xresolution" and "capability_videoin_c<0~(n-1)>_min resolution"Addition\$<0~(m-1)>_h d_enable\$ <bolean>4/4Enable "Dynamic intra frame period". * Only available when "capability_videoin_c&lt;0~(n-1)&gt;_dint raperiod_support" is 1. * We support this parameter when the version number (httpversion) is equal or greater than 0301c.\$&lt;0~(m-1)&gt;_h 264_intraperiod250, 500, 1000, 2000, 3000, 40004/4The time interval between two I-frames (Intra coded picture). The unit is millisecond (ms).\$&lt;0~(m-1)&gt;_h 264_interperiodcbr, vbr4/4Cbr: Constant bit rate mode. vbr: Fixed quality level if frames are encoded in the same quality.\$&lt;0~(m-1)&gt;_h 264_quant1~5, 99, 1006/4Set the pre-defined quality level: 1. Kedium 2. Standard 3. Good 4. Detailed 5. Excellent 100: Use the quality level in "grecent" 99: Use the quality level in "grecent" 99: Use the quality level in "qualue" sor.\$&lt;0~(m-1)&gt;_h0~514/4Manual video quality level input. The Q</bolean>	solution	"capability_videoin_c<0~(n-1)>_reso		
to "capability_videoin_c<0~(n-1)>_ma xresolution" and "capability_videoin_c<0~(n-1)>_min resolution"Lenable "Dynamic intra frame period". * Only available when "capability_videoin_c<0~(n-1)>_dint raperiod_support" is 1. * We support this parameter when the version number (httpversion) is equal or greater than 0301c.s<0~(m-1)>_h250, 500, 1000, 2000, 3000, 4000 264_intraperiod4/4Enable "Dynamic intra frame period". * Only available when "capability_videoin_c<0~(n-1)>_dint raperiod_support" is 1. * We support this parameter when the version number (httpversion) is equal or greater than 0301c.s<0~(m-1)>_h250, 500, 1000, 2000, 3000, 40004/4The time interval between two 1-frames (Intra coded picture). The unit is millisecond (ms).s<0~(m-1)>_hcbr, vbr4/4Cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_h1~5,99, 100Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qualue" is "only valid when "ratecontroinode"= vbr.s<0~(m-1)>_h0~514/4Manual video quality level input. The Q		lution".		
to "capability_videoin_c<0~(n-1)>_ma xresolution" and "capability_videoin_c<0~(n-1)>_min resolution"Lenable "Dynamic intra frame period". * Only available when "capability_videoin_c<0~(n-1)>_dint raperiod_support" is 1. * We support this parameter when the version number (httpversion) is equal or greater than 0301c.s<0~(m-1)>_h250, 500, 1000, 2000, 3000, 4000 264_intraperiod4/4Enable "Dynamic intra frame period". * Only available when "capability_videoin_c<0~(n-1)>_dint raperiod_support" is 1. * We support this parameter when the version number (httpversion) is equal or greater than 0301c.s<0~(m-1)>_h250, 500, 1000, 2000, 3000, 40004/4The time interval between two 1-frames (Intra coded picture). The unit is millisecond (ms).s<0~(m-1)>_hcbr, vbr4/4Cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_h1~5,99, 100Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qualue" is "only valid when "ratecontroinode"= vbr.s<0~(m-1)>_h0~514/4Manual video quality level input. The Q				
"capability_videoin_c<0~(n-1)>_ma xresolution" and "capability_videoin_c<0~(n-1)>_min resolution"Image: solution in the solution is equal to its		Besides, available options is referred		
xresolution" and "capability_videoin_c<0~(n-1)>_min resolution"4/4Enable "Dynamic intra frame period". * Only available when "capability_videoin_c<0~(n-1)>_dint raperiod_support" is 1. * We support this parameter when the version number (httpversion) is equal or greater than 0301c.s<0~(m-1)>_h250, 500, 1000, 2000, 3000, 4000 264_intraperiod 264_intraperiod4/4The time interval between two I-frames (Intra coded picture). The unit is millisecond (ms).s<0~(m-1)>_hcbr, vbr4/4Ctr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_h1~5,99, 1004/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qualue" * Only valid when "ratecontrolmode"= vbr.s<0~(m-1)>_h0~514/4Manual video quality level input. The Q		to		
"capability_videoin_c<0~(n-1)>_minImage: Comparison of the second of the se		"capability_videoin_c<0~(n-1)>_ma		
resolution"Image: Constant of the second of the		xresolution" and		
\$<0~(m-1)>_h 264_dintraperio d_enable\$\$Enable "Dynamic intra frame period". * Only available when "capability_videoin_c<0~(n-1)>_dint raperiod_support" is 1. * We support this parameter when the version number (httpversion) is equal or greater than 0301c.\$<0~(m-1)>_h 264_intraperiod250, 500, 1000, 2000, 3000, 40004/4The time interval between two I-frames (Intra coded picture). The unit is millisecond (ms).\$<0~(m-1)>_h 264_ratecontrol mode250, vbr4/4Cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.\$<0~(m-1)>_h 264_quant1~5, 99, 1004/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qpercent" 99: Use the quality level in qualue" +0		"capability_videoin_c<0~(n-1)>_min		
264_dintraperiod d_enable* Only available when "capability_videoin_c<0~(n-1)>_dint raperiod_support" is 1. * We support this parameter when the version number (httpversion) is equal or greater than 0301c.\$<0~(m-1)>_h 264_intraperiod250, 500, 1000, 2000, 3000, 40004/4The time interval between two I-frames (Intra coded picture). The unit is millisecond (ms).\$<0~(m-1)>_h 264_ratecontrol modecbr. vbr4/4cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.\$<0~(m-1)>_h 264_quant1~5,4/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "gpercent" 99: Use the quality level in "gpercent" 99: Use the quality level in "gpercent" 90: Use the quality level in "gpercent" 90: Use the quality level in "gpercent"		resolution"		
d_enable"capability_videoin_c<0~(n-1)>_dit raperiod_support" is 1. * We support this parameter when the version number (httpversion) is equal or greater than 0301c.s<0~(m-1)>_h250, 500, 1000, 2000, 3000, 40004/4The time interval between two I-frames (Intra coded picture). The unit is millisecond (ms).s<0~(m-1)>_hcbr, vbr4/4Cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_h1~5,4/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qpercent" 99: Use the quality level in "quale" vbr.	s<0~(m-1)>_h	<boolean></boolean>	4/4	Enable "Dynamic intra frame period".
s<0~(m-1)>_h250, 500, 1000, 2000, 3000, 40004/4The time interval between two I-frames (Intra coded picture). The unit is millisecond (ms).s<0~(m-1)>_hcbr, vbr4/4Cbr: Costant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_h1~5,4/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "gpercent" 99: Use the quality level in "qualue" * Only valid when "ratecontrolmode"= vbr.s<0~(m-1)>_h0~514/4Manual video quality level input. The Q	264_dintraperio			* Only available when
s<0~(m-1)>_h250, 500, 1000, 2000, 3000, 40004/4* We support this parameter when the version number (httpversion) is equal or greater than 0301c.s<0~(m-1)>_h250, 500, 1000, 2000, 3000, 40004/4The time interval between two I-frames (Intra coded picture). The unit is millisecond (ms).s<0~(m-1)>_hcbr. vbr4/4Cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_h1~5,4/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qpercent" 99: Use the quality level in "qualue" vbr.s<0~(m-1)>_h0~514/4Manual video quality level input. The Q	d_enable			"capability_videoin_c<0~(n-1)>_dint
s<0~(m-1)>_h250, 500, 1000, 2000, 3000, 40004/4The time interval between two I-frames (Intra coded picture). The unit is millisecond (ms).s<0~(m-1)>_hcbr, vbr4/4Cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_h1~5,4/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qpercent" 99: Use the quality level in "qpalue" * Only valid when "ratecontrolmode"= vbr.s<0~(m-1)>_h0~514/4Manual video quality level input. The Q				raperiod_support" is 1.
Image: sequence of the sequenc				* We support this parameter when the
s<0~(m-1)>_h       250, 500, 1000, 2000, 3000, 4000       4/4       The time interval between two I-frames (Intra coded picture). The unit is millisecond (ms).         s<0~(m-1)>_h       cbr, vbr       4/4       Cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.         s<0~(m-1)>_h       1~5,       4/4       Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qvalue"         s<0~(m-1)>_h       0~51       4/4       Manual video quality level input. The Q				version number (httpversion) is equal
264_intraperiodI-frames (Intra coded picture). The unit is millisecond (ms).s<0~(m-1)>_hcbr, vbr4/4cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_h1~5,4/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qpercent" 99: Use the quality level in "qvalue" xor.s<0~(m-1)>_h0~514/4Manual video quality level input. The Q				or greater than 0301c.
s<0~(m-1)>_h 264_ratecontrol modecbr, vbrcbr, vbrcbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_h1~5,4/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "quality 99: Use the quality level in "quality"s<0~(m-1)>_h0~514/4Manual video quality level input. The Q	s<0~(m-1)>_h	250, 500, 1000, 2000, 3000, 4000	4/4	The time interval between two
s<0~(m-1)>_h 264_ratecontrol modecbr, vbr4/4cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_h1~5,4/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qpercent" 99: Use the quality level in "qvalue" * Only valid when "ratecontrolmode" = vbr.s<0~(m-1)>_h0~514/4Manual video quality level input. The Q	264_intraperiod			I-frames (Intra coded picture).
264_ratecontrol modevbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_h1~5,4/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qvalue" * Only valid when "ratecontrolmode"= vbr.s<0~(m-1)>_h0~514/4Manual video quality level input. The Q				The unit is millisecond (ms).
modeImage: second s	s<0~(m-1)>_h	cbr, vbr	4/4	<b>cbr</b> : Constant bit rate mode.
s<0~(m-1)>_h         1~5,         4/4         Set the pre-defined quality level:           264_quant         99, 100         1: Medium           2: Standard         3: Good           4: Detailed         5: Excellent           100: Use the quality level in         "qpercent"           "qpercent"         99: Use the quality level in "qvalue"           * Only valid when "ratecontrolmode"=         vbr.           s<0~(m-1)>_h         0~51         4/4         Manual video quality level input. The Q	264_ratecontrol			<b>vbr</b> : Fixed quality mode, all frames are
264_quant       99, 100       1: Medium         2: Standard       2: Standard         3: Good       4: Detailed         5: Excellent       100: Use the quality level in         "qpercent"       99: Use the quality level in "qvalue"         99: Use the quality level in "qvalue"       * Only valid when "ratecontrolmode"=         vbr.       vbr.	mode			encoded in the same quality.
264_quant       99, 100       1: Medium         2: Standard       2: Standard         3: Good       4: Detailed         5: Excellent       100: Use the quality level in         "qpercent"       99: Use the quality level in "qvalue"         99: Use the quality level in "qvalue"       * Only valid when "ratecontrolmode"=         vbr.       vbr.				
<ul> <li>S&lt;0~(m-1)&gt;_h</li> <li>O~51</li> <li>Standard</li> <li>Standard&lt;</li></ul>	s<0~(m-1)>_h	1~5,	4/4	Set the pre-defined quality level:
s<0~(m-1)>_h       0~51         A       S         A       Detailed         A       Detailed         B       S         B       A         B       A         B       A         B       A         B       A         B       A         B       A         B       A         B       A         B       A	264_quant	99, 100		1: Medium
s<0~(m-1)>_h A: Detailed 4: Detailed 5: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qvalue" * Only valid when "ratecontrolmode"= vbr. 4/4 Manual video quality level input. The Q				2: Standard
s<0~(m-1)>_h0~514/45: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qvalue" vbr.				3: Good
s<0~(m-1)>_h0~514/4100: Use the quality level in "qpercent" 99: Use the quality level in "qvalue" vbr.				4: Detailed
s<0~(m-1)>_h       0~51       4/4       "qpercent"         "qpercent"       99: Use the quality level in "qvalue"         * Only valid when "ratecontrolmode"=       vbr.         s<0~(m-1)>_h       0~51				5: Excellent
s<0~(m-1)>_h       0~51       4/4       Manual video quality level in put. The Q				100: Use the quality level in
s<0~(m-1)>_h       0~51       4/4       Manual video quality level input. The Q				"qpercent"
s<0~(m-1)>_h0~514/4Manual video quality level input. The Q				99: Use the quality level in "qvalue"
s<0~(m-1)>_h0~514/4Manual video quality level input. The Q				
s<0~(m-1)>_h 0~51 4/4 Manual video quality level input. The Q				* Only valid when "ratecontrolmode"=
				vbr.
264_qvalue value which is used by encoded library	s<0~(m-1)>_h	0~51	4/4	Manual video quality level input. The Q
	264_qvalue			value which is used by encoded library

s<0~(m-1)>_h       1~100       4/4       Select customized quality in a normalized full range.         s<0~(m-1)>_h       20000~'capability_videoin_c<0~(n-1)       4/4       Select customized quality in a normalized full range.         s<0~(m-1)>_h       20000~'capability_videoin_c<0~(n-1)       4/4       The maximum allowed bit rate in fixed quality mode.         s<0~(m-1)>_h       20000~'capability_videoin_c<0~(n-1)       4/4       The maximum allowed bit rate in fixed quality mode.         s<0~(m-1)>_h       20000~'capability_videoin_c<0~(n-1)       4/4       The maximum allowed bit rate in fixed quality mode.         s<0~(m-1)>_h       20000~'capability_videoin_c<0~(n-1)       4/4       The maximum allowed bit rate in fixed quality mode.         s<0~(m-1)>_h       20000~'capability_videoin_c<0~(n-1)       4/4       The maximum allowed bit rate in fixed quality mode.         s<0~(m-1)>_h       1~564_maxbitrate"       4/4       Set the pre-defined quality level:         s<0~(m-1)>_h       1~5, 100       4/4       Set the pre-defined quality level:         s: Keellent       100: Use the quality level in "cbr_qpercent"       * Only available when "ratecontrolmode"= cbr. * Only av			1	
s<0~(m-1)>_h       1~100       4/4       Select customized quality in a normalized full range.         264_qpercent       1~100       4/4       Select customized quality in a normalized full range.         1: Worst quality       100: Best quality       100: Best quality         s<0~(m-1)>_h       20000~"capability_videoin_c<0~(n-1)				directly.
s<0~(m-1)>_h       1~100       4/4       Select customized quality in a normalized full range.         264_qpercent       1~100       4/4       Select customized quality in a normalized full range.         1: Worst quality       100: Best quality       100: Best quality         s<0~(m-1)>_h       20000~"capability_videoin_c<0~(n-1)				
s<0~(m-1)>_h 264_qpercent1~1004/4Select customized quality in a normalized full range. 1: Worst quality 100: Best quality * Only valid when "ratecontrolmode"= wbr and "quant"= 100.s<0~(m-1)>_h 264_maxbitrate20000~"capability_videoin_c<0~(n-1) >_h 264_maxbitrate"4/4The maximum allowed bit rate in fixed quality mode. When the bit rate exceeds this value, frames will be dropped to restrict the bit rate. * Only valid when "ratecontrolmode"= wbrs<0~(m-1)>_h 264_cbr_quant1~5, 1004/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "cor_gpercent" * Only available when "capability_smartstream_version"=2. 0s<0~(m-1)>_h 264_cbr_queree nt1~1004/4Select customized quality in a normalized full range. 1: Worst quality 10: Best quality				
s<0~(m-1)>_h       1~100       4/4       Select customized quality in a normalized full range.         264_gpercent       1. Worst quality       100: Best quality         264_gpercent       20000~"capability_videoin_c<0~(n-1)				
264_qpercent       normalized full range.         1: Worst quality       100: Best quality         3<0000-"capability_videoin_c<0~(n-1)				
s<0~(m-1)>_h       20000~"capability_videoin_c<0~(n-1)		1~100	4/4	
s<0~(m-1)>_h20000~"capability_videoin_c<0~(n-1)	264_qpercent			
s<0~(m-1)>_h20000~"capability_videoin_c<0~(n-1)4/4The maximum allowed bit rate in fixed quality mode. When the bit rate exceeds this value, frames will be dropped to restrict the 				1: Worst quality
s<0~(m-1)>_h ate20000~"capability_videoin_c<0~(n-1) )>_h 264_maxbitrate"4/4The maximum allowed bit rate in fixed quality mode. When the bit rate exceeds this value, frames will be dropped to restrict the bit rate. * Only valid when "ratecontrolmode"= vbrs<0~(m-1)>_h 264_cbr_quant1~5, 1004/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "cbr_qpercent" * Only available when "ratecontrolmode"= cbr. * Only available when "ratecontrolmode"= cbr. * Only available when "ratecontrolmode"= cbr. * Only available when "capability_smartstream_version"=2. 0s<0~(m-1)>_h 264_cbr_qperce nt1~1004/4Select customized quality in a normalized full range. 1: Worst quality 100: Best quality				100: Best quality
s<0~(m-1)>_h       2000~"capability_videoin_c<0~(n-1)				* Only valid when "ratecontrolmode"=
264_maxvbrbitr       )>_h264_maxbitrate"       quality mode.         ate       When the bit rate exceeds this value, frames will be dropped to restrict the bit rate.       * Only valid when "ratecontrolmode"= vbr         s<0~(m-1)>_h       1~5, 100       4/4       Set the pre-defined quality level:         264_cbr_quant       1~5, 100       4/4       Set the pre-defined quality level:         264_cbr_quant       1~5, 100       4/4       Set the pre-defined quality level:         1: Medium       2: Standard       3: Good       4: Detailed         5: Excellent       100: Use the quality level in       "cbr_qpercent"         * Only available when       "ratecontrolmode"= cbr.       * Only available when         * capability_smartstream_version"=2.       0       0         s<0~(m-1)>_h       1~100       4/4       Select customized quality in a normalized full range.				vbr and "quant"= 100.
ateWhen the bit rate exceeds this value, frames will be dropped to restrict the bit rate.s<0~(m-1)>_h1~5, 1004/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "cbr_apercent"s<0~(m-1)>_h1~1004/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "cbr_apercent"s<0~(m-1)>_h1~1004/4Set customized quality in a normalized full range. 1: Worst quality 100: Best quality	s<0~(m-1)>_h	20000~"capability_videoin_c<0~(n-1	4/4	The maximum allowed bit rate in fixed
s<0~(m-1)>_h1~5, 1004/4frames will be dropped to restrict the bit rate.264_cbr_quant1~5, 1004/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "cbr_qpercent"s<0~(m-1)>_h1~1004/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "cbr_qpercent"s<0~(m-1)>_h1~1004/4Select customized quality in a normalized full range. 1: Worst quality 100: Best quality	264_maxvbrbitr	)>_h264_maxbitrate"		quality mode.
s<0~(m-1)>_h       1~5, 100       4/4       Set the pre-defined quality level:         264_cbr_quant       1~5, 100       4/4       Set the pre-defined quality level:         264_cbr_quant       1~5, 100       4/4       Set the pre-defined quality level:         264_cbr_quant       1~5, 100       4/4       Set the pre-defined quality level:         264_cbr_quant       1~5, 100       4/4       Set the pre-defined quality level:         1: Medium       2: Standard       3: Good       4: Detailed         5: Excellent       100: Use the quality level in       "cbr_qpercent"         * Only available when       "ratecontroimode"= cbr.       * Only available when         "ratecontroimode"= cbr.       * Only available when       "capability_smartstream_version"=2.         0       0       4/4       Select customized quality in a normalized full range.         nt       1: Worst quality       100: Best quality	ate			When the bit rate exceeds this value,
s<0~(m-1)>_h 264_cbr_quant1~5, 1004/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "cbr_qpercent"s<0~(m-1)>_h 264_cbr_qperce nt1~1004/4Select customized quality in a normalized full range. 1: Worst quality 100: Best quality				frames will be dropped to restrict the
Image: score (m-1)>_h1~5, 1004/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "cbr_qpercent"score (m-1)>_h1~1004/4Select customized quality in a normalized full range. 1: Worst quality 100: Best quality 100: Best quality				bit rate.
Image: score (m-1)>_h1~5, 1004/4Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "cbr_qpercent"score (m-1)>_h1~1004/4Select customized quality in a normalized full range. 1: Worst quality 100: Best quality 100: Best quality				* Only valid when "rates on training do"-
s<0~(m-1)>_h       1~5, 100       4/4       Set the pre-defined quality level:         264_cbr_quant       1: Medium       2: Standard         3: Good       3: Good       4: Detailed         5: Excellent       100: Use the quality level in       "cbr_qpercent"         * Only available when       "ratecontrolmode"= cbr.       * Only available when         "capability_smartstream_version"=2.       0       0         s<0~(m-1)>_h       1~100       4/4       Select customized quality in a         1c4_cbr_qperce       1~100       4/4       Select customized full range.         1: Worst quality       100: Best quality       100: Best quality				
264_cbr_quant1: Medium264_cbr_quant1: Medium2: Standard2: Good4: Detailed5: Excellent100: Use the quality level in "cbr_qpercent"* Only available when "ratecontrolmode" = cbr. * Only available when "capability_smartstream_version"=2. 0s<0~(m-1)>_h1~100264_cbr_qperce nt1~1004/4Select customized quality in a normalized full range. 1: Worst quality 100: Best quality 100: Best quality	$c < 0 \sim (m-1) > h$	1.5.100	1/1	
s<0~(m-1)>_h       1~100       4/4       Select customized quality in a normalized full range.         nt       1~100       4/4       Select quality		1.05, 100	4/4	
s<0~(m-1)>_h nt1~1004/4Select customized quality in a normalized full range. 1: Worst quality 10: Best quality 10: Best quality				
s<0~(m-1)>_h1~1004/4Select customized quality in a normalized full range. 1: Worst quality 100: Best quality				
s<0~(m-1)>_h1~1004/4Select customized quality in a normalized full range. 1: Worst quality 100: Best quality				
s<0~(m-1)>_h1~100nt1~1001~1004/41~1004/41~1001.1.1001.1.1001.1.1001.1.1001.1.1001.1.1001.1.1001.1.1001.1.1001.1.1001.1.1001.1.1001.1.1001.1.1001.1.1001.1.1001.1.1.100				
s<0~(m-1)>_h therefore1~1004/4Select customized quality in a normalized full range. 1: Worst quality 100: Best quality				
* Only available when "ratecontrolmode" = cbr. * Only available when "capability_smartstream_version" = 2. 0 s<0~(m-1)>_h 264_cbr_qperce nt 1~100 4/4 Select customized quality in a normalized full range. 1: Worst quality 100: Best quality				
s<0~(m-1)>_h       1~100       4/4       Select customized quality in a normalized full range.         nt       1: Worst quality       1: Worst quality				cbi_qpercent
s<0~(m-1)>_h       1~100       4/4       Select customized quality in a normalized full range.         nt       1: Worst quality       1: Worst quality				* Only available when
s<0~(m-1)>_h       1~100       4/4       Select customized quality in a normalized full range.         nt       1.: Worst quality       1: Worst quality         100: Best quality       100: Best quality				"ratecontrolmode"= cbr.
s<0~(m-1)>_h       1~100       4/4       Select customized quality in a normalized full range.         nt       1.: Worst quality       1: Worst quality         100: Best quality       100: Best quality				* Only available when
Image: s<0~(m-1)>_h1~1004/4Select customized quality in a normalized full range.264_cbr_qperce11.1001.100nt1.1001.1001.1001.100100: Best quality1.1001.1001.100				
264_cbr_qperce       normalized full range.         nt       1: Worst quality         100: Best quality				
nt 1: Worst quality 100: Best quality	s<0~(m-1)>_h	1~100	4/4	Select customized quality in a
100: Best quality	264_cbr_qperce			normalized full range.
	nt			1: Worst quality
* Only valid when "ratecontrolmode"=				
* Only valid when "ratecontrolmode"=				
				* Only valid when "ratecontrolmode"=

		1	
			cbr and "quant"= 100.
			* Only available when
			"capability_smartstream_version"=2.
			0
s<0~(m-1)>_h	20000~"capability_videoin_c<0~(n-1	4/4	The target bit rate in constant bit rate
264_bitrate	)>_h264_maxbitrate"		mode.
			* Only valid when "ratecontrolmode"=
			cbr
s<0~(m-1)>_h	framerate, imagequality	4/4	Set prioritypolicy
264_prioritypoli			
су			* Only valid when "ratecontrolmode"=
			cbr
s<0~(m-1)>_h	1~"capability_videoin_c<0~(n-1)>_h	1/4	The maximum frame rates of a H264
264_maxframe	264 maxframerate"	,	stream at different
_	—		resolutions("capability_videoin_c<0~
			(n-1)>_resolution") are recorded in
			"capability_videoin_c<0~(n-1)>_h26
			4_maxframerate"
s<0~(m-1)>_h	0~2	1/4	Indicate H264 profiles
264_profile		1/1	0: baseline
204_prome			1: main profile
			2: high profile
s<0~(m-1)>_h	<boolean></boolean>	4/4	Enable "Dynamic intra frame period".
		4/4	* Only available when
265_dintraperio			
d_enable			"capability_videoin_c<0~(n-1)>_dint
			raperiod_support" is 1 and h265 is
			listed in "capability_videoin_codec".
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0301c.
s<0~(m-1)>_h	250, 500, 1000, 2000, 3000, 4000	4/4	The time interval between two
265_intraperiod			I-frames (Intra coded picture).
			The unit is millisecond (ms).
			* Only available when h265 is listed in
			"capability_videoin_codec".
s<0~(m-1)>_h	cbr, vbr	4/4	<b>cbr</b> : Constant bit rate mode.
265_ratecontrol			<b>vbr</b> : Fixed quality mode, all frames are
mode			encoded in the same quality.

			* Only available when h265 is listed in
			"capability_videoin_codec".
s<0~(m-1)>_h	1~5,	4/4	Set the pre-defined quality level:
265_quant	99, 100		1: Medium
			2: Standard
			3: Good
			4: Detailed
			5: Excellent
			100: Use the quality level in
			"qpercent"
			99: Use the quality level in "qvalue"
			* Only available when h265 is listed in
			"capability_videoin_codec" and
			"ratecontrolmode"= vbr.
s<0~(m-1)>_h	0~51	4/4	Manual video quality level input. The Q
265_qvalue			value which is used by encoded library
			directly.
			* Only available when h265 is listed in
			"capability_videoin_codec".
			* Only valid when "ratecontrolmode"=
			vbr and $s<0~(m-1)>_h265_quant =$
			99.
s<0~(m-1)>_h	1~100	4/4	Select customized quality in a
265_qpercent			normalized full range.
			1: Worst quality
			100: Best quality
			* Only available when h265 is listed in
			"capability_videoin_codec".
			* Only valid when "ratecontrolmode"=
			vbr and "quant"= 100.
s<0~(m-1)>_h	20000~"capability_videoin_c<0~(n-1	4/4	The maximum allowed bit rate in fixed
265_maxvbrbitr	)>_h265_maxbitrate"		quality mode.
ate			When the bit rate exceeds this value,
			frames will be dropped to restrict the
			bit rate.
L	l	l	

s<0~(m-1)>_h1~1004/4Set the quality level in "capability_videoin_codec". * Only valid when habes is listed in "capability_videoin_codec". * Only valid when "ratecontrolmode"= vbr265_cbr_quant1~5, 1004/4Set the pre-defined quality level: 1.1 Medium 2.1 Standard 3.1 Good 4.1 Detailed 5.1 Excellent 1.00: Use the quality level in "cbr_gpercent"265_cbr_quant1~1004/4Set the quality level in "cbr_gpercent"265_cbr_quant1~1004/4Set the quality level in "cbr_gpercent"s<0~(m-1)>_h1~1004/4Select customized quality in a normalized full range. 1.1 Worst quality 100: Best quality 100: Best quality 100: Best quality 100: Best qualitys<0~(m-1)>_h2000~'capability_videoin_c<0~(n-n) >_h4/4Select customized quality in a normalized full range. 1.1 Worst quality 100: Best quality 100: Bes				
265_cbr_quant1: Medium265_cbr_quant1: Medium265_cbr_quant1: Medium265_cbr_qpercent1: Medium265_cbr_qpercent1: Detailed265_cbr_qpercent* Only available when h265 is listed in "capability_videoin_codec" and "retecontroimode"= cbr. * Only available when "capability_martstream_version"="2" o"260~(m-1)>_h1~1004/4Select customized quality in a normalized full range. 1: Worst quality 100: Best quality * Only available when h265 is listed in "capability_videoin_codec". * Only available when h265 is listed in "capability_videoin_codec". * Only available when h265 is listed in "capability_videoin_codec". * Only available when "capability_videoin_codec". * Only available when h265 is listed in "capability_wideoin_codec". * Only available when h265 is listed in "capability_videoin_codec". * Only availa				"capability_videoin_codec". * Only valid when "ratecontrolmode"=
<ul> <li>Scov(m-1)&gt;_h</li> <li>20000~"capability_videoin_c&lt;0~(n-1)</li> <li>20000~(n-1)</li> <li>20000~(n-1)</li> <li>20000~(n-1)</li> <li>20000~(n-1)</li></ul>	s<0~(m-1)>_h	1~5, 100	4/4	Set the pre-defined quality level:
s<0~(m-1)>_h 21~1004/4Select customized quality in a normalized full range. 1: Worst quality 	265_cbr_quant			1: Medium
s<0~(m-1)>_h1~1004/4Select customized quality in a normalized full range. 1: Worst quality 100: Best quality 				2: Standard
S: Excellent 100: Use the quality level in "cbr_qpercent"* Only available when h265 is listed in "capability_videoin_codec" and "ratecontrolmode" = cbr. * Only available when "capability_smartstream_version"="2 .0"\$<0~(m-1)>_h 265_cbr_qperce nt1~1004/4\$elect customized quality in a normalized full range. 1: Worst quality 100: Best quality 100: Best quality 100: Best quality * Only available when h265 is listed in "capability_videoin_codec". * Only available when "capability_wideoin_codec". * Only available when "capability_wideoin_codec". * Only available when "capability_wideoin_codec". * Only available when "capability_wideoin_codec". * Only available when h265 is listed in "capability_wideoin_codec". * Only				3: Good
s<0~(m-1)>_h 265_bitrate1~1004/4100: Use the quality level in "cbr_qpercent"s<0~(m-1)>_h 265_cbr_qperce nt1~1004/4Select customized quality in a normalized full range. 1: Worst quality 100: Best quality 100: Be				4: Detailed
s<0~(m-1)>_h 265_cbr_qperce1~1004/4Select customized quality in a normalized full range. 1: Worst quality 100: Best quality 100: Best quality 100: Best quality 100: Best quality * Only available when "rcapability_videoin_codec". * Only available when pace is listed in "capability_videoin_codec". * Only available when pace is listed in "capability_videoin_codec". * Only available when "rcapability_smartstream_version"="2">-0"s<0~(m-1)>_h 265_cbr_qperce nt1~1004/4Select customized quality in a normalized full range. 1: Worst quality 100: Best quality * Only available when h265 is listed in "capability_videoin_codec". * Only valiable when "ratecontrolmode"= cbr and "quant"= 100. * Only available when * Only available when h265 is listed in "capability_smartstream_version"="2">-0"s<0~(m-1)>_h20000~"capability_videoin_c<0~(n-1) > h265_maxbitrate"4/4The target bit rate in constant bit rate mode. * Only available when h265 is listed in "capability_videoin_codec". * Only available when "ratecontrolmode"= cbr				5: Excellent
* Only available when h265 is listed in "capability_videoin_codec" and "ratecontrolmode"= cbr. * Only available when "capability_smartstream_version"="2 .0"\$<0~(m-1)>_h 265_cbr_qperce nt1~1004/4Select customized quality in a normalized full range. 1: Worst quality 100: Best quality 100: Best quality * Only available when h265 is listed in "capability_videoin_codec". * Only available when "ratecontrolmode"= cbr and "quant"= 100. * Only available when "capability_smartstream_version"="2" .0"\$<0~(m-1)>_h 265_maxbitrate"20000~"capability_videoin_c<0~(n-1) .h265_maxbitrate"4/4The target bit rate in constant bit rate mode. * Only available when h265 is listed in "capability_videoin_codec". * Only available when "ratecontrolmode"= cbr				100: Use the quality level in
Image: set of the				"cbr_qpercent"
Image: set of the				
s<0~(m-1)>_h1~1004/4Select customized quality in a normalized full range. 1: Worst quality 100: Best quality 100: Best quality 100: Best quality 100: Best quality * Only available when h265 is listed in "capability_videoin_codec". * Only available when h265 is listed in "capability_smartstream_version"="2" .s<0~(m-1)>_h20000~"capability_videoin_c<0~(n-1) >_h4/4The target bit rate in constant bit rate mode.s<0~(m-1)>_h20000~"capability_videoin_c<0~(n-1) >_h265_maxbitrate"4/4The target bit rate in constant bit rate mode.s<0~(m-1)>_h20000~"capability_videoin_c<0~(n-1) >_h265_maxbitrate"4/4The target bit rate in constant bit rate mode.				* Only available when h265 is listed in
Image: series of the series				"capability_videoin_codec" and
Image: solution of the second secon				"ratecontrolmode"= cbr.
Image: solution in the second secon				* Only available when
s<0~(m-1)>_h       1~100       4/4       Select customized quality in a normalized full range.         nt       1: Worst quality       100: Best quality       100: Best quality         normalized full range.       1: Worst quality       100: Best quality       * Only available when h265 is listed in "capability_videoin_codec".         s<0~(m-1)>_h       20000~"capability_videoin_c<0~(n-1				"capability_smartstream_version"="2
265_cbr_qperce ntnormalized full range.nt1: Worst quality 100: Best quality 100: Best quality * Only available when h265 is listed in "capability_videoin_codec". * Only valid when "ratecontrolmode"= cbr and "quant"= 100. * Only available when "capability_smartstream_version"="2" .0"s<0~(m-1)>_h 265_bitrate20000~"capability_videoin_c<0~(n-1) >_h265_maxbitrate"4/4The target bit rate in constant bit rate mode. * Only available when h265 is listed in "capability_videoin_codec". * Only available when h265 is listed i				.0"
nt nt 1: Worst quality 100: Best quality * Only available when h265 is listed in "capability_videoin_codec". * Only valid when "ratecontrolmode"= cbr and "quart"= 100. * Only available when "capability_smartstream_version"="2 .0" s<0~(m-1)>_h 20000~"capability_videoin_c<0~(n-1 265_bitrate )>_h265_maxbitrate" 4/4 The target bit rate in constant bit rate mode. * Only available when h265 is listed in "capability_videoin_codec". * Only available when h265 is listed in "capability_videoin_codec".	s<0~(m-1)>_h	1~100	4/4	Select customized quality in a
s<0~(m-1)>_h20000~"capability_videoin_c<0~(n-1)	265_cbr_qperce			normalized full range.
S<0~(m-1)>_h 265_bitrate 20000~"capability_videoin_c<0~(n-1) 265_bitrate 20000~"capability_videoin_c<0~(n-1) 265_bitrate 4/4 4/4 7. Nonly available when h265 is listed in "capability_smartstream_version"="2 .0" 7. Nonly available when "capability_smartstream_version"="2 .0" 8. Only available when "capability_smartstream_version"="2 .0" 8. Only available when h265 is listed in "capability_videoin_cc<0~(n-1) 8. Only available when h265 is listed in "capability_videoin_codec". * Only available when h265 is listed in "capability_videoin_codec". * Only available when h265 is listed in "capability_videoin_codec". * Only valid when "ratecontrolmode"= .0	nt			1: Worst quality
s<0~(m-1)>_h 265_bitrate20000~"capability_videoin_c<0~(n-1 )>_h265_maxbitrate"4/4The target bit rate in constant bit rate mode.* Only available when "capability_smartstream_version"="2 .0"* Only available when "capability_smartstream_version"="2 .0"s<0~(m-1)>_h 265_bitrate20000~"capability_videoin_c<0~(n-1 .14/4The target bit rate in constant bit rate mode.265_bitrate>_h265_maxbitrate"* Only available when h265 is listed in "capability_videoin_codec". * Only available when h265 is listed in "capability_videoin_codec". * Only valid when "ratecontrolmode"= cbr				100: Best quality
s<0~(m-1)>_h 265_bitrate20000~"capability_videoin_c<0~(n-1 )>_h265_maxbitrate"4/4The target bit rate in constant bit rate mode.* Only available when "capability_smartstream_version"="2 .0"* Only available when "capability_smartstream_version"="2 .0"s<0~(m-1)>_h 265_bitrate20000~"capability_videoin_c<0~(n-1 .14/4The target bit rate in constant bit rate mode.265_bitrate>_h265_maxbitrate"* Only available when h265 is listed in "capability_videoin_codec". * Only available when h265 is listed in "capability_videoin_codec". * Only valid when "ratecontrolmode"= cbr				
<pre>* Only valid when "ratecontrolmode"= cbr and "quant"= 100. * Only available when "capability_smartstream_version"="2 .0"  \$&lt;0~(m-1)&gt;_h 20000~"capability_videoin_c&lt;0~(n-1) 265_bitrate )&gt;_h265_maxbitrate" 4/4 The target bit rate in constant bit rate mode. * Only available when h265 is listed in "capability_videoin_codec". * Only available when "ratecontrolmode"= cbr</pre>				* Only available when h265 is listed in
cbr and "quant"= 100. * Only available when "capability_smartstream_version"="2 .0"s<0~(m-1)>_h 265_bitrate20000~"capability_videoin_c<0~(n-1) )>_h265_maxbitrate"4/4The target bit rate in constant bit rate mode.* Only available when h265 is listed in "capability_videoin_codec". * Only available when h265 is listed in "capability_videoin_codec". * Only valid when "ratecontrolmode"= cbr				"capability_videoin_codec".
<pre>* Only available when "capability_smartstream_version"="2 .0"</pre> \$<0~(m-1)>_h 20000~"capability_videoin_c<0~(n-1 )>_h265_maxbitrate"    4/4 The target bit rate in constant bit rate mode.   * Only available when h265 is listed in "capability_videoin_codec".   * Only available when h265 is listed in "capability_videoin_codec".   * Only valid when "ratecontrolmode"= cbr				* Only valid when "ratecontrolmode"=
s<0~(m-1)>_h       20000~"capability_videoin_c<0~(n-1)				cbr and "quant"= 100.
s<0~(m-1)>_h       20000~"capability_videoin_c<0~(n-1				* Only available when
s<0~(m-1)>_h 20000~"capability_videoin_c<0~(n-1 4/4 The target bit rate in constant bit rate 265_bitrate )>_h265_maxbitrate" * Only available when h265 is listed in "capability_videoin_codec". * Only valid when "ratecontrolmode"= cbr				"capability_smartstream_version"="2
265_bitrate )>_h265_maxbitrate" mode. * Only available when h265 is listed in "capability_videoin_codec". * Only valid when "ratecontrolmode"= cbr				.0"
* Only available when h265 is listed in "capability_videoin_codec". * Only valid when "ratecontrolmode"= cbr	s<0~(m-1)>_h	20000~"capability_videoin_c<0~(n-1	4/4	The target bit rate in constant bit rate
"capability_videoin_codec". * Only valid when "ratecontrolmode"= cbr	265_bitrate	)>_h265_maxbitrate"		mode.
"capability_videoin_codec". * Only valid when "ratecontrolmode"= cbr				
* Only valid when "ratecontrolmode"= cbr				* Only available when h265 is listed in
cbr				"capability_videoin_codec".
				* Only valid when "ratecontrolmode"=
$s<0~(m-1)>_h$ framerate, image quality 4/4 Set priority policy				cbr
	s<0~(m-1)>_h	framerate, imagequality	4/4	Set prioritypolicy

cy* Only available when h265 is listed in "capability_videoin_codec". * Only valid when "ratecontrolmode"= cbrs<0~(m-1)>_h 265_maxframe1~"capability_videoin_c<0~(n-1)>_h 265_maxframerate"1/4The maximum frame rates of a H265 stream at different resolutions("capability_videoin_c<0~ (n-1)>_resolution") are recorded in "capability_videoin_c<0~(n-1)>_h26 5_maxframerate"s<0~(m-1)>_h 265_profile0~21/4Indicate H265 profiles 0: baseline 1: main profile 2: high profiles<0~(m-1)>_m jpeg_ratecontro Imodecbr, vbr4/4cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_m jpeg_quant1~5, 99, 1004/4* Only available when "ratecontrolmode"= vbr: Set the pre-defined quality level in "generent" 99: 100s<0~(m-1)>_m jpeg_qvalue10~200 (Only valid when "capability_video quality level in "generent" 99: Use the quality level in "qualue" 99: Use the quality level in "qualue" yale which is used by encoded library qirectly.	265_prioritypoli			
sc0~(m-1)>_h1~"capability_videoin_cc<0~(n-1)>_h1/4"capability_videoin_ccdo~(n-1)>_h265_maxframe1~"capability_videoin_cc<0~(n-1)>_h1/4The maximum frame rates of a H265 stream at different resolution("capability_videoin_cc<0~ (n-1)>_resolution") are recorded in "capability_videoin_cc<0~(n-1)>_h26 S_maxframerate"sc0~(m-1)>_h0~21/4Indicate H265 profiles 0: baseline 1: main profile 2: high profile265_profile0~21/4Indicate H265 profiles 0: baseline 1: main profile 2: high profilesc0~(m-1)>_mcbr, vbr4/4Cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.sc0~(m-1)>_m1~5,99, 1004/4* Only valid when "ratecontrolmode"= vbr. Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qapacent" 99: Use the quality level in "qapace" 99: Use the quality level in "qapace" 99: Use the quality level in "qapace" 99: Use the quality level in "qapace"sc0~(m-1)>_m10~200 (Only valid when "capability_api_httpversion" format is4/4Manual video quality level in Teq value which is used by encoded library directty.				* Only available when h265 is listed in
s<0~(m-1)>_h 265_maxframerate"1~"capability_videoin_c<0~(n-1)>_h 265_maxframerate"1/4"The maximum frame rates of a H265 stream at different resolutions("capability_videoin_c<0~ (n-1)>_resolution") are recorded in "capability_videoin_c<0~(n-1)>_h26 5_maxframerate"1/4The maximum frame rates of a H265 stream at different resolutions("capability_videoin_c<0~ (n-1)>_resolution") are recorded in "capability_videoin_c<0~(n-1)>_h26 5_maxframerate"1/4Indicate H265 profiles265_profile0~21/4Indicate H265 profiles 0: baseline 1: main profile 2: high profile0: baseline 1: main profile 2: high profile260~(m-1)>_mcbr, vbr4/4Cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_m1~5,99, 1004/4* Only available when "ratecontrolmode"= vbr: Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qaperent" 99: Use the quality level in "qapuer"s<0~(m-1)>_m10~200 (Only valid when "capability_api_httpversion" format is4/4* Only value winch is used by encoded library directly.	Cy			
Image: score (m-1)>_h1~"capability_videoin_c<0~(n-1)>_h1/4The maximum frame rates of a H265 stream at different resolutions("capability_videoin_c<0~ (n-1)>_resolution") are recorded in "capability_videoin_c<0~ (n-1)>_resolution") are recorded in "capability_videoin_c<0~ (n-1)>_resolution") are recorded in "capability_videoin_c<0~ (n-1)>_h26 5_maxframerate"\$<0~(m-1)>_h0~21/4Indicate H265 profile 0: baseline 1: main profile 2: high profile\$<0~(m-1)>_mcbr, vbr4/4cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.\$<0~(m-1)>_m1~5,99, 1004/4* Only validowen "ratecontrolmode"= vbr: Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qualue"\$<0~(m-1)>_m10~200 (Only valid when "capability_wide on cuality level in "qualue"4/4Manual video quality level in "qualue"\$<0~(m-1)>_m10~200 (Only valid when "capability_api_httpversion" format is4/4Manual video quality level in "qualue"				
s<0~(m-1)>_h       1~"capability_videoin_c<0~(n-1)>_h       1/4       The maximum frame rates of a H265         265_maxframe       265_maxframerate"       1/4       The maximum frame rates of a H265         265_maxframe       265_maxframerate"       1/4       The maximum frame rates of a H265         265_maxframerate       265_maxframerate"       * Conspability_videoin_c<0~(n-1)>_h26         5 <maxframerate< td="">       * Only available when h265 is listed in "capability_videoin_cc40~(n-1)&gt;_h26         5<maxframerate< td="">       * Only available when h265 is listed in "capability_videoin_cc40c".         265_profile       0~2       1/4       Indicate H265 profile         265_profile       0~2       1/4       Indicate H265 is listed in "capability_videoin_cc40c".         2s(0~(m-1)&gt;_m)       cbr, vbr       4/4       Cbr: Constant bit rate mode.         ybg_ratecontrol       whore       4/4       Cbr: Constant bit rate mode.         ybg_quant       99, 100       4/4       * Only vaild when "ratecontrolmode"= vbr.         ScO~(m-1)&gt;_m       1~5,       99, 100       4/4       * Only valid when "ratecontrolmode"= vbr.         Sco_(m-1)&gt;_m       100.00       4/4       * Only valid when "ratecontrolmode"= vbr.         Sco_(m-1)&gt;_m       10~200       4/4       * Only valid when "ratecontrolmode" in value"         &lt;</maxframerate<></maxframerate<>				
265_maxframe265_maxframerate"stream at different resolution") are recorded in "capability_videoin_c<0~ (n-1)>_resolution") are recorded in "capability_videoin_c<0~ (n-1)>_resolution") are recorded in "capability_videoin_c<0~ (n-1)>_h26 5_maxframerate"s<0~(m-1)>_h0~21/4Indicate H265 profiles 0: baseline 1: main profile 2: high profile265_profile0~21/4Indicate H265 profiles 0: baseline 1: main profile 2: high profile * Only available when h265 is listed in "capability_videoin_codec".s<0~(m-1)>_mcbr, vbr4/4cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_m1~5,99, 1004/4* Only valid when "ratecontrolmode"= vbr. Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qapercent" 99: Use the quality level in "qapercent" 99: Use the quality level in "qvalue"s<0~(m-1)>_m10~200 (Only valid when "capability_aide on many size on the same quality level in "que which is used by encoded library "capability_ain_httpversion" format is	$a < 0 \cdot (m + 1) > b$	$1 \cdot (a - b)$	1/4	
s<0~(m-1)>_m ipeg_ratecontrol0~21/4Indicate H265 profiles 0: baseline 1: main profile 2: high profiles<0~(m-1)>_m output0~21/4Indicate H265 profiles 0: baseline 1: main profile 2: high profiles<0~(m-1)>_m ipeg_ratecontrolcbr, vbr4/4cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_m ipeg_quant1~5, 99, 1004/4cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_m ipeg_quant1~5, 99, 1004/4* Only valid when "ratecontrolmode"= vbr: Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qapacent" 99: Use the quality level in "qapace"s<0~(m-1)>_m ipeg_quant10~200 (Only valid when "capability_aip_inttpversion" format is4/4Manual video quality level in "qauler"			1/4	
s<0~(m-1)>_m jpeg_quant0~21/4(n-1)>_resolution") are recorded in "capability_videoin_c<0~(n-1)>_h26 5_maxframerate" * Only available when h265 is listed in "capability_videoin_codec".s<0~(m-1)>_h 265_profile0~21/4Indicate H265 profiles 0: baseline 1: main profile 2: high profile * Only available when h265 is listed in "capability_videoin_codec".s<0~(m-1)>_m jpeg_ratecontro Imodecbr, vbr4/4cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_m jpeg_quant1~5, 99, 1004/4* Only available when "ratecontrolmode"= vbr: Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in mingerent" 99: Use the quality level in "qapatility 2: Use the quality level in "qapatility level in mingerent" 99: Use the quality level in "qapatility level in "capability_api_httpversion" format is4/4Manual video quality level input. The Q value which is used by encoded library directly.	205_maxirame			
s<0~(m-1)>_h 265_profile0~21/4Indicate H265 profiles 0: baseline 1: main profile 2: high profiles<0~(m-1)>_h 265_profile0~21/4Indicate H265 profiles 0: baseline 1: main profile 2: high profiles<0~(m-1)>_m jpeg_ratecontro Imodecbr, vbr4/4cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_m jpeg_quant1~5, 99, 1004/4* Only validable when "ratecontrolmode"= vbr.s<0~(m-1)>_m jpeg_quant1~5, 99, 1004/4* Only valid when "ratecontrolmode"= vbr.s<0~(m-1)>_m jpeg_quant10~200 (Only valid when4/4* Only valid when "ratecontrolmode"= vbr.s<0~(m-1)>_m jpeg_quant10~200 (Only valid when* 0* Only valid when "ratecontrolmode"= vbr.s<0~(m-1)>_m ipeg_quant10~200 (Only valid when* 0* 0s<0~(m-1)>_m ipeg_quant10~200 (Only valid when* 0s				
S<0~(m-1)>_h 265_profile0~21/4Indicate H265 profiles 0: baseline 1: main profile 2: high profile265_profile0~21/4Indicate H265 profiles 0: baseline 1: main profile 2: high profile * Only available when h265 is listed in "capability_videoin_codec".s<0~(m-1)>_m jpeg_ratecontro Imodecbr, vbr4/4cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_m jpeg_quant1~5,99, 1004/4* Only available when h265 is trade and the same quality.s<0~(m-1)>_m jpeg_quant1~5,99, 1004/4* Only available when h265 is trade and the same quality.s<0~(m-1)>_m jpeg_quant1~5,99, 1003< Good 4: Detailed 3: Good 4: Detailed 3: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qpercent" 99: Use the quality level in "qpercent" 99: Use the quality level in "qalue"s<0~(m-1)>_m jpeg_qvalue10~200 (Only valid when "capability_api_httpversion" format is4/4Manual video quality level input. The Q value which is used by encoded library directly.				
s<0~(m-1)>_h 265_profile0~21/4Indicate H265 profiles 0: baseline 1: main profile 2: high profile265_profile0~21/4Indicate H265 profiles 0: baseline 1: main profile 2: high profiles<0~(m-1)>_m ipeg_ratecontro lmodecbr; vbr4/4cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_m jpeg_quant1~5,99, 1004/4* Only available when h265 is is listed in "capability_videoin_codec".s<0~(m-1)>_m jpeg_quant1~5,99, 1004/4* Only valid when "ratecontrol vbr. Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qatue"s<0~(m-1)>_m jpeg_qvalue10~200 (Only valid when "capability_api_httpversion" format is4/4Manual video quality level in unique quicetty.				
s<0~(m-1)>_h 265_profile0~21/4Indicate H265 profiles 0: baseline 1: main profile 2: high profile * Only available when h265 is listed in "capability_videoin_codec".s<0~(m-1)>_m jpeg_ratecontro lmodecbr, vbr4/4cbr: Constant bit rate mode. vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_m jpeg_quant1~5,4/4* Only available when "ratecontrolmode"= vbr: Fixed quality mode, all frames are encoded in the same quality.s<0~(m-1)>_m jpeg_quant1~5,4/4* Only valid when "ratecontrolmode"= vbr. Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qpercent" 99: Use the quality level in "qpercent" 99: Use the quality level in "qualee"s<0~(m-1)>_m jpeg_qvalue10~200 (Only valid when "capability_api_httpversion" format is4/4Manual video quality level input. The Q value which is used by encoded library directly.				5_maxframerate"
s<0~(m-1)>_h       0~2       1/4       Indicate H265 profiles         265_profile       0~2       1/4       Indicate H265 profiles         265_profile       0       baseline       1: main profile         2: high profile       2: high profile       1: main profile         2: high profile       * Only available when h265 is listed in "capability_videoin_codec".         s<0~(m-1)>_m       cbr. vbr       4/4       cbr: Constant bit rate mode.         imode       1~5,       4/4       * Only valid when "ratecontrolmode"= vbr.         jpeg_quant       99, 100       4/4       * Only valid when "ratecontrolmode"= vbr.         Set the pre-defined quality level:       1: Medium       2: Standard         3: Good       4: Detailed       5: Excellent         100: Use the quality level in "qualue"       * gercent"       99: Use the quality level in "qualue"         s<0~(m-1)>_m       10~200       4/4       Manual video quality level in "qualue"         s<0~(m-1)>_m       10~200       4/4       Manual video quality level in "qualue"				* Only available when h265 is listed in
265_profile       0: baseline         265_profile       0: baseline         1: main profile       1: main profile         2: high profile       * Only available when h265 is listed in "capability_videoin_codec".         s<0~(m-1)>_m       cbr, vbr         jpeg_ratecontro       4/4         Imode       1~5,         99, 100       4/4         * Only valid when "ratecontrolonde"=         vbr:       Set the pre-defined quality level:         1: Medium       2: Standard         3: Good       4: Detailed         5: Excellent       100: Use the quality level in "qualue"         s<0~(m-1)>_m       10~200         (Only valid when       4/4         Manual video quality level in "qvalue"         s<0~(m-1)>_m       10~200         (Only valid when       4/4				"capability_videoin_codec".
Image: Constant of the second secon	s<0~(m-1)>_h	0~2	1/4	Indicate H265 profiles
2: high profile\$<0~(m-1)>_mcbr, vbrjpeg_ratecontrocbr, vbrimode4/4\$<0n(m-1)>_m1~5,99, 100\$<0~(m-1)>_m1~5,99, 1004/4* Only valid when "ratecontrolmode"= vbr.ybrSet the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qvalue"\$<0~(m-1)>_m10~200 (Only valid when "capability_api_httpversion" format is	265_profile			0: baseline
s<0~(m-1)>_m       cbr, vbr       4/4       cbr: Constant bit rate mode.         jpeg_ratecontro       imode       vbr: Fixed quality mode, all frames are encoded in the same quality.         s<0~(m-1)>_m       1~5,       4/4       * Only valid when "ratecontrolmode"=         jpeg_quant       99, 100       4/4       * Only valid when "ratecontrolmode"=         ybr: Fixed quality mode, all frames are encoded in the same quality.       set the pre-defined quality level:         1: Medium       2: Standard       3: Good         4: Detailed       5: Excellent       100: Use the quality level in "qpercent"         s<0~(m-1)>_m       10~200       4/4       Manual video quality level in unitation quality level in u				1: main profile
Image: score (m-1)>_m jpeg_ratecontro lmodecbr, vbr4/4"capability_videoin_codec".s<0~(m-1)>_m jpeg_quant1~5,4/4* Only valid when "ratecontrolmode"= vbr.good (m-1)>_m peg_quant1~5,4/4* Only valid when "ratecontrolmode"= vbr.s<0~(m-1)>_m peg_quant1~5,4/4* Only valid when "ratecontrolmode"= vbr.s<0~(m-1)>_m peg_quant1~5,4/4* Only valid when "ratecontrolmode"= vbr.s<0~(m-1)>_m peg_quant1~5,99, 100100s<0~(m-1)>_m peg_quant10~200 (Only valid when4/4* Only valid when "ratecontrolmode"= vbr.s<0~(m-1)>_m peg_qvalue10~200 (Only valid when "capability_api_httpversion" format is4/4Manual video quality level in my qualues<0~(m-1)>_m (only valid when "capability_api_httpversion" format is4/4Manual video quality level in my qualue				2: high profile
Image: score (m-1)>_m jpeg_ratecontro lmodecbr, vbr4/4"capability_videoin_codec".s<0~(m-1)>_m jpeg_quant1~5,4/4* Only valid when "ratecontrolmode"= vbr.good (m-1)>_m peg_quant1~5,4/4* Only valid when "ratecontrolmode"= vbr.s<0~(m-1)>_m peg_quant1~5,4/4* Only valid when "ratecontrolmode"= vbr.s<0~(m-1)>_m peg_quant1~5,4/4* Only valid when "ratecontrolmode"= vbr.s<0~(m-1)>_m peg_quant1~5,99, 100100s<0~(m-1)>_m peg_quant10~200 (Only valid when4/4* Only valid when "ratecontrolmode"= vbr.s<0~(m-1)>_m peg_qvalue10~200 (Only valid when "capability_api_httpversion" format is4/4Manual video quality level in my qualues<0~(m-1)>_m (only valid when "capability_api_httpversion" format is4/4Manual video quality level in my qualue				* Only available when h265 is listed in
s<0~(m-1)>_m       cbr, vbr       4/4       cbr: Constant bit rate mode.         jpeg_ratecontro       lmode       vbr: Fixed quality mode, all frames are encoded in the same quality.         s<0~(m-1)>_m       1~5,       4/4       * Only valid when "ratecontrolmode"=         jpeg_quant       99, 100       4/4       * Only valid when "ratecontrolmode"=         vbr:       Set the pre-defined quality level:       1: Medium         2: Standard       3: Good       4: Detailed         5: Excellent       100: Use the quality level in       "qpercent"         jpeg_qvalue       10~200       4/4       Manual video quality level in gvalue"         s<0~(m-1)>_m       10~200       4/4       Manual video quality level in uput. The Q         value which is used by encoded library       "capability_api_httpversion" format is       4/4       Manual video quality level input. The Q				
jpeg_ratecontro Imode1~5,4/4* Only valid when "ratecontroImode"= vbr.jpeg_quant99, 1004/4* Only valid when "ratecontroImode"= vbr.s<0~(m-1)>_m ipeg_quant99, 1004/4* Only valid when "ratecontroImode"= vbr.Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qualue"s<0~(m-1)>_m jpeg_qvalue10~200 (Only valid when "capability_api_httpversion" format is4/4Manual video quality level input. The Q value which is used by encoded library directly.	s<0~(m-1)> m	chr yhr	4/4	
Imodeencoded in the same quality.s<0~(m-1)>_m1~5,4/4* Only valid when "ratecontroImode"= vbr.jpeg_quant99, 100vbr.Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qvalue"s<0~(m-1)>_m10~2004/4Manual video quality level input. The Q value which is used by encoded library directly.			- , -	
s<0~(m-1)>_m1~5,4/4* Only valid when "ratecontrolmode"= vbr.jpeg_quant99, 1004/4* Only valid when "ratecontrolmode"= vbr.Set the pre-defined quality level: 1: Medium 2: Standard 3: Good 4: Detailed 5: Excellent 100: Use the quality level in "qpercent" 99: Use the quality level in "qvalue"s<0~(m-1)>_m10~200 (Only valid when "capability_api_httpversion" format is4/4Manual video quality level input. The Q value which is used by encoded library directly.				
jpeg_quant99, 100vbr.Set the pre-defined quality level:1: Medium1: Medium2: Standard2: Standard3: Good3: Good4: Detailed5: Excellent100: Use the quality level in "qpercent"100: Use the quality level in "qoercent"99: Use the quality level in "qvalue"s<0~(m-1)>_m10~2004/4Manual video quality level in urqvalue'capability_api_httpversion'' format is4/4	inioue			cheoded in the same quality.
s<0~(m-1)>_m10~2004/4Manual video quality level in "qpalue"s<0~(m-1)>_m10~2004/4Manual video quality level in "qualue"icapability_api_httpversion" format is4/4Manual video quality level in used by encoded library directly.	s<0~(m-1)>_m	1~5,	4/4	* Only valid when "ratecontrolmode"=
s<0~(m-1)>_m10~2004/4Manual video quality level in "qvalue"s<0~(m-1)>_m10~2004/4Manual video quality level in put. The Qjpeg_qvalue(Only valid when "capability_api_httpversion" format is4/4Manual video quality level input. The Q value which is used by encoded library directly.	jpeg_quant	99, 100		vbr.
s<0~(m-1)>_m10~2004/4Manual video quality level in qvalue"s<0~(m-1)>_m10~2004/4inc4/4Manual video quality level in qvalue"inc <td></td> <td></td> <td></td> <td>Set the pre-defined quality level:</td>				Set the pre-defined quality level:
s<0~(m-1)>_m10~2004/4Manual video quality level in "qvalue"jpeg_qvalue(Only valid when "capability_api_httpversion" format is4/4Manual video quality level input. The Q value which is used by encoded library directly.				1: Medium
s<0~(m-1)>_m10~2004/4Manual video quality level in "qvalue"jpeg_qvalue(Only valid when "capability_api_httpversion" format is4/4Manual video duality level in put. The Q value which is used by encoded library directly.				2: Standard
s<0~(m-1)>_m10~2004/4Manual video quality level in uput. The Qjpeg_qvalue(Only valid whenvalue which is used by encoded library"capability_api_httpversion" format isinterctly.				3: Good
s<0~(m-1)>_m10~2004/4Manual video quality level in "qvalue"jpeg_qvalue(Only valid whenvalue which is used by encoded library"capability_api_httpversion" format isimage: capability_api_httpversionimage: capability_api_httpversion				4: Detailed
s<0~(m-1)>_m10~2004/4Manual video quality level in "qvalue"jpeg_qvalue(Only valid whenvalue which is used by encoded library"capability_api_httpversion" format isimage: directly.				5: Excellent
s<0~(m-1)>_m       10~200       4/4       Manual video quality level in put. The Q         jpeg_qvalue       (Only valid when       value which is used by encoded library         "capability_api_httpversion" format is       directly.				100: Use the quality level in
s<0~(m-1)>_m10~2004/4Manual video quality level input. The Qjpeg_qvalue(Only valid whenvalue which is used by encoded library"capability_api_httpversion" format isdirectly.				"qpercent"
jpeg_qvalue     (Only valid when     value which is used by encoded library       "capability_api_httpversion" format is     directly.				99: Use the quality level in "qvalue"
"capability_api_httpversion" format is directly.	s<0~(m-1)>_m	10~200	4/4	Manual video quality level input. The Q
	jpeg_qvalue	(Only valid when		value which is used by encoded library
		"capability_api_httpversion" format is		directly.
		XXXXX_1 or XXXXX_3		

	ex: 0301a_1 or 0301a_3)		* Only valid when "ratecontrolmode"=
	or 1~99		vbr and s<0~(m-1)>_mjpeg_quant =
	(Only valid when		99
	"capability_api_httpversion" format is		
	XXXXX_2,		
	ex: 0301a_2)		
	<product dependent=""></product>		
s<0~(m-1)>_m	1~100	4/4	Select customized quality in a
jpeg_qpercent			normalized full range.
			1: Worst quality
			100: Best quality
			* Only valid when "ratecontrolmode"=
			vbr and s<0~(m-1)>_mjpeg_quant =
			100.
s<0~(m-1)>_m	20000~"capability_videoin_c<0~(n-1	4/4	The maximum allowed bit rate in fixed
jpeg_maxvbrbit	)>_mjpeg_maxbitrate"		quality mode.
rate			When the bit rate exceeds this value,
			frames will be dropped to restrict the
			bit rate.
			* Only valid when "ratecontrolmode"=
			vbr
s<0~(m-1)>_m	1~5, 100	4/4	Set the pre-defined quality level:
jpeg_cbr_quant			1: Medium
			2: Standard
			3: Good
			4: Detailed
			5: Excellent
			100: Use the quality level in
			"cbr_qpercent"
			* Only available when
			"ratecontrolmode"= cbr.
			* Only available when
			"capability_smartstream_version"="2
			.0"
s<0~(m-1)>_m	1~100	4/4	Select customized quality in a
jpeg_cbr_qperc			normalized full range.
ent			1: Worst quality
	1	I	

			100: Best quality
			100. Best quality
			* Only valid when "ratecontrolmode"=
			cbr and "quant"= 100.
			* Only available when
			"capability_smartstream_version"="2 .0"
		A / A	
s<0~(m-1)>_m	20000~"capability_videoin_c<0~(n-1	4/4	The target bit rate in constant bit rate
jpeg_bitrate	)>_mjpeg_maxbitrate"		mode.
			* Only valid when "rate control mode"
			* Only valid when "ratecontrolmode"=
			cbr
s<0~(m-1)>_m	framerate, imagequality	4/4	Set prioritypolicy
jpeg_prioritypoli			* Only valid when "ratecontrolmode"=
cy			cbr
s<0~(m-1)>_m	1~"capability_videoin_c<0~(n-1)>_	1/4	The maximum frame rates of a mjpeg
jpeg_maxframe	mjpeg_maxframerate"		stream at different
			resolutions("capability_videoin_c<0~
			(n-1)>_resolution") are recorded in
			"capability_videoin_c<0~(n-1)>_mjp
			eg_maxframerate"
s<0~(m-1)>_ra	<boolean></boolean>	1/4	Change resolution to fit 4:3 ratio.
tiocorrect			For PAL:
			D1/4CIF(720/704x576) -> (768x576)
			CIF(352x288)->(384x288)
			For NTSC:
			D1/4CIF(720/704x480) -> (640x480)
			CIF(352x240)->(320x240)
			* Only available when
			capability_videoin_type is 0 or 1.
wdrpro_mode	<boolean></boolean>	4/4	Enable WDR pro
<product< td=""><td></td><td></td><td></td></product<>			
dependent>			* Only available when
			"capability_image_c<0~(n-1)>_wdrp
			ro_mode" > 0
wdrpro_strengt	1~100	4/4	The strength of WDR Pro.
h			The bigger value means the stronger
<product< td=""><td></td><td></td><td>strength of WDR Pro.</td></product<>			strength of WDR Pro.
dependent>			* Only available when

			"capability_image_c<0~(n-1)>_wdrp
			ro_strength" is 1
wdra mada	<boolean></boolean>	4/4	Enable WDR enhanced.
wdrc_mode		4/4	
<product< td=""><td></td><td></td><td>* Only available when</td></product<>			* Only available when
dependent>			<pre>"capability_image_c&lt;0~(n-1)&gt;_wdrc</pre>
			_mode" is 1
wdrc_strength	1~100	4/4	The strength of WDR enhanced.
<product< td=""><td></td><td></td><td>The bigger value means the stronger</td></product<>			The bigger value means the stronger
dependent>			strength of WDR enhanced.
			* Only available when
			"capability_image_c<0~(n-1)>_wdrc
			_mode" is 1
aespeed_mode	<boolean></boolean>	4/4	Turning AE converge speed on or off.
<product< td=""><td></td><td></td><td>0: off</td></product<>			0: off
dependent>			1: on
			* Only available when
			capability_image_c<0~(n-1)>_aesp
			eed" is 1
aespeed_speedl	1~100	4/4	The speed level of AE converge speed.
evel		,	1~20: level 1
<product< td=""><td></td><td></td><td>21~40: level 2</td></product<>			21~40: level 2
dependent>			41~60: level 3
			61~80: level 4
			81~100: level 5
			Level $1 \sim 4$ (low $\sim$ high)
			The higher speed level meas shorter
			AE converged time during AE
			executing.
			* Only available when
			"capability_image_c<0~(n-1)>_aesp
			eed" is 1
aespeed_sensiti	1~100	4/4	The sensitivity of AE converge speed.
vity			1~20: level 1
<product< td=""><td></td><td></td><td>21~40: level 2</td></product<>			21~40: level 2
dependent>			41~60: level 3
			61~80: level 4
			81~100: level 5
			Level 1~4(low ~ high)
			The higher sensitivity level meas that

			it is easy to be trigger while scene
			changed.
			* Only available when
			"capability_image_c<0~(n-1)>_aesp
			eed" is 1 and
			"capability_image_c<0~(n-1)>_aesp
			eedsupportsensitivity" is 1.
flickerless	<boolean></boolean>	4/4	Turn on(1) or turn off(0) the flickerless
<product< td=""><td></td><td></td><td>mode</td></product<>			mode
dependent>			* Only available when
			"capability_image_c<0~(n-1)>_flicke
			rless" is 1
mounttype	ceiling, wall, floor	1/6	wall mount: 180° panoramic view
<product< td=""><td></td><td></td><td>ceiling mount: 360° surround view</td></product<>			ceiling mount: 360° surround view
dependent>			without blind spots
			floor mount: 360° surround view
			without blind spots
			* Only available when
			"capability_fisheye" > 0
enablewatermar	0, 1	1/6	0: Not to add watermarks on images
k			1: Add watermarks on images
<product< td=""><td></td><td></td><td></td></product<>			
dependent>			* Only available when
			"capability_fisheye" > 0
s<0~(m-2)>_fi	'10, 1P, 2P, 1R, 4R' for ceiling/floor	1/4	Local dewarp mode.
sheyedewarpmo	mount		"10" is original mode (disable).
de	'10, 1P, 1R, 4R' for wall mount		Supported dewarp mode is different by
<product< td=""><td><product dependent=""></product></td><td></td><td>mount type.</td></product<>	<product dependent=""></product>		mount type.
dependent>			(videoin_c<0~(n-1)>_mounttype)
			Supported mode list could be
			extracted from
			(capability_videoin_c<0~(n-1)>_local
			dewarp_typeceilingmount) and
			(capability_videoin_c<0~(n-1)>_local
			dewarp_typewallmount)
			* Only available when
			"capability_fisheyelocaldewarp_c<0~(
			capability_nvideoin)-1>" > 0

# Group: videoin\_c<0~(n-1)>\_s<0~(m-1)>\_h264\_smartstream2 (capability\_smartstream\_support=1 and capability\_smartstream\_version=2.0)

Group: videoin\_c<0~(n-1)>\_s<0~(m-1)>\_h265\_smartstream2 (capability\_smartstream\_support=1,

capability\_smartstream\_version=2.0 and h265 is listed in "capability\_videoin\_codec")

n denotes the value of "capability\_nvideoin",m denotes the value of " capability\_nmediastream"

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	4/4	Enable or Disable smart codec function
mode	autotracking,manual,hybrid	4/4	Set Smart stream mode
			"autotracking": only available when
			"capability_smartstream_mode_autot
			racking" is 1.
			"manual": only available when
			"capability_smartstream_mode_manu
			al" is 1.
			"hybrid": only available when
			"capability_smartstream_mode_hybri
			d" is 1.
qualitypriority	-5,-4,-3,-2,-1,1,2,3,4,5	4/4	The differential value of Q between the
			regions of interest (ROI) and the areas
			of non-interest (non-ROI) of the
			display image.
			If the value is a positive number, the
			video quality of ROI is better than the
			non-ROI areas. The level is from 1 to
			5. Level 5 is the maximum level of the
			quality difference between the ROI and
			non-ROI areas.
			If the value is a negative number the
			If the value is a negative number, the
			video quality of non-ROI areas is
			better than the ROI. The level is from
			-1 to -5. Level -5 is the maximum level
			of the quality difference between the
			ROI and non-ROI areas.

#### Group: videoin\_c<0~(n-1)>\_s<0~(m-1)>\_h264\_smartstream2\_win\_i<0~(k-1)>

(capability\_smartstream\_support=1, capability\_smartstream\_version=2.0 and

capability\_smartstream\_mode\_manual = 1)

Group: videoin\_c<0~(n-1)>\_s<0~(m-1)>\_h265\_smartstream2\_win\_i<0~(k-1)>

(capability\_smartstream\_support=1, capability\_smartstream\_version=2.0 and h265 is listed in

"capability\_videoin\_codec" and capability\_smartstream\_mode\_manual = 1)

n denotes the value of "capability\_nvideoin",m denotes the value of " capability\_nmediastream",k denotes the value of "capability\_smartstream\_nwindow\_manual".

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	4/4	Enable or disable the window.
home	0~320,0~240	4/4	Left-top corner coordinate of the window.
size	0~320x0~240	4/4	Width and height of the window

#### **7.8.1.1** Alternative video input profiles per channel

In addition to the primary setting of video input, there can be alternative profile video input setting for each channel which might be for different scene of light (daytime or nighttime).

Group: videoin\_c<0~(n-1)>\_profile\_i<0~(m-1)> for n channel profucts and m profile

n denotes the value of "capability\_nvideoin" and m denotes the value of "capability\_nvideoinprofile"

(capability.nvideoinprofile> 0)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	4/4	Enable/disable this profile setting
policy	night,	4/4	The mode which the profile is applied to.
	schedule		
			* Not support "policy=day" anymore when the
			version number (httpversion) is equal or
			greater than 0301a.
begintime	hh:mm	4/4	Begin time of schedule mode.
endtime	hh:mm	4/4	End time of schedule mode.
minexposure	<1~32000>,	4/4	Minimum exposure time
<product dependent=""></product>	<5~32000>,		1~32000 => 1s ~ 1/32000s
	<1~8000>,		5~32000 => 1/5s ~ 1/32000s
	<5~8000>,		1~8000 => 1s ~ 1/8000s
	etc.		5~8000 => 1/5s ~ 1/8000s
			etc.
	* Available value is		
	listed in		* Only available when

		1	
	"capability_image_c		"capability_image_c<0~(n-1)>_exposure_mi
	<0~(n-1)>_exposu		nrange" != "-"
	re_minrange"		* Only valid when "piris_mode"=manual or
			"irismode"=fixed
			* Only available when
			"capability_image_c<0~(n-1)>_exposure_ra
			ngetype" is "twovalues".
maxexposure	<1~32000>,	4/4	Maximum exposure time
<product dependent=""></product>	<5~32000>,		1~32000 => 1s ~ 1/32000s
	<1~8000>,		5~32000 => 1/5s ~ 1/32000s
	<5~8000>,		1~8000 => 1s ~ 1/8000s
	etc.		5~8000 => 1/5s ~ 1/8000s
			etc.
	* Available value is		
	listed in		* This parameter may also restrict image
	"capability_image_c		frame rate from sensor due to sensor
	<0~(n-1)>_exposu		generates a frame per exposure time. Ex: If
	re_maxrange"		this is set to 1/5s $\sim$ 1/8000s and camera takes
			1/5s on the night, then sensor only outputs 5
			frame/s.
			* Only available when
			"capability_image_c<0~(n-1)>_exposure_m
			axrange" != "-"
			* Only valid when "piris_mode"=manual or
			"irismode"=fixed
			* Only available when
			capability_image_c<0~(n-1)>_exposure_ra
			ngetype" is "twovalues".
shuttervalue	<1~32000>,	4/4	Exposure time
<pre><pre>conduct dependent&gt;</pre></pre>	<5~32000>,		$1 \sim 32000 => 1s \sim 1/32000s$
	<1~8000>,		5~32000 => 1/5s ~ 1/32000s
	<5~8000>,		$1 \sim 8000 => 1s \sim 1/8000s$
	etc.		$5 \sim 8000 => 1/5s \sim 1/8000s$
			etc.
	* Available value is		
	listed in		* This parameter may also restrict image
	"capability_image_c		frame rate from sensor due to sensor
	<0~(n-1)>_exposu		generates a frame per exposure time. Ex: If
	re_maxrange"		this is set to $1/5s \sim 1/8000s$ and camera takes

		1	<u> </u>
			1/5s on the night, then sensor only outputs 5
			frame/s.
			* Only available when
			"capability_image_c<0~(n-1)>_exposure_m
			axrange" != "-" and
			"capability_image_c<0~(n-1)>_exposure_ra
			ngetype" is "onevalue".
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0302a.
enableblc	<boolean></boolean>	4/4	Enable backlight compensation.
<not anymore="" support=""></not>			* Not support this parameter anymore when
			the version number (httpversion) is equal or
			greater than 0301a.
			* It's recommanded to use
			"exposurewin_c <n>_mode" to switch on/off</n>
			BLC.
	0.12	4/4	
exposurelevel	0~12	4/4	Exposure level
			"0,12": This range takes the concept from DC's
			exposure tuning options. The definition is:
			0: EV -2.0
			1: EV -1.7
			2: EV -1.3
			3: EV -1.0
			4: EV -0.7
			5: EV -0.3
			6: EV 0
			7: EV +0.3
			8: EV +0.7
			9: EV +1.0
			10: EV +1.3
			11: EV +1.7
			12: EV +2.0
			*Only available when
			"capability_image_c0_exposure_mode" is 0
exposuremode	auto,	4/4	Select exposure mode.
<product dependent=""></product>	shutterpriority,	-	
	irispriority,		"auto": Automatically adjust the Iris, Gain
L		I	

	qualitypriority,		and Shutter Speed to fit the exposure level.
	manual,		"shutterpriority": Manually adjust with
	etc		variable Shutter Speed, and keep adjusting
			Iris, Gain automatically.
	(Available options		"irispriority": Manually adjust with variable
	are list in		Iris, and keep adjusting Gain and Shutter
	"capability_image_c		speed automatically.
	<0~(n-1)>_exposu		"qualitypriority": Automatically adjust the
	re_modetype")		Iris, Gain and Shutter Speed by VIVOTEK
			quality algorithm.
			"manual": Manually adjust with variable
			Shutter, Iris and Gain.
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0302a.
			*Only available when
			"capability_image_c0_exposure_mode" is 0
whitebalance	auto,	4/4	Modes of white balance.
<product dependent=""></product>	manual,		"auto": Auto white balance
	rbgain,		"rbgain": Use rgain and bgain to set white
	widerange,		balance manually.
	outdoor,		"manual": 2 cases:
	indoor,		a. if "rbgain" is not supported, this means
	sodiumauto,		keep current white balance status.
	etc		b. if "rbgain" is supported, "rgain" and
			"bgain" are updated to the current values
	(Available values are		which is got from white balance module. Then,
	listed in		act as rbgain mode
	"capability_image_c		"widerange": Auto Tracing White balance
	<0~(n-1)>_wbmod		(2000K to 10000K).
	e")		"outdoor": auto white balance mode
			specifically for outdoor.
			"indoor": auto white balance mode
			specifically for indoor.
			"sodiumauto": sodium vapor lamps.
			* Only available when
			"capability_image_c<0~(n-1)>_wbmode" !="
			_"
	I		<u> </u>

		1	
rgain	0~100	4/4	Manual set rgain value of gain control setting.
			0: Weak <-> 100: Strong
			* Only available when "rbgain" is listed in
			"capability_image_c<0~(n-1)>_wbmode".
			* Only valid when
			"videoin_c<0~(n-1)>_whitebalance" != auto
			* Normalized range.
bgain	0~100	4/4	Manual set bgain value of gain control setting.
			0: Weak <-> 100: Strong
			* Only available when "rbgain" is listed in
			"capability_image_c<0~(n-1)>_wbmode".
			* Only valid when
			"videoin_c<0~(n-1)>_whitebalance" != auto
			* Normalized range.
maxgain	0~100	4/4	Maximum gain value.
			0: Low <-> 100: High
			* Only available when
			"capability_image_c<0~(n-1)>_agc_maxgain
			" != "-"
			* Only valid when "piris_mode"=manual or
			"irismode"=fixed
			* Normalized range.
			* Only available when
			"capability_image_c<0~(n-1)>_exposure_ra
			ngetype" is "twovalues".
mingain	0~100	4/4	Minimum gain value.
			0: Low <-> 100: High
			* Only available when
			"capability_image_c<0~(n-1)>_agc_mingain
			" != "-"
			* Only valid when "piris_mode"=manual or
			"irismode"=fixed
			* Normalized range.
			* Only available when
			' "capability_image_c<0~(n-1)>_exposure_ra
			ngetype" is "twovalues".

piris_mode       manual, indoor,       1/4       Control P-Iris mode. <product dependent="">       outdoor,-       1/4       Control P-Iris mode.         <product dependent="">       outdoor,-       1/4       Control P-Iris mode.         <product dependent="">       outdoor,-       1/4       Control P-Iris mode.         <product dependent="">       outdoor,-       1/4       Control P-Iris mode.         <product dependent="">       outdoor,-       1/4       Control P-Iris mode.         <product dependent="">       outdoor,-       1/4       Control P-Iris mode.         <product dependent="">       outdoor,-       1/4       Control P-Iris mode.         <product dependent="">       outdoor,-       1/4       Control P-Iris mode.         <product dependent="">       outdoor,-       1/4       Control P-Iris mode.         <product dependent="">       outdoor,-       1/4       Control P-Iris mode.         <product dependent="">       outdoor,-       1/4       Control P-Iris mode.         <product dependent="">       outdoor,-       1/4       Control P-Iris mode.         <product dependent="">       indoor,-       1/4       Control P-Iris mode.         <product dependent="">       indoor,-       indoor environment.       "indoor": Auto-setting p-Iris by "initstype" = pi</product></product></product></product></product></product></product></product></product></product></product></product></product></product>	gainvalue	0~100	4/4	Gain value.
piris_position       1~100       1/4       Manual set P-Iris.         piris_position       1~100       1/4       Manual set P-Iris.         piris_position       1~100       1/4       Manual set P-Iris.	guinvalue	0.100	-7/ -1	
"capability_image_c<0~(n-1)>_agc_maxgain         "!= "-" and         "capability_image_c<0~(n-1)>_exposure_ra         ngetype" is "onevalue".         * Normalized range.         * We support this parameter when the version         number (httpversion) is equal or greater than         0302a.         piris_mode         outdoor,-         outdoor,-         1/4         Control P-Iris mode.         "outdoor,-         outdoor,-         in indoor environment.         "indoor": Auto-setting P-Iris to get best         quality, but easy to meet rolling or flicker effect         in indoor environment.         "indoor": Avoid rolling and flicker effect first.         "manual": Manual set P-Iris by         "piris_position".         "-": not support (only available when         "capability_image_c<0~(n-1)>_sensortype"         is "smartsensor")         * Only available when         "capability_image_c<0~(n-1)>_iristype"=piri         s         piris_position         1~100       1/4         Manual set P-Iris.         1: Open <-> 100: Close				0. Low < 2 100. High
"capability_image_c<0~(n-1)>_agc_maxgain         "!= "-" and         "capability_image_c<0~(n-1)>_exposure_ra         ngetype" is "onevalue".         * Normalized range.         * We support this parameter when the version         number (httpversion) is equal or greater than         0302a.         piris_mode         outdoor,-         outdoor,-         1/4         Control P-Iris mode.         "outdoor,-         outdoor,-         in indoor environment.         "indoor": Auto-setting P-Iris to get best         quality, but easy to meet rolling or flicker effect         in indoor environment.         "indoor": Avoid rolling and flicker effect first.         "manual": Manual set P-Iris by         "piris_position".         "-": not support (only available when         "capability_image_c<0~(n-1)>_sensortype"         is "smartsensor")         * Only available when         "capability_image_c<0~(n-1)>_iristype"=piri         s         piris_position         1~100       1/4         Manual set P-Iris.         1: Open <-> 100: Close				* Only available when
"!="-" and         "capability_image_c<0~(n-1)>_exposure_ra         ngetype" is "onevalue".         * Normalized range.         * We support this parameter when the version         number (httpversion) is equal or greater than         0302a.         piris_mode <product dependent="">         outdoor,-         1/4         Control P-Iris mode.         "outdoor,-         outdoor,-         "indoor": Auto-setting P-Iris to get best         quality, but easy to meet rolling or flicker effect         in indoor environment.         "indoor": Avoid rolling and flicker effect first.         "manual": Manual set P-Iris by         "piris_position".         "-": not support (only available when         "capability_image_c&lt;0~(n-1)&gt;_sensortype"         is "smartsensor")         * Only available when         "capability_image_c&lt;0~(n-1)&gt;_iristype"=piri         s         piris_position         1~100       1/4         Manual set P-Iris.         1: Open &lt;-&gt; 100: Close</product>				
piris_mode       manual, indoor,       1/4       Control P-Iris mode. <product dependent="">       manual, indoor,       1/4       Control P-Iris mode.         <product dependent="">       outdoor,-       1/4       Control P-Iris mode.         <imature< td="">       "indoor": Auto-setting P-Iris to get best quality, but easy to meet rolling or flicker effect lin indoor environment.         "indoor": Avoid rolling and flicker effect first.       "manual": Manual set P-Iris by "piris_position".         "-": not support (only available when "capability_image_c&lt;0~(n-1)&gt;_sensortype" is "smartsensor")       * Only available when "capability_image_c&lt;0~(n-1)&gt;_iristype"=piri s         piris_position       1~100       1/4       Manual set P-Iris.         piris_position       1~100       1/4       Manual set P-Iris.</imature<></product></product>				
ngetype" is "onevalue".         * Normalized range.         * We support this parameter when the version number (httpversion) is equal or greater than 0302a.         piris_mode <product dependent="">         outdoor,-         1/4         Control P-Iris mode.         "outdoor,-         outdoor,-         "indoor": Auto-setting P-Iris to get best quality, but easy to meet rolling or flicker effect in indoor environment.         "indoor": Avoid rolling and flicker effect first.         "manual": Manual set P-Iris by "piris_position".         "-": not support (only available when "capability_image_c&lt;0~(n-1)&gt;_sensortype" is "smartsensor")         * Only available when "capability_image_c&lt;0~(n-1)&gt;_iristype"=piri s         piris_position       1~100         1/4       Manual set P-Iris. 1: Open &lt;-&gt; 100: Close</product>				
* Normalized range.         * We support this parameter when the version number (httpversion) is equal or greater than 0302a.         piris_mode       manual, indoor, outdoor,- <product dependent="">       0utdoor,-         outdoor,-       1/4         Control P-Iris mode.         "outdoor": Auto-setting P-Iris to get best quality, but easy to meet rolling or flicker effect in indoor environment.         "indoor": Avoid rolling and flicker effect first.         "manual": Manual set P-Iris by         "piris_position".         "-": not support (only available when "capability_image_c&lt;0~(n-1)&gt;_sensortype" is "smartsensor")         * Only available when "capability_image_c&lt;0~(n-1)&gt;_iristype"=piri s         piris_position       1/4         Amount dependent&gt;       1/4</product>				
piris_mode       manual, indoor,       1/4       Control P-Iris mode. <product dependent="">       outdoor,-       "outdoor": Auto-setting P-Iris to get best quality, but easy to meet rolling or flicker effect in indoor environment.         "indoor": Avoid rolling and flicker effect first.       "manual": Manual set P-Iris by "piris_position".         "-": not support (only available when "capability_image_c&lt;0~(n-1)&gt;_sensortype" is "smartsensor")         * Only available when "capability_image_c&lt;0~(n-1)&gt;_iristype"=piri s         piris_position       1~100         1/4       Manual set P-Iris.         1: Open &lt;-&gt; 100: Close</product>				
piris_mode       manual, indoor,       1/4       Control P-Iris mode. <product dependent="">       outdoor,-       "outdoor": Auto-setting P-Iris to get best quality, but easy to meet rolling or flicker effect in indoor environment.         "indoor": Avoid rolling and flicker effect first.       "manual": Manual set P-Iris by         "piris_position".       "-": not support (only available when         "capability_image_c&lt;0~(n-1)&gt;_sensortype"       is "smartsensor")         * Only available when       "capability_image_c&lt;0~(n-1)&gt;_iristype"=piri s         piris_position       1~100       1/4       Manual set P-Iris.         piris_product dependent&gt;       1~100       1/4       Manual set P-Iris.</product>				
piris_mode       manual, indoor,       1/4       Control P-Iris mode. <product dependent="">       outdoor,-       "outdoor": Auto-setting P-Iris to get best quality, but easy to meet rolling or flicker effect in indoor environment.         "indoor": Avoid rolling and flicker effect first.       "manual": Manual set P-Iris by         "piris_position".       "-": not support (only available when         "capability_image_c&lt;0~(n-1)&gt;_sensortype"       is "smartsensor")         * Only available when       "capability_image_c&lt;0~(n-1)&gt;_iristype"=piri s         piris_position       1~100       1/4       Manual set P-Iris.         piris_position       1~00       1/4       Manual set P-Iris.</product>				* We support this parameter when the version
initial control periodmanual, indoor, outdoor,-1/4Control P-Iris mode. "outdoor": Auto-setting P-Iris to get best quality, but easy to meet rolling or flicker effect in indoor environment. "indoor": Avoid rolling and flicker effect first. "manual": Manual set P-Iris by "piris_position". "-": not support (only available when "capability_image_c<0~(n-1)>_sensortype" is "smartsensor") * Only available when "capability_image_c<0~(n-1)>_iristype"=piri spiris_position1~1001/4Manual set P-Iris. 1: Open <-> 100: Close				
<product dependent="">       outdoor,-       "outdoor": Auto-setting P-Iris to get best quality, but easy to meet rolling or flicker effect in indoor environment.         "indoor": Avoid rolling and flicker effect first.       "indoor": Avoid rolling and flicker effect first.         "indoor": Avoid rolling and flicker effect first.       "indoor": Avoid rolling and flicker effect first.         "indoor": Avoid rolling and flicker effect first.       "indoor": Avoid rolling and flicker effect first.         "indoor": Avoid rolling and flicker effect first.       "indoor": Avoid rolling and flicker effect first.         "indoor": Avoid rolling and flicker effect first.       "indoor": Avoid rolling and flicker effect first.         "indoor": Avoid rolling and flicker effect first.       "indoor": not support (only available when         "capability_image_c&lt;0~(n-1)&gt;_sensortype"       is "smartsensor")         * Only available when       "capability_image_c&lt;0~(n-1)&gt;_iristype"=piri s         "piris_position       1~100       1/4       Manual set P-Iris.         <product dependent="">       1~100       1/4       Manual set P-Iris.</product></product>				
<product dependent="">outdoor,-"outdoor": Auto-setting P-Iris to get best quality, but easy to meet rolling or flicker effect in indoor environment. "indoor": Avoid rolling and flicker effect first. "manual": Manual set P-Iris by "piris_position". "-": not support (only available when "capability_image_c&lt;0~(n-1)&gt;_sensortype" is "smartsensor") * Only available when "capability_image_c&lt;0~(n-1)&gt;_iristype"=piri spiris_position1~1001/4Manual set P-Iris. 1: Open &lt;-&gt; 100: Close</product>	piris_mode	manual, indoor,	1/4	Control P-Iris mode.
piris_position       1~100       1/4       Manual set P-Iris.         in indoor environment.       "indoor": Avoid rolling and flicker effect first.         "manual": Manual set P-Iris by       "piris_position".         "-": not support (only available when       "capability_image_c<0~(n-1)>_sensortype"         "capability_image_c<0~(n-1)>_iristype"=piri       s         piris_position       1~100       1/4         Manual set P-Iris.       1: Open <-> 100: Close	<product dependent=""></product>			"outdoor": Auto-setting P-Iris to get best
piris_position1~1001/4Manual set P-Iris.piris_position1: Open <-> 100: Close				quality, but easy to meet rolling or flicker effect
"manual": Manual set P-Iris by "piris_position". "-": not support (only available when "capability_image_c<0~(n-1)>_sensortype" is "smartsensor") * Only available when "capability_image_c<0~(n-1)>_iristype"=piri spiris_position <product dependent="">1~1001/4Manual set P-Iris. 1: Open &lt;-&gt; 100: Close</product>				in indoor environment.
"manual": Manual set P-Iris by "piris_position". "-": not support (only available when "capability_image_c<0~(n-1)>_sensortype" is "smartsensor") * Only available when "capability_image_c<0~(n-1)>_iristype"=piri spiris_position <product dependent="">1~1001/4Manual set P-Iris. 1: Open &lt;-&gt; 100: Close</product>				"indoor": Avoid rolling and flicker effect first.
piris_position       "piris_position".         "-": not support (only available when         "capability_image_c<0~(n-1)>_sensortype"         is "smartsensor")         * Only available when         "capability_image_c<0~(n-1)>_iristype"=piri         s         piris_position       1~100         1/4       Manual set P-Iris.         1: Open <-> 100: Close				_
piris_position1~1001/4Manual set P-Iris. 1: Open <-> 100: Close				
piris_position       1~100       1/4       Manual set P-Iris.         1: Open <-> 100: Close				"-": not support (only available when
piris_position       1~100       1/4       Manual set P-Iris. <product dependent="">       1: Open &lt;-&gt; 100: Close</product>				"capability_image_c<0~(n-1)>_sensortype"
piris_position     1~100     1/4     Manual set P-Iris. <product dependent="">     1: Open &lt;-&gt; 100: Close</product>				is "smartsensor")
piris_position     1~100     1/4     Manual set P-Iris. <product dependent="">     1 : Open &lt;-&gt; 100: Close</product>				* Only available when
piris_position     1~100     1/4     Manual set P-Iris. <product dependent="">     1     1: Open &lt;-&gt; 100: Close</product>				"capability_image_c<0~(n-1)>_iristype"=piri
<pre><pre>conduct dependent&gt;</pre> 1: Open &lt;-&gt; 100: Close</pre>				S
	piris_position	1~100	1/4	Manual set P-Iris.
	<product dependent=""></product>			1: Open <-> 100: Close
↑ Only valid when "piris_mode"=manual or				* Only valid when "piris_mode"=manual or
"capability_image_c<0~(n-1)>_sensortype"				"capability_image_c<0~(n-1)>_sensortype"
is "smartsensor"				is "smartsensor"
* Only available when				* Only available when
"capability_image_c<0~(n-1)>_iristype"=piri				"capability_image_c<0~(n-1)>_iristype"=piri
s				s
irismode fixed, indoor, 4/4 Control DC-Iris mode.	irismode	fixed, indoor,	4/4	Control DC-Iris mode.
outdoor "outdoor": Auto-setting DC-Iris to get best		outdoor		"outdoor": Auto-setting DC-Iris to get best
<pre>  quality, but easy to meet rolling or flicker effect</pre>		<product< td=""><td></td><td>quality, but easy to meet rolling or flicker effect</td></product<>		quality, but easy to meet rolling or flicker effect
dependent> in indoor environment.		dependent>		in indoor environment.
"indoor": Avoid rolling and flicker effect first.				"indoor": Avoid rolling and flicker effect first.

			"fixed": Open the iris to maximum.
			* Only available when
			"capability_image_c<0~(n-1)>_iristype"=dci
			ris
wdrpro_mode	<boolean></boolean>	4/4	Enable WDR pro
		4/4	
<product dependent=""></product>			* Only available when
			* Only available when
			<pre>"capability_image_c&lt;0~(n-1)&gt;_wdrpro_mod e" &gt; 0</pre>
udunus, stusnath	1 100	A / A	
wdrpro_strength	1~100	4/4	The strength of WDR Pro.
<product dependent=""></product>			The bigger value means the stronger strength
			of WDR Pro.
			* Only available when
			"capability_image_c<0~(n-1)>_wdrpro_stren
			gth" is 1
wdrc_mode	<boolean></boolean>	4/4	Enable WDR enhanced.
<product dependent=""></product>			* Only available when
			"capability_image_c<0~(n-1)>_wdrc_mode"
			is 1
wdrc_strength	1~100	4/4	The strength of WDR enhanced.
<product dependent=""></product>			The bigger value means the stronger strength
			of WDR enhanced.
			* Only available when
			"capability_image_c<0~(n-1)>_wdrc_mode"
			is 1
aespeed_mode	<boolean></boolean>	4/4	Turning AE converge speed on or off.
<product dependent=""></product>			0: off
			1: on
			* Only available when
			"capability_image_c<0~(n-1)>_aespeed" is 1
aespeed_speedlevel	1~100	4/4	The speed level of AE converge speed.
<product dependent=""></product>			1~20: level 1
			21~40: level 2
			41~60: level 3
			61~80: level 4
			81~100: level 5
			Level 1~4(low ~ high)
			The higher speed level meas shorter AE
			converged time during AE executing.

			* Only available when
			' "capability_image_c<0~(n-1)>_aespeed" is 1
accord consitivity	1~100	4/4	The sensitivity of AE converge speed.
aespeed_sensitivity	1~100	4/4	
<product dependent=""></product>			1~20: level 1
			21~40: level 2
			41~60: level 3
			61~80: level 4
			81~100: level 5
			Level 1~4(low ~ high)
			The higher sensitivity level meas that it is easy
			to be trigger while scene changed.
			* Only available when
			"capability_image_c<0~(n-1)>_aespeed" is 1
			and
			"capability_image_c<0~(n-1)>_aespeedsupp
			ortsensitivity" is 1.
flickerless	<boolean></boolean>	4/4	Turn on(1) or turn off(0) the flickerless mode
<product dependent=""></product>			* Only available when
			"capability_image_c<0~(n-1)>_flickerless" is
			1

# 7.9 Time Shift settings

Group: timeshift for n channel profucts and m stream

n denotes the value of "capability\_nvideoin", m denotes the value of "capability\_nmediastream"

(capability.timeshift > 0)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	4/4	Enable time shift streaming.
c<0~(n-1)>_s<0~(m-1)	<boolean></boolean>	4/4	Enable time shift streaming for specific
>_allow			stream.

## 7.10 IR cut control

Group: **ircutcontrol** (capability.nvideoinprofile> 0 and capability\_daynight\_c<0~(n-1)>\_support > 0)

n denotes the value of "capability\_nvideoin"

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
mode	auto,	6/6	Set IR cut control mode
	day,		
	night,		
	di,		
	schedule		
	<product< td=""><td></td><td></td></product<>		
	dependent>		
sir	<boolean></boolean>	6/6	Enable/disable Smart IR
<product dependent=""></product>			* Only available when
			"capability_daynight_c<0~"capability_nvideoi
			n"-1>_smartir" is 1
daymodebegintime	00:00~23:59	6/6	Day mode begin time
daymodeendtime	00:00~23:59	6/6	Day mod end time
disableirled	<boolean></boolean>	6/6	Enable/disable built-in IR led
			(capability_daynight_c<0~"capability_nvideoi
			n"-1>_buildinir > 0)
enableextled	<boolean></boolean>	1/6	Enable/disable external IR led
			(capability_daynight_c<0~"capability_nvideoi
			n"-1>_externalir > 0)
extledmode	do, irring	6/6	Turn on an external IR led which is mounted do
	* Available values		(digital output) device or is a IR ring device.
	are listed in		* Only available when
	"capability_daynight		"capability_daynight_c<0~"capability_nvideoi
	_c<0~(n-1)>_extle		n"-1>_externalir" is 1.
	d_interface"		* Only valid when "ircutcontrol_enableextled"
			is 1.
bwmode	<boolean></boolean>	6/6	Switch to B/W in night mode if enabled.
			* Only available when
			"capability_daynight_c<0~(n-1)>_
			blackwhitemode" is 1.
sensitivity	low, normal, high	6/6	Sensitivity of day/night control.
	(if		
	capability_daynight		There are two value format:

	_c<0~(n-1)>_ircut	"low,normal,high": if
Se	ensitivity_type=op	capability_daynight_c<0~(n-1)>_ircutsensiti
ti	ions)	vity_type=options
1	~100 (if	"1~100": if
Ca	apability_daynight	capability_daynight_c<0~(n-1)>_ircutsensiti
	_c<0~(n-1)>_ircut	vity_type=normalize
Se	ensitivity_type=no	
rr	malize)	* Only available when
		"capability_daynight_c<0~(n-1)>
		_ircutsensitivity_type" is not "-".

# 7.11 Image setting per channel

Group: image\_c<0~(n-1)> for n channel profucts and m profile

n denotes the value of "capability\_nvideoin" and m denotes the value of "capability\_nvideoinprofile"

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
brightness	-5~5,100	4/4	-5: Darker <-> 5: Bright
<not recommended="" this="" to="" use=""></not>			100: Use " image_c <n>_brightnesspercent"</n>
			* Only available when bit 0 of
			"capability_image_c<0~(n-1)>_basicsetting"
			is 1
			* We replace "brightness" with
			"brightnesspercent".
			* This parameter will not be used after the
			version number (httpversion) is equal or
			greater than 0400a.
contrast	-5~5,100	4/4	-5: Less contrast <-> 5: More contrast
<not recommended="" this="" to="" use=""></not>			100: Use "
			image_c<0~(n-1)>_contrastpercent"
			* Only available when bit 1 of
			"capability_image_c<0~(n-1)>_basicsetting"
			is 1.
			* We replace "contrast" with "contrastpercent
			۳.

			* This management will not be a set of sub-
			* This parameter will not be used after the
			version number (httpversion) is equal or
			greater than 0400a.
saturation	-5~5,100	4/4	-5: Less saturation <-> 5: More saturation
<not recommended="" this="" to="" use=""></not>			100: Use " image_c <n>_saturationpercent"</n>
			* Only available when bit 2 of
			"capability_image_c<0~(n-1)>_basicsetting"
			is 1.
			* We replace "saturation" with
			"saturationpercent".
			* This parameter will not be used after the
			version number (httpversion) is equal or
			greater than 0400a.
sharpness	-3~3,100	4/4	-3: Softer <-> 3: Sharper
<not recommended="" this="" to="" use=""></not>			100: Use "
			image_c<0~(n-1)>_sharpnesspercent"
			* Only available when bit 3 of
			"capability_image_c<0~(n-1)>_basicsetting"
			is 1.
			* We replace "sharpness" with
			"sharpnesspercent".
			* This parameter will not be used after the
			version number (httpversion) is equal or
			greater than 0400a.
brightnesspercent	0~100	4/4	Set brightness in the normalized range.
			0: Darker <-> 100: Bright
			_
			* Only available when bit 0 of
			' "capability_image_c<0~(n-1)>_basicsetting"
			is 1.
contrastpercent	0~100	4/4	Set contrast in the normalized range.
		,	0: Less contrast <-> 100: More contrast
			* Only available when bit 1 of
			"capability_image_c<0~(n-1)>_basicsetting"
			is 1

saturationpercent	0~100	4/4	Set saturation in the normalized range.
			0: Less saturation <-> 100: More saturation
			* Only available when bit 2 of
			"capability_image_c<0~(n-1)>_basicsetting"
			is 1.
sharpnesspercent	0~100	4/4	Set sharpness in the normalized range.
			0: Softer <-> 100: Sharper
			* Only available when bit 3 of
			"capability_image_c<0~(n-1)>_basicsetting"
			is 1
gammacurve	0~100	4/4	0: Fine-turned gamma curve by Vivotek.
<product dependent=""></product>			1: Gamma value = 0.01
			2: Gamma value = 0.02
			3: Gamma value = 0.03
			100: Gamma value = 1
			* Note: Although we set gamma value to 100
			level, but not all gamma values are valid.
			Internal module will take the closest valid one.
			For example, 1~45 may all be mapped to
			gamma value = 0.45, etc.
			* Only available when
			"capability_image_c<0~(n-1)>_gammacurv
			e" is 1
lowlightmode	<boolean></boolean>	4/4	Enable/disable low light mode.
<product dependent=""></product>			* Only available when
			"capability_image_c<0~(n-1)>_lowlightmode
			" is 1
dnr_mode	<boolean></boolean>	4/4	3D noise reduction.
<product dependent=""></product>			0:disable
			1:enable
			* Only available when
			"capability_image_c<0~(n-1)>_dnr" is 1
dnr_strength	1~100	4/4	Strength of 3DNR
<product dependent=""></product>			* Only available when
			"capability_image_c<0~(n-1)>_dnr" is 1
defog_mode	<boolean></boolean>	4/4	Enable/disable defog mode.

<product dependent=""></product>			0:disable
			1:enable
			* Only available when
			capability_image_c<0~(n-1)>_defog_mode"
			is 1
defog_strength	1~100	4/4	Strength of defog
<product dependent=""></product>			* Only available when
			"capability_image_c<0~(n-1)>_defog_mode"
			is 1
eis_mode	<boolean></boolean>	4/4	Electronic image stabilizer
<product dependent=""></product>			0:disable
			1:enable
			* Only available when 'eis' is listed in
			"capability_image_c<0~(n-1)>_is_mode".
eis_strength	1~100	4/4	Strength of electronic image stabilizer
<product dependent=""></product>			* Only available when 'eis' is listed in
			"capability_image_c<0~(n-1)>_is_mode".
dis_mode	<boolean></boolean>	4/4	Digital image stabilizer
<product dependent=""></product>			0:disable
			1:enable
			* Only available when 'dis' is listed in
			"capability_image_c<0~(n-1)>_is_mode".
dis_strength	1~100	4/4	Strength of digital image stabilizer
<product dependent=""></product>			* Only available when 'dis' is listed in
			"capability_image_c<0~(n-1)>_is_mode".
scene_enable	<boolean></boolean>	4/4	Enable/disable scene mode
<product dependent=""></product>			0: disable
			1: enable
			* Only available when
			"capability_image_c<0~(n-1)>_scenemode_
			support" is 1
scene_mode	visibility,	4/4	Value of scene mode
<product dependent=""></product>	noiseless,		* Only available when
	lpcparkinglot,		"capability_image_c<0~(n-1)>_scenemode_
	lpcstreet		support" is 1
	<product< td=""><td></td><td>* Available value is listed in</td></product<>		* Available value is listed in
	dependent>		"capability_image_c<0~(n-1)>_scenemode_
			supporttype"
restoreatwb	<positive< td=""><td>4/4</td><td>Restore of adjusting white balance of image</td></positive<>	4/4	Restore of adjusting white balance of image
	integer>		according to mode settings

freeze	<boolean></boolean>	4/4	Enable/disable Image freeze while patrolling.
		4/4	0: disable
<product dependent=""></product>			
			1: enable
			* Only available when
			"capability_image_c<0~(n-1)>_freeze" is 1
deinterlace_enable	<boolean></boolean>	4/4	Enable/disable deinterlace function.
			0: disable
			1: enable
			* Only available when
			"capability_image_c<0~(n-1)>_deinterlace_s
			upport" is 1.
deinterlace_mode	spatial,blend	4/4	Users can choose between two different
			deinterlacing techniques:
			Spatical mode provides the best image quality,
			while Blend mode provides better image
			quality (than not using the deinterlace function
			at all).
			* Only available when
			"capability_image_c<0~(n-1)>_deinterlace_s
			upport" is 1.
xoffset	0~100	4/4	Adjusting the image to proper position
			horizontally.
			* Only available when the bit 4 of
			capability_image_c<0~(n-1)>_basicsetting is
			1.
yoffset	0~100	4/4	Adjusting the image to proper position
		., .	vertically.
			* Only available when the bit 5 of
			capability_image_c<0~(n-1)>_basicsetting is
			1.
$refile i < 0 \cdot (m + 1) > enable$	<boolean></boolean>	4/4	Enable/disable this profile setting
profile_i<0~(m-1)>_enable			
profile_i<0~(m-1)>_policy	night,	4/4	The mode which the profile is applied to.
	schedule		
			* Not support "policy=day" anymore when the
			version number (httpversion) is equal or
			greater than 0301a.
profile_i<0~(m-1)>_begintime	hh:mm	4/4	Begin time of schedule mode.
profile_i<0~(m-1)>_endtime	hh:mm	4/4	End time of schedule mode.
profile_i<0~(m-1)>_brightness	-5~5,100	4/4	-5: Darker <-> 5: Bright
<not recommended="" this="" to="" use=""></not>			100: Use "

			image_c<0~(n-1)>_brightnesspercent"
			* Only available when bit 0 of "capability_image_c<0~(n-1)>_basicsetting" is 1
			<ul> <li>* We replace "profile_i0_brightness" with "profile_i0_brightnesspercent".</li> <li>* This parameter will not be used after the version number (httpversion) is equal or greater than 0400a.</li> </ul>
profile_i<0~(m-1)>_contrast <not recommended="" this="" to="" use=""></not>	-5~5,100	4/4	-5: Less contrast <-> 5: More contrast 100: Use " image_c<0~(n-1)>_contrastpercent"
			* Only available when bit 1 of "capability_image_c<0~(n-1)>_basicsetting" is 1.
			<ul> <li>* We replace "profile_i0_contrast" with</li> <li>"profile_i0_contrastpercent ".</li> <li>* This parameter will not be used after the</li> <li>version number (httpversion) is equal or</li> <li>greater than 0400a.</li> </ul>
profile_i<0~(m-1)>_saturation <not recommended="" this="" to="" use=""></not>	-5~5,100	4/4	-5: Less saturation <-> 5: More saturation 100: Use " image_c<0~(n-1)>_saturationpercent"
			* Only available when bit 2 of "capability_image_c<0~(n-1)>_basicsetting" is 1.
			<ul> <li>* We replace "profile_i0_saturation" with</li> <li>"profile_i0_saturationpercent".</li> <li>* This parameter will not be used after the</li> <li>version number (httpversion) is equal or</li> </ul>
profile_i<0~(m-1)>_sharpness <not recommended="" this="" to="" use=""></not>	-3~3,100	4/4	greater than 0400a. -5: Less saturation <-> 5: More saturation 100: Use " image_c<0~(n-1)>_saturationpercent"

	1	1	1
			* Only available when bit 2 of
			"capability_image_c<0~(n-1)>_basicsetting"
			is 1.
			* We replace "profile_i0_saturation" with
			"profile_i0_saturationpercent".
			* This parameter will not be used after the
			version number (httpversion) is equal or
			greater than 0400a.
profile_i<0~(m-1)>_brightness	0~100	4/4	Set brightness in the normalized range.
percent			0: Darker <-> 100: Bright
			* Only available when bit 0 of
			"capability_image_c<0~(n-1)>_basicsetting"
			is 1.
profile_i<0~(m-1)>_contrastpe	0~100	4/4	Set contrast in the normalized range.
rcent			0: Less contrast <-> 100: More contrast
			* Only available when bit 1 of
			"capability_image_c<0~(n-1)>_basicsetting"
			is 1
profile_i<0~(m-1)>_saturation	0~100	4/4	Set saturation in the normalized range.
percent			0: Less saturation <-> 100: More saturation
			* Only available when bit 2 of
			"capability_image_c<0~(n-1)>_basicsetting"
			is 1.
profile_i<0~(m-1)>_sharpness	0~100	4/4	Set sharpness in the normalized range.
percent			0: Softer <-> 100: Sharper
			* Only available when bit 3 of
			"capability_image_c<0~(n-1)>_basicsetting"
			is 1
profile_i<0~(m-1)>_gammacur	0~100	4/4	0: Fine-turned gamma curve by Vivotek.
ve			1: Gamma value = $0.01$
			2: Gamma value = $0.02$
			3: Gamma value = $0.03$
			100: Gamma value = 1
	I	I	

			* Note: Although we set gamma value to 100 level, but not all gamma values are valid. Internal module will take the closest valid one. For example, 1~45 may all be mapped to gamma value = 0.45, etc. * Only available when "capability_image_c<0~(n-1)>_gammacurve " is 1
profile_i<0~(m-1)>_lowlightm ode <product dependent=""></product>	<boolean></boolean>	4/4	Enable/disable low light mode. * Only available when "capability_image_c<0~(n-1)>_lowlightmode " is 1
profile_i<0~(m-1)>_dnr_mode <product dependent=""></product>	<boolean></boolean>	4/4	3D noise reduction. 0:disable 1:enable * Only available when "capability_image_c<0~(n-1)>_dnr" is 1
profile_i<0~(m-1)>_dnr_stren gth <product dependent=""></product>	1~100	4/4	Strength of 3DNR * Only available when "capability_image_c<0~(n-1)>_dnr" is 1
profile_i<0~(m-1)>_defog_mo de <product dependent=""></product>	<boolean></boolean>	4/4	Enable/disable defog mode. 0:disable 1:enable * Only available when "capability_image_c<0~(n-1)>_defog_mode" is 1
profile_i<0~(m-1)>_defog_str ength <product dependent=""></product>	1~100	4/4	Strength of defog * Only available when "capability_image_c<0~(n-1)>_defog_mode" is 1
profile_i<0~(m-1)>_eis_mode <product dependent=""></product>	<boolean></boolean>	4/4	Electronic image stabilizer 0:disable 1:enable * Only available when 'eis' is listed in "capability_image_c<0~(n-1)>_is_mode".
profile_i<0~(m-1)>_eis_streng th <product dependent=""></product>	1~100	4/4	Strength of electronic image stabilizer * Only available when 'eis' is listed in "capability_image_c<0~(n-1)>_is_mode".
profile_i<0~(m-1)>_dis_mode	<boolean></boolean>	4/4	Digital image stabilizer

<product dependent=""></product>			0:disable
			1:enable
			* Only available when 'dis' is listed in
			"capability_image_c<0~(n-1)>_is_mode".
profile_i<0~(m-1)>_dis_streng	1~100	4/4	Strength of digital image stabilizer
th			* Only available when 'dis' is listed in
<product dependent=""></product>			"capability_image_c<0~(n-1)>_is_mode".
profile_i<0~(m-1)>_scene_ena	<boolean></boolean>	4/4	Enable/disable scene mode
ble			0: disable
<product dependent=""></product>			1: enable
			* Only available when
			"capability_image_c<0~(n-1)>_scenemode_
			support" is 1
profile_i<0~(m-1)>_scene_mo	visibility,	4/4	Value of scene mode
de	noiseless,		* Only available when
<product dependent=""></product>	lpcparkinglot,		"capability_image_c<0~(n-1)>_scenemode_
	lpcstreet		support" is 1
	<product< td=""><td></td><td>* Available value is listed in</td></product<>		* Available value is listed in
	dependent>		"capability_image_c<0~(n-1)>_scenemode_
			supporttype"

### 7.12 Exposure window setting per channel

Group: **exposurewin\_c<0~(n-1)>** for n channel profucts

n denotes the value of "capability\_nvideoin"

#### (Only available when "capability\_image\_c<0~(n-1)>\_exposure\_mode"=1)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
mode	auto, custom,blc,hlc	4/4	"auto": Use full image view as the only
			exposure window.
	* Available values are listed in		"custom": Use custom windows.
	"capability_image_c<0~(n-1)>_		"blc": Use BLC(Back Light Compensation),
	exposure_winmode"		and the only exposure window is located at the
			center of view.
			"hlc": Use HLC (High Light Compensation),
			and to perform the masking of bright light
			area.

### Group: exposurewin\_c<0~(n-1)>\_win\_i<0~(k-1)>

n denotes the value of "capability\_nvideoin",

k denotes the value of "capability\_image\_c<0~(n-1)>\_exposure\_winnum".

(Only available when "capability\_image\_c<0~(n-1)>\_exposure\_mode"=1 and when custom is listed in

"capability\_image\_c<0~(n-1)>\_exposure\_winmode" and valid when "exposurewin\_c<0~(n-1)>\_mode"=custom or "exposurewin\_c<0~(n-1)>\_mode"=hlc)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	4/4	Enable or disable the window.
policy	0~1	4/4	0: Indicate exclusive.
			1: Indicate inclusive.
			* Only available when exclusive is listed in
			"capability_image_c<0~(n-1)>_exposure_wi
			ntype".
home	<0~320,0~240>	4/4	Left-top corner coordinate of the window.
			* Only available when qvga is listed in
			"capability_image_c<0~(n-1)>_exposure_wi
			ndomain".
size	<0~320x0~240>	4/4	Width and height of the window.
			* Only available when qvga is listed in

			"capability_image_c<0~(n-1)>_exposure_wi ndomain".
homepx	<0~W,0~H>	4/4	Left-top corner coordinate of the window.
	W: 0~ The current image width -1		* Only available when px is listed in
	H: 0~ The current image height -1		"capability_image_c<0~(n-1)>_exposure_wi ndomain".
sizepx	<0~Wx0~ H>	4/4	Width and height of the window.
	W: 0~ The current image width -1		* Only available when px is listed in
	H: 0~ The current image height -1		"capability_image_c<0~(n-1)>_exposure_wi ndomain".
homestd	<0~9999,0~9999>	4/4	Left-top corner coordinate of the window.
			* Only available when std is listed in
			"capability_image_c<0~(n-1)>_exposure_wi ndomain".
sizestd	<0~9999x0~9999>	4/4	Width and height of the window.
			* Only available when std is listed in "capability_image_c<0~(n-1)>_exposure_wi
			ndomain".

### Group: exposurewin\_c<0~(n-1)>\_profile\_i<0~(m-1)> for n channel profuct and m profile,

n denotes the value of "capability\_nvideoin", m denotes the value of "capability\_nvideoinprofile",

(Only available when "capability\_image\_c<0~(n-1)>\_exposure\_mode"=1)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
mode	auto, custom,blc,hlc	4/4	The mode indicates how to decide the
			exposure.
	* Available values are listed in		"auto": Use full view as the only one exposure
	"capability_image_c<0~(n-1)>_		window.
	exposure_winmode"		"custom": Use inclusive and exclusive
			window.
			"blc": Use BLC(Back Light Compensation),
			and the only exposure window is located at the
			center of view.
			"hlc": Use HLC (High Light Compensation),
			and to perform the masking of bright light
			area.

VIVOTEK

Group: **exposurewin\_c<0~(n-1)>\_profile\_i<0~(m-1)>\_win\_i<0~(k-1)>** for m profile and n channel product,

n denotes the value of "capability\_nvideoin", m denotes the value of "capability\_nvideoinprofile",

k denotes the value of "capability\_image\_c<0~(n-1)>\_exposure\_winnum".

(Only available when "capability\_image\_c<0~(n-1)>\_exposure\_mode"=1 and when custom is listed in

"capability\_image\_c<0~(n-1)>\_exposure\_winmode" and valid when "exposurewin\_c<0~(n-1)>\_mode"=custom or "exposurewin\_c<0~(n-1)>\_mode"=hlc)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	4/4	Enable or disable the window.
policy	0~1	4/4	0: Indicate exclusive.
			1: Indicate inclusive.
			* Only available when exclusive is listed in
			"capability_image_c<0~(n-1)>_exposure_wi
			ntype".
home	<0~320,0~240>	4/4	Left-top corner coordinate of the window.
			* Only available when qvga is listed in
			"capability_image_c<0~(n-1)>_exposure_wi
			ndomain".
size	<0~320x0~240>	4/4	Width and height of the window.
			* Only available when qvga is listed in
			"capability_image_c<0~(n-1)>_exposure_wi
			ndomain".
homepx	<0~W,0~H>	4/4	Left-top corner coordinate of the window.
	W: 0~ The current image width -1		* Only available when px is listed in
	H: 0~ The current image height -1		"capability_image_c<0~(n-1)>_exposure_wi
			ndomain".
sizepx	<0~Wx0~ H>	4/4	Width and height of the window.
	W: 0~ The current image width -1		* Only available when px is listed in
	H: 0~ The current image height -1		"capability_image_c<0~(n-1)>_exposure_wi
			ndomain".
homestd	<0~9999,0~9999>	4/4	Left-top corner coordinate of the window.
			* Only available when std is listed in
			"capability_image_c<0~(n-1)>_exposure_wi

			ndomain".
sizestd	<0~9999x0~9999>	4/4	Width and height of the window.
			* Only available when std is listed in
			"capability_image_c<0~(n-1)>_exposure_wi
			ndomain".

# 7.13 Audio input per channel

Group: **audioin\_c<0~(n-1)>** for n channel products (capability.naudioin>0)

n denotes the value of "capability\_nvideoin"

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
source	micin, linein	4/4	micin => use built-in microphone input.
<not recommended="" td="" to="" use<=""><td><product< td=""><td></td><td>linein =&gt; use external microphone input.</td></product<></td></not>	<product< td=""><td></td><td>linein =&gt; use external microphone input.</td></product<>		linein => use external microphone input.
this>	dependent>		
			* Reserved for compatibility, and suggest don't
			use this since the version number
			(httpversion) is equal or greater than 0301a.
			* We replace "source" with "input". More
			details, please refer the parameter description
			of "input".
input	intmic, extmic	4/4	intmic: Internal (built-in) microphone.
	<product< td=""><td></td><td>(Only available when capability_audio_intmic</td></product<>		(Only available when capability_audio_intmic
	dependent>		= 1)
			extmic: External microphone input.
			(Only available when capability_audio_extmic
			=1)
			* Note: If physical microphone switch is
			showed on product, this value is updated
			during booting to fit switch status.
volume_internal	0~100	4/4	Volume when take internal microphone as
			input source.
			0: Minimum
			100: Maximum
			* Only available when the channel supports
			internal microphone (The related bit of
			"capability_audio_intmic" is equal to 1).

volume_external	0~100	4/4	Volume when take external microphone as
volume_external	0~100	4/4	input source.
			0: Minimum
			100: Maximum
			* Only available when the channel supports
			external microphone (The related bit of
			"capability_audio_extmic" is equal to 1).
mute	0, 1	1/4	0: Mute off
			1: Mute on
gain	0~100	4/4	Gain of input.
<not recommended="" td="" to="" use<=""><td></td><td></td><td>(audioin_c&lt;0~(n-1)&gt;_source = linein)</td></not>			(audioin_c<0~(n-1)>_source = linein)
this>			
			* Reserved for compatibility, and suggest don't
			use this since the version number
			(httpversion) is equal or greater than 0301a.
			* We replace "gain" with "volume_internal"
			and "volume_external". More details, please
			refer the parameter description of
			"volume_internal" and "volume_external".
boostmic	0~100	4/4	Enable microphone boost.
<not recommended="" td="" to="" use<=""><td></td><td></td><td>Gain of input.</td></not>			Gain of input.
this>			(audioin_c<0~(n-1)>_source = micin)
			* Reserved for compatibility, and suggest don't
			use this since the version number
			(httpversion) is equal or greater than 0301a.
			* We replace "boostmic" with
			"volume_internal" and "volume_external".
			More details, please refer the parameter
			description of "volume_internal" and
			"volume_external".
s0_codectype	aac4, gamr, g711,	4/4	Set audio codec type for input.
	g726		aac4: Advanced Audio Coding (AAC)
	(Available codec are		gamr: Adaptive Multi-Rate (AMR)
	listed in		g711: G.711
	"capability_audioin_		g726: G.726
	codec")		
s0_aac4_bitrate	16000,	4/4	Set AAC4 bitrate in bps.
		-	

			1
	48000,		* Only available if AAC is supported.
	64000,		
	96000,		
	128000		
s0_gamr_bitrate	4750,	4/4	AMR encoded bitrate in bps.
	5150,		
	5900,		* Only available if AMR is supported.
	6700,		
	7400,		
	7950,		
	10200,		
	12200		
s0_g711_mode	pcmu,	4/4	Set G.711 companding algorithm.
	pcma		pcmu: µ-law algorithm
			pcma: A-law algorithm
			* Only available if G.711 is supported.
s0_g726_bitrate	16000,	4/4	Set G.726 encoded bitrate in bps.
	24000,		
	32000,		* Only available if G.726 is supported.
	40000		
s0_g726_bitstreampackin	little, big	4/4	Set G.726 bit streaming packing mode.
gmode			little: Little-endian bitstream format.
			big: Big-endian bitstream format.
			* Only available if G.726 is supported.
s0_g726_vlcmode	0, 1	4/4	Enable vlcmode for G.726.
			0: Standard mode.
			1: Solve compatibility problem with VLC
			player.
			* Only available if G.726 is supported.
aec_enable	<boolean></boolean>	4/4	Enable acoustic echo cancellation.
			* Only available when
			"capability_audio_aecmode" is "manual".
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0306b.
alarm_enable	<boolean></boolean>	4/4	Enable audio detection
		.,	

alarm_level	1~100	4/4	Audio detection alarm level
profile_i0_enable	<boolean></boolean>	4/4	Enable/disable this profile setting
profile_i0_policy	night,	4/4	The mode which the profile is applied to.
	schedule		
			* Not support "policy=day" anymore when the
			version number (httpversion) is equal or
			greater than 0301a.
profile_i0_begintime	hh:mm	4/4	Begin time of schedule mode.
profile_i0_endtime	hh:mm	4/4	End time of schedule mode.
profile_i0_alarm_level	1~100	4/4	Audio detection alarm level

### 7.14 Motion detection settings

#### Group: motion\_c<0~(n-1)> for n channel products

n denotes the value of "capability\_nvideoin"

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	4/4	Enable motion detection.
win_sensitivity	0 ~ 100	4/4	Sensitivity of all motion detection windows.
			* The value "0" is reserved for compatibility
			and will not be used after the version number
			(httpversion) is equal or greater than 0400a.

### Group: motion\_c<0~(n-1)>\_win\_i<0~(k-1)>

n denotes the value of "capability\_nvideoin", k denotes the value of "capability\_nmotion".

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	4/4	Enable motion detection window.
name	string[14]	4/4	Name of motion window.
polygonstd	0 ~ 9999,0 ~ 9999,	4/4	Coordinate of polygon window position.
	0 ~ 9999,0 ~ 9999,		(4 points: x0,y0,x1,y1,x2,y2,x3,y3)
	0 ~ 9999,0 ~ 9999,		* Only available when
	0 ~ 9999,0 ~ 9999		"capability_motion_wintype" = polygon.
			* Only available when std is listed in "capability_motion_windomain"
objsize	1 ~ 100	4/4	Percent of motion detection window.
sensitivity	0 ~ 100	4/4	Sensitivity of motion detection window.
<not recommended="" td="" to="" use<=""><td></td><td></td><td></td></not>			

thics			
this>			* We replace "sensitivity" with
			"win_sensitivity".
			* This parameter will not be used after the
			version number (httpversion) is equal or
			greater than 0400a.
polygonpx	0 ~ W,0 ~ H, 0 ~	4/4	Coordinate of polygon window position.
<not recommended="" td="" to="" use<=""><td>W,0 ~ H, 0 ~ W,0 ~</td><td></td><td>(4 points: x0,y0,x1,y1,x2,y2,x3,y3)</td></not>	W,0 ~ H, 0 ~ W,0 ~		(4 points: x0,y0,x1,y1,x2,y2,x3,y3)
this>	H, 0 ~ W,0 ~ H		* Only available when
	W: 0~ The current		"capability_motion_wintype" = polygon.
	image width -1		
	H: 0~ The current		* Only available when px is listed in
	image height -1		"capability_motion_windomain".
			* It's recommended to use polygonsd
			* This parameter will not be used after the
			version number (httpversion) is equal or
			greater than 0400a.
nalyzan	0 220 0 240 0	A / A	
polygon	0 ~ 320,0 ~ 240, 0	4/4	Coordinate of polygon window position.
<not recommended="" td="" to="" use<=""><td>~ 320,0 ~ 240, 0 ~</td><td></td><td>(4 points: x0,y0,x1,y1,x2,y2,x3,y3)</td></not>	~ 320,0 ~ 240, 0 ~		(4 points: x0,y0,x1,y1,x2,y2,x3,y3)
this>	320,0 ~ 240, 0 ~		* Only available when
	320,0 ~ 240		"capability_motion_wintype" = polygon.
			* Only available when qvga is listed in
			"capability_motion_windomain".
			* It's recommended to use polygonsd
			* This parameter will not be used after the
			version number (httpversion) is equal or
			greater than 0400a.
left	0 ~ 320	4/4	Left coordinate of window position.
<not recommended="" td="" to="" use<=""><td></td><td></td><td>* Only available when</td></not>			* Only available when
this>			"capability_motion_wintype" = rectangle.
			* Only available when qvga is listed in
			"capability_motion_windomain".
			* It's recommended to use polygonsd
			* This parameter will not be used after the
			version number (httpversion) is equal or
			greater than 0400a.
			5. cator than o rooth

		1	
top	0 ~ 240	4/4	Top coordinate of window position.
<not recommended="" td="" to="" use<=""><td></td><td></td><td>* Only available when</td></not>			* Only available when
this>			"capability_motion_wintype" = rectangle.
			* Only available when qvga is listed in
			"capability_motion_windomain".
			* It's recommended to use polygonsd
			* This parameter will not be used after the
			version number (httpversion) is equal or
			greater than 0400a.
width	0 ~ 320	4/4	Width of motion detection window.
<not recommended="" td="" to="" use<=""><td></td><td></td><td>* Only available when</td></not>			* Only available when
this>			"capability_motion_wintype" = rectangle.
			* Only available when qvga is listed in
			"capability_motion_windomain".
			* It's recommended to use polygonsd
			* This parameter will not be used after the
			version number (httpversion) is equal or
			greater than 0400a.
height	0 ~ 240	4/4	Height of motion detection window.
<not recommended="" td="" to="" use<=""><td></td><td></td><td>* Only available when</td></not>			* Only available when
this>			"capability_motion_wintype" = rectangle.
			* Only available when qvga is listed in
			"capability_motion_windomain".
			* It's recommended to use polygonsd
			* This parameter will not be used after the
			version number (httpversion) is equal or
			greater than 0400a.

Group: motion\_c<0~(n-1)>\_profile\_i<0~(m-1)> for m profile and n channel product,

n denotes the value of "capability\_nvideoin", m denotes the vaule of " capability\_nmotionprofile ",

(capability\_nmotionprofile > 0)

N	AME	VALUE	SECURITY	DESCRIPTION
			(get/set)	
er	nable	<boolean></boolean>	4/4	Enable profile $1 \sim (m-1)$ .

policy	night, schedule	4/4	The mode which the profile is applied to.
			* Not support "policy=day" anymore when the version number (httpversion) is equal or greater than 0301a.
begintime	hh:mm	4/4	Begin time of schedule mode.
endtime	hh:mm	4/4	End time of schedule mode.
win_sensitivity	0 ~ 100	4/4	Sensitivity of all motion detection windows. * The value "0" is reserved for compatibility and will not be used after the version number (httpversion) is equal or greater than 0400a.

Group: **motion\_c<0~(n-1)>\_profile\_i<0~(m-1)>\_win\_i<0~(k-1)>** for m profile and n channel product, n denotes the value of "capability\_nvideoin", m denotes the value of "capability\_nmotionprofile",

k denotes the value of "capability\_nmotion".

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	4/4	Enable motion detection window.
name	string[14]	4/4	Name of motion window.
polygonstd	0 ~ 9999,0 ~ 9999,	4/4	Coordinate of polygon window position.
	0 ~ 9999,0 ~ 9999,		(4 points: x0,y0,x1,y1,x2,y2,x3,y3)
	0 ~ 9999,0 ~ 9999,		* Only available when
	0 ~ 9999,0 ~ 9999		"capability_motion_wintype" = polygon.
			* Only available when std is listed in "capability_motion_windomain
objsize	1 ~ 100	4/4	Percent of motion detection window.
sensitivity	0 ~ 100	4/4	Sensitivity of motion detection window.
<not recommended="" td="" to="" use<=""><td></td><td></td><td></td></not>			
this>			* We replace "sensitivity" with
			"win_sensitivity".
			* This parameter will not be used after the
			version number (httpversion) is equal or
			greater than 0400a.
polygonpx	0 ~ W,0 ~ H, 0 ~	4/4	Coordinate of polygon window position.
<not recommended="" td="" to="" use<=""><td>W,0 <math display="inline">\sim</math> H, 0 <math display="inline">\sim</math> W,0 <math display="inline">\sim</math></td><td></td><td>(4 points: x0,y0,x1,y1,x2,y2,x3,y3)</td></not>	W,0 $\sim$ H, 0 $\sim$ W,0 $\sim$		(4 points: x0,y0,x1,y1,x2,y2,x3,y3)
this>	H, 0 ~ W,0 ~ H		* Only available when
	W: 0~ The current		"capability_motion_wintype" = polygon.

	image width -1 H: 0~ The current image height -1		* Only available when px is listed in "capability_motion_windomain".
			<ul> <li>* It's recommended to use polygonsd</li> <li>* This parameter will not be used after the version number (httpversion) is equal or greater than 0400a.</li> </ul>
polygon <not recommended="" to="" use<br="">this&gt;</not>	0 ~ 320,0 ~ 240, 0 ~ 320,0 ~ 240, 0 ~ 320,0 ~ 240, 0 ~ 320,0 ~ 240	4/4	Coordinate of polygon window position. (4 points: x0,y0,x1,y1,x2,y2,x3,y3) * Only available when "capability_motion_wintype" = polygon.
			* Only available when qvga is listed in "capability_motion_windomain".
			<ul> <li>* It's recommended to use polygonsd</li> <li>* This parameter will not be used after the version number (httpversion) is equal or greater than 0400a.</li> </ul>
left <not recommended="" to="" use<br="">this&gt;</not>	0 ~ 320	4/4	Left coordinate of window position. * Only available when "capability_motion_wintype" = rectangle.
			* Only available when qvga is listed in "capability_motion_windomain".
			<ul> <li>* It's recommended to use polygonsd</li> <li>* This parameter will not be used after the version number (httpversion) is equal or greater than 0400a.</li> </ul>
top <not recommended="" to="" use<br="">this&gt;</not>	0 ~ 240	4/4	Top coordinate of window position. * Only available when "capability_motion_wintype" = rectangle.
			* Only available when qvga is listed in "capability_motion_windomain".
			<ul><li>* It's recommended to use polygonsd</li><li>* This parameter will not be used after the</li></ul>

			version number (httpversion) is equal or
			greater than 0400a.
width	0 ~ 320	4/4	Width of motion detection window.
<not recommended="" td="" to="" use<=""><td></td><td></td><td>* Only available when</td></not>			* Only available when
this>			"capability_motion_wintype" = rectangle.
			* Only available when qvga is listed in
			"capability_motion_windomain".
			* It's recommended to use polygonsd
			* This parameter will not be used after the
			version number (httpversion) is equal or
			greater than 0400a.
height	0 ~ 240	4/4	Height of motion detection window.
<not recommended="" td="" to="" use<=""><td></td><td></td><td>* Only available when</td></not>			* Only available when
this>			"capability_motion_wintype" = rectangle.
			* Only available when qvga is listed in
			"capability_motion_windomain".
			* It's recommended to use polygonsd
			* This parameter will not be used after the
			version number (httpversion) is equal or
			greater than 0400a.

# 7.15 Tampering detection settings

Group: **tampering\_c<0~(n-1)>** for n channel products (capability.tampering > 0)

n denotes the value of "capability\_nvideoin"

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	4/4	Enable or disable tamper detection.
threshold	0~100	4/4	Threshold of tamper detection.
duration	10~600	4/4	If tampering value exceeds the "threshold" for
			more than "duration" second(s), then tamper
			detection is triggered.
ignorewidth	0, <positive integer=""></positive>	1/7	Indicate the width to offset to start to analysis
			the image.
dark_enable	<boolean></boolean>	4/4	Enable or disable image too dark detection
dark_threshold	0~100	4/4	Threshold of image too dark detection
dark_duration	1~10	4/4	If image too dark value exceeds the
			"threshold" for more than "duration"
			second(s), then image too dark detection is
			triggered.
bright_enable	<boolean></boolean>	4/4	Enable or disable image too bright detection
bright_threshold	0~100	4/4	Threshold of image too bright detection
bright_duration	1~10	4/4	If image too bright value exceeds the
			"threshold" for more than "duration"
			second(s), then image too bright detection is
			triggered.
blurry_enable	<boolean></boolean>	4/4	Enable or disable image too blurry detection
blurry_threshold	0~100	4/4	Threshold of image too blurry detection
blurry_duration	1~10	4/4	If image too blurry value exceeds the
			"threshold" for more than "duration"
			second(s), then image too blurry detection is
			triggered.

# 7.16 DDNS

Group: **ddns** (capability.protocol.ddns > 0)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	6/6	Enable or disable the dynamic DNS.
provider	CustomSafe100,	6/6	Safe100 => safe100.net
	DyndnsDynamic,		DyndnsDynamic => dyndns.org (dynamic)
	DyndnsCustom,		DyndnsCustom => dyndns.org
	Safe100		CustomSafe100 =>
			Custom server using safe100 method
<provider>_hostname</provider>	string[128]	6/6	Your DDNS hostname.
<provider>_usernameem</provider>	string[64]	6/6	Your user name or email to login to the DDNS
ail			service provider
<provider>_passwordkey</provider>	string[64]	7/6	Your password or key to login to the DDNS
			service provider.
<provider>_servername</provider>	string[128]	6/6	The server name for safe100.
			(This field only exists if the provider is
			customsafe100)

# 7.17 Express link

### Group: expresslink

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	6/6	Enable or disable express link.
state	onlycheck,	6/6	Camera will check the status of network
	onlyoffline,		environment and express link URL
	checkonline,		
	badnetwork		
url	string[64]	6/6	The url user define to link to camera

# 7.18 UPnP presentation

#### Group: upnppresentation

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	6/6	Enable or disable the UPnP presentation
			service.

### 7.19 UPnP port forwarding

Group: upnpportforwarding

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	6/6	Enable or disable the UPnP port forwarding
			service.
upnpnatstatus	0~3	6/7	The status of UPnP port forwarding, used
			internally.
			0 = OK, 1 = FAIL, 2 = no IGD router, 3 = no
			need for port forwarding

## 7.20 System log

### Group: **syslog**

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enableremotelog	<boolean></boolean>	6/6	Enable remote log.
serverip	<ip address=""></ip>	6/6	Log server IP address.
serverport	514, 1025~65535	6/6	Server port used for log.
level	0~7	6/6	Levels used to distinguish the importance of
			the information:
			0: LOG_EMERG
			1: LOG_ALERT
			2: LOG_CRIT
			3: LOG_ERR
			4: LOG_WARNING
			5: LOG_NOTICE
			6: LOG_INFO
			7: LOG_DEBUG
setparamlevel	0~2	6/6	Show log of parameter setting.

	0: disable
	1: Show log of parameter setting set from
	external.
	2. Show log of parameter setting set from
	external and internal.

### 7.21 SNMP

### Group: **snmp** (capability.protocol.snmp > 0)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
v2	<boolean></boolean>	6/6	SNMP v2 enabled. 0 for disable, 1 for enable
v3	<boolean></boolean>	6/6	SNMP v3 enabled. 0 for disable, 1 for enable
secnamerw	string[31]	6/6	Read/write security name
secnamero	string[31]	6/6	Read only security name
authpwrw	string[8~128]	7/6	Read/write authentication password
authpwro	string[8~128]	7/6	Read only authentication password
authtyperw	MD5,SHA	6/6	Read/write authentication type
authtypero	MD5,SHA	6/6	Read only authentication type
encryptpwrw	string[8~128]	7/6	Read/write passwrd
encryptpwro	string[8~128]	7/6	Read only password
encrypttyperw	DES	6/6	Read/write encryption type
encrypttypero	DES	6/6	Read only encryption type
rwcommunity	string[31]	6/6	Read/write community
rocommunity	string[31]	6/6	Read only community
syslocation	string[128]	6/6	System location
syscontact	string[128]	6/6	System contact

# 7.22 Layout configuration

### Group: layout

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
logo_default	<boolean></boolean>	1/6	0 => Custom logo
			1 => Default logo
logo_link	string[128]	1/6	Hyperlink of the logo
	http://www.vivotek.		
	<u>com</u>		
logo_powerbyvvtk_hidden	<boolean></boolean>	1/6	0 => display the power by vivotek logo
			1 => hide the power by vivotek logo
custombutton_manualtrig	<boolean></boolean>	1/6	Show or hide manual trigger (VI) button in
ger_show			homepage
			0 -> Hidden
			1 -> Visible
theme_option	1~4	1/6	$1 \sim 3$ : One of the default themes.
			4: Custom definition.
theme_color_font	string[7]	1/6	Font color
theme_color_configfont	string[7]	1/6	Font color of configuration area.
theme_color_titlefont	string[7]	1/6	Font color of video title.
theme_color_controlback	string[7]	1/6	Background color of control area.
ground			
theme_color_configbackg	string[7]	1/6	Background color of configuration area.
round			
theme_color_videobackgr	string[7]	1/6	Background color of video area.
ound			
theme_color_case	string[7]	1/6	Frame color

### 7.23 Privacy mask

Group: **privacymask\_c<0~(n-1)>** for n channel products and m privacy mask window.

n denotes the value of "capability\_nvideoin" and m denotes the value of

"capability\_videoin\_c<0~(n-1)>\_nprivacymask"

NAME	VALUE	SECURITY (get/set)	DESCRIPTION
enable	<boolean></boolean>	4/4	Enable privacy mask.
win_i<0~(m-1)>_enable	<boolean></boolean>	4/4	Enable privacy mask window.
win_i<0~(m-1)>_name	string[14]	4/4	Name of the privacy mask window.
win_i<0~(m-1)>_left	0 ~ 320	4/4	Left coordinate of window position.
			* Only available when
			"capability_image_c<0~(n-1)>_privacymask
			_wintype" = rectangle.
win_i<0~(m-1)>_top	0 ~ 240	4/4	Top coordinate of window position.
			* Only available when
			"capability_image_c<0~(n-1)>_privacymask
			_wintype" = rectangle.
win_i<0~(m-1)>_width	0 ~ 320	4/4	Width of privacy mask window.
			* Only available when
			"capability_image_c<0~(n-1)>_privacymask
			_wintype" = rectangle.
win_i<0~(m-1)>_height	0 ~ 240	4/4	Height of privacy mask window.
			* Only available when
			"capability_image_c<0~(n-1)>_privacymask
			_wintype" = rectangle.
win_i<0~(m-1)>_polygo	0 ~ 320,0 ~ 240,	4/4	Coordinate of polygon window position.
n	0 ~ 320,0 ~ 240,		(4 points: x0,y0,x1,y1,x2,y2,x3,y3)
	0 ~ 320,0 ~ 240,		* Only available when
	0 ~ 320,0 ~ 240		"capability_image_c <n>_privacymask_winty</n>
			pe" = polygon.
			* Only available when qvga is listed in
			"capability_image_c<0~(n-1)>_privacymask windomain".
win_i<0~(m-1)>_polygo	0 ~ W,0 ~ H,	4/4	Coordinate of polygon window position.
npx	0 ~ W,0 ~ H,	,	(4 points: x0,y0,x1,y1,x2,y2,x3,y3)
r.	0 ~ W,0 ~ H,		* Only available when

	0 110		
	0 ~ W,0 ~ H		"capability_image_c<0~(n-1)>_privacymask
	W: 0~ The current		_wintype" = polygon.
	image width -1		
	H: 0~ The current		* Only available when px is listed in
	image height -1		"capability_image_c<0~(n-1)>_privacymask
			_windomain".
win_i<0~(m-1)>_polygo	0 ~ 9999,0 ~ 9999,	4/4	Coordinate of polygon window position.
nstd	0 ~ 9999,0 ~ 9999,		(4 points: x0,y0,x1,y1,x2,y2,x3,y3)
	0 ~ 9999,0 ~ 9999,		* Only available when
	0 ~ 9999,0 ~ 9999		"capability_image_c<0~(n-1)>_privacymask
			_wintype" = polygon.
			* Only available when std is listed in
			"capability_image_c<0~(n-1)>_privacymask
			_windomain".

### 7.24 3D Privacy mask

Group: privacymask3d\_c<0~(n-1)> for n channel products and m privacy mask window.

(capability\_image\_c<0~(n-1)>\_privacymask\_wintype = 3Drectangle)

n denotes the value of "capability\_nvideoin" and m denotes the value of

"capability\_videoin\_c<0~(n-1)>\_nprivacymask"

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	4/4	Enable the 3D privacy mask
color	0~"	4/4	Privacy mask color
	capability_image_c<0~(n-1)		
	>_privacymask_ncolor"-1		
win_i<0~(m-1)>_name	string[40]	4/4	Name of the privacy mask window.
win_i<0~(m-1)>_pan	"capability_ptz_c<0~(n-1)>	4/4	Pan position of window position.
	_minpan" ~		* Only available when bit0 of
	"capability_ptz_c<0~(n-1)>		"capability_camctrl_c<0~(n-1)>_buil
	_maxpan"		dinpt" is "1"
win_i<0~(m-1)>_tilt	"capability_ptz_c<0~(n-1)>	4/4	Tilt position of window position.
	_mintilt" ~		* Only available when bit1 of
	"capability_ptz_c<0~(n-1)>		"capability_camctrl_c<0~(n-1)>_buil
	_maxtilt"		dinpt" is "1"
win_i<0~(m-1)>_zoom	"capability_ptz_c<0~(n-1)>	4/4	Zoom position of window position.
	_minzoom" ~		

	"capability_ptz_c<0~(n-1)> _maxzoom"		
win_i<0~(m-1)>_fliped	<boolean></boolean>	4/4	Flip side of window position.
			0: Non-flip side
			1: Flip side

# 7.25 Capability

### Group: capability

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
api_httpversion	<string></string>	0/7	The version of VIVOTEK WebAPI with 4
	This number start		integers plus 1 alphabet, There are composed
	with 0301a.		by "major version", "minor version",
			"revision","_platform". ex: 0301a_1
			<u>Major version</u>
			Increase the major version when change,
			remove the old features/interfaces or the
			firmware has substantially change in
			architecture and not able to roll back to
			previous version. This may cause
			incompatibility with supporting software.
			Minor version
			Increase the minor version when add new
			features/interfaces without change the old
			features and interfaces.
			<u>Revision</u>
			Increase the revision when fix bugs without
			change any features of the output.
			_platform
			This is a constant, it is used to distinguish
			between different platforms
			API version format:
			MMmmr_k
			Where "MM" is the major version, "mm" is the
			minor version and "r" is the revision.
			'M' and 'm' and 'k' are decimal digit from 0 to 9,
			while 'r' is an alphabetic.

			EX: 0302b_1 => Major version = 03, minor
			version = 02, revision = b, platform = $1$
			The 4 integer numbers are WebAPI version, we
			use short name: [httpversion] for it in this
			document.
			The 5th character is model-based version for
			API bug-fix and it's default to "a".
			Ex: If some APIs in a model does not follow the
			API definition of 0301a_1, we will fix them and
			change this API value to 0301b_1.
bootuntimo	<positive integer=""></positive>	0/7	Server bootup time.
bootuptime		0/ /	
nir	0,	0/7	Number of IR interfaces.
<not anymore="" support=""></not>	<positive integer=""></positive>		(Recommand to use
			capability_daynight_c<0~"capability_nvideoi
			n"-1>_builtinir for built-in IR and
			capability_daynight_c<0~"capability_nvideoi
			n"-1>_externalir for external IR)
			* Not support this parameter anymore when
			the version number (httpversion) is equal or
			greater than 0301a.
npir	0,	0/7	Number of PIRs.
	<positive integer=""></positive>		
ndi	0,	0/7	Number of digital inputs.
	<positive integer=""></positive>		
nvi	0,	0/7	Number of virtual inputs (manual trigger)
	<positive integer=""></positive>		
ndo	0,	0/7	Number of digital outputs.
	<positive integer=""></positive>	-,	
naudioin	0,	0/7	The number of audio input channel. 0 means
nadaroni	<positive integer=""></positive>	0, 1	no audio input support.
naudioout	0,	0/7	The number of audio output channel
naudioodt	<pre>&gt; </pre> o, <	0,7	
nuideain		0/7	
nvideoin	<positive integer=""></positive>	0/7	Number of video inputs.
nvideoout	0, <positive< td=""><td>0/7</td><td>Number of video out interface.</td></positive<>	0/7	Number of video out interface.
nvideoout	0, <positive Integer&gt;</positive 	0/7	Number of video out interface.
nvideoout nvideoinprofile		0/7	Number of video out interface. Number of video input profiles.

naudiosetting	<positive integer=""></positive>	0/7	Number of audio settings per channel.
<not anymore="" support=""></not>			* Not support this parameter anymore when
			the version number (httpversion) is equal or
			greater than 0301a.
			* We replace "naudiosetting" with "naudioin".
			More details, please refer the parameter
			description of "volume_internal" and
			"volume_external".
nuart	0,	0/7	Number of UART interfaces.
	<positive integer=""></positive>		
nmotion	<positive integer=""></positive>	0/7	The number of motion window.
nmotionprofile	0, <positive< td=""><td>0/7</td><td>Number of motion profiles.</td></positive<>	0/7	Number of motion profiles.
	integer>		
ptzenabled	0, <positive< td=""><td>0/7</td><td>An 32-bit integer, each bit can be set</td></positive<>	0/7	An 32-bit integer, each bit can be set
	integer>		separately as follows:
			Bit 0 => Support camera control function;
			0(not support), 1(support)
			Bit $1 =>$ (only available when bit0 is 1)
			Built-in or external video source;
			0(external), 1(built-in)
			Bit $2 \Rightarrow$ (only available when bit0 is 1)
			Support pan operation;
			0(not support), 1(support)
			Bit $3 =>$ (only available when bit0 is 1)
			Support tilt operation;
			0(not support), 1(support)
			Bit $4 =>$ (only available when bit0 is 1)
			Support zoom operation;
			0(not support), 1(support)
			(only available when RS-485 interface is
			supported or SD/PZ/PT/PD/video server
			series)
			Bit 5 => (only available when bit0 is 1)
			Support focus operation;
			0(not support), 1(support)
			(only available when RS-485 interface is
			supported or SD/PZ/PT/PD/video server
			series)
			Bit 6 => (only available when bit0 is 1)
			Reserved bit; always 0.

			Bit 7 => (only available when bit0 is 1)
			External or built-in PT;
			0(built-in), 1(external)
windowless	<boolean></boolean>	0/7	Indicate whether to support windowless
			plug-in.
evctrlchannel	<boolean></boolean>	0/7	Indicate whether to support HTTP tunnel for
			event/control transfer.
joystick	<boolean></boolean>	0/7	Indicate whether to support joystick control.
remotefocus	0, <positive integer=""></positive>	0/7	An 4-bit integer, which indicates the supportive
<not recommended="" td="" to="" use<=""><td></td><td></td><td>application of remotefocus.</td></not>			application of remotefocus.
this>			If the value of this parameter is larger than 0,
			it means that the camera supports
			remotefocus function.
			bit 0 => Indicate whether to support both
			zoom and focus function.
			bit 1 => Only support zoom function.
			bit 2 => Only support focus function.
			bit 3 => Currently, this is a reserved bit, and
			the default value is 0.
			* It's strongly non-recommended to use this.
			* This is reserved for compatibility and will not
			be used after the version number (httpversion)
			is equal or greater than 0400a.
			* We replace "capability_remotefocus" with "
			capability_image_c0_remotefocus".
npreset	0, <positive< td=""><td>0/7</td><td>Number of preset locations</td></positive<>	0/7	Number of preset locations
	integer>		
presettourdirection	<boolean></boolean>	0/7	Indicate whether to support preset tour
			direction function. It means users can choose
			which direction the preset tour goes.
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0307a.
eptz	0, <positive< td=""><td>0/7</td><td>For "nvideoin" = 1, the definition is as</td></positive<>	0/7	For "nvideoin" = 1, the definition is as
	integer>		following:
			A 32-bits integer, each bit can be set
			separately as follows:

		1	1
			Bit 0 => 1st stream supports ePTZ or not.
			Bit 1 => 2nd stream supports ePTZ or not, and
			so on.
			For nvideoin $>= 2$ , the definition is different:
			First all 32 bits are divided into groups for
			channel.
			Ex:
			nvideoin = 2, bit $0 \sim 15$ are the 1st group for 1st
			channel, bit 16~31 are the 2nd group for 2nd
			channel.
			nvideoin = 3, bit $0 \sim 9$ are the 1st group for 1st
			channel, bit 10~19 are the 2nd group for 2nd
			channel, bit 20~31 are the 3rd group for 3rd
			channel.
			Then, the 1st bit of the group indicates 1st
			stream of a channel support ePTZ or not. The
			2nd bit of the group indicates 2nd stream of a
			channel support ePTZ or not, and so on.
			* For most products, the last stream of a
			channel will not support ePTZ. It is reserved
			for full view of the channel. For some
			dual-stream products, both streams support
			ePTZ.
nanystream	0, <positive< td=""><td>0/7</td><td>number of any media stream per channel</td></positive<>	0/7	number of any media stream per channel
	integer>		
iva	<boolean></boolean>	0/7	Indicate whether to support Intelligent Video
			analysis
whitelight	<boolean></boolean>	0/7	Indicate whether to support white light led.
iris	<boolean></boolean>	0/7	Indicate whether to support iris control.
supportsd	<boolean></boolean>	0/7	Indicate whether to support local storage.
fisheye	<boolean></boolean>	0/7	The parameter is used to determine whether
			the product is fisheye or not.
tampering	<boolean></boolean>	0/7	Indicate whether to support tampering
			detection.
tamperingmode	tamper,toodark,toob	0/7	Available tampering mode list.
	right,tooblurry		* Only available when "capability_tampering"
			is 1.

adaptiverecording	<boolean></boolean>	0/7	Indicate whether to support adaptive
			recording.
adaptivestreaming	<boolean></boolean>	0/7	Indicate whether to support adaptive
			streaming.
supporttriggertypes	seq,boot,motion,net	0/7	list all the trigger types which are supported in
	workfail,recnotify,ta		the camera:
	mpering,vi,vadp,di,		"seq" = Periodic condition
	volalarm,temperatu		"boot" = System boot
	re,pir, visignal,		"motion" = Video motion detection
	backup,smartsd,		"networkfail" = network connection failure
	shockalarm, virestor		"recnotify" = Recording notification.
	e		"tampering" = Tamper detection.
	<product< td=""><td></td><td>"vi" = Virtual input (Manual trigger)</td></product<>		"vi" = Virtual input (Manual trigger)
	dependent>		"vadp" = VADP trigger.
			"di"= Digital input.
			"volalarm" = Audio detection.
			"temperature" = Temperature detection.
			"pir" = PIR detection.
			"visignal" = Video input signal loss.
			"backup" = Backing up recorded files.
			"smartsd" = Lifetime detection of SD card.
			"shockalarm" = Shock detection.
			"visignal" = Video input signal restore.
			* Only available when [httpversion] >= 0301a
storage_dbenabled	<boolean></boolean>	0/7	Media files are indexed in database.
protocol_https	< boolean >	0/7	Indicate whether to support HTTP over SSL.
protocol_rtsp	< boolean >	0/7	Indicate whether to support RTSP.
protocol_sip	<boolean></boolean>	0/7	Indicate whether to support SIP.
protocol_maxconnection	<positive integer=""></positive>	0/7	The maximum number of allowed
			simultaneous connections.
protocol_maxgenconnecti	<positive integer=""></positive>	0/7	The maximum general streaming connections .
on			
protocol_rtp_multicast_sc	<boolean></boolean>	0/7	Indicate whether to support scalable multicast.
alable			
protocol_rtp_multicast_ba	<boolean></boolean>	0/7	Indicate whether to support backchannel
ckchannel			multicast.
protocol_rtp_tcp	<boolean></boolean>	0/7	Indicate whether to support RTP over TCP.

protocol_spush_mjpeg	<boolean></boolean>	0/7	Indicate whether to support server push MJPEG.
protocol_snmp	<boolean></boolean>	0/7	Indicate whether to support SNMP.
protocol_ipv6	<boolean></boolean>	0/7	Indicate whether to support IPv6.
protocol_pppoe	<boolean></boolean>	0/7	Indicate whether to support PPPoE.
protocol_ieee8021x	<boolean></boolean>	0/7	Indicate whether to support IEEE802.1x.
protocol_qos_cos	<boolean></boolean>	0/7	Indicate whether to support CoS.
protocol_qos_dscp	<boolean></boolean>	0/7	Indicate whether to support QoS/DSCP.
protocol_ddns	<boolean></boolean>	0/7	Indicate whether to support DDNS.
videoin_type	0, 1, 2	0/7	0 => Interlaced CCD 1 => Progressive CCD 2 => CMOS
videoin_nresolution	<positive integer=""></positive>	0/7	This equals "capability_videoin_c0_nresolution".
			* This is kept for compatibility.
videoin_resolution	A list of <wxh> <product dependent&gt;</product </wxh>	0/7	This equals "capability_videoin_c0_resolution".
			* This is kept for compatibility.
videoin_maxframerate	A list of <integer></integer>	0/7	This equals "capability_videoin_c0_maxframerate".
			* This is kept for compatibility.
videoin_mjpeg_maxframe rate	A list of <integer> and "-"</integer>	0/7	This equals "capability_videoin_c0_mjpeg_maxframerate ".
			* This is kept for compatibility.
videoin_h264_maxframer ate	A list of <integer> and "-"</integer>	0/7	This equals "capability_videoin_c0_h264_maxframerate".
			* This is kept for compatibility.
videoin_codec	mjpeg, h264, h265 <product dependent&gt;</product 	0/7	Available codec of a device, split by comma. The sequence is not limited. EX:

			FD8183 supports H.264 and MJPEG, then this
			is "mjpeg,h264".
			IP9171 supports H.264, MJPEG and H.265,
			then this is "mjpeg,h264,h265"
videoin_streamcodec	A list of <positive< td=""><td>0/7</td><td>This equals</td></positive<>	0/7	This equals
	Integer>		"capability_videoin_c0_streamcodec".
			* This is kept for compatibility.
videoin_flexiblebitrate	<boolean></boolean>	0/7	Indicate whether to support
			flexible bit rate control.
videoout_codec	A list of the available	0/7	Available codec list.
	codec types		"-": not supported
	separated by		
	commas		
	<product< td=""><td></td><td></td></product<>		
	dependent>		
timeshift	<boolean></boolean>	0/7	Indicate whether to support time shift caching
			stream.
audio_aec	<boolean></boolean>	0/7	Indicate whether to support acoustic echo
			cancellation.
audio_aecmode	auto,	0/7	Indicate the acoustic echo cancellation control
	manual		mode.
			"auto": control by camera automatically.
			"manual": Manually turn on/off the control
			mode.
			*Only available when
			capability_audio_aec" is "1".
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0306b.
audio_aecaffect	-,	0/7	When acoustic echo cancellation function is
	, maxframerate:fixed	,	enabled, some features may become
	:15		malfunction or be forced to a given value. The
	<product< td=""><td></td><td>affected functions are list here.</td></product<>		affected functions are list here.
	dependent>		
			The format is "Affect API
			name":"Policy":"Description"
			hame i rolley i Description
			"Policy" can be categorized into following

		1	
			groups:
			- (disabled) : UI turns grey and users can't
			select it.
			- (unchanged) : UI keeps the status as before
			and user can't change it.
			- (hidden) : UI is hidden.
			- (fixed) : UI is fixed to one selection or value.
			- (ranged) : UI is fixed to multiple selections or
			values.
			- (enabled) : UI is checked.
			- (notsupport) : the affected function is not
			available.
			"Affect API name" can be described in
			hierarchy, such as
			"exposurewin.mode.blc:disabled:" which
			means blc exposure window is disabled. API
			name can be one word as well, such as
			"exposurelevel:fixed:6" which means
			exposurelevel is fixed to level 6.
			"Description" can be a nonnegative integer or
			string or NULL.
			For example:
			"maxframerate:fixed:15" which means the
			max frame rate is 15fps when acoustic echo
			cancellation function is enabled.
			"-" means no feature is affected.
			* Only available when "capability_audio_aec"
			is "1".
			* We support this parameter when the version
			number (httpversion) is equal or greater than
		o (7	0306b.
audio_mic	<boolean></boolean>	0/7	Indicate whether to support built-in
<not anymore="" support=""></not>			microphone input.
			* Not support this parameter anymore when
			the version number (httpversion) is equal or
			greater than 0301a.
			* We replace "audio_mic" with "audio_intmic".

Γ			
audio_intmic	<0~Positive	0/7	Internal (Built-in) Microphone.
	Integer>		0: Not support
			1: Support
			Bit 0 for CH0, bit 1 for CH1, and so on.
audio_extmic	<0~Positive	0/7	External Microphone.
	Integer>		0: Not support
			1: Support
			Bit 0 for CH0, bit 1 for CH1, and so on.
audio_alarm	<0~Positive	0/7	0: Not support audio alarm.
	Integer>		1: Support audio alarm.
			Bit 0 for CH0, bit 1 for CH1, and so on.
audio_linein	<boolean></boolean>	0/7	Indicate whether to support external line
<not anymore="" support=""></not>			input.
			* Not support this parameter anymore when
			the version number (httpversion) is equal or
			greater than 0301a.
			* It will be replaced by audio_intmic and
			audio_extmic.
audio_lineout	<boolean></boolean>	0/7	Indicate whether to support line output.
audio_michardwareswitch	<boolean></boolean>	0/7	Indicate whether the hardware supports
			built-in/external mic switch
audio_headphoneout	<boolean></boolean>	0/7	Indicate whether to support headphone
<not anymore="" support=""></not>			output.
			* Not support this parameter anymore when
			the version number (httpversion) is equal or
			greater than 0301a.
audioin_codec	aac4, gamr, g711,	0/7	Available audio codec. We take comma to split
	g726, -	0/7	codec without any space.
	<product< td=""><td></td><td>couec without any space.</td></product<>		couec without any space.
	dependent>		aac4: Advanced Audio Coding (AAC)
	dependent>		
			gamr: Adaptive Multi-Rate (AMR)
			g711: G.711
			g726: G.726
	~711	0/7	-: Not supported.
audioout_codec	g711, -	0/7	Available codec list for SIP.
	<pre><pre>product</pre></pre>		-: Not supported.
	dependent>		
motion_wintype	rectangle, polygon	0/7	The supported motion window type.

			polygon: The window is a 2D polygon shape.
			rectangle: The window is a 2D rectangle shape.
motion_windomain	qvga, px, std, -	0/7	The domain to set an motion window.
		-,-	qvga: a 320x240 range to represent the whole
			image.
			px: Locate a window in the image with pixels.
			std: A normalized 0~9999 range.
			-: Not supported.
smartstream_support	<boolean></boolean>	0/7	Indicate whether smart stream is supported.
smartstream_version	<integer></integer>	0/7	Number of smart stream version
smartstream_nstream	<positive integer=""></positive>	0/7	Number of stream that support smart stream.
			* Only available when
			"capability_smartstream_support" is 1
smartstream_windomain	qvga, px, std, -	0/7	The domain to set an focus window.
			qvga: a 320x240 range to represent the whole
			image.
			px: Locate a window in the image with pixels.
			std: A normalized 0~9999 range.
			-: Not supported.
			* Only available when
			"capability_smartstream_support" is 1
smartstream_mode_autot	<boolean></boolean>	0/7	Indicate whether autotracking smart stream is
racking			supported.
			* Only available when
			"capability_smartstream_support" is 1
smartstream_mode_man	<boolean></boolean>	0/7	Indicate whether manual smart stream is
ual			supported.
			* Only available when
			"capability_smartstream_support" is 1
smartstream_mode_hybri	<boolean></boolean>	0/7	Indicate whether hybrid(autotracking+
d			manual) smart stream is supported.
			* Only available when
			"capability_smartstream_support" is 1
smartstream_nwindow_a	<positive integer=""></positive>	0/7	Maximum number of tracking window of
utotracking			autotracking.
			* Only available when
			"capability_smartstream_support" is 1
smartstream_nwindow_m	<positive integer=""></positive>	0/7	Maximum number of tracking window of

anual			manual.
			* Only available when
			"capability_smartstream_support" is 1
amartatroam pwindow h	constitue integers	0/7	Maximum number of tracking window of
smartstream_nwindow_h	<positive integer=""></positive>	0/7	5
ybrid_autotracking			autotracking in hybrid mode.
			* Only available when
			"capability_smartstream_support" is 1
smartstream_nwindow_h	<positive integer=""></positive>	0/7	Maximum number of tracking window of
ybrid_manual			manual in hybrid mode.
			* Only available when
			"capability_smartstream_support" is 1
vadp_supportfeature	<positive integer=""></positive>	0/7	An 32-bit integer, each bit can be set
			separately as follows:
			Bit 0 => VADP interface
			Bit 1 => Capture video raw data
			Bit 2 => Support encode jpeg
			Bit 3 => Capture audio raw data
			Bit 4 => Support event trigger
			Bit 5 => Support license registration
			Bit 6 => Support shared memory API
			Bit 7 => Support digital signature of package
			Bit 8 => Support snapshot
vadp_npackage	<positive integer=""></positive>	0/7	Indicate the maximum number of VADP
			package that can be uploaded to the device.
camctrl_httptunnel	<boolean></boolean>	0/7	Indicate whether to support httptunnel.
<not anymore="" support=""></not>			* Not support this parameter anymore when
			the version number (httpversion) is equal or
			greater than 0301b.
			* It will be replaced by
			capability_camctrl_ptztunnel.
camctrl_ptztunnel	<boolean></boolean>	0/7	Indicate whether to support ptztunnel.
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0301b.
			This equals
			"capability_camctrl_c0_ptztunnel".
			* This is kept for compatibility
competed privilege	chaologra	0/7	* This is kept for compatibility.
camctrl_privilege	<boolean></boolean>	0/7	Indicate whether to support "Manage
			Privilege" of PTZ control in the security page.

	1		1
			1: support both /cgi-bin/camctrl/camctrl.cgi
			and /cgi-bin/viewer/camctrl.cgi
			0: support only /cgi-bin/viewer/camctrl.cgi
			This is equivalent
			to"capability_camctrl_c0_privilege".
			* This is kept for compatibility.
uart_httptunnel	<boolean></boolean>	0/7	Indicate whether to support HTTP tunnel for
			UART transfer.
transmission_mode	Tx,	0/7	Indicate transmission mode of the machine:
	Rx,		TX = server, Rx = receiver box, Both = DVR.
	Both		
network_wire	<boolean></boolean>	0/7	Indicate whether to support Ethernet.
network_wireless	<boolean></boolean>	0/7	Indicate whether to support wireless.
network_dualmode	<boolean></boolean>	0/7	Indicate whether network dual mode is
			supported.
			* Only available when
			"capability_network_wireless" is "1".
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0305a.
wireless_s802dot11b	<boolean></boolean>	0/7	Indicate whether to support wireless
			802.11b+.
wireless_s802dot11g	<boolean></boolean>	0/7	Indicate whether to support wireless 802.11g.
wireless_s802dot11n	<boolean></boolean>	0/7	Indicate whether to support wireless 802.11n.
wireless_beginchannel	1 ~ 14	0/7	Indicate the begin channel of wireless network
wireless_endchannel	1 ~ 14	0/7	Indicate the end channel of wireless network
wireless_encrypt_wep	<boolean></boolean>	0/7	Indicate whether to support wireless WEP.
wireless_encrypt_wpa	<boolean></boolean>	0/7	Indicate whether to support wireless WPA.
wireless_encrypt_wpa2	<boolean></boolean>	0/7	Indicate whether to support wireless WPA2.
wireless_apmode_enable	<boolean></boolean>	0/7	Indicate whether wireless AP mode is
			supported.
			* Only available when
			* Only available when
			"capability_network_wireless" is "1".
			* We support this parameter when the version

		1	number (httpversion) is equal or greater than
			0305a.
wireless_apmode_ssidpref	<string></string>	0/7	Indicate the prefix of broadcasted SSID when
ix	(String)	0,7	camera is in wireless AP mode.
			* Only available when
			"capability_wireless_apmode_enable" is "1".
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0305a.
derivative_brand	<boolean></boolean>	0/7	Indicate whether to support the upgrade
			function for the derivative brand. For example,
			if the value is true, the VVTK product can be
			upgraded to VVXX. (TCVV<->TCXX is
			excepted)
test_ac	<boolean></boolean>	0/7	Indicate whether to support test ac key.
version_onvifdaemon	<string></string>	0/7	Indicate ONVIF daemon version
version_onviftesttool	<string></string>	0/7	Indicate ONVIF test tool version
media_totalspace	<positive integer=""></positive>	0/7	Available memory space (KB) for media.
media_snapshot_maxpre	<positive integer=""></positive>	0/7	Maximum snapshot number before event
event			occurred.
media_snapshot_maxpost	<positive integer=""></positive>	0/7	Maximum snapshot number after event
event			occurred.
media_snapshot_maxsize	<positive integer=""></positive>	0/7	Maximum size (KB) of a snapshot.
media_videoclip_maxsize	<positive integer=""></positive>	0/7	Maximum size (KB) of a videoclip.
media_videoclip_maxleng	<positive integer=""></positive>	0/7	Maximum length (second) of a videoclip.
th			
media_videoclip_maxpree	<positive integer=""></positive>	0/7	Maximum duration (second) after event
vent			occurred in a videoclip.
image_iristype	<string></string>	0/7	Indicate iris type.
<not recommended="" td="" to="" use<=""><td></td><td></td><td>• "piris": P-Iris</td></not>			• "piris": P-Iris
this>			• "dciris": DC-Iris
			• "-": No Iris control support
			* When "capability_iris"=0, this value must be
			"-"
			• * Note: For some box-type cameras, this value
			may be varied depending on mounted lens.
			may be varied depending on mounted ichs.

Γ		1	1
			* We replace "capability_image_iristype" with
			"capability_image_c0_iristype".
			* Reserved for compatibility, and suggest don't
			use this since [httpversion] > 0301a
image_focusassist	<boolean></boolean>	0/7	Indicate whether to support focus assist.
<not recommended="" td="" to="" use<=""><td></td><td></td><td>* We replace "capability_image_ focusassist "</td></not>			* We replace "capability_image_ focusassist "
this>			with "capability_image_c0_ focusassist".
			* Reserved for compatibility, and suggest don't
			use this since [httpversion] > 0301a
localstorage_manageable	<boolean></boolean>	0/7	Indicate whether manageable local storage is
			supported.
			* Only available when "capability_supportsd"
			is 1 or "capability_storage_dbenabled" is 1.
localstorage_seamless	<boolean></boolean>	0/7	Indicate whether seamless recording is
			supported.
			* Only available when "capability_supportsd"
			is 1 or "capability_storage_dbenabled" is 1.
localstorage_modnum	0,	0/7	The maximum MOD connection numbers.
	<positive integer=""></positive>		* Only available when "capability_supportsd"
			is 1 or "capability_storage_dbenabled" is 1.
localstorage_modversion	<string></string>	0/7	Indicate MOD daemon version.
	-		* Only available when "capability_supportsd"
			is 1 or "capability_storage_dbenabled" is 1.
localstorage_stormgrversi	<string></string>	0/7	Indicate storage manager daemon version.
on	_		* Only available when "capability_supportsd"
			is 1 or "capability_storage_dbenabled" is 1.
localstorage_supportedge	0,	0/7	An 32-bit integer, which indicates the
	<positive integer=""></positive>		supportive application of edge storage.
			If the value of this parameter is larger than 0,
			it means that the camera supports edge
			recording function.
			bit 0 : It supports to record directly to an
			on-board SD-Card.
			bit 1~: Currently, they are reserved bit, and
			the default value is 0.
			* Only available when "capability_supportsd"
			is 1 or "capability_storage_dbenabled" is 1.
localstorage_slconnum	0, <positive integer=""></positive>	0/7	The maximum seamless connection number.
localscoluge_sicolinam			* Only available when "capability_supportsd"
			City available when capability_supportsu

			is 1 or "capability_storage_dbenabled" is 1.
localstorage_smartsd	<boolean></boolean>	0/7	The "Lifetime and Log SD Card" feature allows
			users to obtain the card's remaining lifetime
			information.
			0: Non-support this feature
			1: Support this feature
			* Only Sony SD card can support this function
			now.
			* Only available when "capability_supportsd"
			is 1 or "capability_storage_dbenabled" is 1.
remotecamctrl_master	0, <positive< td=""><td>0/7</td><td>Indicate whether to support remote auxiliary</td></positive<>	0/7	Indicate whether to support remote auxiliary
	integer>		camera (master side), this value means
			supporting max number of auxiliary camera.
remotecamctrl_slave	<boolean></boolean>	0/7	Indicate whether to support remote camera
			control (slave side).
fisheyelocaldewarp_c<0~	0, <positive< td=""><td>0/7</td><td>Indicate the supported streams of local</td></positive<>	0/7	Indicate the supported streams of local
(capability_nvideoin)-1>	integer>		dewarp. One bit represents one supported
<product dependent=""></product>			stream. The LSB indicates stream 0.
			Ex: "3" means stream 0 and stream 1 support
			local dewarp.
			* Only available when "capability_fisheye" > 0
shockalarm_support	<boolean></boolean>	0/7	Indicate whether to support the shock
			detection.
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0306e.

### Group: capability\_camctrl\_c<0~(n-1)> n denotes the value of "capability\_nvideoin"

(capability\_ptzenabled > 0)

st We support this group when the version number (httpversion) is equal or greater than 0303b.

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
ptztunnel	<boolean></boolean>	0/7	Indicate whether to support ptztunnel in this
			video input.

privilege	<boolean></boolean>	0/7	Indicate whether to support "Manage Privilege"
			of PTZ control in the security page in this video
			input.
			1: support both /cgi-bin/camctrl/camctrl.cgi and
			/cgi-bin/viewer/camctrl.cgi
			0: support only /cgi-bin/viewer/camctrl.cgi
rs485	<boolean></boolean>	0/7	An 32-bit integer, each bit can be set separately
			as follows:
			Bit 0 => support rs485-in
			Bit 1 => support rs485-out
buildinpt	<boolean></boolean>	0/7	An 32-bit integer, each bit can be set separately
			as follows:
			Bit 0 => support build-in pan
			Bit 1 => support build-in tilt
zoommodule	<boolean></boolean>	0/7	Indicate whether to support zoom lens. In our
			product, only SD series and IZ series use the
			zoom lens.
			* Both varifocal and zoom lenses are built with
			movable elements that permit changing the
			effective focal length. And the key difference
			between a varifocal and a zoom lens can be
			explained by thinking about a lens that has been
			focused on an object at any focal length. A
			varifocal will need to be refocused whenever the
			focal length is adjusted; the zoom will stay in
			focus when the focal length is adjusted.

focusmode	auto,onetimeauto,spo 0/7	Focus mode selection:
	tlight,manual	"auto": Camera will automatically adjust the
	<product dependent=""></product>	focus position full time to adapt a clear picture.
		"onetimeauto": Camera will automatically
		adjust the focus position one time, which follows
		any PTZ control.
		"spotlight": Camera will automatically adjust
		the focus position full time, and to consider a
		spotlight avoidance situation.
		"manual": Turn off the automatically focus
		function. For user to control the focus position
		manually as their purpose.
		* Only available when
		"capability_camctrl_c<0~(n-1)_zoommodule"
		is 1.
		* We support this parameter when the version
		number (httpversion) is equal or greater than
		0304a.

Group: capability\_ptz\_c<0~(n-1)> n denotes the value of "capability\_nvideoin"

(capability\_ptzenabled > 0 and capability\_camctrl\_c< $0\sim(n-1)>$ \_zoommodule !=0)

\* We support this group when the version number (httpversion) is equal or greater than 0303b.

PARAMETER	VALUE	SECURITY (get/set)	DESCRIPTION
panspeedlv	0, <positive integer=""></positive>	0/7	The maximum speed level of pan motion. *Only available when bit0 of "capability_camctrl_c<0~(n-1)>_buildinpt" is "1"
minpan	0, <positive integer=""></positive>	0/7	The lower limit for pan position. *Only available when bit0 of "capability_camctrl_c<0~(n-1)>_buildinpt" is "1"
maxpan	0, <positive integer=""></positive>	0/7	The upper limit for pan position. *Only available when bit0 of "capability_camctrl_c<0~(n-1)>_buildinpt" is "1"
minpanangle	<integer></integer>	0/7	The lower limit for pan angle. *Only available when bit0 of "capability_camctrl_c<0~(n-1)>_buildinpt" is "1"

maxpanangle	<integer></integer>	0/7	The upper limit for pan angle.
inaxpanangie	tinteger	0, ,	*Only available when bit0 of
			"capability_camctrl_c<0~(n-1)>_buildinpt" is
			"1"
tiltspeedlv	0, <positive integer=""></positive>	0/7	The maximum speed level of tilt motion.
			*Only available when bit1 of
			"capability_camctrl_c<0~(n-1)>_buildinpt" is
			"1"
mintilt	0, <positive integer=""></positive>	0/7	The lower limit for tilt position.
			*Only available when bit1 of
			"capability_camctrl_c<0~(n-1)>_buildinpt" is
			"1"
maxtilt	0, <positive integer=""></positive>	0/7	The upper limit for tilt position.
			*Only available when bit1 of
			"capability_camctrl_c<0~(n-1)>_buildinpt" is
			"1"
mintiltangle	<integer></integer>	0/7	The lower limit for tilt angle.
			*Only available when bit1 of
			"capability_camctrl_c<0~(n-1)>_buildinpt" is
			"1"
maxtiltangle	<integer></integer>	0/7	The upper limit for tilt angle.
			*Only available when bit1 of
			"capability_camctrl_c<0~(n-1)>_buildinpt" is
			"1"
zoomspeedlv	0, <positive integer=""></positive>	0/7	The maximum speed level of zoom motion.
			*Only available when the value of
			"capability_camctrl_c<0~(n-1)>_zoommodule"
			is "1"
minzoom	0, <positive integer=""></positive>	0/7	The lower limit for zoom position.
			*Only available when the value of
			"capability_camctrl_c<0~(n-1)>_zoommodule"
			is "1"
maxzoom	0, <positive integer=""></positive>	0/7	The upper limit for zoom position.
			*Only available when the value of
			"capability_camctrl_c<0~(n-1)>_zoommodule"
			is "1"
maxdzoom	0, <positive integer=""></positive>	0/7	The upper limit for digital zoom position.
			*Only available when the value of
			"capability_camctrl_c<0~(n-1)>_zoommodule"
			is "1"

focusspeedlv	0, <positive integer=""></positive>	0/7	The maximum speed level of focus motion. *Only available when the value of "capability_camctrl_c<0~(n-1)>_zoommodule"
minfocus	0, <positive integer=""></positive>	0/7	is "1" The lower limit for focus position.
		0, ,	*Only available when the value of
			"capability_camctrl_c<0~(n-1)>_zoommodule" is "1"
maxfocus	0, <positive integer=""></positive>	0/7	The upper limit for focus position.
			*Only available when the value of
			"capability_camctrl_c<0~(n-1)>_zoommodule"
			is "1"

### Group: capability\_daynight\_c<0~(n-1)> n denotes the value of "capability\_nvideoin"

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
support	<boolean></boolean>	0/7	Indicate whether the camera supports day/night
			mode switch
builtinir	<boolean></boolean>	0/7	Indicate whether to support built-in IR led.
externalir	<boolean></boolean>	0/7	Indicate whether to support external IR led.
optimizedir	<boolean></boolean>	0/7	Indicate whether to support optimized IR control
			technology.
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0307b.
smartir	<boolean></boolean>	0/7	Indicate whether to support smart IR.
ircutfilter	<boolean></boolean>	0/7	Indicate whether to support IR cut.
lightsensor	<boolean></boolean>	0/7	Indicate whether to support light sensor.
blackwhitemode	<boolean></boolean>	0/7	Indicate whether to support automatically
			switch to Black & White display during the night
			mode.
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0302a.

ircutsensitivity_type	<string></string>	0/7	Indicate the cgi interface of
			"ircutcontrol_sensitivity".
			"options": the value of
			"ircutcontrol_sensitivity" parameter is "low,
			normal,high".
			"normalize": the value of
			"ircutcontrol_sensitivity" parameter is "1~100"
			"-":not support
			* Only available when
			"capability_daynight_c<0~(n-1)>_support" is
			1.
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0302a.
ircutsensitivity_supportlevel	0,	0/7	The value indicate the support strength level of
	<positive integer=""></positive>		ircutsensitivity.
			* Only available when
			"capability_daynight_c<0~(n-1)>_support" is 1
			and
			"capability_daynight_c<0~(n-1)>_ircutsensitivi
			ty_type" is not "-".
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0302a.
extled_interface	do,irring	0/7	The device interface of external IR led:
	<product dependent=""></product>		"do": digital output
			"irring": IR ring
			* Only available when
			"capability_daynight_c<0~(n-1)>_externalir" is
			1
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0304a.

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
lens_type	fisheye, fixed,	0/7	The lens type of this channel.
	varifocal, changeable,		fisheye: Fisheye lens
	motor, -		fixed: Build-in fixed-focus lens.
	<product dependent=""></product>		varifocal: Build-in varifocal lens.
			changeable: changeable lens. Like box-type
			camera, users can install any C-Mount or
			CS-Mount lens as they wish.
			motor: Lens with motor to support zoom, focus,
			etc.
			-: N/A
			* Only available when [httpversion] >= 0301a
rotation	<boolean></boolean>	0/7	Indicate current mode whether support video
			rotation

# Group: **capability\_videoin\_c<0~(n-1)>** n denotes the value of "capability\_nvideoin"

rotationaffect	-	0/7	When rotation is enabled, some features may
	<product dependent=""></product>		become malfunction or be forced to a given
			value. The affected functions are list here.
			The format is "Affect API
			name":"Policy":"Description"
			"Policy" can be categorized into following
			groups:
			- (disabled) : UI turns grey and users can't select
			it.
			- (unchanged) : UI keeps the status as before
			and user can't change it.
			- (hidden) : UI is hidden.
			- (fixed) : UI is fixed to one selection or value.
			- (ranged) : UI is fixed to multiple selections or
			values.
			- (enabled) : UI is checked.
			- (notsupport) : the affected function is not
			available.
			"Affect API name" can be described in hierarchy,
			such as "exposurewin.mode.blc:disabled:"
			which means blc exposure window is disabled.
			API name can be one word as well, such as
			"exposurelevel:fixed:6" which means
			exposurelevel is fixed to level 6.
			"Description" can be a nonnegative integer or
			string or NULL.
			"-" means no feature is affected.
			* When "rotation"=0, this value must be "-"
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0304b.

streamcodec	<positive integer=""></positive>	0/7	Represent supported codec types of each
			stream.
			This contains a list of positive integers, split by
			comma. Each one stands for a stream, and the
			definition is as following:
			Bit 0: Support MPEG4.
			Bit 1: Support MJPEG
			Bit 2: Support H.264
			Bit 3: Support H.265
mode	0, <positive integer=""></positive>	0/7	Indicate current video mode.
nmode	<positive integer=""></positive>	0/7	Indicate how many video modes supported by
			this channel.
maxsize	<wxh></wxh>	0/7	The maximum resolution of all modes in this
			channel, the unit is pixel.
nprivacymask	0, <positive integer=""></positive>	0/7	Number of privacy mask per channel
nresolution	<positive integer=""></positive>	0/7	The maximum resolution options (listed in
			"resolution") in current video mode.
resolution	A list of <wxh></wxh>	0/7	Resolution options in current video mode. These
	<product dependent=""></product>		options are the possible options for
			"videoin_c <n>_s<m>_resolution".</m></n>
			The last one is the maximum resolution in
			current mode.
maxresolution	A list of <integer></integer>	0/7	Represent supported maximum resolution of
			each stream in current video mode.
			* The element number is defined as
			"capability_nmediastream".
minresolution	A list of <integer></integer>	0/7	Represent supported minimum resolution of
			each stream in current video mode.
			* The element number is defined as
			"capability_nmediastream".
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0304b.

maxframerate	A list of <integer></integer>	0/7	Indicate frame rate that the video source
	5	,	outputs in current video mode.
			One to one mapping to the resolution in
			"resolution".
			* The element number is defined as
			"nresolution" in this group.
			* This parameter may be changed when
			"videoin_c <n>_cmosfreq"=50 or</n>
			"videoin_c <n>_modulation"=pal.</n>
			Ex: 30 fps is changed to 25 fps, 60 fps is changed
			to 50 fps, and so on.
mjpeg_maxframerate	A list of <positive< td=""><td>0/7</td><td>Maximum fps that the device can encoded with</td></positive<>	0/7	Maximum fps that the device can encoded with
	Integer> and "-"		MJPEG on resolutions in current video mode.
			"-" means not support.
			* One to one mapping to the resolution in
			"resolution".
			* The element number is defined as
			"nresolution" in this group.
			* This parameter may be changed when
			"videoin_c <n>_cmosfreq"=50 or</n>
			"videoin_c <n>_modulation"=pal.</n>
			Ex: 30 fps is changed to 25 fps, 60 fps is
			changed to 50 fps, and so on.
			* Only available when 'mjpeg' is listed in
			"capability_videoin_codec".
mjpeg_maxbitrate	<positive integer="">, -</positive>	0/7	Maximum bitrates of MJPEG.
			The unit is bps.
			"-" means MJPEG does not support bit rate
			control.
			* Only available when 'mjpeg' is listed in
			"capability_videoin_codec".

h264_maxframerate	A list of <positive< th=""><th>0/7</th><th>Maximum fps that the device can encoded with</th></positive<>	0/7	Maximum fps that the device can encoded with
	Integer> and "-"		H.264 on resolutions in current video mode.
			"-" means not support.
			* One to one mapping to the resolution in
			"resolution".
			* The element number is defined as
			"nresolution" in this group.
			* This parameter may be changed when
			"videoin_c <n>_cmosfreq"=50 or</n>
			"videoin_c <n>_modulation"=pal.</n>
			Ex: 30 fps is changed to 25 fps, 60 fps is
			changed to 50 fps, and so on.
			* Only available when 'h264' is listed in
			"capability_videoin_codec".
h264_maxbitrate	<positive integer=""></positive>	0/7	Maximum bitrates of H.264.
			The unit is bps.
			* Only available when 'h264' is listed in
			"capability_videoin_codec".
h265_maxframerate	A list of <positive< td=""><td>0/7</td><td>Maximum fps that the device can encoded with</td></positive<>	0/7	Maximum fps that the device can encoded with
	Integer> and "-"		H.265 on resolutions in current video mode.
			"-" means not support.
			* One to one mapping to the resolution in
			"resolution".
			* The element number is defined as
			"nresolution" in this group.
			* This parameter may be changed when
			"videoin_c <n>_cmosfreq"=50 or</n>
			"videoin_c <n>_modulation"=pal.</n>
			Ex: 30 fps is changed to 25 fps, 60 fps is
			changed to 50 fps, and so on.
			* Only available when 'h265' is listed in
			"capability_videoin_codec".
h265_maxbitrate	<positive integer=""></positive>	0/7	Maximum bitrates of H.265.
			The unit is bps.
			* Only available when 'h265' is listed in
			"capability_videoin_codec".

fisheye_mounttype	ceiling, wall, floor	0/7	Indicate the supported type.
<product dependent=""></product>	<product dependent=""></product>		wall mount: 180° panoramic view
			ceiling mount: 360° surround view without blind
			spots
			floor mount: 360° surround view without blind
			spots
			* Only available when "capability_fisheye" > 0
dintraperiod_support	<boolean></boolean>	0/7	0: Non-support "Dynamic intra frame period"
			1: Support "Dynamic intra frame period"
			"Dynamic intra frame period" can be used to
			reduce bitrate by reducing the number of
			I-frame.
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0301c.
cameraunit_name	CU8131,	0/7	A "camera unit" name of a split-type camera
	CU8171,		system, which the camera unit and the video
	CU8161-H,		core are separated.
	СU8162-Н,		-: If the camera is not a split-type camera
	СU8163-Н,		system, the value of this parameter is "-".
	СU8361-Н,		
	,		* We support this parameter when the version
	-		number (httpversion) is equal or greater than
	<product dependent=""></product>		0302b.
cmosfreq_support	<boolean></boolean>	0/7	0: The power line frequency(50/60Hz) is
			detected by camera automatically.
			1: The power line frequency(50/60Hz) can be
			set by user.
			$^{st}$ We support this parameter when the version
			number (httpversion) is equal or greater than
			0308a.

#### Group: capability\_videoin\_c<0~(n-1)>\_localdewarp

#### (capability\_fisheyelocaldewarp\_c<0~(capability\_nvideoin)-1> > 0)

n denotes the value of "capability\_nvideoin"

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
typeceilingmount	10, 1P, 2P, 1R, 4R	0/7	Available dewarp types of ceiling and floor
			mount.

typewallmount	10, 1P, 1R, 4R	0/7	Available dewarp types of wall mount.
resolutionC1P	A list of <wxh></wxh>	0/7	Available resolutions of 1P mode of ceiling and
			floor mount.
resolutionC2P	A list of <wxh></wxh>	0/7	Available resolutions of 2P mode of ceiling and
			floor mount.
resolutionC1R	A list of <wxh></wxh>	0/7	Available resolutions of 1R mode of ceiling and
			floor mount.
resolutionC4R	A list of <wxh></wxh>	0/7	Available resolutions of 4R mode of ceiling and
			floor mount.
resolutionW1P	A list of <wxh></wxh>	0/7	Available resolutions of 1P mode of wall mount.
resolutionW1R	A list of <wxh></wxh>	0/7	Available resolutions of 1R mode of wall mount.
resolutionW4R	A list of <wxh></wxh>	0/7	Available resolutions of 4R mode of wall mount.

Group: capability\_videoin\_c<0~(n-1)>\_mode<0~(m-1)> n denotes the value of "capability\_nvideoin", m

denotes the value of "capability\_videoin\_c<0~(n-1)>\_nmode"

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
rotation	<boolean></boolean>	0/7	Indicate this mode whether support video
			rotation

eptz	0, <positive integer=""></positive>	0/7	Indicate this mode whether support eptz.
			For "nvideoin" = 1, the definition is as following:
			A 32-bits integer, each bit can be set separately
			as follows:
			Bit $0 = > 1$ st stream supports ePTZ or not.
			Bit 1 => 2nd stream supports ePTZ or not, and
			so on.
			For nvideoin >= 2, the definition is different:
			First all 32 bits are divided into groups for
			channel.
			Ex:
			nvideoin = 2, bit $0 \sim 15$ are the 1st group for 1st
			channel, bit 16~31 are the 2nd group for 2nd
			channel.
			nvideoin = 3, bit $0 \sim 9$ are the 1st group for 1st
			channel, bit 10~19 are the 2nd group for 2nd
			channel, bit 20~31 are the 3rd group for 3rd
			channel.
			Then, the 1st bit of the group indicates 1st
			stream of a channel support ePTZ or not. The
			2nd bit of the group indicates 2nd stream of a
			channel support ePTZ or not, and so on.
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0304b.
wdrpro	0, 1, 2	0/7	Indicate this mode whether support WDR pro.
			0: Non-support WDR Pro
			1: Support WDR Pro
			2: Support WDR Pro and WDR Pro II
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0304b.

effectivepixel	<wxh></wxh>	0/7	The visible area of full scene in this video mode.
		-, -	The unit is pixel in source.
			* If
			"effectivepixel"<"capability_videoin_c<0~(n-1)
			>_maxsize", then the visible area is located at the center of full scene.
outputsize	<wxh></wxh>	0/7	The output size of source, equal to the captured
			size by device, in this video mode. The unit is
			pixel.
			This value is used as a basic coordinate system
			for many features, like ePTZ, privacy mask,
			motion, etc.
			* Source (most for image sensor) may perform
			scale or binning, etc on image data, and output
			data with smaller size. This parameter is
			designed to represent this.
binning	0, 1, 3	0/7	Indicate binning is used or not in this video
			mode.
			0: No binning
			1: 2x2 binning
			3: 3x3 binning
			* Binning is a technology to increase light
			sensitivity by combining multiple pixels to one.
			The drawback is reduced resolution. We design
			this parameter to disclose this information.
nresolution	<positive integer=""></positive>	0/7	How many resolution options in this video mode.
resolution	A list of <wxh></wxh>	0/7	Resolution options in this video mode.
			The last one is the maximum resolution in this
			video mode.
			* The element number is defined as
			"nresolution" in this group.
maxresolution	A list of <integer></integer>	0/7	Represent supported maximum resolution of
		<i>,</i> ,,	each stream in current video mode.
			* The element number is defined as
			"capability_nmediastream".

minresolution	A list of <integer></integer>	0/7	Represent supported minimum resolution of
		- /	each stream in current video mode.
			* The element number is defined as
			"capability_nmediastream".
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0304b.
maxframerate	A list of <positive< td=""><td>0/7</td><td>Indicates frame rate that the video source</td></positive<>	0/7	Indicates frame rate that the video source
Inaxinamerate		0/ /	
	Integer>		outputs in this video mode.
			* One to one manning to the recolution in
			* One to one mapping to the resolution in
			"resolution".
			* The element number is defined as
			"nresolution" in this group.
			* This parameter records the frame rate when
			"videoin_c<0~(n-1)>_cmosfreq"=60 or
			"videoin_c<0~(n-1)>_modulation"=ntsc
maxfps_mjpeg	A list of <positive< td=""><td>0/7</td><td>Maximum fps which the device can encoded with</td></positive<>	0/7	Maximum fps which the device can encoded with
	Integer> and "-"		MJPEG on resolutions in this video mode.
			"-" means not support.
			* One to one mapping to the resolution in
			"resolution".
			* The element number is defined as
			"nresolution" in this group.
			* This parameter records the frame rate when
			"videoin_c<0~(n-1)>_cmosfreq"=60 or
			"videoin_c<0~(n-1)>_modulation"=ntsc
			* Only available when 'mjpeg' is listed in
			"capability_videoin_codec".

maxfps_h264	A list of <positive< th=""><th>0/7</th><th>Maximum fps which the device can encoded with</th></positive<>	0/7	Maximum fps which the device can encoded with
	Integer> and "-"		H.264 on resolutions in this video mode.
			"-" means not support.
			* One to one mapping to the resolution in
			"resolution".
			* The element number is defined as
			"nresolution" in this group.
			* This parameter records the frame rate when
			"videoin_c<0~(n-1)>_cmosfreq"=60 or
			"videoin_c<0~(n-1)>_modulation"=ntsc
			* Only available when 'h264' is listed in
			"capability_videoin_codec".
maxfps_h265	A list of <positive< td=""><td>0/7</td><td>Maximum fps which the device can encoded with</td></positive<>	0/7	Maximum fps which the device can encoded with
	Integer> and "-"		H.265 on resolutions in this video mode.
			"-" means not support.
			* One to one mapping to the resolution in
			"resolution".
			* The element number is defined as
			"nresolution" in this group.
			* This parameter records the frame rate when
			"videoin_c<0~(n-1)>_cmosfreq"=60 or
			"videoin_c<0~(n-1)>_modulation"=ntsc
			* Only available when 'h265' is listed in
			"capability_videoin_codec".
description	<string[128]></string[128]>	0/7	Description about this mode.

# Group: **capability\_image\_c<0~(n-1)>** n denotes the value of "capability\_nvideoin"

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
basicsetting	0, <positive integer=""></positive>	0/7	A 32-bits integer, each bit can be set
			separately as follows:
			Bit 0 => Supports Brightness or not.
			Bit 1 => Supports Contrast or not.
			Bit 2 => Supports Saturation or not.
			Bit 3 => Supports Sharpness or not.
			Bit 4 => Supports adjusting the image
			to proper position horizontally or not.
			Bit 5 => Supports adjusting the image

			to proper position vertically or not.
wdrara mada	0.1.2	0/7	
wdrpro_mode	0, 1, 2	0/7	0: Non-support WDR Pro
			1: Support WDR Pro
			2: Support WDR Pro and WDR Pro II
wdrpro_strength	0, 1	0/7	0: Non-support tuning strength of
			WDR Pro
			1: Support tuning strength of WDR Pro
			* If
			"capability_image_c<0~(n-1)>_wdrp
			ro"=1, this may be either 0 or 1.
wdrpro_supportlevel	0, <positive integer=""></positive>	0/7	This contains a list of positive integers,
			split by comma.
			If "wdrpro_mode" =1, then the value
			indicate the support strength level of
			WDR Pro.
			If "wdrpro_mode" =2, then the first
			number indicate the support strength
			level of WDR Pro, and the scecond
			number indicate the support strength
			level of WDR Pro II.
wdrpro_affect	-,	0/7	When WDR Pro is enabled, some
	exposurewin.mode:fixed:au		features may become malfunction or
	to,		be forced to a given value. The
	exposurewin.mode.blc:disab		affected functions are list here.
	led:,		
	aespeed:disabled:,		The format is "Affect API
	exposurelevel:hidden:,		name":"Policy":"Description"
	exposurelevel:fixed: <x>,</x>		
	exposurelevel:fixed: <x>/<x< td=""><td></td><td>"Policy" can be categorized into</td></x<></x>		"Policy" can be categorized into
	>,		following groups:
	exposurelevel:ranged: <x>-</x>		- (disabled) : UI turns grey and users
	<x>,</x>		can't select it.
	exposuremode:fixed:auto		- (unchanged) : UI keeps the status as
			before and user can't change it.
	<x>: nonnegative integer</x>		- (hidden) : UI is hidden.
	<product dependent=""></product>		- (fixed) : UI is fixed to one selection or
			value.
			- (ranged) : UI is fixed to multiple
			selections or values.

		1	
			- (enabled) : UI is checked.
			- (notsupport) : the affected function
			is not available.
			"Affect API name" can be described in
			hierarchy, such as
			"exposurewin.mode.blc:disabled:"
			which means blc exposure window is
			disabled. API name can be one word as
			well, such as "exposurelevel:fixed:6"
			which means exposurelevel is fixed to
			level 6.
			level 0.
			"Description" can be a nonnegative
			integer or string or NULL.
			For example:
			"exposurelevel:fixed:6/8/12" which
			means exposurelevel is fixed to level
			6, level 8 and level 12.
			"-" means no feature is affected.
			* When "wdrpro"=0, this value must
			be "-"
wdrpro_description	<string></string>	0/7	Description about WDR Pro mode.
			* Only available when
			"capability_image_c<0~(n-1)>_wdrp
			ro_mode" > 0
wdrc_mode	0, 1	0/7	0: Non-support WDR Enhanced
			1: Support WDR Enhanced
wdrc_supportlevel	0, <positive integer=""></positive>	0/7	Indicate the support strength level of
			WDR Enhanced.
wdrc_affect	-,	0/7	When WDR Enhanced is enabled, some
	exposurewin.mode:fixed:au		features may become malfunction or
	to,		be forced to a given value. The
	exposurewin.mode.blc:disab		affected functions are list here.
	led:,		
	aespeed:disabled:,		The format is "Affect API
	exposurelevel:hidden:,		name":"Policy":"Description"
	exposurelevel:fixed: <x>,</x>		
	exposurelevel:fixed: <x>/<x< td=""><td></td><td>"Policy" can be categorized into</td></x<></x>		"Policy" can be categorized into
	>,		following groups:

	exposurelevel:ranged: <x>-</x>		- (disabled) : UI turns grey and users
	<x>,</x>		can't select it.
	exposuremode:fixed:auto		- (unchanged) : UI keeps the status as
			before and user can't change it.
	<x>: nonnegative integer</x>		- (hidden) : UI is hidden.
	<product dependent=""></product>		- (fixed) : UI is fixed to one selection or
			value.
			- (ranged) : UI is fixed to multiple
			selections or values.
			- (enabled) : UI is checked.
			- (notsupport) : the affected function
			is not available.
			"Affect API name" can be described in
			hierarchy, such as
			"exposurewin.mode.blc:disabled:"
			which means blc exposure window is
			disabled. API name can be one word as
			well, such as "exposurelevel:fixed:6"
			which means exposurelevel is fixed to
			level 6.
			"Description" can be a nonnegative
			integer or string or NULL.
			For example:
			"exposurelevel:fixed:6/8/12" which
			means exposurelevel is fixed to level
			6, level 8 and level 12.
			"-" means no feature is affected.
			* When "wdrc"=0, this value must be
			- n_ n
dnr	0,1	0/7	0: Non-support 3D digital noise
			reduction
			1: Support 3D digital noise reduction
dnrstrength	<positive integer=""></positive>	0/7	Indicate the support strength level of
			3D digital noise reduction.
			* Only available when
			"capability_image_c<0~(n-1)>_dnr"

[			
			> 0.
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0306d.
dnrtype	2d,3d	0/7	Description about DNR type.
			* Only available when
			"capability_image_c<0~(n-1)>_dnr"
			> 0.
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0308a.
eis	0,1	0/7	0: Non-support electronic image
			stabilizer
			1: Support electronic image stabilizer
is_mode	eis,	0/7	Indicate the image stabilizer mode.
	dis,		"eis": electronic image stabilizer
	-		"dis": digital image stabilizer
			"-": not support
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0302a.
is_strength	<boolean></boolean>	0/7	0: Non-support tuning strength of
			image stabilizer mode.
			1: Support tuning strength of image
			stabilizer mode.
			* Only available when
			"capability_image_c<0~(n-1)>_is_m
			ode" is not "-".
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0302a.
is_supportlevel	0, <positive integer=""></positive>	0/7	Indicate the support strength level of
			image stabilizer mode.
			* Only available when

		1	1
			"capability_image_c<0~(n-1)>_is_m
			ode" is not "-".
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0302a.
is_affect	-,	0/7	When Is mode is not "-", some
	minexposure:hidden:,		features may become malfunction or
	mingain:hidden:,		be forced to a given value. The
	wdrpro:unchanged:,		affected functions are list here.
	3dnr:unchanged:,		
	or others		The format is "Affect API
			name":"Policy":"Description"
	<x>: nonnegative integer</x>		
	<product dependent=""></product>		"Policy" can be categorized into
			following groups:
			- (disabled) : UI turns grey and users
			can't select it.
			- (unchanged) : UI keeps the status as
			before and
			user can't change it.
			- (hidden) : UI is hidden.
			- (fixed) : UI is fixed to one selection or
			value.
			- (ranged) : UI is fixed to multiple
			selections or values.
			- (enabled) : UI is checked.
			- (notsupport) : the affected function
			is not available.
			"Affect API name" can be described in
			hierarchy, such as
			"exposurewin.mode.blc:disabled:"
			which means blc exposure window is
			disabled. API name can be one word as
			well, such as "exposurelevel:fixed:6"
			which means exposurelevel is fixed to
			level 6.
			"Description" can be a nonnegative

			integer or string or NULL.
			"-" means no feature is affected.
			* Only available when
			"capability_image_c<0~(n-1)>_is_m
			ode" is not "-".
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0302a.
scenemode_support	0,1	0/7	0: Non-support scene mode
			1: Support scene mode
scenemode_supporttype	visibility,	0/7	list all the scene mode which are
<product dependent=""></product>	noiseless,		supported in the camera.
	lpcparkinglot,		
	lpcstreet		* Only available when
	<product dependent=""></product>		"capability_image_c<0~(n-1)>_
			scenemode_support" is 1
scenemode_visibility_affe	-,	0/7	When scene mode is enabled, some
ct	minexposure:hidden:,		features may become malfunction or
<product dependent=""></product>	mingain:hidden:,		be forced to a given value. The
	wdrpro:unchanged:,		affected functions are list here.
	3dnr:unchanged:,		
	or others		The format is "Affect API
			name":"Policy":"Description"
	<x>: nonnegative integer</x>		
	<product dependent=""></product>		"Policy" can be categorized into
			following groups:
			- (disabled) : UI turns grey and users
			can't select it.
			- (unchanged) : UI keeps the status as
			before and
			user can't change it.
			- (hidden) : UI is hidden.
			- (fixed) : UI is fixed to one selection or
			value.
			- (ranged) : UI is fixed to multiple
			selections or values.
			- (enabled) : UI is checked.
			- (notsupport) : the affected function
			is not available.

			"Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6.
			"Description" can be a nonnegative integer or string or NULL.
			<pre>"-" means no feature is affected. * Only available when visibility is listed in "capability_image_c&lt;0~(n-1)&gt;_ scenemode_supporttype" and "capability_image_c&lt;0~(n-1)&gt;_ scenemode_support" is 1</pre>
scenemode_noiseless_aff	-,	0/7	When scene mode is enabled, some
ect	, minexposure:hidden:,	-,	features may become malfunction or
<pre><product dependent=""></product></pre>	mingain:hidden:,		be forced to a given value. The
P	wdrpro:unchanged:,		affected functions are list here.
	3dnr:unchanged:,		
	or others		The format is "Affect API
			name":"Policy":"Description"
	<x>: nonnegative integer</x>		
	<product dependent=""></product>		"Policy" can be categorized into
			following groups:
			- (disabled) : UI turns grey and users
			can't select it.
			- (unchanged) : UI keeps the status as
			before and
			user can't change it.
			- (hidden) : UI is hidden.
			- (fixed) : UI is fixed to one selection or
			value.
		1	
			- (ranged) : UI is fixed to multiple
			<ul> <li>- (ranged) : UI is fixed to multiple selections or values.</li> <li>- (enabled) : UI is checked.</li> </ul>

		- (notsupport) : the affected function is not available.
		"Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6.
		"Description" can be a nonnegative integer or string or NULL.
		<pre>"-" means no feature is affected. * Only available when visibility is listed in "capability_image_c&lt;0~(n-1)&gt;_ scenemode_supporttype " and "capability_image_c&lt;0~(n-1)&gt;_ scenemode_support" is 1</pre>
-,	0/7	When scene mode is enabled, some
<pre>minexposure:hidden:, mingain:hidden:, wdrpro:unchanged:,</pre>		features may become malfunction or be forced to a given value. The affected functions are list here.
3dnr:unchanged:, or others		The format is "Affect API name":"Policy":"Description"
<x>: nonnegative integer <product dependent=""></product></x>		<ul> <li>"Policy" can be categorized into following groups:</li> <li>(disabled) : UI turns grey and users can't select it.</li> <li>(unchanged) : UI keeps the status as before and user can't change it.</li> <li>(hidden) : UI is hidden.</li> <li>(fixed) : UI is fixed to one selection or value.</li> </ul>
	<pre>mingain:hidden:, wdrpro:unchanged:, 3dnr:unchanged:, or others <x>: nonnegative integer</x></pre>	<pre>minexposure:hidden:, mingain:hidden:, wdrpro:unchanged:, 3dnr:unchanged:, or others <x>: nonnegative integer</x></pre>

	1	1	1
			selections or values.
			- (enabled) : UI is checked.
			- (notsupport) : the affected function
			is not available.
			"Affect API name" can be described in
			hierarchy, such as
			"exposurewin.mode.blc:disabled:"
			which means blc exposure window is
			disabled. API name can be one word as
			well, such as "exposurelevel:fixed:6"
			which means exposurelevel is fixed to
			level 6.
			"Value" can be a nonnegative integer
			or string or NULL.
			"-" means no feature is affected.
			* Only available when visibility is listed
			in "capability_image_c<0~(n-1)>_
			scenemode_supporttype " and
			"capability_image_c<0~(n-1)>_
			scenemode_support" is 1
scenemode_lpcstreet_aff	-,	0/7	When scene mode is enabled, some
ect	, minexposure:hidden:,	0, 1	features may become malfunction or
<product dependent=""></product>	mingain:hidden:,		be forced to a given value. The
	wdrpro:unchanged:,		affected functions are list here.
	3dnr:unchanged:,or others		
	Sum function geo., or others		The format is "Affect API
	<x>: nonnegative integer</x>		name":"Policy":"Description"
	<pre><pre>cyroduct dependent&gt;</pre></pre>		
			"Policy" can be categorized into
			following groups:
			- (disabled) : UI turns grey and users
			can't select it.
			- (unchanged) : UI keeps the status as
			before and
			user can't change it.
			- (hidden) : UI is hidden.
			- (fixed) : UI is fixed to one selection or

	1	1	
			value.
			- (ranged) : UI is fixed to multiple
			selections or values.
			- (enabled) : UI is checked.
			- (notsupport) : the affected function
			is not available.
			"Affect API name" can be described in
			hierarchy, such as
			"exposurewin.mode.blc:disabled:"
			which means blc exposure window is
			disabled. API name can be one word as
			well, such as "exposurelevel:fixed:6"
			which means exposurelevel is fixed to
			level 6.
			"Description" can be a nonnegative
			integer or sting or NULL.
			"-" means no feature is affected.
			* Only available when visibility is listed
			in "capability_image_c<0~(n-1)>_
			scenemode_supporttype " and
			"capability_image_c<0~(n-1)>_
			scenemode_support" is 1
wbmode	auto,	0/7	Available white balance mode.
	manual,		"-" means white balance is not
	rbgain,		supported.
	widerange,		
	outdoor,indoor,		
	sodiumauto,		
	-		
	<product dependent=""></product>		
iristype	piris,	0/7	Indicate iris type.
	dciris,		"piris": P-Iris
	-		"dciris": DC-Iris
			"-": No Iris control support
			* Note: For some cameras, this value
			may be varied depending on mounted

			lens.
sensortype	rawsensor,	0/7	Indicate sensor type.
	smartsensor,	- ,	"rawsensor": Raw sensor
	-		"smartsensor": Smart sensor
			"-": N/A
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0302a.
exposure_mode	0,1	0/7	0: Non-support exposure control.
			1: Support exposure control.
exposure_modetype	auto,	0/7	Available mode of exposure setting.
	shutterpriority,		* Only available when
	irispriority,		"capability_image_c<0~(n-1)>_
	manual		exposure_mode" is 1.
	<product dependent=""></product>		
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0302a.
exposure_rangetype	onevalue,	0/7	Support interface of exposure range.
	twovalues		"onevalue": The parameter is a
			constant value.
			"twovalues": Need two parameters
			to indicate the exposure range.
			* Only available when
			"capability_image_c<0~(n-1)>_
			exposure_mode" is 1.
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0302a.
exposure_shuttervaluetyp	fixed,	0/7	* One to one mapping to the mode
e	maximum,		type in "exposure_modetype".
	-		"fixed": The shutter value is the
			assigned value
			(videoin_c<0~(n-1)>_shuttervalue).
			"maximum": The shutter value can
			be up to the assigned value
			(videoin_c<0~(n-1)>_shuttervalue).
			"-": not support.

exposure_automode_affect-,0/7* Only available when "capability_image_c<0~(n-1)>_ exposure_mode" is 1 and "capability_image_c<0~(n-1)>_expo sure_rangetype" is "onevalue". * We support this parameter when the version number (httpversion) is equal or greater than 0302a.exposure_gainvaluetypefixed,0/7* One to one mapping to the mode type in "exposure_mode" is 1 and "fixed". The shutter value is the assigned value (videoin_c<0~(n-1)>_gainvalue). "maximum": The shutter value can be up to the assigned value (videoin_c<0~(n-1)>_gainvalue) "=": not support.exposure_automode_affer ct-,0/7* Only available when "capability_image_c<0~(n-1)>_gainvalue) "=": not support.exposure_automode_affer ct-,0/7When exposure_mode is 1 and "capability_image_c<0~(n-1)>_gainvalue)exposure_automode_affer ct-,0/7When exposure_mode is enabled, version number (httpversion) is equal or greater than 0302a.exposure_automode_affer ct-,0/7When exposure mode is enabled, version number (httpversion) is equal or greater than 0302a.exposure_automode_affer en:, defog:disabled:, wdrpo:disabled:, wdrpo:disabled:, wdrpo:disabled:, wdrpo:disabled:, value, the affected functions are list here. exposure/subjection"exposure_automode_affer en:, defog:disabled:, wdrpo:disabled:, wdrpo:disabled:, wdrpo:disabled:, wdrpo:disabled:, wdrpo:disabled:, wdrpo:disabled:, wdrpo:disabled:, wdrpo:disabled:, value, the affected functions are list here. "Policy": can be categorized into following groups: -(disabled; ill turns grey and users can't select it.		1		1
exposure_antomode_affer ct-O/7* One to one mapping to the mode type in "exposure_mode" is 1 and "capability_image_c<0~(n-1)>_expo sure_rangetype" is "onevalue". * We support this parameter when the version number (httpversion) is equal or greater than 0302a.exposure_gainvaluetypefixed, maximum, -0/7* One to one mapping to the mode type in "exposure_modetype". "fixed": The shutter value is the assigned value (videoin_c<0~(n-1)>_gainvalue), "maximum": The shutter value can be up to the assigned value (videoin_c<0~(n-1)>_gainvalue) "": not support.exposure_automode_affer ct-,0/7When exposure_mode is and "capability_image_c<0~(n-1)>_exposure_mode" is 1 and "capability_image_c<0~(n-1)>_exp				* Only available when
exposure_gainvaluetypefixed, maximum,0/7* Chapbility_image_c<0~(n-1)>_expo sure_rangetype" is "onevalue". * We support this parameter when the version number (httpversion) is equal or greater than 0302a.exposure_gainvaluetypefixed, maximum, - - -0/7* One to one mapping to the mode type in "exposure_modetype". "fixed": The shutter value is the assigned value (videoin_c<0~(n-1)>_gainvalue). "maximum": The shutter value can be up to the assigned value (videoin_c<0~(n-1)>_gainvalue) "-*": not support.exposure_automode_affer ct-,0/7When exposure_mode' is 1 and "capability_image_c<0~(n-1)>_exposure_mode' is 1 and "capability_image_c<0				"capability_image_c<0~(n-1)>_
sure_rangetype" is "onevalue", * We support this parameter when the version number (httpversion) is equal or greater than 0302a.exposure_gainvaluetypefixed, maximum, - <td></td> <td></td> <td></td> <td>exposure_mode" is 1 and</td>				exposure_mode" is 1 and
* We support this parameter when the version number (httpversion) is equal or greater than 0302a.exposure_gainvaluetypefixed, maximum,0/7* One to one mapping to the mode 				"capability_image_c<0~(n-1)>_expo
exposure_gainvaluetypefixed, maximum,0/7* One to one mapping to the mode type in "exposure_modetype". "fixed": The shutter value is the assigned value (videoin_c<0~(n-1)>_gainvalue), "maximum": The shutter value can be up to the assigned value (videoin_c<0~(n-1)>_gainvalue), "maximum": The shutter value can be up to the assigned value (videoin_c<0~(n-1)>_gainvalue), "maximum": The shutter value can be up to the assigned value (videoin_c<0~(n-1)>_gainvalue), "maximum": The shutter value can be up to the assigned value (videoin_c<0~(n-1)>_gainvalue), ""-": not support.* Only available when "capability_image_c<0~(n-1)>_expo sure_mode" is 1 and "capability_image_c<0~(n-1)>_expo sure_mode" is 1 and "capability_image_c<0~(n-1)>_expo sure_mode" is 1 and "capability_image_c<0~(n-1)>_expo sure_mode" is 1 and "capability_image_c<0~(n-1)>_expo sure_maneter when the version number (httpversion) is equal or greater than 0302a.exposure_automode_affe ct-,0/7When exposure auto mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. exposurelevel:hidden:, or others0/7When exposure auto mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here.exposurelevel:hidden:, or othersThe format is "Affect API name":"Policy":"Description" <x>: nonnegative integer <pre><pre><pre>conduct dependent&gt;</pre>Following groups: cont select it.</pre></pre></x>				sure_rangetype" is "onevalue".
exposure_gainvaluetypefixed, maximum, - -0/7* One to one mapping to the mode type in "exposure_modetype". "fixed": The shutter value is the assigned value (videoin_c<0~(n-1)>_gainvalue). "maximum": The shutter value can be up to the assigned value (videoin_c<0~(n-1)>_gainvalue). "maximum": The shutter value can be up to the assigned value (videoin_c<0~(n-1)>_gainvalue). "-": not support.* Only available when "capability_image_c<0~(n-1)>_ exposure_mode" is 1 and "capability_image_c<0~(n-1)>_exposure_mode" is 1 and "capability_image_c<0~(n-1)>_exposure_node" is 1 and "capability_image_c<0~(n-1)>_exposure_exposure_in-mode_bic:hidd en:, defog:disabled:, wdrpro:disabled:, wdrpro:disabled:, exposurelevel:hidden:, or others0/7When exposure auto mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. exposurelevel:hidden:, or others-, exposurelevel:hidden:, or others-, matimum of the format is "Affect API name": "Policy": Can be categorized into following groups: - (disabled): UI turns grey and users can't select it.				* We support this parameter when the
exposure_gainvaluetypefixed, maximum, -0/7* One to one mapping to the mode type in "exposure_modetype". "fixed": The shutter value is the assigned value (videoin_c<0~(n-1)>_gainvalue). "maximum": The shutter value can be up to the assigned value (videoin_c<0~(n-1)>_gainvalue). "-": not support. * Only available when "capability_image_c<0~(n-1)>_ exposure_mode" is 1 and "capability_image_c<0~(n-1)>_exposure_mode" is 1 and "capability_image_c<0~(n-1)>_exposure_mode is 1 and "capability_image_c<0~(n-1)>_exposure_mode is 1 and "capability_image_c<0~(n-1)>_exposure_				version number (httpversion) is equal
maximum,type in "exposure_modetype""fixed": The shutter value is the assigned value (videoin_c<0~(n-1)>_gainvalue)."maximum": The shutter value can be up to the assigned value (videoin_c<0~(n-1)>_gainvalue)"maximum": The shutter value can be up to the assigned value (videoin_c<0~(n-1)>_gainvalue)""aximum": The shutter value can be up to the assigned value (videoin_c<0~(n-1)>_gainvalue)""": ": not support.* Only available when "capability_image_c<0~(n-1)>_exposure_mode" is 1 and "capability_image_c<0~(n-1)>_exposure_mode" is 1 and "capability_image_c<0~(n-1)>_exposure_mode" is 1 and "capability_image_c<0~(n-1)>_exposure_node" is 1 and "capability_image_c<0~(n-1)>_exposure_mode" is 1 and "capability_image_c<0~(n-1)>_exposure_mode" is 1 and "capability_image_c<0~(n-1)>_exposure_mode" is 1 and "capability_image_c<0~(n-1)>_exposure_mode" is 1 and "capability_image_c<0~(n-1)>_exposure_mode".exposure_automode_affe ct-,0/7When exposure auto mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. exposureivel:hidden:, or othersexposure/evel:hidden:, or othersexposure/evel:hidden:, or othersexposure/integer <pre>exposure/integer <pre>exposure/integer <pre>exposure/integer <pre>evelot_tevelot_tevelot_t<td></td><td></td><td></td><td>or greater than 0302a.</td></pre></pre></pre></pre>				or greater than 0302a.
-"fixed": The shutter value is the assigned value (videoin_c<0~(n-1)>_gainvalue). "maximum": The shutter value can be up to the assigned value (videoin_c<0~(n-1)>_gainvalue) "": not support.* Only available when "capability_image_c<0~(n-1)>_ exposure_mode" is 1 and "capability_image_c<0~(n-1)>_expo sure_rangetype" is "onevalue". * We support this parameter when the version number (httpversion) is equal or greater than 0302a.exposure_automode_affe en:, defog:disabled;, wdrpro:disabled;, exposureelvel:hidden:, or others0/7When exposure auto mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. exposurely:hidden:, or othersThe format is "Affect API name": "Policy": "Description" <x>: nonnegative integer <product dependent="">"Policy" can be categorized into following groups: - (disabled): UI turns grey and users can't select it.</product></x>	exposure_gainvaluetype	fixed,	0/7	* One to one mapping to the mode
exposure_automode_affer ct-,0/7When exposure duo mode is enabled; version number (httpversion) is equal or greater than 0302a.exposure_automode_affer en.,-,0/7When exposure auto mode is enabled; version number (httpversion) is equal or greater than 0302a.exposure_automode_affer en.,-,0/7When exposure auto mode is enabled; version number (httpversion) is equal or greater than 0302a.exposure_automode_affer en.,-,0/7When exposure auto mode is enabled; version number (httpversion) is equal or greater than 0302a.exposure_automode_affer en.,-,0/7When exposure auto mode is enabled; some features may become malfunction or be forced to a given value. The affected functions are list here.exposurelevel:hilden:, or others-,-,-,exposure/automice-,-,-,exposure/automice-,-,-,exposure/automice-,-,-,exposure/automice-,-,-,exposure/automice-,-,-,exposure/automice-,-,-,exposure/automice-,-,-,exposure/automice-,-,-,exposure/automice-,-,-,exposure/automice-,-,-,exposure/automice-,-,-,exposure/automice-,-,-,exposure/automice-,-,-,exposure/automice-,-,-,exposure/au		maximum,		type in "exposure_modetype".
exposure_automode_affer ct-,0/7Wene resoure_and 0.202.exposure_automode_affer ct-,0/7Wene resoure and 0.202.ct-,0/7Wene resoure and 0.202.exposure_automode_affer ct-,0/7Wene resoure and 0.202.ct-,0/7Wene resoure and 0.202.exposure_automode_affer ct-,0/7Wene resoure and 0.202.ct-,0/7Wene resoure and 0.202.exposure_automode_affer ct-,0/7Wene resoure and mode is enabled, some features may become maifunction or be forced to a given value. The affected functions are list here.exposurelevel:hidden:, or othersThe format is "Affect API name":"Policy":"Description" <x>: nonnegative integer -,"Policy" can be categorized into following groups: - (disabled): UI turns grey and users can't select it.</x>		-		"fixed": The shutter value is the
"maximum": The shutter value can be up to the assigned value (videoin_c<0~(n-1)>_gainvalue) "-": not support.* Only available when "capability_image_c<0~(n-1)>_ exposure_mode" is 1 and "capability_image_c<0~(n-1)>_expo sure_rangetype" is "onevalue". * We support this parameter when the version number (httpversion) is equal or greater than 0302a.exposure_automode_affe ct-,0/7When exposure auto mode is enabled, some features may become maifunction or be forced to a given value. The affected functions are list here. exposurelevel:hidden:, or others0/7When exposure auto mode is enabled, some features may become maifunction or be forced to a given value. The affect API name":"Policy":"Description" <x>: nonnegative integer <pre>cyroduct dependent&gt;"Policy" can be categorized into following groups: - (disabled): UI turns grey and users can't select it.</pre></x>				assigned value
exposure_automode_affer ct-,0/7When exposure_o(-(n-1)>exp				(videoin_c<0~(n-1)>_gainvalue).
exposure_automode_affer ct-, exposure_automode_affer exposure_inition or be forced to a given defog:disabled:, wdrpro:disabled:, exposurelevel:hidden:, or others0/7Wen exposure auto mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. exposurelevel:hidden:, or others0/7Wen exposure auto mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. exposurelevel:hidden:, or othersWene exposure auto mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. exposurelevel:hidden:, or othersThe format is "Affect API name":"Policy":"Description" -(disabled): UI turns grey and users can't select it.				"maximum": The shutter value can
Image: series of the series				be up to the assigned value
Image: series of the series				(videoin c<0~(n-1)> gainvalue)
* Only available when "capability_image_c<0~(n-1)>_ exposure_mode" is 1 and "capability_image_c<0~(n-1)>_expo sure_rangetype" is "onevalue". * We support this parameter when the version number (httpversion) is equal or greater than 0302a.exposure_automode_affe ct-,0/7When exposure auto mode is enabled, exposureautomode.blc:hidd en:, defog:disabled:, wdrpro:disabled:, exposurelevel:hidden:, or others0/7When exposure auto mode is enabled, rangetype" is "onevalue".exposure_automode_affe ct-,0/7When exposure auto mode is enabled, rangetype" is "onevalue".exposure_automode_affe ct-,Image: canue rangetype" is				
Image: Second				
exposure_mode" is 1 and "capability_image_c<0~(n-1)>_expo sure_rangetype" is "onevalue". * We support this parameter when the version number (httpversion) is equal or greater than 0302a.exposure_automode_affe ct-,0/7When exposure auto mode is enabled, some features may become en:, defog:disabled:, wdrpro:disabled;, exposurelevel:hidden:, or others0/7When exposure auto mode is enabled, some features may become walue. The affected functions are list here. exposurelevel:hidden:, or others <td< td=""><td></td><td></td><td></td><td>* Only available when</td></td<>				* Only available when
exposure_mode" is 1 and "capability_image_c<0~(n-1)>_expo sure_rangetype" is "onevalue". * We support this parameter when the version number (httpversion) is equal or greater than 0302a.exposure_automode_affe ct-,0/7When exposure auto mode is enabled, some features may become en:, defog:disabled:, wdrpro:disabled;, exposurelevel:hidden:, or others0/7When exposure auto mode is enabled, some features may become walue. The affected functions are list here. exposurelevel:hidden:, or others <td< td=""><td></td><td></td><td></td><td>"capability_image_c&lt;0~(n-1)&gt;_</td></td<>				"capability_image_c<0~(n-1)>_
Image: series of the series				exposure mode" is 1 and
sure_rangetype" is "onevalue".exposure_automode_affe ct-,0/7When exposure auto mode is enabled, or greater than 0302a.exposure_automode_affe ct-,0/7When exposure auto mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list wdrpro:disabled:, exposurelevel:hidden:, or othersN/7When exposure auto mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here.exposurelevel:hidden:, exposurelevel:hidden:, or othersexposurelevel:hidden:, or others-The format is "Affect API name":"Policy":"Description" <x>: nonnegative integer <product dependent="">"Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it.</product></x>				
* We support this parameter when the version number (httpversion) is equal or greater than 0302a.exposure_automode_affe-,0/7When exposure auto mode is enabled, some features may becomectexposurewin.mode.blc:hiddsome features may becomeen:,udfog:disabled:,value. The affected functions are list wdrpro:disabled:,wdrpro:disabled:,intere.exposurelevel:hidden:,intere.or othersThe format is "Affect API name":"Policy":"Description" <x>: nonnegative integer-<product dependent="">"Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it.</product></x>				
Image: series of the series				
Image: series of the series				
exposure_automode_affe ct exposurewin.mode.blc:hidd en:, defog:disabled:, wdrpro:disabled:, exposurelevel:hidden:, or others   (4) 0/7 When exposure auto mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. The format is "Affect API name":"Policy":"Description"  (4) Some features may become malfunction or be forced to a given value. The affect API name":"Policy":"Description"  (4) Some features may become malfunction or be forced to a given value. The affect API name":"Policy":"Description"  (4) Some features (4) Some features may become (4) Some features (4) Some				
ctexposurewin.mode.blc:hiddsome features may becomeen:,malfunction or be forced to a givendefog:disabled:,value. The affected functions are listwdrpro:disabled:,here.exposurelevel:hidden:,The format is "Affect APIor othersrame":"Policy":"Description" <x>: nonnegative integer"Policy" can be categorized into<product dependent="">following groups:- (disabled): UI turns grey and userscan't select it.</product></x>	exposure automode affe		0/7	
en:,malfunction or be forced to a givendefog:disabled:,value. The affected functions are listwdrpro:disabled:,here.exposurelevel:hidden:,The format is "Affect APIor othersname":"Policy":"Description" <x>: nonnegative integer"Policy" can be categorized into<product dependent="">following groups:- (disabled): UI turns grey and userscan't select it.</product></x>			0/7	
defog:disabled:,value. The affected functions are list here.wdrpro:disabled:,here.exposurelevel:hidden:,-or othersThe format is "Affect API name":"Policy":"Description" <x>: nonnegative integer-<product dependent="">"Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it.</br></product></x>				
wdrpro:disabled:,       here.         exposurelevel:hidden:,       The format is "Affect API         or others       The format is "Affect API         name":"Policy":"Description" <x>: nonnegative integer         <product dependent="">         "Policy" can be categorized into         following groups:         - (disabled): UI turns grey and users         can't select it.</product></x>				
exposurelevel:hidden:, or othersThe format is "Affect API name":"Policy":"Description" <x>: nonnegative integer*********************************</x>				
or othersThe format is "Affect API name": "Policy": "Description" <x>: nonnegative integer<product dependent="">"Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it.</product></x>				nere.
<pre></pre>		-		
<pre><x>: nonnegative integer <pre>// Policy" can be categorized into following groups:</pre></x></pre>		or others		
<pre><pre><pre>oduct dependent&gt;</pre> <pre> "Policy" can be categorized into following groups:     - (disabled) : UI turns grey and users     can't select it.</pre></pre></pre>				name":"Policy":"Description"
following groups: - (disabled) : UI turns grey and users can't select it.		<x>: nonnegative integer</x>		
- (disabled) : UI turns grey and users can't select it.		<product dependent=""></product>		"Policy" can be categorized into
can't select it.				following groups:
				- (disabled) : UI turns grey and users
				can't select it.
- (unchanged) : UI keeps the status as				- (unchanged) : UI keeps the status as

before and         user can't change it.         - (hidden) : UI is hidden.         - (fixed) : UI is fixed to one selection or         value.         - (ranged) : UI is fixed to multiple         selections or values.         - (enabled) : UI is checked.         - (notsupport) : the affected function         is not available.         "Affect API name" can be described in         hierarchy, such as         "exposurewin.mode.bic:disabled:"         which means blc exposure window is         disabled. API name can be one word as         well, such as "exposurelevel is fixed to         level 6.         "Description" can be a nonnegative         integer or string or NULL.         "-" means no feature is affected.         * Only available when auto is listed in         "capability_image_cco-(n-1)>_         exposure_mode' is 1.         * We support this parameter when the         version number (httpversion) is equal         or greater than 0302a.				
<ul> <li>- (hidden): UI is hidden.</li> <li>- (fixed): UI is fixed to one selection or value.</li> <li>- (ranged): UI is fixed to multiple selections or values.</li> <li>- (enabled): UI is checked.</li> <li>- (notsupport): the affected function is not available.</li> <li>"Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means so feature is affected.</li> <li>* Only available when auto is listed in "capability_image_c&lt;0~(n-1)&gt;_ exposure_mode" is 1.</li> <li>* We support this parameter when the version number (httpversion) is equal or greater than 0302a.</li> </ul>				before and
<ul> <li>- (fixed): UI is fixed to one selection or value.         <ul> <li>- (ranged): UI is fixed to multiple selections or values.</li> <li>- (ranged): UI is fixed to multiple selections or values.</li> <li>- (enabled): UI is checked.</li> <li>- (notsupport): the affected function is not available.</li> </ul> </li> <li>"Affect API name" can be described in hierarchy, such as         <ul> <li>"exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6"</li> <li>"Description" can be a nonnegative integer or string or NULL.</li> <li>"-" means no feature is affected.</li> <li>* Only available when auto is listed in "capability_image_c&lt;0~(n-1)&gt;_ exposure_modetype" and "capability_image_c&lt;0~(n-1)&gt;_ exposure_mode" is 1.</li> <li>* We suport this parameter when the version number (httpversion) is equal or greater than 0302a.</li> </ul> </li> <li>exposure_shutterpriority ¬, 0/7 When exposure shutter priority mode</li> </ul>				user can't change it.
value (ranged) : UI is fixed to multiple selections or values. - (enabled) : UI is checked. - (notsupport) : the affected function is not available."Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel is fixed to level 6."Description" can be a nonnegative integer or string or NULL."-" means no feature is affected. * Only available when auto is listed in "capability_image_c<0~(n-1)>_ exposure_modetype" and "capability_image_c<0~(n-1)>_ exposure_modetype" and "capability_image_c<0~(n-1)>_* We support this pa				- (hidden) : UI is hidden.
exposure_shutterpriority-, and0/7When exposure shutter priority mode				- (fixed) : UI is fixed to one selection or
exposure_shutterpriority-,0/7When exposure shutter priority mode				value.
exposure_shutterpriority-, model (model): UI is checked (notsupport): the affected function is not available."Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6."Description" can be a nonnegative integer or string or NULL."-" means no feature is affected. * Only available when auto is listed in "capability_image_c<0~(n-1)>_ exposure_modetype" and "capability_image_c<0~(n-1)>_ exposure_mode" is 1. * We support this parameter when the version number (httpversion) is equal or greater than 0302a.exposure_shutterpriority-,0/7When exposure shutter priority model				- (ranged) : UI is fixed to multiple
exposure_shutterpriority-, (notsupport): the affected function is not available (notsupport): the affected function is not available."Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6."Description" can be a nonnegative integer or string or NULL."-" means no feature is affected. * Only available when auto is listed in "capability_image_c<0~(n-1)>_ exposure_modetype" and "capability_image_c<0~(n-1)>_ exposure_modetype" is 1. * We support this parameter when the version number (httpversion) is equal or greater than 0302a.exposure_shutterpriority-,0/7When exposure shutter priority mode				selections or values.
kinis not available.is not available."Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6.is Description" can be a nonnegative integer or string or NULL."Description" can be a nonnegative integer or string or NULL."-" means no feature is affected. * Only available when auto is listed in "capability_image_c<0~(n-1)>_ exposure_modetype" and "capability_image_c<0~(n-1)>_ exposure_modetype" is 1. * We support this parameter when the version number (httpversion) is equal or greater than 0302a.exposure_shutterpriority-,0/7				- (enabled) : UI is checked.
exposure_shutterpriority-,Q/7When exposure shutter priority modevariationvari				- (notsupport) : the affected function
exposure_shutterpriority-,0/7When exposure shutter priority mode0/7When exposure shutter priority mode				is not available.
exposure_shutterpriority-,0/7When exposure shutter priority mode				
exposure_shutterpriority-,O/7When exposure shutter priority mode.9-,0/7When exposure window is999/7When exposure window is999/7When exposure evel:fixed:999/7When exposure evel:fixed:9999/7999/7When exposure evel:fixed:999/7When exposure evel:fixed:999/7When exposure evel:fixed:999/7When exposure evel:fixed:999/7When exposure evel:fixed:999/7When exposure evel:fixed:999/7When exposure index priority mode				"Affect API name" can be described in
exposure_shutterpriority-,0/7Which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel:fixed:6" which means exposurelevel is fixed to level 6."Description" can be a nonnegative integer or string or NULL."Description" can be a nonnegative integer or string or NULL."-" means no feature is affected."Only available when auto is listed in "capability_image_c<0~(n-1)>_ exposure_modetype" and "capability_image_c<0~(n-1)>_ exposure_mode" is 1.* We support this parameter when the version number (httpversion) is equal or greater than 0302a.				hierarchy, such as
exposure_shutterpriority-,0/7When exposure shutter priority mode				"exposurewin.mode.blc:disabled:"
exposure_shutterpriority-,0/7Well, such as "exposurelevel:fixed:6"which means exposurelevel is fixed to level 6."Description" can be a nonnegative integer or string or NULL."-" means no feature is affected."-" means no feature is affected.* Only available when auto is listed in "capability_image_c<0~(n-1)>_ exposure_modet is 1. * We support this parameter when the version number (httpversion) is equal or greater than 0302a.				which means blc exposure window is
exposure_shutterpriority-,0/7Which means exposurelevel is fixed to level 6.which means exposurelevel is fixed to level 6."Description" can be a nonnegative integer or string or NULL."-" means no feature is affected. * Only available when auto is listed in "capability_image_c<0~(n-1)>_ exposure_modetype" and "capability_image_c<0~(n-1)>_ exposure_modetype" is 1. * We support this parameter when the version number (httpversion) is equal or greater than 0302a.exposure_shutterpriority-,0/7				disabled. API name can be one word as
exposure_shutterpriority-,O/7level 6.level 6."Description" can be a nonnegative integer or string or NULL."-" means no feature is affected. * Only available when auto is listed in "capability_image_c<0~(n-1)>_ exposure_modetype" and "capability_image_c<0~(n-1)>_ exposure_mode" is 1. * We support this parameter when the version number (httpversion) is equal or greater than 0302a.				well, such as "exposurelevel:fixed:6"
exposure_shutterpriority-,0/7Wen exposure shutter priority mode				which means exposurelevel is fixed to
exposure_shutterpriority-,0/7When exposure shutter priority modeinteger or string or NULL.integer or string or NULL.integer or string or NULL."-" means no feature is affected.* Only available when auto is listed in "capability_image_c<0~(n-1)>_ exposure_modetype" and "capability_image_c<0~(n-1)>_ exposure_mode" is 1.* We support this parameter when the version number (httpversion) is equal or greater than 0302a.				level 6.
exposure_shutterpriority-,0/7When exposure shutter priority modeinteger or string or NULL.integer or string or NULL.integer or string or NULL."-" means no feature is affected.* Only available when auto is listed in "capability_image_c<0~(n-1)>_ exposure_modetype" and "capability_image_c<0~(n-1)>_ exposure_mode" is 1.* We support this parameter when the version number (httpversion) is equal or greater than 0302a.				
exposure_shutterpriority-,0/7When exposure shutter priority mode				"Description" can be a nonnegative
exposure_shutterpriority-,0/7% Only available when auto is listed in "capability_image_c<0~(n-1)>_ exposure_modetype" and "capability_image_c<0~(n-1)>_ exposure_mode" is 1. * We support this parameter when the version number (httpversion) is equal or greater than 0302a.				integer or string or NULL.
exposure_shutterpriority-,0/7% Only available when auto is listed in "capability_image_c<0~(n-1)>_ exposure_modetype" and "capability_image_c<0~(n-1)>_ exposure_mode" is 1. * We support this parameter when the version number (httpversion) is equal or greater than 0302a.				
exposure_shutterpriority-,0/7"capability_image_c<0~(n-1)>_exposure_modetype" and "capability_image_c<0~(n-1)>_exposure_mode" is 1.* We support this parameter when the version number (httpversion) is equal or greater than 0302a.				"-" means no feature is affected.
exposure_modetype" and "capability_image_c<0~(n-1)>_ exposure_mode" is 1. * We support this parameter when the version number (httpversion) is equal or greater than 0302a. exposure_shutterpriority -, 0/7 When exposure shutter priority mode				* Only available when auto is listed in
exposure_shutterpriority-,0/7We new support when the priority mode				"capability_image_c<0~(n-1)>_
exposure_shutterpriority       -,         0/7       When exposure shutter priority mode				exposure_modetype" and
exposure_shutterpriority       -,       0/7       We support this parameter when the version number (httpversion) is equal or greater than 0302a.				"capability_image_c<0~(n-1)>_
exposure_shutterpriority     -,     0/7     When exposure shutter priority mode				exposure_mode" is 1.
exposure_shutterpriority-,0/7When exposure shutter priority mode				* We support this parameter when the
exposure_shutterpriority -, 0/7 When exposure shutter priority mode				version number (httpversion) is equal
				or greater than 0302a.
	exposure_shutterpriority	-,	0/7	When exposure shutter priority mode
mode_affect exposurewin.mode.blc:hidd is enabled, some features may become	mode_affect	exposurewin.mode.blc:hidd		is enabled, some features may become
en:, malfunction or be forced to a given		en:,		malfunction or be forced to a given
defog:disabled:, value. The affected functions are list		defog:disabled:,		value. The affected functions are list
wdrpro:disabled:, here.		wdrpro:disabled:,		here.
exposurelevel:hidden:,		exposurelevel:hidden:,		
or others The format is "Affect API		or others		The format is "Affect API
name":"Policy":"Description"				name":"Policy":"Description"

	<x>: nonnegative integer</x>		
	<pre><pre>cxp i nonnegative integet <pre>cqproduct dependent&gt;</pre></pre></pre>		"Policy" can be categorized into
			following groups:
			- (disabled) : UI turns grey and users
			can't select it.
			- (unchanged) : UI keeps the status as before and
			user can't change it.
			- (hidden) : UI is hidden.
			- (fixed) : UI is fixed to one selection or
			value.
			- (ranged) : UI is fixed to multiple
			selections or values.
			- (enabled) : UI is checked.
			- (notsupport) : the affected function
			is not available.
			"Affect API name" can be described in
			hierarchy, such as
			"exposurewin.mode.blc:disabled:"
			which means blc exposure window is
			disabled. API name can be one word as
			well, such as "exposurelevel:fixed:6"
			which means exposurelevel is fixed to
			level 6.
			"Description" can be a nonnegative
			integer or string or NULL.
			"-" means no feature is affected.
			* Only available when shutterpriority is
			listed in
			"capability_image_c<0~(n-1)>_
			exposure_modetype" and
			"capability_image_c<0~(n-1)>_
			exposure_mode" is 1.
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0302a.
		0/7	
exposure_irisprioritymod	-,	0/7	When exposure iris priority mode is

en;, defog:disabled:, wdrpro:disabled:, exposurelevel:hidden:, or others <product dependent=""> The format is "Affect API name":"Policy":"Description" <product dependent=""> "Policy" can be categorized into following groups: - (disabled): UI turns grey and users can't select it. - (unchanged): UI keeps the status as before and user can't change it. - (hidden): UI is fixed to one selection or value. - (ranged): UI is fixed to multiple selections or values. - (notsupport): the affected function is not available. "Affect API name" can be described in hierarchy, such as "exposurelevel:fixed:6" which means ble exposure window is disabled. API name" can be described in hierarchy such as "exposurelevel:fixed:6" which means posurelevel:fixed:6" which means posur</product></product>	e_affect	exposurewin.mode.blc:hidd	enabled, some features may become
defog:disabled:,       value. The affected functions are list         wdrpro:disabled:,       here.         exposurelevel:hidden:,       or others         or others       The format is "Affect API name":"Policy":"Description" <x>: nonnegative integer       "Policy" can be categorized into following groups:         - (disabled): UI turns grey and users can't select it.       - (unchanged): UI keeps the status as before and user can't change it.         - (inidden): UI is fixed to multiple selections or values.       - (anged): UI is fixed to multiple selections or values.         - (ranged): UI is fixed to multiple selections or values.       - (enabled): UI is checked.         - (notsupport): the affected function is not available.       "Affect API name" can be described in hierarchy, such as         "exposure/win.mode.bit:disabled:"       which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel: fixed:6"         which means exposurelevel is fixed to level 6.       "Description" can be a nonnegative integer or string or NULL.</x>	_		
wdroro:disabled:, exposurelevel:hidden:, or others <x>: nonnegative integer <product dependent=""> The format is "Affect API name":"Policy": "Description" <x>: nonnegative integer <product dependent=""> "Policy" can be categorized into following groups: - (disabled): UI turns grey and users can't select it. - (unchanged): UI turns grey and users can't select it. - (unchange): UI is hidden. - (fixed): UI is hidden. - (fixed): UI is fixed to one selection or value. - (ranged): UI is fixed to one selection or value. - (ranged): UI is fixed to multiple selections or values. - (enabled): UI is fixed to multiple selections or values. - (enabled): UI is fixed to multiple selections or value. - (notsupport): the affected function is not available. "Affect API name" can be described in hierarchy, such as "exposurevin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6. "Description" can be a nonnegative integer or string or NULL. "-" means no feature is affected.</product></x></product></x>			
exposurelevel:hidden:, or others 			here.
or others       The format is "Affect API name": "Policy": "Description" <x>: nonnegative integer       "Policy" can be categorized into following groups:         <ul> <li>(disabled): UI turns grey and users can't select it.</li> <li>(unchanged): UI keeps the status as before and user can't change it.</li> <li>(hidden): UI is hidden.</li> <li>(fixed): UI is fixed to one selection or value.</li> <li>(ranged): UI is fixed to multiple selections or values.</li> <li>(enabled): UI is checked.</li> <li>(notsupport): the affected function is not available.</li> </ul> <li>"Affect API name" can be described in hierarchy, such as         <ul> <li>"exposurewin.mode.bic:disabled:"</li> <li>which means bic exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6"</li> <li>which means bic exposure window is disabled. API name can be one mord as well, such as "exposurelevel is fixed to level 6.</li> <li>"Description" can be a nonnegative integer or string or NULL.</li> <li>"-" means no feature is affected.</li> </ul> </li> </x>			
<pre><pre><pre><pre><pre>cyroduct dependent&gt;</pre> <pre>"Policy" can be categorized into following groups:     - (disabled) : UI turns grey and users     can't select it.     - (unchanged) : UI keeps the status as     before and     user can't change it.     - (hidden) : UI is fixed to one selection or     value.     - (fixed) : UI is fixed to one selection or     value.     - (ranged) : UI is fixed to one selection or     value.     - (ranged) : UI is fixed to multiple     selections or values.     - (enabled) : UI is checked.     - (notsupport) : the affected function     is not available.     "Affect API name" can be described in     hierarchy, such as     "exposurewin.mode.blc:disabled:"     which means blc exposure window is     disabled. API name can be one word as     well, such as "exposurelevel if.txed:6"     which means exposurelevel is fixed to     level 6.     "Description" can be a nonnegative     integer or string or NULL.     "-" means no feature is affected. </pre></pre></pre></pre></pre>			The format is "Affect API
<pre>&gt;product dependent&gt;     "Policy" can be categorized into     following groups:         - (disabled) : UI turns grey and users         can't select it.         - (unchanged) : UI keeps the status as         before and         user can't change it.         - (hidden) : UI is hidden.         - (fixed) : UI is fixed to one selection or         value.         - (ranged) : UI is fixed to one selection or         value.         - (ranged) : UI is fixed to multiple         selections or values.         - (enabled) : UI is checked.         - (notsupport) : the affected function         is not available.         "Affect API name" can be described in         hierarchy, such as         "exposurewin.mode.blc:disabled:"         which means blc exposure window is         disabled. API name can be one word as         well, such as "exposurelevel if.Ked:6"         which means exposurelevel is fixed to         level 6.         "Description" can be a nonnegative         integer or string or NULL.         "-" means no feature is affected. </pre>			name":"Policy":"Description"
following groups: - (disabled) : UI turns grey and users can't select it. - (unchanged) : UI keeps the status as before and user can't change it. - (hidden) : UI is hidden. - (fixed) : UI is fixed to one selection or value. - (ranged) : UI is fixed to multiple selections or values. - (enabled) : UI is checked. - (notsupport) : the affected function is not available. "Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6. "Description" can be a nonnegative integer or string or NULL. "-" means no feature is affected.		<x>: nonnegative integer</x>	
<ul> <li>- (disabled) : UI turns grey and users can't select it.</li> <li>- (unchanged) : UI keeps the status as before and user can't change it.</li> <li>- (hidden) : UI is hidden.</li> <li>- (fixed) : UI is fixed to one selection or value.</li> <li>- (ranged) : UI is fixed to multiple selections or values.</li> <li>- (enabled) : UI is checked.</li> <li>- (notsupport) : the affected function is not available.</li> <li>"Affect API name" can be described in hierarchy, such as</li> <li>"exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed;6" which means sposurelevel is fixed to level 6.</li> <li>"Description" can be a nonnegative integer or string or NULL.</li> <li>"-" means no feature is affected.</li> </ul>		<product dependent=""></product>	"Policy" can be categorized into
can't select it. - (unchanged): UI keeps the status as before and user can't change it. - (hidden): UI is hidden. - (fixed): UI is fixed to one selection or value. - (ranged): UI is fixed to multiple selections or values. - (enabled): UI is checked. - (notsupport): the affected function is not available. "Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6. "Description" can be a nonnegative integer or string or NULL. "-" means no feature is affected.			following groups:
<ul> <li>- (unchanged): UI keeps the status as before and user can't change it.</li> <li>- (hidden): UI is hidden.</li> <li>- (fixed): UI is fixed to one selection or value.</li> <li>- (ranged): UI is fixed to multiple selections or values.</li> <li>- (enabled): UI is checked.</li> <li>- (notsupport): the affected function is not available.</li> <li>"Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6.</li> <li>"Description" can be a nonnegative integer or string or NULL.</li> <li>"-" means no feature is affected.</li> </ul>			- (disabled) : UI turns grey and users
before and user can't change it. - (hidden) : UI is hidden. - (fixed) : UI is fixed to one selection or value. - (ranged) : UI is fixed to multiple selections or values. - (enabled) : UI is checked. - (notsupport) : the affected function is not available. "Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6. "Description" can be a nonnegative integer or string or NULL. "" means no feature is affected.			can't select it.
user can't change it. - (hidden) : UI is hidden. - (fixed) : UI is fixed to one selection or value. - (ranged) : UI is fixed to multiple selections or values. - (enabled) : UI is checked. - (notsupport) : the affected function is not available. "Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6. "Description" can be a nonnegative integer or string or NULL. "-" means no feature is affected.			- (unchanged) : UI keeps the status as
<ul> <li>- (hidden): UI is hidden.</li> <li>- (fixed): UI is fixed to one selection or value.</li> <li>- (ranged): UI is fixed to multiple selections or values.</li> <li>- (enabled): UI is checked.</li> <li>- (notsupport): the affected function is not available.</li> <li>"Affect API name" can be described in hierarchy, such as</li> <li>"exposurewin.mode.blc:disabled:"</li> <li>which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6"</li> <li>which means exposurelevel is fixed to level 6.</li> <li>"Description" can be a nonnegative integer or string or NULL.</li> <li>"-" means no feature is affected.</li> </ul>			before and
<ul> <li>- (fixed) : UI is fixed to one selection or value.</li> <li>- (ranged) : UI is fixed to multiple selections or values.</li> <li>- (enabled) : UI is checked.</li> <li>- (notsupport) : the affected function is not available.</li> <li>"Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6.</li> <li>"Description" can be a nonnegative integer or string or NULL.</li> <li>"-" means no feature is affected.</li> </ul>			user can't change it.
value.       - (ranged) : UI is fixed to multiple selections or values.         - (enabled) : UI is checked.       - (enabled) : UI is checked.         - (notsupport) : the affected function is not available.       - (notsupport) : the affected function is not available.         "Affect API name" can be described in hierarchy, such as       "exposurewin.mode.blc:disabled:"         which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6"         which means exposurelevel is fixed to level 6.         "Description" can be a nonnegative integer or string or NULL.         "-" means no feature is affected.			- (hidden) : UI is hidden.
<ul> <li>- (ranged): UI is fixed to multiple selections or values.</li> <li>- (enabled): UI is checked.</li> <li>- (notsupport): the affected function is not available.</li> <li>"Affect API name" can be described in hierarchy, such as</li> <li>"exposurewin.mode.blc:disabled:"</li> <li>which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6"</li> <li>which means exposurelevel is fixed to level 6.</li> <li>"Description" can be a nonnegative integer or string or NULL.</li> <li>"-" means no feature is affected.</li> </ul>			- (fixed) : UI is fixed to one selection or
selections or values. - (enabled) : UI is checked. - (notsupport) : the affected function is not available. "Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6. "Description" can be a nonnegative integer or string or NULL. "-" means no feature is affected.			value.
<ul> <li>- (enabled) : UI is checked.</li> <li>- (notsupport) : the affected function is not available.</li> <li>"Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6.</li> <li>"Description" can be a nonnegative integer or string or NULL.</li> <li>"-" means no feature is affected.</li> </ul>			- (ranged) : UI is fixed to multiple
<ul> <li>- (notsupport) : the affected function is not available.</li> <li>"Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6.</li> <li>"Description" can be a nonnegative integer or string or NULL.</li> <li>"-" means no feature is affected.</li> </ul>			selections or values.
is not available. "Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6. "Description" can be a nonnegative integer or string or NULL. "-" means no feature is affected.			- (enabled) : UI is checked.
<ul> <li>"Affect API name" can be described in hierarchy, such as</li> <li>"exposurewin.mode.blc:disabled:"</li> <li>which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6"</li> <li>which means exposurelevel is fixed to level 6.</li> <li>"Description" can be a nonnegative integer or string or NULL.</li> <li>"-" means no feature is affected.</li> </ul>			- (notsupport) : the affected function
hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6. "Description" can be a nonnegative integer or string or NULL. "-" means no feature is affected.			is not available.
hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6. "Description" can be a nonnegative integer or string or NULL. "-" means no feature is affected.			
"exposurewin.mode.blc:disabled:"         which means blc exposure window is         disabled. API name can be one word as         well, such as "exposurelevel:fixed:6"         which means exposurelevel is fixed to         level 6.         "Description" can be a nonnegative         integer or string or NULL.         "-" means no feature is affected.			"Affect API name" can be described in
which means blc exposure window is         disabled. API name can be one word as         well, such as "exposurelevel:fixed:6"         which means exposurelevel is fixed to         level 6.         "Description" can be a nonnegative         integer or string or NULL.         "-" means no feature is affected.			hierarchy, such as
disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6. "Description" can be a nonnegative integer or string or NULL. "-" means no feature is affected.			"exposurewin.mode.blc:disabled:"
well, such as "exposurelevel:fixed:6"         which means exposurelevel is fixed to         level 6.         "Description" can be a nonnegative         integer or string or NULL.         "-" means no feature is affected.			which means blc exposure window is
which means exposurelevel is fixed to level 6.         "Description" can be a nonnegative integer or string or NULL.         "-" means no feature is affected.			disabled. API name can be one word as
level 6. "Description" can be a nonnegative integer or string or NULL. "-" means no feature is affected.			well, such as "exposurelevel:fixed:6"
"Description" can be a nonnegative integer or string or NULL. "-" means no feature is affected.			which means exposurelevel is fixed to
integer or string or NULL. "-" means no feature is affected.			level 6.
integer or string or NULL. "-" means no feature is affected.			
"-" means no feature is affected.			"Description" can be a nonnegative
			integer or string or NULL.
* Only available when irispriority is			"-" means no feature is affected.
			* Only available when irispriority is
listed in			listed in
"capability_image_c<0~(n-1)>_			"capability_image_c<0~(n-1)>_

		T	
			exposure_modetype" and
			"capability_image_c<0~(n-1)>_
			exposure_mode" is 1.
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0302a.
exposure_qualitypriority	-,	0/7	When exposure quality priority mode
mode_affect	exposurewin.mode.blc:hidd		is enabled, some features may become
	en:,		malfunction or be forced to a given
	defog:disabled:,		value. The affected functions are list
	wdrpro:disabled:,		here.
	exposurelevel:hidden:,		
	or others		The format is "Affect API
			name":"Policy":"Description"
	<x>: nonnegative integer</x>		
	<product dependent=""></product>		"Policy" can be categorized into
			following groups:
			- (disabled) : UI turns grey and users
			can't select it.
			- (unchanged) : UI keeps the status as
			before and
			user can't change it.
			- (hidden) : UI is hidden.
			- (fixed) : UI is fixed to one selection or
			value.
			- (ranged) : UI is fixed to multiple
			selections or values.
			- (enabled) : UI is checked.
			- (notsupport) : the affected function
			is not available.
			"Affect API name" can be described in
			hierarchy, such as
			"exposurewin.mode.blc:disabled:"
			which means blc exposure window is
			disabled. API name can be one word as
			well, such as "exposurelevel:fixed:6"
			which means exposurelevel is fixed to
			level 6.

	1	1	1
			"Description" can be a nonnegative
			integer or string or NULL.
			"-" means no feature is affected.
			* Only available when qualitypriority is
			listed in
			"capability_image_c<0~(n-1)>_
			exposure_modetype" and
			"capability_image_c<0~(n-1)>_
			exposure_mode" is 1.
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0305a.
		0/7	
exposure_manualmode_a	-,	0/7	When exposure manual mode is
ffect	exposurewin.mode.blc:hidd		enabled, some features may become
	en:,		malfunction or be forced to a given
	defog:disabled:,		value. The affected functions are list
	wdrpro:disabled:,		here.
	exposurelevel:hidden:,		
	or others		The format is "Affect API
			name":"Policy":"Description"
	<x>: nonnegative integer</x>		
	<product dependent=""></product>		"Policy" can be categorized into
			following groups:
			- (disabled) : UI turns grey and users
			can't select it.
			- (unchanged) : UI keeps the status as
			before and
			user can't change it.
			- (hidden) : UI is hidden.
			- (fixed) : UI is fixed to one selection or
			value.
			- (ranged) : UI is fixed to multiple
			selections or values.
			- (enabled) : UI is checked.
			- (notsupport) : the affected function
			is not available.
			"Affect API name" can be described in
			hierarchy, such as

			1
			"exposurewin.mode.blc:disabled:"
			which means blc exposure window is
			disabled. API name can be one word as
			well, such as "exposurelevel:fixed:6"
			which means exposurelevel is fixed to
			level 6.
			"Description" can be a nonnegative
			integer or string or NULL.
			"-" means no feature is affected.
			* Only available when manual is listed
			in "capability_image_c<0~(n-1)>_
			exposure_modetype" and
			"capability_image_c<0~(n-1)>_
			exposure_mode" is 1.
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0302a.
exposure_levelrange	_	0/7	Available range for
exposure_levenange	-, "0,12"	0,7	"videoin_c<0~(n-1)>_exposurelevel"
	0,12		
			* When "exposure_mode"=0, this
			value must be set to "-".
			* Only available when
			"capability_image_c<0~(n-1)>_
			exposure_mode" is 1.
exposure_winmode	auto,	0/7	Available options for
	custom,		"exposurewin_c<0~(n-1)>_mode"
	blc,		
	hlc		* "-" means group: exposurewin is not
	-		supported.
	<product dependent=""></product>		* When exposure_mode="0", this
			value must be set to "-".
			* Only available when
			"capability_image_c<0~(n-1)>_
			exposure_mode" is 1.
exposure_hlcmode_suppo	<boolean></boolean>	0/7	Indicate whether to support exposure
rtwindow			window in hlc mode.

			· · · · · · · · · · · · · · · · · · ·
			* Only available when
			"capability_image_c<0~(n-1)>_
			exposure_mode" is 1 and hlc is listed
			in "capability_image_c<0~(n-1)>_
			exposure_winmode".
exposure_hlcmode_affect	-,	0/7	When hlc mode is enabled, some
	or others		features may become malfunction or
			be forced to a given value. The
	<x>: nonnegative integer</x>		affected functions are list here.
	<product dependent=""></product>		
			The format is "Affect API
			name":"Policy":"Description"
			"Policy" can be categorized into
			following groups:
			- (disabled) : UI turns grey and users
			can't select it.
			- (unchanged) : UI keeps the status as
			before and
			user can't change it.
			- (hidden) : UI is hidden.
			- (fixed) : UI is fixed to one selection or
			value.
			- (ranged) : UI is fixed to multiple
			selections or values.
			- (enabled) : UI is checked.
			- (notsupport) : the affected function
			is not available.
			"Affect API name" can be described in
			hierarchy, such as
			"exposurewin.mode.blc:disabled:"
			which means blc exposure window is
			disabled. API name can be one word as
			well, such as "exposurelevel:fixed:6"
			which means exposurelevel is fixed to
			level 6.
			"Description" can be a nonnegative
			integer or string or NULL.

**** means no feature is affected.         * Only available when         **** means no feature is affected.         * Only available when         ***** means no feature is affected.         * Only available when         ************************************				
* We support this parameter when the version number (httpversion) is equal or greater than 0304a.         exposure_wintype       inclusive, exclusive, -         -       'Inclusive": The image inside a window is the target area of exposure control.         "exclusive,'       -         -       ''Inclusive": The image inside a window is omitted by exposure control.         "exclusive": The image inside a window is omitted by exposure control.       "exclusive": The image inside a window is somitted by exposure control.         *** '': Not supported.       * Only available when "capability_image_c<0~(n-1)>_ exposure_mode" is 1.         exposure_windomain       qvga, px, std, -       0/7         qvga, px, std, -       0/7       The domain to set an exposure window in the image with pixels.         "std": A normalized 0~9999 range.       "-"": Not supported.         * Only available when "capability_image_c<0~(n-1)>_ exposure_mode" is 1.         exposure_winnum       Q, <positive integer="">       0/7         exposure_winnum       Q, <positive integer="">       0/7         Indicate the number of custom exposure windows.       * If no "custom" is listed in "exposure_winnode", this should be 0.</positive></positive>				* Only available when "capability_image_c<0~(n-1)>_ exposure_mode" is 1 and hlc is listed in "capability_image_c<0~(n-1)>_
exposure_wintypeinclusive, exclusive, -0/7The supported exposure window type. "inclusive": The image inside a window is the target area of exposure control. "exclusive": The image inside a window is omitted by exposure control. "exclusive": The image inside a 				
exposure_wintype       inclusive, exclusive, -       0/7       The supported exposure window type. "inclusive": The image inside a window is the target area of exposure control. "exclusive": The image inside a window is omitted by exposure control. "-"": Not supported.         * Only available when "capability_image_c<0~(n-1)>_ exposure_mode" is 1.         exposure_windomain       qvga, px, std, -       0/7       The domain to set an exposure window. "qvga": a 320x240 range to represent the whole image. "px": Locate a window in the image with pixels. "std": A normalized 0~9999 range. "-"": Not supported. * Only available when "capability_image_c<0~(n-1)>_ exposure_mode" is 1.         exposure_winnum       0, <positive integer="">       0/7       Indicate the number of custom exposure windows. * If no "custom" is listed in "exposure_winnode", this should be 0.</positive>				version number (httpversion) is equal
exclusive,       "inclusive": The image inside a window is the target area of exposure control.         "exclusive": The image inside a window is omitted by exposure control.       "exclusive": The image inside a window is omitted by exposure control.         "exclusive": Not supported.       * Only available when "capability_image_c<0~(n-1)>_ exposure_mode" is 1.         exposure_windomain       qvga, px, std, -       0/7       The domain to set an exposure window.         "qvga": a 320x240 range to represent the whole image.       "px": Locate a window in the image with pixels.         "std": A normalized 0~9999 range.       "-"": Not supported.         * Only available when "capability_image_c<0~(n-1)>_ exposure_mode" is 1.         exposure_winnum       0, <positive integer="">       0/7       Indicate the number of custom exposure_windows.         * If no "custom" is listed in "exposure_winmode", this should be 0.       0.</positive>				or greater than 0304a.
-       window is the target area of exposure control.         "exclusive": The image inside a window is omitted by exposure control.       "exclusive": The image inside a window is omitted by exposure control.         "-": Not supported.       * Only available when "capability_image_<<0~(n-1)>_ exposure_mode" is 1.         exposure_windomain       qvga, px, std, -       0/7       The domain to set an exposure window.         "qvga": a 320x240 range to represent the whole image.       "px": Locate a window in the image with pixels.       "std": A normalized 0~9999 range.         "-": Not supported.       * Only available when       "capability_image_c<0~(n-1)>_ exposure_mode" is 1.         exposure_winnum       0, <positive integer="">       0/7       Indicate the number of custom exposure windows.         * If no "custom" is listed in "exposure_winnode", this should be 0.       0,        * If no "custom" is listed in "exposure windows.</positive>	exposure_wintype	inclusive,	0/7	The supported exposure window type.
exposure_windomain       qvga, px, std, -       0/7       The domain to set an exposure window.         "qvga": a 320x240 range to represent the whole image.       "px": Locate a window in the image with pixels.         "std": A normalized 0~9999 range.       "-": Not supported.         * Only available when       "capability_image_c<0~(n-1)>_         exposure_windomain       qvga, px, std, -       0/7       The domain to set an exposure window.         "qvga": a 320x240 range to represent the whole image.       "px": Locate a window in the image with pixels.       "std": A normalized 0~9999 range.         "-": Not supported.       * Only available when       "capability_image_c<0~(n-1)>_       exposure_mode" is 1.         exposure_winnum       0, <positive integer="">       0/7       Indicate the number of custom exposure windows.         * If no "custom" is listed in "exposure_winnode", this should be 0.       0.</positive>		exclusive,		"inclusive": The image inside a
exposure_windomain       Qvga, px, std, -       0/7       The domain to set an exposure window.         "qvga": a 320x240 range to represent the whole image.       "px": Locate a window in the image.         "px": Locate a window in the image.       "px": Locate a window in the image.         "px": Not supported.       * Only available when         "capability_image_c<0~(n-1)>_       exposure_mode" is 1.         exposure_windomain       qvga, px, std, -       0/7         The domain to set an exposure window.       "qvga": a 320x240 range to represent the whole image.         "px": Locate a window in the image.       "px": Locate a window in the image with pixels.         "std": A normalized 0~9999 range.       "-"": Not supported.         * Only available when       "capability_image_c<0~(n-1)>_         exposure_winnum       0, <positive integer="">       0/7         Indicate the number of custom exposure windows.       * If no "custom" is listed in "exposure_winmode", this should be 0.</positive>		-		window is the target area of exposure
exposure_windomain       qvga, px, std, -       0/7       The domain to set an exposure window.         "qvga": a 320x240 range to represent the whole image.       "px": Locate a window in the image.         "px": Locate a window in the image.       "px": Locate a window in the image.         "std": A normalized 0~9999 range.       "-"": Not supported.         * Only available when       "capability_image_c<0~(n-1)>_exposure_mode" is 1.         exposure_winnum       0, <positive integer="">       0/7         Indicate the number of custom exposure windows.       * If no "custom" is listed in "exposure_windows.         * If no "custom" is listed in "exposure_windows.       * If no "custom" is listed in "exposure_windows.</positive>				
exposure_windomain       qvga, px, std, -       0/7       The domain to set an exposure window.         "qvga": a 320x240 range to represent the whole image.       "px": Locate a window in the image with pixels.         "std": A normalized 0~9999 range.       "-": Not supported.         * Only available when       "capability_image_c<0~(n-1)>_         exposure_windomain       qvga, px, std, -       0/7         The domain to set an exposure window.       "qvga": a 320x240 range to represent the whole image.         "px": Locate a window in the image with pixels.       "std": A normalized 0~9999 range.         "-": Not supported.       * Only available when         "capability_image_c<0~(n-1)>_       exposure_mode" is 1.         exposure_winnum       0, <positive integer="">       0/7       Indicate the number of custom exposure windows.         * If no "custom" is listed in "exposure_window.       * If no "custom" is listed in "exposure_window", this should be 0.</positive>				"exclusive": The image inside a
Image: series of the series				
* Only available when         "capability_image_c<0~(n-1)>_         exposure_windomain       qvga, px, std, -         0/7       The domain to set an exposure         window.       "qvga": a 320x240 range to         represent the whole image.       "px": Locate a window in the image.         "px": Locate a window in the image.       "inft": A normalized 0~9999 range.         "-": Not supported.       * Only available when         "capability_image_c<0~(n-1)>_       exposure_mode" is 1.         exposure_winnum       0, <positive integer="">       0/7         Indicate the number of custom       exposure windows.         * If no "custom" is listed in       "exposure_winmode", this should be         0.       0.</positive>				
exposure_windomain       qvga, px, std, -       0/7       The domain to set an exposure window.         "qvga": a 320x240 range to represent the whole image.       "px": Locate a window in the image with pixels.         "std": A normalized 0~9999 range.       "-"": Not supported.         * Only available when       "capability_image_c<0~(n-1)>_         exposure_winnum       0, <positive integer="">       0/7         Indicate the number of custom exposure windows.       * If no "custom" is listed in "exposure_winmode", this should be 0.</positive>				"-": Not supported.
exposure_windomain       qvga, px, std, -       0/7       The domain to set an exposure window.         "qvga": a 320x240 range to represent the whole image.       "px": Locate a window in the image with pixels.         "std": A normalized 0~9999 range.       "-"": Not supported.         * Only available when       "capability_image_c<0~(n-1)>_         exposure_winnum       0, <positive integer="">       0/7         Indicate the number of custom exposure windows.       * If no "custom" is listed in "exposure_winmode", this should be 0.</positive>				* Only available when
exposure_windomain       qvga, px, std, -       0/7       The domain to set an exposure window.         "qvga": a 320x240 range to represent the whole image.       "px": Locate a window in the image with pixels.       "std": A normalized 0~9999 range.         "-": Not supported.       * Only available when       "capability_image_c<0~(n-1)>_         exposure_winnum       0, <positive integer="">       0/7       Indicate the number of custom exposure windows.         * If no "custom" is listed in "exposure_winmode", this should be 0.       0.</positive>				
exposure_winnum       0, <positive integer="">       0/7       Indicate the number of custom exposure windows.         * If no "custom" is listed in "exposure_winnode", this should be 0.       0.</positive>				exposure_mode" is 1.
exposure_winnum0, <positive integer="">0/7Indicate the number of custom exposure_winmode", this should be 0.</positive>	exposure_windomain	qvga, px, std, -	0/7	The domain to set an exposure
exposure_winnum       0, <positive integer="">       0/7       Indicate the number of custom exposure windows.         * If no "custom" is listed in "exposure_winmode", this should be 0.       0.</positive>				window.
exposure_winnum       0, <positive integer="">       0/7       Indicate the number of custom exposure windows.         * If no "custom" is listed in "exposure_winmode", this should be 0.       0.</positive>				"qvga": a 320x240 range to
with pixels.         "std": A normalized 0~9999 range.         "-": Not supported.         * Only available when         "capability_image_c<0~(n-1)>_         exposure_winnum         0, <positive integer="">         0/7         Indicate the number of custom         exposure windows.         * If no "custom" is listed in         "exposure_winmode", this should be         0.</positive>				represent the whole image.
exposure_winnum       0, <positive integer="">       0/7       Indicate the number of custom exposure windows.         * If no "custom" is listed in "exposure_winmode", this should be 0.       0.</positive>				"px": Locate a window in the image
exposure_winnum       0, <positive integer="">       0/7       Indicate the number of custom exposure windows.         * If no "custom" is listed in "exposure_winmode", this should be 0.       0.</positive>				with pixels.
* Only available when         "capability_image_c<0~(n-1)>_         exposure_winnum       0, <positive integer="">       0/7         Indicate the number of custom         exposure windows.         * If no "custom" is listed in         "exposure_winmode", this should be         0.</positive>				"std": A normalized 0~9999 range.
exposure_winnum       0, <positive integer="">       0/7       Indicate the number of custom exposure windows.         exposure_winnum       0, <positive integer="">       0/7       Indicate the number of custom exposure windows.         image: the state of the st</positive></positive>				
exposure_winnum       0, <positive integer="">       0/7       Indicate the number of custom exposure windows.         * If no "custom" is listed in "exposure_winmode", this should be 0.       0.</positive>				
exposure_winnum       0, <positive integer="">       0/7       Indicate the number of custom exposure windows.         * If no "custom" is listed in "exposure_winmode", this should be 0.</positive>				
exposure windows. * If no "custom" is listed in "exposure_winmode", this should be 0.				
* If no "custom" is listed in "exposure_winmode", this should be 0.	exposure_winnum	0, <positive integer=""></positive>	0/7	
"exposure_winmode", this should be 0.				exposure windows.
0.				* If no "custom" is listed in
				"exposure_winmode", this should be
* Only available when				
				* Only available when

"capability_image_c<0~(n- exposure_mode" is 1.	
evnosure mode" is 1	·1)>_
exposure_ntsc_totalrange   A list of <positive integer=""> 0/7 Available total range for NT</positive>	SC analog
output.	
* Only available when	
"capability_image_c<0~(n-	1)>_
exposure_mode" is 1.	
* We support this parameter	er when
the version number (httpve	rsion) is
equal or greater than 0301a	
exposure_pal_totalrange A list of <positive integer=""> 0/7 Available total range for PAI</positive>	L analog
output.	
* Only available when	
"capability_image_c<0~(n-	1)>_
exposure_mode" is 1.	. –
* We support this paramete	er when
the version number (httpve	
equal or greater than 0301a	-
exposure_maxrange "1,32000", 0/7 Available range for "videoin_c <n>_maxexposu</n>	ro"
-, $"1,32000" => 1s \sim 1/3200$	US
or others "1,8000" => 1s ~ 1/8000s	
<pre><product dependent=""> etc.</product></pre>	
"-" means maximum expos	ure time is
not available.	
* When "exposure_mode"=	0, this
value must be set to "-".	
* Only available when	
"capability_image_c<0~(n-	1)>_
exposure_mode" is 1.	
exposure_minrange "1,32000", 0/7 Available range for	
"1,8000", "videoin_c <n>_minexposur</n>	re"
-, "1,32000" => 1s ~ 1/3200	0s
or others "1,8000" => 1s ~ 1/8000s	
<product dependent=""> etc.</product>	
"-" means minimum exposu	ure time is
not available.	

			Τ
			* When "exposure_mode"=0, this
			value must be set to "-".
			* Only available when
			"capability_image_c<0~(n-1)>_
			exposure_mode" is 1.
privacymask_wintype	rectangle,	0/7	The supported mask window type.
	polygon,		"polygon": The window is a 2D
	3Drectangle		polygon shape.
			"rectangle": The window is a 2D
			rectangle shape.
			"3Drectangle": The window is a 3D
			rectangle shape.
privacymask_windomain	qvga, px, std, -	0/7	The domain to set an window.
			"qvga": a 320x240 range to
			represent the whole image.
			"px": Locate a window in the image
			with pixels.
			"std": A normalized 0~9999 range.
			"-": Not supported.
privacymask_ncolor	<positive integer=""></positive>	0/7	Available total color numbers of
r,		-,	privacy mask.
agc_maxgain	"0,100",	0/7	Available range for
	n_n	-,	"videoin_c <n>_maxgain"</n>
			"0,100" => 0~100 percent
			"-" means "videoin_c <n>_maxgain" is</n>
			not available.
agc_mingain	"0,100",	0/7	Available range for
age_mingam	"_"	0,7	"videoin_c <n>_mingain"</n>
			"0,100" => 0~100 percent
			"-" means "videoin_c <n>_mingain" is</n>
			not available.
	0.1	0/7	
flickerless	0,1	0/7	0: Non-support flickerless
			1: Support flickerless
flickerlessaffect	-,	0/7	When flickerless is enabled, some
	minexposure:hidden:,		features may become malfunction or
	mingain:hidden:,		be forced to a given value. The
	or others		affected functions are list here.
	<x>: nonnegative integer</x>		The format is "Affect API
	<product dependent=""></product>		name":"Policy":"Description"

			"Policy" can be categorized into
			following groups:
			- (disabled) : UI turns grey and users
			can't select it.
			- (unchanged) : UI keeps the status as
			before and
			user can't change it.
			- (hidden) : UI is hidden.
			- (fixed) : UI is fixed to one selection or
			value.
			- (ranged) : UI is fixed to multiple
			selections or values.
			- (enabled) : UI is checked.
			- (notsupport) : the affected function
			is not available.
			"Affect API name" can be described in
			hierarchy, such as
			"exposurewin.mode.blc:disabled:"
			which means blc exposure window is
			disabled. API name can be one word as
			well, such as "exposurelevel:fixed:6"
			which means exposurelevel is fixed to
			level 6.
			"Description" can be a poppositive
			"Description" can be a nonnegative
			integer or string or NULL.
			"-" means no feature is affected.
			* When "flickerless" = 0, this value
			must be "-"
defog_mode	0,1	0/7	0: Non-support defog
delog_mode	0,1	0,7	1: Support defog
	0, 1	0/7	0: Non-support tuning strength of
	0, 1		defog
			1: Support tuning strength of defog
			1. Support tuning strength of delog
			* If
			"capability_image_c<0~(n-1)>_defog
			capability_intage_c<0.v(ii-1)>_delog

			_mode"=1, this may be either 0 or 1.
defog_supportlevel	0, <positive integer=""></positive>	0/7	The value indicate the support
			strength level of defog.
defog_affect	-,	0/7	When defog is enabled, some features
	wdrpro:unchanged:,		may become malfunction or be forced
	or others		to a given value. The affected
			functions are list here.
	<x>: nonnegative integer</x>		
	<product dependent=""></product>		The format is "Affect API
			name":"Policy":"Description"
			"Policy" can be categorized into
			following groups:
			- (disabled) : UI turns grey and users
			can't select it.
			- (unchanged) : UI keeps the status as
			before and
			user can't change it.
			- (hidden) : UI is hidden.
			- (fixed) : UI is fixed to one selection o
			value.
			- (ranged) : UI is fixed to multiple
			selections or values.
			- (enabled) : UI is checked.
			- (notsupport) : the affected function
			is not available.
			"Affect API name" can be described ir
			hierarchy, such as
			"exposurewin.mode.blc:disabled:"
			which means blc exposure window is
			disabled. API name can be one word as
			well, such as "exposurelevel:fixed:6"
			which means exposurelevel is fixed to
			level 6.
			"Description" can be a nonnegative
			integer or string or NULL.
			"-" means no feature is affected.

aespeed       0,1       0/7       0: Non-support AE speed         aespeedsupportlevel <positive integer="">       0/7       The value indicate the support strength level of aespeed.         aespeedsupportlevel       <positive integer="">       0/7       The value indicate the support strength level of aespeed.         aespeedsupportsensitivity       0,1       0/7       O: Non-support tuning the sens of AE converge speed.         aespeedsupportsensitivity       0,1       0/7       O: Non-support tuning the sensitivit converge speed.         aespeedsupportsensitivity       0,1       0/7       O: Non-support tuning the sensitivit converge speed.         aespeedsupportsensitivity       0,1       0/7       O: Non-support tuning Gamma "capability_image_c&lt;0~(n-1)&gt; eed" is 1.         gammacurve       0,1       0/7       O: Non-support tuning Gamma curv         lowlightmode       -,0,1       0/7       -: Internal parameter, must not to user.         0: Non-support low light mode       1: Support low light mode       -: Support low light mode</positive></positive>	sitivity y of AE _aesp curve e
aespeedsupportlevel <positive integer="">       0/7       The value indicate the support strength level of aespeed.         aespeedsupportlevel       <positive integer="">       0/7       The value indicate the support strength level of aespeed.         aespeedsupportsensitivity       0,1       0/7       0: Non-support tuning the sense of AE converge speed.         aespeedsupportsensitivity       0,1       0/7       0: Non-support tuning the sensitivit converge speed.         aespeedsupportsensitivity       0,1       0/7       0: Non-support tuning the sensitivit converge speed.         aespeedsupportsensitivity       0,1       0/7       0: Non-support tuning the sensitivit converge speed.         aespeedsupportsensitivity       0,1       0/7       0: Non-support tuning damma to support tuning Gamma to support tuning Gamma to support tuning Gamma to support tuning Gamma to support to user.         aespeedsupportsensitivity       -,0,1       0/7       -: Internal parameter, must not to user.</positive></positive>	sitivity y of AE _aesp curve e
aespeedsupportlevel <positive integer="">       0/7       The value indicate the support strength level of aespeed.         * Only available when       "capability_image_c&lt;0~(n-1)&gt;       eed" is 1.         aespeedsupportsensitivity       0,1       0/7       0: Non-support tuning the sensitivit converge speed.         aespeedsupportsensitivity       0,1       0/7       0: Non-support tuning the sensitivit converge speed.         gammacurve       0,1       0/7       0: Non-support tuning the sensitivit converge speed.         gammacurve       0,1       0/7       0: Non-support tuning Gamma 1: Support tuning Gamma 1: Support tuning Gamma curv         lowlightmode       -,0,1       0/7       -: Internal parameter, must not to user.</positive>	sitivity y of AE _aesp curve e
And the set of a speed.strength level of a speed.aespeedsupportsensitivity0,10/70: Non-support tuning the sense of AE converge speed. 1: Support tuning the sensitivitie converge speed. 1: Support tuning the sensitivitie converge speed. * Only available when "capability_image_c<0~(n-1)> eed" is 1.gammacurve0,10/70: Non-support tuning the sensitivitie converge speed. * Only available when "capability_image_c<0~(n-1)> eed" is 1.gammacurve0,10/70: Non-support tuning Gamma 1: Support 1: Supp	sitivity y of AE _aesp curve e
aespeedsupportsensitivity       0,1       0/7       0: Non-support tuning the sense of AE converge speed.         aespeedsupportsensitivity       0,1       0/7       0: Non-support tuning the sense of AE converge speed.         aespeedsupportsensitivity       0,1       0/7       0: Non-support tuning the sense of AE converge speed.         gammacurve       0,1       0/7       0: Non-support tuning the sense of AE converge speed.         gammacurve       0,1       0/7       0: Non-support tuning Gamma 1: Support tuning Gamma 1: Support tuning Gamma 1: Support tuning Gamma curve         lowlightmode       -,0,1       0/7       -: Internal parameter, must not to user.	sitivity y of AE _aesp curve e
aespeedsupportsensitivity0,10/70: Non-support tuning the sense of AE converge speed. 1: Support tuning the sensitivity converge speed. * Only available when "capability_image_c<0~(n-1)> eed" is 1.gammacurve0,10/70: Non-support tuning Gamma 1: Support tuning Gamma curv 0.1lowlightmode-,0,10/7-: Internal parameter, must not to user. 0: Non-support low light mode	sitivity y of AE _aesp curve e
eed" is 1.aespeedsupportsensitivity0,10/70: Non-support tuning the sense of AE converge speed. 1: Support tuning the sensitivit converge speed. * Only available when "capability_image_c<0~(n-1)> eed" is 1.gammacurve0,10/70: Non-support tuning Gamma 1: Support tuning Gamma curvelowlightmode-,0,10/7-: Internal parameter, must not to user. 0: Non-support low light mode	sitivity y of AE _aesp curve e
aespeedsupportsensitivity0,10/70: Non-support tuning the sensitivity of AE converge speed. * Only available when "capability_image_c<0~(n-1)> eed" is 1.gammacurve0,10/70: Non-support tuning Gamma 1: Support tuning Gamma curv 1: Support tuning Gamma curvlowlightmode-,0,10/7-: Internal parameter, must not to user. 0: Non-support low light mode	aesp curve
a b c c c c c c c c c c c c c c c c c c	aesp curve
Image: speed s	_aesp curve
gammacurve0,10/70: Non-support tuning Gamma curvelowlightmode-,0,10/7-: Internal parameter, must not to user. 0: Non-support low light mode	_aesp curve
gammacurve       0,1       0/7       0: Non-support tuning Gamma 1: Support tuning Gamma curv         lowlightmode       -,0,1       0/7       -: Internal parameter, must not to user.         0: Non-support low light mode	curve
gammacurve0,10/70: Non-support tuning Gamma 1: Support tuning Gamma curv 1: Support tuning Gamma curv to user. 0: Non-support low light mode	curve
gammacurve     0,1     0/7     0: Non-support tuning Gamma 1: Support tuning Gamma curv       lowlightmode     -,0,1     0/7     -: Internal parameter, must not to user. 0: Non-support low light mode	curve
gammacurve       0,1       0/7       0: Non-support tuning Gamma         lowlightmode       -,0,1       0/7       -: Internal parameter, must not to user.         0: Non-support low light mode	e
Iowlightmode       -,0,1       0/7       -: Internal parameter, must not to user.         0: Non-support low light mode	e
Iowlightmode     -,0,1     0/7     -: Internal parameter, must not to user.       0: Non-support low light mode	
to user. 0: Non-support low light mode	open
to user. 0: Non-support low light mode	
1: Support low light mode	
focusassist 0,1 0/7 0: Non-support focus assist	
1: Support focus assist	
remotefocus 0, <positive integer=""> 0/7 An 4-bit integer, which indicate</positive>	s the
supportive application of remot	efocus
in this channel.	
If the value of this parameter is	s larger
than 0, it means that the came	ra
supports remotefocus function	in this
channel.	
bit 0 => Indicate whether to s	support
both zoom and focus function.	
bit 1 => Only support zoom	
function.	
bit 2 => Only support focus	
function.	
bit 3 => Currently, this is a re	eserved
bit, and the default value is 0.	

focuswindomain	avaa ny sta -	0/7	The domain to set a focus window.
Tocuswindonnann	qvga, px, std, -	0/ /	
			"qvga": a 320x240 range to
			represent the whole image.
			<b>"px"</b> : Locate a window in the image
			with pixels.
			"std": A normalized 0~9999 range.
			"-": Not supported.
focuswindow_nwindow	0, <positive integer=""></positive>	0/7	Number of focus window
focuswindow_range	<leftrange,rightrange,topra< td=""><td>0/7</td><td>Available range for focuswindow.</td></leftrange,rightrange,topra<>	0/7	Available range for focuswindow.
	nge,lowrange>		* We support this parameter when the
	<product dependent=""></product>		version number (httpversion) is equal
			or greater than 0305d.
			*-: Not supported.
lensconfiguration_support	0,1	0/7	Indicate whether to support different
			image library configuration files for
			specific exchangeable lens.
freeze	<boolean></boolean>	0/7	0: Non-support image freeze feature
			1: Support image freeze feature
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0302a.
autotrack_support	<boolean></boolean>	0/7	0: Non-support auto tracking feature
			1: Support auto tracking feature
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0302a.
smartsensor_iristotalrang	A list of iris value	0/7	Available total step for iris value.
e		-,-	* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0302a.
			* Only available when
			"capability_image_c<0~(n-1)>_sens
			ortype" is "smartsensor"
dointorlace suprart	chaoloon	0/7	
deinterlace_support	<boolean></boolean>	0/7	Indicate whether to support deinterlace function.
			* We support this parameter when the
			version number (httpversion) is equal
			or greater than 0308a.
deinterlace_mode	spatial, blend	0/7	Spatical mode provides the best image
			quality, while Blend mode provides

	better image quality (than not using
	the deinterlace function at all).
	* Only available when
	capability_image_c<0~(n-1)>_deinte
	rlace_support is 1

#### Group: capability\_peripheral\_c<0~(n-1)> n denotes the value of "capability\_nvideoin"

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
devicecontrol	<boolean></boolean>	0/7	Indicate whether to support the peripheral
			device control.
			* We support this parameter when the version
			number (httpversion) is equal or greater than
			0305c.

### 7.26 Customized event script

Group: event\_customtaskfile\_i<0~2>

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
name	string[40]	6/6	Custom script identification of this entry.
date	string[4~20]	6/6	Date of custom script.
time	string[4~20]	6/6	Time of custom script.

# 7.27 Event setting

### Group: event\_i<0~2>

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
name	string[40]	6/6	Identification of this entry.
enable	0, 1	6/6	Enable or disable this event.
priority	0, 1, 2	6/6	Indicate the priority of this event:
			"0"= low priority
			"1"= normal priority
			"2"= high priority
delay	1~999	6/6	Delay in seconds before detecting the next
			event.
trigger	boot,	6/6	Indicate the trigger condition:
	di,		"boot" = System boot
	pir,		"di"= Digital input
	motion,		"pir"= PIR detection
	seq,		"motion" = Video motion detection
	recnotify,		"seq" = Periodic condition
	tampering,		"visignal" = Video input signal loss.
	vi,		"recnotify" = Recording notification.
	volalarm,		"tampering" = Tamper detection.
	visignal,		"vi"= Virtual input (Manual trigger)
	vadp,		"volalarm"= Audio detection
	smartsd		"smartsd" = Lifetime detection of SD card
	<product dependent=""></product>		
triggerstatus	string[40]	6/6	The status for event trigger
di	0, <positive integer=""></positive>	6/6	Indicate the source id of di trigger.
			This field is required when trigger condition is
			"di″.
			One bit represents one digital input. The LSB
			indicates DI 0.
			* Only available when "capability_ndi" > 0

mdwin	0, <positive integer=""></positive>	6/6	Indicate the source window id of motion
			detection.
			This field is required when trigger condition is
			"md″.
			One bit represents one window.
			The LSB indicates the $1^{st}$ window.
			For example, to detect the $1^{st}$ and $3^{rd}$ windows,
			set mdwin as 5.
mdwin0	0, <positive integer=""></positive>	6/6	Similar to mdwin. The parameter takes effect
			when profile 1 of motion detection is enabled.
vi	0, <positive integer=""></positive>	6/6	Indicate the source id of vi trigger.
			This field is required when trigger condition is
			"vi″.
			One bit represents one digital input. The LSB
			indicates VI 0.
vadp	0, <positive integer=""></positive>	6/6	Indicate the source id of vadp event notification.
<product dependent=""></product>			Each bit corresponds to one vadp source, and
			the LSB indicates source id 0.
			For example, to detect event from any one of
			source id 0, 1 and 3, set vadp to 11.
			* Only available when vadp is listed in
			"capability_supporttriggertypes"
valevel	0,1	6/6	Select audio detection event.
		0,0	0: not select
			1: select
valevel0	0,1	6/6	Select audio detection profile event.
		0,0	0: not select
			1: select
intor	1~999	6/6	
inter	222	0/0	Interval of snapshots in minutes.
			This field is used when trigger condition is "seq".

weekday	0~127	6/6	Indicate which weekday is scheduled.
,			One bit represents one weekday.
			bit0 (LSB) = Saturday
			bit1 = Friday
			bit2 = Thursday
			bit3 = Wednesday
			bit4 = Tuesday
			bit5 = Monday
			bit6 = Sunday
			For example, to detect events on Friday and
			Sunday, set weekday as 66.
begintime	hh:mm	6/6	Begin time of the weekly schedule.
endtime	hh:mm	6/6	End time of the weekly schedule.
			(00:00 ~ 24:00 sets schedule as always on)
lowlightcondition	0, 1	6/6	Switch on white light LED in low light condition
<product dependent=""></product>			0 => Do action at all times
			1 = > Do action in low-light conditions
action_do_i<0~(ndo-1)>_e	e <boolean></boolean>	6/6	Enable or disable trigger digital output.
nable			* Only available when "capability_ndo" > 0
action_do_i<0~(ndo-1)>_	1~999	6/6	Duration of the digital output trigger in seconds.
duration			* Only available when "capability_ndo" > 0
action_cf_enable	<boolean></boolean>	6/6	Enable or disable sending media to SD card.
			* Only available when "capability_supportsd" >
			0
action_cf_folder	string[128]	6/6	Path to store media.
			* Only available when "capability_supportsd" >
			0
action_cf_media	NULL, 0~4,101	6/6	Index of the attached media.
			101 means "Recording Notify"
			* Only available when "capability_supportsd" >
			0
action_cf_datefolder	<boolean></boolean>	6/6	Enable this to create folders by date, time, and
			hour automatically.
			* Only available when "capability_supportsd" >
			0
action_cf_backup	<boolean></boolean>	6/6	Enable or disable the function that send media to
			SD card for backup if network is disconnected.
			* Only available when "capability_supportsd" >
			0

action_server_i<0~4>_ena	a <boolean></boolean>	6/6	Enable or disable this server action.
ble			
action_server_i<0~4>_me	NULL, 0~4,101	6/6	Index of the attached media.
dia			101 means "Recording Notify"
action_server_i<0~4>_dat	<boolean></boolean>	6/6	Enable this to create folders by date, time, and
efolder			hour automatically.
action_goto_enable	<boolean></boolean>	6/6	Enable/disable ptz goto preset position on event
<product dependent=""></product>			triggered.
			* Only available when capability_ptzenabled >
			0.
action_goto_name	string[40]	6/6	Specify the preset name that ptz goto on event
<product dependent=""></product>			triggered.
			* Only available when capability_ptzenabled >
			0.
action_goto_sync	<boolean></boolean>	6/6	Capture media after moving to the location.
<product dependent=""></product>			* Only avaliable when the bit4 of
			capability_ptzenabled is 1 and the bit7 of
			capability_ptzenabled is 0, or
			capability_camctrl_c0_zoommodule > 0
action_autotrack_enable	<boolean></boolean>	6/6	Enable/disable auto tracking on event triggerd.
<product dependent=""></product>			* Only avaliable when the bit4 of
			capability_ptzenabled is 1 and the bit7 of
			capability_ptzenabled is 0

# 7.28 Server setting for event action

### Group: **server\_i**<0~4>

PARAMETER	VALUE	SECURITY (get/set)	DESCRIPTION
name	string[40]	6/6	Identification of this entry
type	email,	6/6	Indicate the server type:
	ftp,		"email" = email server
	http,		"ftp" = FTP server
	ns		"http" = HTTP server
			"ns" = network storage
http_url	string[128]	6/6	URL of the HTTP server to upload.
http_username	string[64]	6/6	Username to log in to the server.
http_passwd	string[64]	7/6	Password of the user.
ftp_address	string[128]	6/6	FTP server address.
ftp_username	string[64]	6/6	Username to log in to the server.
ftp_passwd	string[64]	7/6	Password of the user.
ftp_port	0~65535	6/6	Port to connect to the server.
ftp_location	string[128]	6/6	Location to upload or store the media.
ftp_passive	<boolean></boolean>	6/6	Enable or disable passive mode.
			0 = disable passive mode
			1 = enable passive mode
email_address	string[128]	6/6	Email server address.
email_sslmode	<boolean></boolean>	6/6	Enable support SSL.
email_port	0~65535	6/6	Port to connect to the server.
email_username	string[64]	6/6	Username to log in to the server.
email_passwd	string[64]	7/6	Password of the user.
email_senderemail	string[128]	6/6	Email address of the sender.
email_recipientemail	string[640]	6/6	Email address of the recipient.
ns_location	string[128]	6/6	Location to upload or store the media.
ns_username	string[64]	6/6	Username to log in to the server.
ns_passwd	string[64]	7/6	Password of the user.
ns_workgroup	string[64]	6/6	Workgroup for network storage.

# 7.29 Media setting for event action

### Group: media\_i<0~4>

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
name	string[40]	6/6	Identification of this entry
type	snapshot,	6/6	Media type to send to the server or
	systemlog,		store on the server.
	videoclip,		
	recordmsg		
snapshot_source	0~"capability_nmediastream"-1	6/6	Indicate the source of media stream.
			0 means the first stream.
			1 means the second stream and etc.
			2 means the third stream and etc.
			3 means the fourth stream and etc.
snapshot_prefix	string[16]	6/6	Indicate the prefix of the filename.
			media_i0=> Snapshot1_
			media_i1=> Snapshot2_
			media_i2=> Snapshot3_
			media_i3=> Snapshot4_
			media_i4=> Snapshot5_
snapshot_datesuffix	0, 1	6/6	Add date and time suffix to filename:
			1 = Add date and time suffix.
			0 = Do not add.
snapshot_preevent	0~"	6/6	Indicates the number of pre-event
	capability_media_snapshot_maxpr		images.
	eevent"		
snapshot_postevent	0~"	6/6	Indicates the number of post-event
	capability_media_snapshot_maxpo		images.
	stevent"		
videoclip_source	0~"capability_nmediastream"-1	6/6	Indicate the source of media stream.
			0 means the first stream.
			1 means the second stream and etc.
			2 means the third stream and etc.
			3 means the fourth stream and etc.
videoclip_prefix	string[16]	6/6	Indicate the prefix of the filename.
videoclip_preevent	0 ~ "	6/6	Indicates the time for pre-event
	capability_media_videoclip_maxpre		recording in seconds.
	event"		

videoclip_maxduration	1 ~ "	6/6	Maximum duration of one video clip in
	capability_media_videoclip_maxlen		seconds.
	gth"		
videoclip_maxsize	50 ~ "	6/6	Maximum size of one video clip file in
	capability_media_videoclip_maxsiz		Kbytes.
	e"		

# 7.30 Recording

Group: recording\_i<0~1>

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
name	string[40]	6/6	Identification of this entry.
trigger	schedule,	6/6	The event trigger type
	networkfail		schedule: The event is triggered by schedule
			networkfail: The event is triggered by the
			failure of network connection.
enable	<boolean></boolean>	6/6	Enable or disable this recording.
priority	0, 1, 2	6/6	Indicate the priority of this recording:
			"0" indicates low priority.
			"1" indicates normal priority.
			"2" indicates high priority.
source	0~"capability_nmediastream"-1	6/6	Indicate the source of media stream.
			0 means the first stream.
			1 means the second stream and so on.
maxretentiontime	<string></string>	6/6	To specify the expired time for automatic clean
			up, and it only takes effect for video clip
			generated by recording_i <0~1>.
			Format is
			"``P[Y]Y[MM]M[DDD]DT[hh]H[mm]M[ss]S'
			, similar with ISO8601 with symbols P
			Ex. P7D, it means 7 days. P1DT10H, it means
			1 days and 10 hours.
			The parameter takes offect when
			The parameter takes effect when
			autocleanup_
			maxretentiontime_recording_enabled is
			enabled.

limitsize	<boolean></boolean>	6/6	0: Entire free space mechanism
			1: Limit recording size mechanism
cyclic	<boolean></boolean>	6/6	0: Disable cyclic recording
			1: Enable cyclic recording
notify	<boolean></boolean>	6/6	0: Disable recording notification
			1: Enable recording notification
notifyserver	0~31	6/6	Indicate which notification server is
			scheduled.
			One bit represents one application server
			(server_i0~i4).
			bit0 (LSB) = server_i0.
			bit1 = server_i1.
			bit2 = server_i2.
			bit3 = server_i3.
			bit4 = server_i4.
			For example, enable server_i0, server_i2, and
			server_i4 as notification servers; the
			notifyserver value is 21.
weekday	0~127	6/6	Indicate which weekday is scheduled.
			One bit represents one weekday.
			bit0 (LSB) = Saturday
			bit1 = Friday
			bit2 = Thursday
			bit3 = Wednesday
			bit4 = Tuesday
			bit5 = Monday
			bit6 = Sunday
			For example, to detect events on Friday and
			Sunday, set weekday as 66.
begintime	hh:mm	6/6	Start time of the weekly schedule.
endtime	hh:mm	6/6	End time of the weekly schedule.
			(00:00~24:00 indicates schedule always on)
prefix	string[16]	6/6	Indicate the prefix of the filename.
cyclesize	100~	6/6	The maximum size for cycle recording in
			Kbytes when choosing to limit recording size.
reserveamount	0~1500000	6/6	The reserved amount in Mbytes when
			choosing cyclic recording mechanism.

dest	cf,	6/6	The destination to store the recorded data.
	0~4		"cf" means local storage (CF or SD card).
			"0" means the index of the network storage.
cffolder	string[128]	6/6	Folder name.
maxsize	100~2000	6/6	Unit: Mega bytes.
			When this condition is reached, recording file
			is truncated.
maxduration	60~3600	6/6	Unit: Second
			When this condition is reached, recording file
			is truncated.
adaptive_enable	<boolean></boolean>	6/6	Indicate whether the adaptive recording is
			enabled
adaptive_preevent	0~9	6/6	Indicate when is the adaptive recording
			started before the event trigger point
			(seconds)
adaptive_postevent	0~10	6/6	Indicate when is the adaptive recording
			stopped after the event trigger point
			(seconds)

### **7.31 HTTPS**

### Group: **https** (capability.protocol.https > 0)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	6/6	To enable or disable secure HTTP.
policy	<boolean></boolean>	6/6	If the value is 1, it will force HTTP connection
			redirect to HTTPS connection
method	auto,	6/6	auto =>Create self-signed certificate
	manual,		automatically.
	install		manual =>Create self-signed certificate
			manually.
			install =>Create certificate request and install.
status	-3 ~ 1	6/6	Specify the https status.
			-3= Certificate not installed
			-2 = Invalid public key
			-1 = Waiting for certificate
			0= Not installed
			1 = Active
countryname	string[2]	6/6	Country name in the certificate information.

stateorprovincename	string[128]	6/6	State or province name in the certificate
			information.
localityname	string[128]	6/6	The locality name in thecertificate information.
organizationname	string[64]	6/6	Organization name in the certificate
	VIVOTEK Inc.		information.
unit	string[64]	6/6	Organizational unit name in thecertificate
	VIVOTEK Inc.		information.
commonname	string[64]	6/6	Common name in the certificate information.
	www.vivotek.com		
validdays	0 ~ 3650	6/6	Valid period for the certification.

# 7.32 Storage management setting

Group: **disk\_i<0~(n-1)>** n is the total number of storage devices. (capability.storage.dbenabled > 0)

Currently it's only for local storage (SD, CF card), so n is equal to 1.

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
cyclic_enabled	<boolean></boolean>	6/6	Enable cyclic storage method.
autocleanup_enabled	<boolean></boolean>	6/6	Enable automatic clean up method.
<not recommended="" td="" to="" use<=""><td></td><td></td><td>Expired and not locked media files will be</td></not>			Expired and not locked media files will be
this>			deleted.
			* For forward compatibility reservations, but
			only group disk_i0_autocleanup is effective.
			* Not recommended to use this. Please refers
			"autocleanup" group.
			* This parameter will not be used after the
			version number (httpversion) is equal or greater
			than 0400a.
autocleanup_maxage	<positive integer=""></positive>	6/6	To specify the expired days for automatic clean
<not recommended="" td="" to="" use<=""><td></td><td></td><td>up.</td></not>			up.
this>			* For forward compatibility reservations, but
			only group disk_i0_autocleanup is effective.
			* Not recommended to use this. Please refers
			"autocleanup" group.
			* This parameter will not be used after the
			version number (httpversion) is equal or greater
			than 0400a.

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enabled	<boolean></boolean>	6/6	Enable automatic clean up method.
			Expired and not locked media files will be
			deleted.
maxretentiontime_recordin	<boolean></boolean>	6/6	Enable automatic clean up method for video clip
g_enabled			generated by recording task.
			The parameter takes effect when
			autocleanup_enabled is enabled.
maxretentiontime_recordin	<string></string>	6/6	To specify the expired time for automatic clean
g_i <0~1>_maxage			up, and it only takes effect for video clip
			generated by recording_i <0 $\sim$ 1>.
			Format is
			"``P[Y]Y[MM]M[DDD]DT[hh]H[mm]M[ss]S'
			, similar with ISO8601 with symbols P
			Ex. P7D, it means 7 days. P1DT10H, it means 1
			days and 10 hours.
			The parameter takes effect when autocleanup_
			maxretentiontime_recording_enabled is
			enabled.
maxretentiontime_others_e	<boolean></boolean>	6/6	Enable automatic clean up method for all media
nabled			files except media files generated by recording
			task.
			The parameter takes effect when
			autocleanup_enabled is enabled.

maxretentiontime_others_	<string></string>	6/6	To specify the expired time for automatic clean
maxage			up, and it takes effect for all media files except
			media files generated by recording task.
			Format is
			"``P[Y]Y[MM]M[DDD]DT[hh]H[mm]M[ss]S'
			, similar with ISO8601 with symbols P
			Ex. P7D, it means 7 days. P1DT10H, it means 1
			days and 10 hours.
			The parameter takes effect when
			autocleanup_maxretentiontime_others_enabled
			is enabled.

# 7.33 Region of interest

Group: **roi\_c<0~(n-1)>** for n channel product and m is the index of video stream which support ePTZ.

	(capability.eptz > 0 or capat	oility_fisheye = 1)
ſ		

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
s<0~(m-1)>_home	<w,h></w,h>	1/6	ROI left-top corner coordinate.* If the minimal
	<product dependent=""></product>		window size is 64x64, then the
			"win_i0_home"=(0~resolution_W-64,
			$0$ ~resolution_H-64), which the resolution is the
			value in current stream.
			* If the stream doesn't support ePTZ, the
			permissions of this parameter must be set as
			1/7.
s<0~(m-1)>_size	<wxh></wxh>	1/6	ROI width and height. The width value must be
	<product dependent=""></product>		multiples of 16 and the height value must be
			multiples of 8
			* The minimal window size is 64x64.
			* If the stream doesn't support ePTZ, the
			permissions of this parameter must be set as
			1/7.

# 7.34 ePTZ setting

Group: eptz_c<0~(n-1)> for n channel product.	. (capability.eptz > 0 or capability_fisheye = 1)
---	---

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
osdzoom	<boolean></boolean>	1/4	Indicates multiple of zoom in is "on-screen
<not recommended="" td="" to="" use<=""><td></td><td></td><td>display" or not.</td></not>			display" or not.
this>			
			* Reserved for compatibility, and suggest don't
			use this since [httpversion] > 0302a
			* We replace "eptz_c<0~(n-1)>_osdzoom" with
			" videoin_c<0~(n-1)>_zoomratiodisplay".
smooth	<boolean></boolean>	1/4	Enable the ePTZ "move smoothly" feature
tiltspeed	-5 ~ 5	1/4	Tilt speed
			* Only available when "capability_fisheye" is 1
		1/7	Tilt speed
			(It should be set by eCamCtrl.cgi rather than by
			setparam.cgi.)
panspeed	-5 ~ 5	1/4	Pan speed
			* Only available when "capability_fisheye" is 1
		1/7	Pan speed
			(It should be set by eCamCtrl.cgi rather than by
			setparam.cgi.)
zoomspeed	-5 ~ 5	1/4	Zoom speed
			* Only available when "capability_fisheye" is 1
		1/7	Zoom speed
			(It should be set by eCamCtrl.cgi rather than by
			setparam.cgi.)
autospeed	1 ~ 5	1/4	Auto pan/patrol speed
			* Only available when "capability_fisheye" is 1
		1/7	Auto pan/patrol speed
			(It should be set by eCamCtrl.cgi rather than by
			setparam.cgi.)
rotatespeed	1 ~ 5	1/4	Rotate speed (only for Fisheye series)
			* Only available when "capability_fisheye" is 1
			and
			"capability_fisheyelocaldewarp_c<0~(n-1)>" is
			0

Group: **eptz\_c<0~(n-1)>\_s<0~(m-1)>** for n channel product and m is the index of video stream which support ePTZ. (capability.eptz > 0 or capability\_fisheye = 1)

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
patrolseq	string[120]	1/4	The patrol sequence of ePTZ. All the patrol
			position indexes will be separated by ","
patroldwelling	string[160]	1/4	The dwelling time (unit: second) of each patrol
			point, separated by ",".
preset_i<0~19>_name	string[40]	1/4	Name of ePTZ preset.
			* Only available when "capability_fisheye" is 1
		1/7	Name of ePTZ preset.
			(It should be set by ePreset.cgi rather than by
			setparam.cgi.)
preset_i<0~19>_pos	<w,h></w,h>	1/4	Left-top corner coordinate of the preset.
	<product dependent=""></product>		* Only available when "capability_fisheye" is 1
		1/7	Left-top corner coordinate of the preset.
			(It should be set by ePreset.cgi rather than by
			setparam.cgi.)
preset_i<0~19>_size	<wxh></wxh>	1/4	Width and height of the preset.
	<product dependent=""></product>		* Only available when "capability_fisheye" is 1
		1/7	Width and height of the preset.
			(It should be set by ePreset.cgi rather than by
			setparam.cgi.)

### 7.35 Focus Window setting

Group: focuswindow\_c<0~(n-1)> for n channel products

n denotes the value of "capability\_nvideoin".

(capability\_image\_c<0~(n-1)>\_focuswindow\_nwindow > 0)

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
win_i0_enable	<boolean></boolean>	4/4	Enable or disable the window.
win_i0_home	<w,h></w,h>	4/4	Left-top corner coordinate of the window.
	<product dependent=""></product>		* If the minimal window size is 192x144, then
			the "win_i0_home"=(0~resolution_W-192,
			0~resolution_H-144), which the resolution is
			the value in current stream.
win_i0_size	<wxh></wxh>	4/4	Width and height of the window.
	<product dependent=""></product>		* The minimal window size is 192x144

### 7.36 Seamless recording setting

Group: **seamlessrecording** (capability.localstorage.seamless> 0)

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
diskmode	seamless,	1/6	"seamless" indicates enable seamless recording.
	manageable		"manageable" indicates disable seamless
			recording.
maxconnection	3	1/7	Maximum number of connected seamless
			streaming.
enable	<boolean></boolean>	1/7	Indicate whether seamless recording is
			recording to local storage or not at present.
			(Read only)
guid<0~2>_id	string[127]	1/7	The connected seamless streaming ID.
			(Read only)
guid<0~2>_number	0~3	1/7	Number of connected seamless streaming with
			guid<0~2>_id.
			(Read only)

### 7.37 VIVOTEK Application Development Platformsetting

Group: vadp

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
version	<string></string>	6/7	Indicate the VADP version.
resource_total_memory	0, <positive integer=""></positive>	6/7	Indicate total available memory size for VADP
			modules.
resource_total_storage	0, <positive integer=""></positive>	6/7	Indicate total size of the internal storage
			space for storing VADP modules.
resource_free_memory	0, <positive integer=""></positive>	6/7	Indicate free memory size for VADP modules.
resource_free_storage	0, <positive integer=""></positive>	6/7	Indicate current free storage size for
			uploading VADP modules.
module_number	0, <positive integer=""></positive>	6/7	Record the total module number that already
			stored in the system.
module_order	string[40]	6/6	The execution order of the enabled modules.
module_save2sd	<boolean></boolean>	6/6	Indicate if the module should be saved to SD
			card when user want to upload it.
			If the value is false, save module to the
			internal storage space and it will occupy
			storage size.
number	string[128]	6/7	This number is used to register license key for
			VADP application.

#### Group: vadp\_module\_i<0~(n-1)> for n VADP package number (capability\_vadp\_npackage > 0)

n denotes the value of "capability\_vadp\_npackage".

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	6/6	Indicate if the module is enabled or not.
			If yes, also add the index of this module to the
			module_order.
name	string[40]	6/6	Module name
extendedname	string[40]	6/6	Extended module name. If this value is not
			blank, it will be shown on the VADP UI first
			instead of vadp_module_i <n>_name.</n>
url	string[120]	6/6	Define the URL string after the IP address if the
			module provides it own web page.
vendor	string[40]	6/6	The provider of the module.

vendorurl	string[120]	6/6	URL of the vendor.
version	string[40]	6/6	Version of the module.
license	string[40]	6/6	Indicate the license status of the module.
licmsg	string[128]	6/6	Indicate the message that will be show on
			license status when mouse over.
path	string[40]	6/6	Record the storage path of the module.
initscr	string[40]	6/6	The script that will handle operation
			commands from the system.
status	string[40]	6/6	Indicate the running status of the module.
statmsg	string[128]	6/6	Indicate the message that will be show on the
			running status when mouse over.
vvtklicensemec	string[40]	6/7	Indicate the module use VIVOTEK license
			mechanism

#### Group: **vadp\_schedule\_i**<0~(n-1)> for n VADP package number

#### n denotes the value of "capability\_vadp\_npackage".

#### (Only available when "capability\_vadp\_npackage" > 0 and the version number of "vadp\_version" >= "1.3.2.0")

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	6/6	Enable or disable the schedule mode to
			control the execution of the VADP package
begintime	hh:mm	6/6	Begin time of the schedule
endtime	hh:mm	6/6	End time of the schedule

#### Group: vadp\_event

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
ntrigger	0, <positive integer=""></positive>	6/7	Indicate the number of topics to be transferred
			to event manager for trigger.
triggerlist_i<0~(n-1)>_to	string[256]	6/6	Indicate the event notification with this topic
pic			will be transferred to event manager as trigger.
			n is equal to ntrigger above.

### 7.38 camera PTZ control

#### Group: **camctrl** (capability.camctrl.ptztunnel > 0)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enableptztunnel	<boolean></boolean>	1/4	Enable PTZ tunnel for camera control.

#### Group: camctrl\_c<0~(n-1)> for n channel products (capability.ptzenabled > 0)

n denotes the value of "capability\_nvideoin" and k denotes the value of "capability\_npreset"

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
panspeed	-5 ~ 5	1/4	Pan speed
tiltspeed	-5 ~ 5	1/4	Tilt speed
zoomspeed	-5 ~ 5	1/4	Zoom speed
focusspeed	-5 ~ 5	1/4	Auto focus speed
patrolseq	string[120]	1/4	(For external device)
			The indexes of patrol points, separated by ","
patroldwelling	string[160]	1/4	(For external device)
			The dwelling time of each patrol point,
			separated by ","
preset_i<0~(k-1)>_name	string[40]	1/4	Name of the preset location.
preset_i<0~(k-1)>_	0 ~ 999	1/4	The dwelling time of each preset location
dwelling			
uart	0 ~ "	1/4	Select corresponding uart
	capability_nuart"-1		(capability.nuart>0).
cameraid	0~255	1/4	Camera ID controlling external PTZ camera.
isptz	0 ~ 2	1/4	0: disable PTZ commands.
			1: enable PTZ commands with PTZ driver.
			2: enable PTZ commands with UART tunnel.
			* Only available when bit7 of
			capability_ptzenabled is 1
disablemdonptz	<boolean></boolean>	1/4	Disable motion detection on PTZ operation.

### 7.39 camera PTZ control (IZ series)

# Group: **camctrl\_c<0~(n-1)>** for n channel products (capability\_camctrl\_c0\_zoommodule = 1 and capability\_camctrl\_c0\_buildinpt = 0)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
ccdtype	string[16]	6/7	(Internal used, read only)
motortype	string[16]	6/7	(Internal used, read only)
cameraid	0 ~ 255	1/4	Camera ID controlling external PTZ
			camera.
			Note:
			Please set your speed dome to the
			appropriate baud rate, and Camera ID,
			e.g. 2400bps, camera ID 1,2,3,,,,etc.
			All Camera IDs on the same controlling
			system (NVR or rs485 keyboard) have
			to be distinct.
			Therefore, once you send a controlling
			signal, each camera will only accept the
			inputs with the corresponding ID.
panspeed	-5 ~ 5	1/4	Pan speed
tiltspeed	-5 ~ 5	1/4	Tilt speed
zoomspeed	-5 ~ 5	1/4	Zoom speed
autospeed	-5 ~ 5	1/4	Auto pan speed
focusspeed	-5 ~ 5	1/4	Auto focus speed
focusmode	auto,onetimeauto,spotligh	1/4	Indicate the focus control mode.
	t,manual		
	* Available values are		
	listed in		
	"capability_camctrl_c<0~		
	(n-1)>_focusmode"		
uart	0 ~ "capability_nuart"-1	1/4	Select corresponding uart
			(capability.nuart>0).
isptz	0 ~ 2	1/4	0: disable PTZ commands.
			1: enable PTZ commands with PTZ
			driver.
			2: enable PTZ commands with UART
			tunnel.

n denotes the value of "capability\_nvideoin" and k denotes the value of "capability\_npreset"

			* Only available when bit7 of
			capability_ptzenabled is 1
preset_i<0~(k-1)>_name	string[40]	1/4	Name of the preset location.
preset_i<0~(k-1)>_zoom	capability_ptz_c<0~(n-1)	1/4	Zoom position at each preset location.
	>_minzoom ~	-/ .	
	capability_ptz_c<0~(n-1)		
	>_maxzoom		
preset_i<0~(k-1)>_focus	capability_ptz_c<0~(n-1)	1/4	Focus position at each preset location.
	>_minfocus ~	-/ 1	rocus posición de cuen preser location.
	capability_ptz_c<0~(n-1)		
	>_maxfocus		
 preset_i<0~(k-1)>	0 ~ 999	1/4	The dwelling time of each preset
dwelling	0.009999	1/4	location
preset_i<0~(k-1)>_focus		1/4	The focus mode of each preset, which is
setting	sync, fixcurrent	1/4	essential and should be grouped with
Setting	nxcurrenc		"preset_i<0~(k-1)>_name."
			* We support this parameter when the
			version number (httpversion) is equal or
			greater than 0305b.
naturalizad	atrina[120]	1/4	
patrolseq	string[120]	1/4	(For external device)
			The indexes of patrol points, separated
a shushda a Rasa		1/4	by ","
patroldwelling	string[160]	1/4	(For external device)
			The dwelling time of each patrol point,
			separated by ","
disablemdonptz	<boolean></boolean>	1/4	Disable motion detection on PTZ
			operation.
defaulthome	<boolean></boolean>	1/4	This field tells system to use default
			home position or not.
axisz	capability_ptz_c<0~(n-1)	1/4	Custom home zoom position.
	>_minzoom ~		
	capability_ptz_c<0~(n-1)		
	>_maxzoom		
axisf	capability_ptz_c<0~(n-1)	1/4	Custom home focus position.
	>_minfocus ~		
	capability_ptz_c<0~(n-1)		
	>_maxfocus		
digitalzoom	<boolean></boolean>	1/4	Enable/disable digital zoom
zoomenhance	<boolean></boolean>	1/4	Enable /disable zoom enhancement
returnhome	<boolean></boolean>	1/4	Enable/disable return home while idle.

returnhomeinterval	1~999	1/4	While idle over this time interval, idle
			action will be taken.
idleaction_enable	<boolean></boolean>	1/4	Enable/disable idle action while idle
idleaction_type	home	1/4	This field tells what kind of action should
			be taken while idle.
idleaction_interval	1~999	1/4	While idle over this time interval, idle
			action will be taken.

### 7.40 camera PTZ control (SD series)

#### Group: camctrl\_c<0~(n-1)> for n channel products (the bit7 of capability\_ptzenabled is 0 and the bit4 of

#### capability\_ptzenabled is 1)

n denotes the value of "capability\_nvideoin" and k denotes the value of "capability\_npreset"

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
ccdtype	string[16]	6/7	(Internal used, read only)
motortype	string[16]	6/7	(Internal used, read only)
cameraid	1 ~ 255	1/4	Camera ID controlling external PTZ
			camera.
			Note:
			Please set your speed dome to the
			appropriate baud rate, and Camera ID,
			e.g. 2400bps, camera ID 1,2,3,,,,etc.
			All Camera IDs on the same controlling
			system (NVR or rs485 keyboard) have
			to be distinct.
			Therefore, once you send a controlling
			signal, each camera will only accept the
			inputs with the corresponding ID.
panspeed	-5 ~ 5	1/4	Pan speed
tiltspeed	-5 ~ 5	1/4	Tilt speed
zoomspeed	-5 ~ 5	1/4	Zoom speed
autospeed	-5 ~ 5	1/4	Auto pan speed
focusspeed	-5 ~ 5	1/4	Auto focus speed
focusmode	auto,onetimeauto,spotligh	1/4	Indicate the focus control mode.
	t,manual		
	* Available values are		
	listed in		
	"capability_camctrl_c<0~		
	(n-1)>_focusmode"		

preset_i<0~(k-1)>_name	string[40]	1/4	Name of the preset location.
preset_i<0~(k-1)>_pan	capability_ptz_c<0~(n-1)	1/4	Pan position at each preset location.
	>_minpan ~		
	capability_ptz_c<0~(n-1)		
	>_maxpan		
preset_i<0~(k-1)>_tilt	capability_ptz_c<0~(n-1)	1/4	Tilt position at each preset location.
	>_mintilt ~		
	capability_ptz_c<0~(n-1)		
	>_maxtilt		
preset_i<0~(k-1)>_zoom	capability_ptz_c<0~(n-1)	1/4	Zoom position at each preset location.
	>_minzoom ~		
	capability_ptz_c<0~(n-1)		
	>_maxzoom		
preset_i<0~(k-1)>_focus	capability_ptz_c<0~(n-1)	1/4	Focus position at each preset location.
	>_minfocus ~		
	capability_ptz_c<0~(n-1)		
	>_maxfocus		
preset_i<0~(k-1)>_focus	sync,	1/4	The focus mode of each preset, which is
setting	fixcurrent		essential and should be grouped with
			"preset_i<0~(k-1)>_name."
			* We support this parameter when the
			version number (httpversion) is equal or
			greater than 0305b.
preset_i<0~(k-1)>_fliped	<boolean></boolean>	1/4	Flip side at each preset location.
patrol_i<0~39>_name	string[40]	1/4	(For internal device)
			The name of patrol location
patrol_i<0~39>_ dwelling	0 ~ 999	1/4	(For internal device)
			The dwelling time of each patrol location
disablemdonptz	<boolean></boolean>	1/4	Disable motion detection on PTZ
			operation.
defaulthome	<boolean></boolean>	1/4	This field tells system to use default
			home position or not.
axisx	capability_ptz_c<0~(n-1)	1/4	Custom home pan position.
	>_minpan ~		
	capability_ptz_c<0~(n-1)		
	>_maxpan		
axisy	capability_ptz_c<0~(n-1)	1/4	Custom home tilt position.
	>_mintilt ~		
	capability_ptz_c<0~(n-1)		
	>_maxtilt		

axisz	capability_ptz_c<0~(n-1)	1/4	Custom home zoom position.
	>_minzoom ~	-/ 1	
	capability_ptz_c<0~(n-1)		
	>_maxzoom		
axisf	capability_ptz_c<0~(n-1)	1/4	Custom home focus position.
	>_minfocus ~	_, .	
	capability_ptz_c<0~(n-1)		
	> maxfocus		
axisflip	<boolean></boolean>	1/4	Custom home flip side.
returnhome	<boolean></boolean>	1/4	Enable/disable return home while idle.
returnhomeinterval	1~999	1/4	While idle over this time interval, idle
			action will be taken.
digitalzoom	<boolean></boolean>	1/4	Enable/disable digital zoom
idleaction_enable	<boolean></boolean>	1/4	Enable/disable idle action while idle
idleaction_type	pan,patrol,home,objtrack,	1/4	This field tells what kind of action should
	prev		be taken while idle.
idleaction_interval	1~999	1/4	While idle over this time interval, idle
			action will be taken.
zoomenhance	<boolean></boolean>	1/4	Enable /disable zoom enhancement
tour_index	-1, 0~19	1/4	Index of the enabled tour group, from 0
			to 19.
			Set -1 to disable all the tour groups.
tour_i<0~19>_name	string[40]	1/4	Name of the tour.
tour_i<0~19>_type	<boolean></boolean>	1/4	0 = Recorded tour
			1 = Preset tour
tour_i<0~19>_speed	-5 ~ 5	1/4	Preset tour: pan and tilt speed when
			moving between presets.
			Recorded tour: unnecessary.
tour_i<0~19>_direction	forward,backward,random	1/4	User can choose which direction the
			preset tour goes.
			"forward": preset tour goes in forward
			order.
			"backward": preset tour goes in
			backward order.
			"random": the presets of the tour will
			be recalled randomly.
			* Only available when
			"capability_presettourdirection" is 1.
			* We support this parameter when the
			version number (httpversion) is equal or

			greater than 0307a.
tour_i<0~19>_checklist	string[512]	1/4	The indexes of preset positions,
			separated by ","
tour_i<0~19>_dwelltime	string[512]	1/4	Preset tour: time to wait before moving
			to the next preset position, separated by
			ж.// /
			Recorded tour: number of seconds to
			wait
			before continuing a loop tour.

### 7.41 UART control

#### Group: **uart** (capability.nuart > 0 and capability.fisheye = 0)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
ptzdrivers_i<0~19,	string[40]	1/4	Name of the PTZ driver.
127>_name			
ptzdrivers_i<0~19,	string[128]	1/4	Full path of the PTZ driver.
127>_location			
enablehttptunnel	<boolean></boolean>	1/4	Enable HTTP tunnel channel to control UART.

### Group: **uart\_i<0~(n-1)>** n is uart port count (capability.nuart > 0 and capability.fisheye = 0)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
baudrate	300,600,1200,2400	4/4	Set baud rate of COM port.
	,4800,9600,19200,		
	38400,57600,11520		
	0		
databit	5,6,7,8	4/4	Data bits in a character frame.
paritybit	none,	4/4	For error checking.
	odd,		
	even		
stopbit	1,2	4/4	1
			2-1.5 , data bit is 5
			2-2
uartmode	rs485,	4/4	RS485 or RS232.
	rs232		
customdrvcmd_i<0~9>	string[128]	1/4	PTZ command for custom camera.

speedlink_i<0~4>_name	string[40]	1/4	Additional PTZ command name.
speedlink_i<0~4>_cmd	string[40]	1/4	Additional PTZ command list.
ptzdriver	0~19,	1/4	The PTZ driver is used by this COM port.
	127 (custom),		
	128 (no driver)		

## 7.42 UART control (SD series)

Group: **uart\_i<0~(n-1)>** n is uart port count (capability.nuart > 0 and the bit7 of capability\_ptzenabled is 0, the bit4 of capability\_ptzenabled is 1)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
cameraid	1~255	4/4	Camera ID controlling external PTZ camera.
			Note:
			Please set your speed dome to the appropriate
			baud rate, and Camera ID, e.g. 2400bps,
			camera ID 1,2,3,,,,etc.
			All Camera IDs on the same controlling system
			(NVR or rs485 keyboard) have to be distinct.
			Therefore, once you send a controlling signal,
			each camera will only accept the inputs with
			the corresponding ID.
baudrate	2400,4800,9600,19	4/4	Set baud rate of COM port.
	200,38400,57600,1		
	15200		
databit	5,6,7,8	4/4	Data bits in a character frame.
paritybit	none,	4/4	For error checking.
	odd,		
	even		
stopbit	1,2	4/4	1
			2-1.5 , data bit is 5
			2-2
uartmode	rs485	4/7	RS485 mode.

# 7.43 Lens configuration

Group: **lens** for n channel products

n denotes the value of "capability\_nvideoin"

### (capability.image.c<0~(n-1)>.lensconfiguration.support = 1)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
selected	<string></string>	6/7	Current selected lens profile.
			e.g. lens_selected=lens_default_i0, it means
			choosen lens configuration is i0 lens of default
			group.

#### Group: lens\_default

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
totalnumbers	0, <positive integer=""></positive>	6/7	Totoal support number of the default lens
			profiles

### Group: lens\_user

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
totalnumbers	0, <positive integer=""></positive>	6/7	Totoal support number of the user lens profiles

#### Group: lens\_default\_i<0~(n-1)> n is lens\_default\_totalnumbers

NAME	VALUE	SECURITY (get/set)	DESCRIPTION
name	<string></string>	6/7	Default lens name

#### Group: lens\_user\_i<0~(n-1)> n is lens\_user\_totalnumbers

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
name	<string></string>	6/7	User-defined lens name

## 7.44 Fisheye info

### Group: **fisheyeinfo** (capability.fisheye > 0)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
revisedcenteraxis	<coordinate></coordinate>	6/7	The actual center axis coordinate
radius	0, <positive< td=""><td>6/7</td><td>The actual center radius</td></positive<>	6/7	The actual center radius
	integer>		

### 7.45 Fisheye local dewarp setting

### Group: **fisheyedewarp\_c<0~(n-1)> (**capability\_fisheyelocaldewarp\_c<0~(n-1)> > 0)

n denotes the value of "capability\_nvideoin", m denotes the value of "capability\_nmediastream"

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
panspeed	-5 ~ 5	1/4	Pan speed of regional view
	<integer></integer>		
tiltspeed	-5 ~ 5	1/4	Tilt speed of regional view
	<integer></integer>		
zoomspeed	-5 ~ 5	1/4	Zoom speed of regional
	<integer></integer>		
s<0~(m-2)>_panorama_	0~359	1/4	Initial pan position of panorama view.
panstart	<integer></integer>		(only available for 1P and 2P mode at ceiling or
			floor mount)
s<0~(m-2)>_region_pan	-90~359	1/4	Pan home angle of regional view
	<integer></integer>		Pan range of ceiling/floor mount is [0~359].
			Pan range of wall mount is [-90~90].
s<0~(m-2)>_region_tilt	-90~90	1/4	Tilt home angle of regional view
	<integer></integer>		Tilt range of ceiling/floor mount is [0~90].
			Tilt range of wall mount is [-90~90].
s<0~(m-2)>_region_zoo	100~300	1/4	Zoom home ratio of regional view
m	<integer></integer>		

### 7.46 PIR behavior define

Group: **pir** (capability.npir > 0)

NAME	VALUE	SECURITY	DESCRIPTION
		(get/set)	
enable	<boolean></boolean>	1/1	Enable/disable PIR

### 7.47 Auto tracking setting

### Group: **autotrack\_c<0~(n-1)>** (capability\_image\_c<0~(n-1)>\_autotrack\_support > 0)

n denotes the value of "capability\_nvideoin"

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
objsize_type	-1~2	1/4	Type of object size.
			-1 : customized width and height
			$0: object size = 30 \times 30$
			$1 : object size = 10 \times 20$
			2 : object size = $10 \times 10$
objsize_customized_width	10~320	1/4	The minimum width of tracking target.
objsize_customized_height	10~240	1/4	The minimum height of tracking target.
sensitivity	0~2	1/4	Tracking sensitivity.
			0: Low
			1: Medium
			2: High

### 7.48 Wireless

#### Group: wireless (capability\_network\_wireless > 0)

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
ssid	string[32]	6/6	SSID for wireless lan settings.
wlmode	Infra,	6/6	Wireless mode.
	Adhoc		Infra: Infrastructure
channel	1~11 or	6/6	A list of WLAN channels.
	1~13 or		Countries apply their own regulations to the
	10~11 or		allowable channels.
	10~13 or		1~11: USA and Canada
	1~14		1~13: Europe
			10~11: Spain
			10~13: France
			1~14: Japan
			* Only valid when "wireless_wlmode" is "Adhoc"

encrypt	none,	6/6	Encryption method:
encrypt		0,0	none: NONE,
	wep,		
	wpa,		wep: WEP,
	wpa2		wpa: WPA,
			wpa2: WPA2PSK
authmode	OPEN, SHARED	6/6	Authentication mode.
			* Only valid when "wireless_encrypt" is "wep"
keylength	64, 128	6/6	Key length in bits.
			* Only valid when "wireless_encrypt" is "wep"
keyformat	HEX, ASCII	6/6	Key1 ~ key4 presentation format.
			* Only valid when "wireless_encrypt" is "wep"
keyselect	1 ~ 4	6/6	Default key number.
			* Only valid when "wireless_encrypt" is "wep"
key1	password [26]	6/6	WEP key1 for encryption.
			* Only valid when "wireless_encrypt" is "wep"
key2	password [26]	6/6	WEP key2 for encryption.
			* Only valid when "wireless_encrypt" is "wep"
key3	password [26]	6/6	WEP key3 for encryption.
			* Only valid when "wireless_encrypt" is "wep"
key4	password [26]	6/6	WEP key4 for encryption.
			* Only valid when "wireless_encrypt" is "wep"
algorithm	AES, TKIP	6/6	Algorithm
			* Only valid when "wireless_encrypt" is "wpa" or
			"wpa2"
presharedkey	password [64]	6/6	WPA/WPA2PSK mode pre-shared key.
			* Only valid when "wireless_encrypt" is "wpa" or
			"wpa2"

### 7.49 Shock detection

Group: **shock\_c<0~(n-1)>** for n channel products

n denotes the value of "capability\_nvideoin" (capability\_peripheral\_c<0~(n-1)>\_shockdetection\_support > 0)

PARAMETER	VALUE	SECURITY	DESCRIPTION
		(get/set)	
alarm_enable	<boolean></boolean>	4/4	Enable shock detection's alarm.
alarm_level	1~100	4/4	The value indicate the support strength level of
			shock detection's alarm.

# 8. Useful Functions

## 8.1 Drive the Digital Output (capability.ndo > 0)

**Note:** This request requires Viewer privileges. **Method:** GET/POST

Syntax:
http://< <i>servername</i> >/cgi-bin/dido/setdo.cgi?do1=< <i>state</i> >[&do2= <state>]</state>
[&do3= <state>][&amp;do4=<state>]</state></state>

Where state is 0 or 1; "0" means inactive or normal state, while "1" means active or triggered state.

PARAMETER	VALUE	DESCRIPTION
do <num></num>	0, 1	0 – Inactive, normal state
		1 – Active, triggered state

**Example:** Drive the digital output 1 to triggered state and redirect to an empty page.

http://myserver/cgi-bin/dido/setdo.cgi?do1=1

# 8.2 Query Status of the Digital Input(capability.ndi > 0)

Note: This request requires Viewer privileges

Method: GET/POST

Syntax:

http://<servername>/cgi-bin/dido/getdi.cgi?[di0][&di1][&di2][&di3]

If no parameter is specified, all of the digital input statuses will be returned.

Return:

HTTP/1.0 200 OK\r\n Content-Type: text/plain\r\n Content-Length: <*length*>\r\n \r\n [di0=<state>]\r\n [di1=<state>]\r\n [di2=<state>]\r\n [di3=<state>]\r\n

where <*state*> can be 0 or 1.

**Example:** Query the status of digital input 1.

Request: http://myserver/cgi-bin/dido/getdi.cgi?di1 Response: HTTP/1.0 200 OK\r\n Content-Type: text/plain\r\n Content-Length: 7\r\n \r\n di1=1\r\n

## 8.3 Query Status of the Digital Output (capability.ndo > 0)

Note: This request requires Viewer privileges

Method: GET/POST

Syntax:

http://<servername>/cgi-bin/dido/getdo.cgi?[do0][&do1][&do2][&do3]

If no parameter is specified, all the digital output statuses will be returned.

Return:
HTTP/1.0 200 OK\r\n
Content-Type: text/plain\r\n
Content-Length: < <i>length</i> >\r\n
\r\n
[do0= <state>]\r\n</state>
[do1= <state>]\r\n</state>
[do2= <state>]\r\n</state>
[do3= <state>]\r\n</state>

where <*state*> can be 0 or 1.

**Example:** Query the status of digital output 1.

Request: http://myserver/cgi-bin/dido/getdo.cgi?do1 Response:

HTTP/1.0 200 OK\r\n Content-Type: text/plain\r\n Content-Length: 7\r\n

## 8.4 Capture Single Snapshot

Note: This request requires Normal User privileges.

Method: GET/POST

Syntax:

```
http://<servername>/cgi-bin/viewer/video.jpg?[channel=<value>][&resolution=<value>]
[&quality=<value>][&streamid=<value>]
```

If the user requests a size larger than all stream settings on the server, this request will fail.

PARAMETER	VALUE	DEFA	DESCRIPTION
		ULT	
channel	0~(n-1)	0	The channel number of the video source.
resolution	IP8165:	0	The resolution of the image.
	(160~640, 120~360)		
	IP8155:		
	(160~1280, 120~1024)		
quality	1~5	3	The quality of the image.
streamid	0~(m-1)	2	The stream number.

The server will return the most up-to-date snapshot of the selected channel and stream in JPEG format. The size and quality of the image will be set according to the video settings on the server.

Return:

HTTP/1.0 200 OK\r\n Content-Type: image/jpeg\r\n [Content-Length: <image size>\r\n]

<br/>

## 8.5 Account Management

Note: This request requires Administrator privileges. Method: POST

Syntax:

http://<servername>/cgi-bin/admin/editaccount.cgi?

method=<value>&username=<name>[&userpass=<value>][&privilege=<value>]

[&privilege=<value>][&return=<return page>]

PARAMETER	VALUE	DESCRIPTION
method	add	Add an account to the server. When using this method, the "username"
		field is necessary. It will use the default value of other fields if not
		specified.
	delete	Remove an account from the server. When using this method, the
		"username" field is necessary, and others are ignored.
	edit	Modify the account password and privilege. When using this method,
		the"username" field is necessary, and other fields are optional. If not
		specified, it will keep the original settings.
username	<name></name>	The name of the user to add, delete, or edit.
userpass	<value></value>	The password of the new user to add or that of the old user to modify.
		The default value is an empty string.
privilege	<value></value>	The privilege of the user to add or to modify.
	viewer	Viewer privilege.
	operator	Operator privilege.
	admin	Administrator privilege.
return	<return page=""></return>	Redirect to the page <return page=""> after the parameter is assigned.</return>
		The <return page=""> should be the relative path according to the root of</return>
		camera. If you omit this parameter, it will redirect to an empty page.
		* If the <return page=""> is invalid path, it will ignore this parameter.</return>

## 8.6 System Logs

**Note:** This request require Administrator privileges. **Method:** GET/POST

Syntax:

http://<servername>/cgi-bin/admin/syslog.cgi

Server will return the most up-to-date system log.

Return: HTTP/1.0 200 OK\r\n Content-Type: text/plain\r\n Content-Length: <syslog length>\r\n \r\n <system log information>\r\n

### 8.7 Upgrade Firmware

**Note:** This request requires Administrator privileges. Method: POST

Syntax:

http://<servername>/cgi-bin/admin/upgrade.cgi

Post data:

fimage=<file name>[&return=<return page>]\r\n \r\n <multipart encoded form data>

Server will accept the file named <file name> to upgrade the firmware and return with <return page> if indicated.

## 8.8 ePTZ Camera Control (capability.eptz > 0 and

## capability\_fisheye = 0)

**Note:** This request requires camctrl privileges. **Method:** GET/POST

Syntax:

http://< <i>servername</i> >/cgi-bin/camctrl/eCamCtrl.cgi?channel= <value>&amp;stream=<value></value></value>
[&move= <value>] – Move home, up, down, left, right</value>
[&auto= <value>] – Auto pan, patrol</value>
[&zoom= <value>] -Zoom in, out</value>
[&zooming= <value>&amp;zs=<value>] -Zoom without stopping, used for joystick</value></value>
[&x= <value>&amp;y=<value>&amp;w=<value>&amp;h=<value>&amp;resolution=<value>] - Zoom in, out on a specific area</value></value></value></value></value>
[&vx= <value>&amp;vy=<value>&amp;vs=<value>] - Shift without stopping, used for joystick</value></value></value>
[&x= <value>&amp;y=<value>&amp;videosize=<value>&amp;resolution=<value>&amp;stretch=<value>] -Click on image</value></value></value></value></value>
(Move the center of image to the coordination (x,y) based on resolution or videosize.)
[ [&speedpan= <value>][&amp;speedtilt=<value>][&amp;speedzoom=<value>][&amp;speedapp=<value>] ] - Set speeds</value></value></value></value>
[&return= <return page="">]</return>

#### Example:

http://myserver/cgi-bin/camctrl/eCamCtrl.cgi?channel=0&stream=0&move=right
http://myserver/cgi-bin/camctrl/eCamCtrl.cgi?channel=0&stream=1&vx=2&vy=2&vz=2
http://myserver/cgi-bin/camctrl/eCamCtrl.cgi?channel=0&stream=1&x=100&y=100&
videosize=640x480&resolution=640x480&stretch=0

In zoom operation, there are two ways to control it, scale zoom and area zoom.

1. [Scale zoom]: contains two control method, relative movement and continuous movement

a. relative movement -

If you trigger a relative movement, it will only zoom certain ratio and stop by itself.

http://IPAddr/cgi-bin/camctrl/eCamCtrl.cgi?stream=0&zoom=tele

http://IPAddr/cgi-bin/camctrl/eCamCtrl.cgi?stream=0&zoom=wide

The zoom ratio to move by relative movement is according to the setting of speedzoom [-5~5].

http://IPAddr/cgi-bin/camctrl/eCamCtrl.cgi?stream=0&speedzoom=5

b. continuous movement -

If you trigger a continuous movement, you have to handle the stop time by yourself.

A continuous movement is convenient to integrate a joystick control.

http://IPAddr/cgi-bin/camctrl/eCamCtrl.cgi?stream=0&zooming=tele&zs=1

<u>http://IPAddr/cgi-bin/camctrl/eCamCtrl.cgi?stream=0&zooming=wide&zs=5</u> zooming is used to indicate the moving direction, and zs is used to indicate the speed. To stop a continuous movement, you have to use the command as below: <u>http://IPAddr/cgi-bin/camctrl/eCamCtrl.cgi?stream=0&zoom=stop&zs=0</u>

2. [Area zoom]: it means to zoom in on a specific area, here is an example for a directly moving

[x, y] is the desired coordinate, and it will be the center after movement

[w, h] is the scaled area size

[resolution] is the base range of this coordinate system

The example shows [w, h] = [864, 488], which means to zoom in to ratio x2.2 based on [1920x1080].

Pay attention to that [x, y, w, h] are essential parameters in an area zoom case, and the stream index is counted from 0 as the first stream.

http://IPAddr/cgi-bin/camctrl/eCamCtrl.cgi?channel=0&stream=0&x=912&y=297&w=864&h=488&resolution=1920x1080

PARAMETER	VALUE	DESCRIPTION
channel	<0~(n-1)>	Channel of video source.
stream	<0~(m-1)>	Stream.
move	home	Move to home ROI.
	up	Move up.
	down	Move down.
	left	Move left.
	right	Move right.
auto	pan	Auto pan.
	patrol	Auto patrol.
	stop	Stop auto pan/patrol.
zoom	wide	Zoom larger view with current speed.
	tele	Zoom further with current speed.
zooming	wide or tele	Zoom without stopping for larger view or further view with zs speed,
		used for joystick control.
zs	0 ~ 6	Set the speed of zooming, "0" means stop.
х	<integer></integer>	The desired coordinate, and it will be the center after movement
у	<integer></integer>	
w	<integer></integer>	The scaled area size
h	<integer></integer>	
resolution	<window size=""></window>	The resolution of streaming.

vx	<integer></integer>	The direction of movement, used for joystick control.
vy	<integer></integer>	
vs	0 ~ 7	Set the speed of movement, "0" means stop.
х	<integer></integer>	x-coordinate clicked by user.
		It will be the x-coordinate of center after movement.
У	<integer></integer>	y-coordinate clicked by user.
		It will be the y-coordinate of center after movement.
videosize	<window size=""></window>	The size of plug-in (ActiveX)window in web page
resolution	<window size=""></window>	The resolution of streaming.
stretch	<boolean></boolean>	0 indicates that it uses <b>resolution</b> (streaming size) as the range of the
		coordinate system.
		1 indicates that it uses <b>videosize</b> (plug-in size) as the range of the
		coordinate system.
speedpan	-5 ~ 5	Set the pan speed.
speedtilt	-5 ~ 5	Set the tilt speed.
speedzoom	-5 ~ 5	Set the zoom speed.
speedapp	1 ~ 5	Set the auto pan/patrol speed.
return	<return page=""></return>	Redirect to the page <return page=""> after the parameter is assigned.</return>
		The <return page=""> should be the relative path according to the root of</return>
		camera. If you omit this parameter, it will redirect to an empty page.
		* If the <return page=""> is invalid path, it will ignore this parameter.</return>

# 8.9 ePTZ Recall (capability.eptz > 0 and capability\_fisheye = 0)

**Note:** This request requires camctrl privileges.

Method: GET/POST

Syntax:

http://<*servername*>/cgi-bin/camctrl/eRecall.cgi?channel=<value>&stream=<value>& recall=<value>[&return=<*return page*>]

PARAMETER	VALUE	DESCRIPTION
channel	<0~(n-1)>	Channel of the video source.
stream	<0~(m-1)>	Stream.
recall	Text string less than 40	One of the present positions to recall.
	characters	
return	<return page=""></return>	Redirect to the page <return page=""> after the parameter is assigned.</return>
		The <return page=""> should be the relative path according to the root of</return>
		camera. If you omit this parameter, it will redirect to an empty page.
		* If the <return page=""> is invalid path, it will ignore this parameter.</return>

# 8.10 ePTZ Preset Locations(capability.eptz > 0 and

## capability\_fisheye = 0)

Note: This request requires Operator privileges.

Method: GET/POST

Syntax:

http://<*servername*>/cgi-bin/operator/ePreset.cgi?channel=<value>&stream=<value>

[&addpos=<value>][&delpos=<value>][&return=<return page>]

PARAMETER	VALUE	DESCRIPTION
channel	<0~(n-1)>	Channel of the video source.
stream	<0~(m-1)>	Stream.
addpos	<text less="" string="" td="" than<=""><td>Add one preset location to the preset list.</td></text>	Add one preset location to the preset list.
	40 characters>	
delpos	<text less="" string="" td="" than<=""><td>Delete preset location from the preset list.</td></text>	Delete preset location from the preset list.
	40 characters>	
return	<return page=""></return>	Redirect to the page <return page=""> after the parameter is assigned.</return>
		The <return page=""> should be the relative path according to the root of</return>
		camera. If you omit this parameter, it will redirect to an empty page.
		* If the <return page=""> is invalid path, it will ignore this parameter.</return>

### 8.11 IP Filtering for ONVIF

Syntax: < product dependent>

http://<servername>/cgi-bin/admin/ipfilter.cgi?type[=<value>]
http://<servername>/cgi-bin/admin/ipfilter.cgi?method=add<v4/v6>&ip=<ipaddress>[&index=<value>][&ret
urn=<return page>]

http://<*servername*>/cgi-bin/admin/ipfilter.cgi?method=del<v4/v6>&index=<value>[&return=<*return page*>]

VALUE	DESCRIPTION
NULL	Get IP filter type
allow, deny	Set IP filter type
addv4	Add IPv4 address into access list.
addv6	Add IPv6 address into access list.
delv4	Delete IPv4 address from access list.
	NULL allow, deny addv4 addv6

	delv6	Delete IPv6 address from access list.
ip	<ip address=""></ip>	Single address: <ip address=""></ip>
		Network address: <ip address="" mask="" network=""></ip>
		Range address: <start -="" address="" end="" ip=""></start>
index	<value></value>	The start position to add or to delete.
return	<return page=""></return>	Redirect to the page <return page=""> after the parameter is assigned.</return>
		The <return page=""> should be the relative path according to the root</return>
		of camera. If you omit this parameter, it will redirect to an empty
		page.
		* If the <return page=""> is invalid path, it will ignore this parameter.</return>

## 8.12 UART HTTP Tunnel Channel (capability.nuart > 0)

Note: This request requires Operator privileges.

Method: GET and POST

Syntax:

http://< <i>servername</i> >/cgi-bin/operator/uartchannel.cgi?[channel= <value>]</value>
GET /cgi-bin/operator/uartchannel.cgi?[channel= <value>]</value>
x-sessioncookie: string[22]
accept: application/x-vvtk-tunnelled
pragma: no-cache
cache-control: no-cache
POST /cgi-bin/operator/uartchannel.cgi
x-sessioncookie: string[22]
content-type: application/x-vvtk-tunnelled
pragma : no-cache
cache-control : no-cache
content-length: 32767
expires: Sun, 9 Jam 1972 00:00:00 GMT

User must use GET and POST to establish two channels for downstream and upstream. The x-sessioncookie in GET and POST should be the same to be recognized as a pair for one session. The contents of upstream should be base64 encoded to be able to pass through a proxy server.

This channel will help to transfer the raw data of UART over the network. Please see UART tunnel spec for detail information

PARAMETER	VALUE	DESCRIPTION
channel	0 ~ (n-1)	The channel number of UART.

## 8.13 Event/Control HTTP Tunnel Channel (capability.

### evctrlchannel > 0)

**Note:** This request requires Administrator privileges. **Method:** GET and POST

Syntax:

http://< <i>servername</i> >/cgi-bin/admin/ctrlevent.cgi
GET /cgi-bin/admin/ctrlevent.cgi
x-sessioncookie: string[22]
accept: application/x-vvtk-tunnelled
pragma: no-cache
cache-control: no-cache
POST /cgi-bin/admin/ ctrlevent.cgi
x-sessioncookie: string[22]
content-type: application/x-vvtk-tunnelled
pragma : no-cache
cache-control : no-cache
content-length: 32767
expires: Sun, 9 Jam 1972 00:00:00 GMT

User must use GET and POST to establish two channels for downstream and upstream. The x-sessioncookie in GET and POST should be the same to be recognized as a pair for one session. The contents of upstream should be base64 encoded to be able to pass through the proxy server.

This channel will help perform real-time event subscription and notification as well as camera control more efficiently. The event and control formats are described in another document.

See Event/control tunnel spec for detail information

### 8.14 Get SDP of Streams

**Note:** This request requires Viewer access privileges. **Method:** GET/POST

Syntax:

http://<servername>/<network\_rtsp\_s<0~m-1>\_accessname>

"m" is the stream number.

"network\_accessname\_<0~(m-1)>" is the accessname for stream "1" to stream "m". Please refer to the

"subgroup of network: rtsp" for setting the accessname of SDP.

You can get the SDP by HTTP GET.

When using scalable multicast, Get SDP file which contains the multicast information via HTTP.

### 8.15 Open the Network Stream

Note: This request requires Viewer access privileges.

Syntax:

For HTTP push server (MJPEG):

http://<*servername*>/<network\_http\_s<0~m-1>\_accessname>

For RTSP (MP4), the user needs to input theURL below into an RTSP compatible player.

rtsp://<servername>/<network\_rtsp\_s<0~m-1>\_accessname>

"m" is the stream number.

For details on streaming protocol, please refer to the "control signaling" and "data format" documents.

# 8.16 Senddata (capability.nuart > 0)

Note: This request requires Viewer privileges.

Method: GET/POST

Syntax:

http://<*servername*>/cgi-bin/viewer/senddata.cgi? [com=<value>][&data=<value>][&flush=<value>] [&wait=<value>] [&read=<value>]

PARAMETER	VALUE	DESCRIPTION
com	1 ~ <max. com="" port<="" td=""><td>The target COM/RS485 port number.</td></max.>	The target COM/RS485 port number.
	number>	
data	<hex decimal<="" td=""><td>The <hex data="" decimal=""> is a series of digits from 0 <math>\sim</math> 9, A <math>\sim</math> F. Each</hex></td></hex>	The <hex data="" decimal=""> is a series of digits from 0 <math>\sim</math> 9, A <math>\sim</math> F. Each</hex>
	data>[, <hex decimal<="" td=""><td>comma separates the commands by 200 milliseconds.</td></hex>	comma separates the commands by 200 milliseconds.
	data>]	
flush	yes,no	yes: Receive data buffer of the COM port will be cleared before read.
		no: Do not clear the receive data buffer.
wait	1 ~ 65535	Wait time in milliseconds before read data.
read	1 ~ 128	The data length in bytes to read. The read data will be in the return
		page.

Return:

HTTP/1.0 200 OK\r\n

Content-Type: text/plain\r\n

Content-Length: <system information length>\r\n

\r\n

<hex decimal data>\r\n

Where hexadecimal data is digits from 0  $\sim$  9, A  $\sim$  F.

# 8.17 Storage managements (capability.storage.dbenabled > 0)

Note: This request requires administrator privileges.

Method: GET and POST

Syntax:

http://<*servername*>/cgi-bin/admin/lsctrl.cgi?cmd=<cmd\_type>[&<parameter>=<value>...]

The commands usage and their input arguments are as follows.

PARAMETER	VALUE	DESCRIPTION
cmd_type	<string></string>	Required.
		Command to be executed, including <i>search</i> , <i>insert</i> , <i>delete</i> , <i>update</i> ,
		and <i>queryStatus</i> .

#### Command: search

PARAMETER	VALUE	DESCRIPTION
label	<integer key="" primary=""></integer>	Optional.
		The integer primary key column will automatically be assigned a
		unique integer.
triggerType	<text></text>	Optional.
		Indicate the event trigger type.
		Please embrace your input value with single quotes.
		Ex. mediaType='motion'
		Support trigger types are product dependent.
mediaType	<text></text>	Optional.
		Indicate the file media type.
		Please embrace your input value with single quotes.
		Ex. mediaType='videoclip'
		Support trigger types are product dependent.
destPath	<text></text>	Optional.
		Indicate the file location in camera.
		Please embrace your input value with single quotes.
		Ex. destPath ='/mnt/auto/CF/NCMF/abc.mp4'
resolution	<text></text>	Optional.
		Indicate the media file resolution.
		Please embrace your input value with single quotes.
		Ex. resolution='800x600'
isLocked	<boolean></boolean>	Optional.

		Indicate if the file is locked or not.
		0: file is not locked.
		1: file is locked.
		A locked file would not be removed from UI or cyclic storage.
triggerTime	<text></text>	Optional.
		Indicate the event trigger time. (not the file created time)
		Format is "YYYY-MM-DD HH:MM:SS"
		Please embrace your input value with single quotes.
		Ex. triggerTime='2008-01-01 00:00:00'
		If you want to search for a time period, please apply "TO"
		operation.
		Ex. triggerTime='2008-01-01 00:00:00'+TO+'2008-01-01
		23:59:59' is to search for records from the start of Jan $1^{st}$ 2008to
		the end of Jan 1 <sup>st</sup> 2008.
limit	<positive integer=""></positive>	Optional.
		Limit the maximum number of returned search records.
offset	<positive integer=""></positive>	Optional.
		Specifies how many rows to skip at the beginning of the matched
		records.
		Note that the offset keyword is used after limit keyword.

To increase the flexibility of search command, you may use "OR" connectors for logical "OR" search operations. Moreover, to search for a specific time period, you can use "TO" connector.

Ex. To search records triggered by motion or di or sequential and also triggered between 2008-01-01 00:00:00 and 2008-01-01 23:59:59.

http://<*servername*>/cgi-bin/admin/lsctrl.cgi?cmd=search&triggerType='motion'+OR+'di'+OR+'seq'&triggerTi me='2008-01-01 00:00:00'+TO+'2008-01-01 23:59:59'

### Command: **delete**

PARAMETER	VALUE	DESCRIPTION
label	<integer key="" primary=""></integer>	Required.
		Identify the designated record.
		Ex. label=1

#### Ex. Delete records whose key numbers are 1, 4, and 8.

http://<servername>/cgi-bin/admin/lsctrl.cgi?cmd=delete&label=1&label=4&label=8

Command: update

PARAMETER	VALUE	DESCRIPTION

label	<integer key="" primary=""></integer>	Required.
		Identify the designated record.
		Ex. label=1
isLocked	<boolean></boolean>	Required.
		Indicate if the file is locked or not.

#### Ex. Update records whose key numbers are 1 and 5 to be locked status.

#### Ex. Update records whose key numbers are 2 and 3 to be unlocked status.

```
http://<servername>/cgi-bin/admin/lsctrl.cgi?cmd=update&isLocked=0&label=2&label=3
```

#### Command: queryStatus

PARAMETER	VALUE	DESCRIPTION
retType	xml or javascript	Optional.
		Ex. retype=javascript
		The default return message is in XML format.

#### Ex. Query local storage status and call for javascript format return message.

http://<*servername*>/cgi-bin/admin/lsctrl.cgi?cmd=queryStatus&retType=javascript

# 8.18 Virtual input (capability.nvi > 0)

**Note:** Change virtual input (manual trigger) status. Method: GET

#### Syntax:

http://<servername>/cgi-bin/admin/setvi.cgi?vi0=<value>[&vi1=<value>][&vi2=<value>] [&return=<return page>]

PARAMETER	VALUE	DESCRIPTION
vi <num></num>	state[(duration)nstate]	Ex: vi0=1
		Setting virtual input 0 to trigger state
	Where "state" is 0, 1. "0"	
	means inactive or normal	Ex: vi0=0(200)1
	state while "1" means	Setting virtual input 0 to normal state, waiting 200
	active or triggered state.	milliseconds, setting it to trigger state.
	Where "nstate" is next	Note that when the virtual input is waiting for next state, it
	state after duration.	cannot accept new requests.
return	<return page=""></return>	Redirect to the page <return page=""> after the parameter is</return>
		assigned. The <return page=""> should be the relative path</return>
		according to the root of camera. If you omit this parameter, it
		will redirect to an empty page.
		* If the <return page=""> is invalid path, it will ignore this</return>
		parameter.

Return Code	Description
200	The request is successfully executed.
400	The request cannot be assigned, ex. incorrect parameters.
	Examples:
	setvi.cgi?vi0=0(10000)1(15000)0(20000)1
	No multiple duration.
	setvi.cgi?vi3=0
	VI index is out of range.
	setvi.cgi?vi=1
	No VI index is specified.
503	The resource is unavailable, ex. Virtual input is waiting for next state.
	Examples:
	setvi.cgi? <mark>vi0</mark> =0(15000)1
	setvi.cgi?vi0=1

# 8.19 Open Timeshift Stream (capability.timeshift > 0,

# timeshift\_enable=1, timeshift\_c<n>\_s<m>\_allow=1)

Note: This request requires Viewer access privileges.

Syntax:

For HTTP push server (MJPEG):

http://<servername>/<network\_http\_s<m>\_accessname>?maxsft=<value>[&tsmode=<value>&reftime=<v alue>&forcechk&minsft=<value>]

For RTSP (MP4 and H264), the user needs to input theURL below into an RTSP compatible player.

rtsp://<servername>/<network\_rtsp\_s<m>\_accessname>?maxsft=<value>[&tsmode=<value>&reftime=<va lue>&forcechk&minsft=<value>]

"n" is the channel index.

"m" is the timeshift stream index.

For details on timeshift stream, please refer to the "TimeshiftCaching" documents.

PARAMETER	VALUE	DEFAULT	DESCRIPTION
maxsft	<positive< td=""><td>0</td><td>Request cached stream at most how many seconds ago.</td></positive<>	0	Request cached stream at most how many seconds ago.
	integer>		
tsmode	normal,	normal	Streaming mode:
	adaptive		normal => Full FPS all the time.
			adaptive => Default send only I-frame for MP4 and H.264, and
			send 1 FPS for MJPEG. If DI or motion window are triggered, the
			streaming is changed to send full FPS for 10 seconds.
			(*Note: this parameter also works on non-timeshift streams.)
reftime	mm:ss	The time	Reference time for maxsft and minsft.
		camera receives	(This provides more precise time control to eliminate the
		the request.	inaccuracy due to network latency.)
			Ex: Request the streaming from 12:20
			rtsp://10.0.0.1/live.sdp?maxsft=10&reftime=12:30
forcechk	N/A	N/A	Check if the requested stream enables timeshift, feature and
			if minsft is achievable.
			If false, return "415 Unsupported Media Type".
minsft	<positive< td=""><td>0</td><td>How many seconds of cached stream client can accept at least.</td></positive<>	0	How many seconds of cached stream client can accept at least.
	integer>		(Used by forcechk)

Return Code	Description
400 Bad Request	Request is rejected because some parameter values are illegal.
415 Unsupported Media Type	Returned, if forcechk appears, when minsft is not achievable or the timeshift
	feature of the target stream is not enabled.

## 8.20 RemoteFocus

## (capability\_image\_c<0~(n-1)>\_remotefocus=1)

Note: This request requires Administrator privileges.

Method: GET/POST

Syntax:

```
http://<servername>/cgi-bin/admin/remotefocus.cgi?function=<value>[&direction=<value>]
[&position=<value>][&steps=<value>][&iris]
```

PARAMETER	VALUE	DESCRIPTION
PARAMILILK	VALUL	DESCRIPTION

function	zoom,	Function type
	focus,	<b>zoom</b> - Move focus motor
	auto,	<b>focus</b> – Move focus motor
	scan,	<b>auto</b> – Perform auto focus
	stop,	<b>scan</b> – Perform focus scan
	positioning,	stop – Stop current operation
	getstatus	<b>positioning</b> – Position the motors
		getstatus-Information of motors, return value as below:
		remote_focus_zoom_motor_max: Maximum steps of zoom motor
		remote_focus_focus_motor_max: Maximum steps of focus motor
		remote_focus_zoom_motor_start: Start point of zoom motor
		remote_focus_zoom_motor_end: End point of zoom motor
		remote_focus_focus_motor_start: Start point of effective focal
		length
		remote_focus_focus_motor_end: End point of effective focal
		length
		remote_focus_zoom_motor: Current position of zoom motor
		remote_focus_focus_motor: Current position of focus motor
		remote_focus_zoom_enable: Current function of zoom motor
		remote_focus_focus_enable: Current function of focus motor
		<pre>remote_focus_iris_open: The current status of iris. 0: irisenable, 1:</pre>
		irisopen
		Current function of zoom/focus motor, return value as below:
		0: no service
		1: zooming
		2. focusing
		3: auto focus
		4: focus scan
		5: positioning (both zoom motor and focus motor)
		12: reset focus
direction	direct,	Motor's moving direction.
	forward,	It works only if function= zoom   focus.
	backward	
position	0~ <motor_max></motor_max>	Motor's position.
	-	It works only if function=zoom   focus and direction=direct.
		<pre></pre>
		remote_focus_zoom_motor_max which replied from
		"function=getstatus"

steps	1 ~ <motor_max></motor_max>	Motor's moving steps.
		It works only if function=zoom   focus and direction=forward
		backward.
		<motor_max> is refer to remote_focus_focus_motor_max or</motor_max>
		remote_focus_zoom_motor_max which replied from
		"function=getstatus"
		* This parameter is for additional fine-tune, the value is from 1 to 30.
iris	N/A	Open iris or not.
		It works only if function=auto   scan.

# 8.21 BackFocus (capability\_image\_c<0~(n-1)>\_remotefocus=4)

**Note:** This request requires Administrator privileges. **Method:** GET/POST

Syntax:

http://<*servername*>/cgi-bin/admin/remotefocus.cgi?function=<value>[&direction=<value>] [&position=<value>][&steps=<value>][&iris]

PARAMETER	VALUE	DESCRIPTION

function	focus,	Function type
	auto,	focus – Move focus motor
	scan,	auto – Perform auto focus
	stop,	<b>scan</b> – Perform focus scan
	positioning,	stop – Stop current operation
	irisopen,	<b>positioning</b> – Position the motors
	irisenable,	resetfocus – reset focus position to default
	resetfocus,	irisopen – Fully open iris. It will maintain this status until sending
	getstatus	irisenable cgi.
		irisenable – leave fully open iris and return back to previous status
		getstatus–Information of motors, return value as below:
		remote_focus_focus_motor_max: Maximum steps of focus motor
		remote_focus_focus_motor_start: Start point of effective focal
		length
		remote_focus_focus_motor_end: End point of effective focal
		length
		remote_focus_focus_motor: Current position of focus motor
		remote_focus_focus_enable: Current function of focus motor
		<pre>remote_focus_iris_open: The current status of iris. 0: irisenable, 1:</pre>
		irisopen
		Current function of zoom/focus motor, return value as below:
		0: no service
		1: zooming
		2. focusing
		3: auto focus
		4: focus scan
		5: positioning (both zoom motor and focus motor)
		12: reset focus
direction	direct,	Motor's moving direction.
	forward,	It works only if function= focus.
	backward	
position	0~ <motor_max></motor_max>	Motor's position.
		It works only if function=focus and direction=direct.
		<motor_max> is refer to remote_focus_focus_motor_max which</motor_max>
		replied from "function=getstatus"

steps	1 ~ <motor_max></motor_max>	Motor's moving steps.	
		It works only if function=focus and direction=forward   backward.	
		<motor_max> is refer to remote_focus_focus_motor_max which</motor_max>	
		replied from "function=getstatus"	
		* This parameter is for additional fine-tune, the value is from 1 to 30.	
iris	N/A	Open iris or not.	
		It works only if function=auto   scan.	

## 8.22 Export Files

**Note:** This request requires Administrator privileges.

Method: GET

Syntax:

For daylight saving time configuration file:

http://<*servername*>/cgi-bin/admin/exportDst.cgi

For language file:

http://<servername>/cgi-bin/admin/export\_language.cgi?currentlanguage=<value>

PARAMETER	VALUE	DESCRIPTION
currentlanguage	0~20	Available language lists.
		Please refer to:
		system_info_language_i0 ~ system_info_language_i19.

For setting backup file:

http://<*servername*>/cgi-bin/admin/export\_backup.cgi?backup

## 8.23 Upload Files

**Note:** This request requires Administrator privileges. Method: POST

Syntax:

For daylight saving time configuration file:

http://<servername>/cgi-bin/admin/upload\_dst.cgi

Post data:

filename =<file name>\r\n

\r\n

<multipart encoded form data>

For language file:

http://<*servername*>/cgi-bin/admin/upload\_lan.cgi

Post data:

filename =<file name>\r\n

\r\n

<multipart encoded form data>

For setting backup file:

http://<servername>/cgi-bin/admin/upload\_backup.cgi

Post data:

filename =<file name>\r\n \r\n <multipart encoded form data>

Server will accept the file named <file name> to upload this one to camera.

## 8.24 Update Lens Configuration

## (capability\_image\_c<0~(n-1)>\_lensconfiguration\_support > 0)

Note: This request requires Administrator privileges.

Method: GET

Syntax:

For list a name of lens currently used:

http://<*servername*>/cgi-bin/admin/update\_lens.cgi?get\_currentlens

For list all names of lens installed in camera:

http://<*servername*>/cgi-bin/admin/update\_lens.cgi?list\_lens

For choose selected lens configuration:

http://<servername>/cgi-bin/admin/update\_lens.cgi?choose\_lens=<value>

You need to reboot manually after you choose another lens configuration.

For choose selected lens configuration and reboot camera:

http://<servername>/cgi-bin/admin/update\_lens.cgi?choose\_reboot\_lens=<value>

The camera will reboot after using this cgi.

For delete selected lens configuration:

http://<servername>/cgi-bin/admin/update\_lens.cgi?delete\_lens=<value>

PARAMETER	VALUE	DESCRIPTION
value	<string></string>	Available lens name.
		Please refer to:
		lens_default_i<0~(n-1)>_name
		lens_user_i<0~(n-1)>_name
		n is a positive integer.

#### Method: POST

Syntax:

For upload user-defined lens configuration:

http://<servername>/cgi-bin/admin/update\_lens.cgi?upload\_lens

Post data:

```
upload_lens_profile_input = <file name>\r\n
\r\n
<multipart encoded form data>
```

Server will accept the file named <file name> to upload the lens profile to camera.

## 8.25 Media on demand (capability.localstorage.modnum > 0)

Media on demand allows users to select and receive/watch/listen to metadata/video/audio contents on demand.

Note: This request requires Viewer access privileges.

Syntax:

rtsp://<servername>/mod.sdp?[&stime=<value>][&etime=<value>][&length =<value>][&loctime

=<value>][&file=<value>][&tsmode=<value>]

PARAMETER	VALUE	DEFAULT	DESCRIPTION
stime	<yyyymmdd_hhmmss.mmm></yyyymmdd_hhmmss.mmm>	N/A	Start time.
etime	<yyyymmdd_hhmmss.mmm></yyyymmdd_hhmmss.mmm>	N/A	End time.
length	<positive integer=""></positive>	N/A	The length of media of interest.
			The unit is second.
loctime	<boolean></boolean>	0	Specify if start/end time is local time format.
			1 for local time, 0 for UTC+0
file	<string></string>	N/A	The media file to be played.
tsmode	<positive integer=""></positive>	N/A	Timeshift mode, the unit is second.

Ex.

stime	etime	length	file	Description
v	V	x	х	Play recordings between stime and etime
				rtsp://10.10.1.2/mod.sdp?stime=20110312_040400.000&etime=
				2011_0312_040510.000
V	X	V	x	Play recordings for length seconds which start from stime
				rtsp://10.10.1.2/mod.sdp?stime=20110312_040400.000&length
				=120
x	v	V	x	Play recordings for length seconds which ends at etime
				rtsp://10.10.1.2/mod.sdp?etime=20110312_040400.000&length
				=120
x	X	X	V	Play file file
				<pre>rtsp://10.10.1.2/mod.sdp?filename=/mnt/link0/</pre>

## 8.26 Fisheye local dewarp camera control (capability.fisheye > 0

### and capability.fisheyelocaldewarp.c0 > 0, only support in 1R

### mode)

**Note:** This request requires camctrl privileges. **Method:** GET/POST

Syntax:

http://<servername>/cgi-bin/camctrl/fdCamCtrl.cgi?channel=<value>&stream=<value>
[&move=<value>] - Move home, up, down, left, right
[&zoom=<value>] - Zoom wide, tele
[[&speedpan=<value>][&speedtilt=<value>][&speedzoom=<value>]] - Set speeds
[&zooming=<value>&zs=<value>] - Zoom without stopping, used for joystick
[&vx=<value>&vy=<value>&vs=<value>] - Shift without stopping, used for joystick
[&x=<value>&y=<value>&videosize=<value>&resolution=<value>&stretch=<value>] - Click on image (Move
the center of image to the coordination (x,y) based on resolution or videosize of 10 mode.)
[&return=<return page>]

#### Example:

http://myserver/cgi-bin/camctrl/fdCamCtrl.cgi?channel=0&stream=0&move=right http://myserver/cgi-bin/camctrl/fdCamCtrl.cgi?channel=0&stream=0&move=top&speedtilt=-1 http://myserver/cgi-bin/camctrl/fdCamCtrl.cgi?channel=0&stream=0&zooming=tele&zs=2 http://myserver/cgi-bin/camctrl/fdCamCtrl.cgi?channel=0&stream=0&vx=5&vy=3&vs=2 http://myserver/cgi-bin/camctrl/fdCamCtrl.cgi?channel=0&stream=0&x=700&y=700&videosize=1920x1920&r esolution=1920x1920&stretch=1

PARAMETER	VALUE	DESCRIPTION	
channel	<0~(n-1)>	Channel of video source.	
stream	<0~(m-1)>	Stream.	
move	home	Move to home position.	
	up	Move up.	
	down	Move down.	
	left	Move left.	
	right	Move right.	

zoom	wide	Zoom larger view with current speed.	
	tele	Zoom further with current speed.	
speedpan	-5 ~ 5	Set the pan speed of current command.	
speedtilt	-5 ~ 5	Set the tilt speed of current command.	
speedzoom	-5 ~ 5	Set the zoom speed of current command.	
zooming	wide or tele	Zoom without stopping for larger view or further view with zs speed, used for joystick control.	
zs	0 ~ 6	Set the speed of zooming, "0" means stop.	
vx	-6 ~ 6	The direction of movement, used for joystick control.	
vy	-6 ~ 6		
vs	0 ~ 7	Set the speed of movement, "0" means stop.	
х	<integer></integer>	x-coordinate clicked by user.	
		It will be the x-coordinate of center after movement.	
У	<integer></integer>	y-coordinate clicked by user.	
		It will be the y-coordinate of center after movement.	
videosize	<window size=""></window>	The size of plug-in (ActiveX) window in web page of 10 content.	
resolution	<window size=""></window>	The resolution of streaming of 10 content.	
stretch	<boolean></boolean>	0 indicates that it uses <b>resolution</b> (streaming size) as the range of	
		the coordinate system.	
		1 indicates that it uses <b>videosize</b> (plug-in size) as the range of the	
		coordinate system.	
return	<return page=""></return>	Redirect to the page <return page=""> after the parameter is assigned.</return>	
		The <return page=""> should be the relative path according to the root of</return>	
		camera. If you omit this parameter, it will redirect to an empty page.	
		* If the <return page=""> is invalid path, it will ignore this parameter.</return>	

## 8.27 3D Privacy Mask

# (capability\_image\_c<0~(n-1)>\_privacymask\_wintype =

### **3Drectangle)** n denotes the value of "capability\_nvideoin"

Note: This request requires admin user privilege Method: GET/POST

Syntax:

http://<*servername*>/cgi-bin/admin/setpm3d.cgi?method=<value>&maskname=<value>&[maskheight=<value>&maskwidth=<value>&videosize=<value>&return=<return page>]

PARAMETER	VALUE	DESCRIPTION
method	add	Add a 3D privacy mask at current location
	delete	Delete a 3D privacy mask
	edit	Edit a 3D privacy mask
maskname	string[40]	3D privacy mask name
maskheight	integer	3D privacy mask height
maskwidth	integer	3D privacy mask width
videosize	<window size=""></window>	Optimal.
		The size of plug-in (ActiveX) window in web page is the size of the
		privacy window size. This field is not necessary, it will use the default
		value if not specified. 320x180 for 16:9 resolution and 320x240 for
		4:3 resolution.
return	<return page=""></return>	Redirect to the page <return page=""> after the parameter is assigned.</return>
		The <return page=""> should be the relative path according to the root of</return>
		camera. If you omit this parameter, it will redirect to an empty page.
		* If the <return page=""> is invalid path, it will ignore this parameter.</return>

## 8.28 Camera Control

## (capability\_camctrl\_c<0~(n-1)>\_zoommodule = 1)

**Note:** This request requires Viewer privileges. **Method:** GET/POST

#### Syntax: (for control API)

http://< <i>servername</i> >/cgi-bin/camctrl/camctrl.cgi?[channel= <value>][&amp;camid=<value>]</value></value>
[&move= <value>] – Move home, up, down, left, right</value>
[&focus= <value>] – Focus operation</value>
[&zoom= <value>] - Zoom in, out</value>
[&zooming= <value>&amp;zs=<value>] - Zoom without stopping, used for joystick</value></value>
[&vx= <value>&amp;vy=<value>&amp;vs=<value>] - Shift without stopping, used for joystick</value></value></value>
[&x= <value>&amp;y=<value>&amp;videosize=<value>&amp;resolution=<value>&amp;stretch=<value>] - Click on image</value></value></value></value></value>
(Move the center of image to the coordination $(x,y)$ based on resolution or videosize.)
[ [&speedpan= <value>][&amp;speedtilt=<value>][&amp;speedzoom=<value>][&amp;speedapp=<value>][&amp;speedlink=<value>][</value></value></value></value></value>
ue>] ] – Set speeds
[&return= <return page="">]</return>

#### Example:

http://myserver/cgi-bin/camctrl/camctrl.cgi?channel=0&camid=1&move=right http://myserver/cgi-bin/camctrl/camctrl.cgi?channel=0&camid=1&zoom=tele http://myserver/cgi-bin/camctrl/camctrl.cgi?channel=0&camid=1&x=300&y=200&resolution=704x480&videosi ze=704x480&strech=1

Example: (set the ptz preset with focus mode)

\* We support this function when the version number of the PTZ control module is equal or greater than 5.0.0.20. http://myserver/cgi-bin/camctrl/camctrl.cgi?name=xxx&focussetting=sync&cam=getsetpreset

PARAMETER	VALUE	DESCRIPTION
channel	<0~(n-1)>	Channel of video source.
camid	0, <positive integer=""></positive>	Camera ID.
move	home	Move to camera to home position.
	ир	Move camera up.
	down	Move camera down.
	left	Move camera left.
	right	Move camera right.

Image: system of the system	speedpan	-5 ~ 5	Set the pan speed.
speedfocus         -5 ~ 5         Set the focus speed.           speedapp         -5 ~ 5         Set the auto pan/patrol speed.           auto         pan         Auto pan.           patrol         Auto patrol.           stop         Stop camera.           zoom         wide         Zoom larger view with current speed.           tele         Zoom further with current speed.           stop         Stop zoom.           zooming         wide or tele         Zoom without stopping for larger view or further view with zs sp used for joystick control.           zs         0 ~ 8 <sd8362>         Set the speed of zooming, "0" means stop.           vx         <integer ,="" 0="" excluding="">         The slope of movement = vy/vx, used for joystick control.           vs         0 ~ 127         Set the speed of movement, "0" means stop.           vx         <integer>         x-coordinate clicked by user.           x         <integer>         y-coordinate clicked by user.           x         <integer>         The size of plug-in (ActiveX) window in web page           resolution         <window size="">         The resolution of streaming.           stretch         <boolean>         0 indicates that it uses <b>resolution</b> (streaming size) as the range of coordinate system.           far         Focus on further</boolean></window></integer></integer></integer></integer></sd8362>	speedtilt	-5 ~ 5	Set the tilt speed.
speedapp         -5 ~ 5         Set the auto pan/patrol speed.           auto         pan         Auto pan.           patrol         Auto patrol.           stop         Stop camera.           zoom         wide         Zoom further with current speed.           tele         Zoom further with current speed.           stop         Stop zoom.           zooming         wide or tele         Zoom without stopping for larger view or further view with zs sp used for joystick control.           zs         0 ~ 8 <sd8362>         Set the speed of zooming, "0" means stop.           vx         <integer ,="" 0="" excluding="">         The slope of movement = vy/vx, used for joystick control.           vy         <integer>         x-coordinate clicked by user.         It will be the x-coordinate of center after movement.           vy         <integer>         y-coordinate clicked by user.         It will be the y-coordinate of center after movement.           videosize         <window size="">         The size of plug-in (ActiveX) window in web page           resolution         <window size="">         The resolution of streaming.           stretch         <bolean>         0 indicates that it uses <b>resolution</b> (streaming size) as the range of coordinate system.           focus         auto         Auto focus.           far         Focus</bolean></window></window></integer></integer></integer></sd8362>	speedzoom	-5 ~ 5	Set the zoom speed.
AutopanAuto par.autoparolAuto patrol.stopStop camera.zoomwideZoom larger view with current speed.teleZoom further with current speed.stopStop zoom.zoomingwide or teleZoom without stopping for larger view or further view with zs sp used for joystick control.zs $0 \sim 8 < SD8362>$ Set the speed of zooming, "0" means stop.vx <integer ,="" 0="" excluding=""> vyThe slope of movement = vy/vx, used for joystick control.vs<math>0 \sim 127</math>Set the speed of movement, "0" means stop.vs<math>0 \sim 127</math>Set the speed of movement, "0" means stop.x<integer>x-coordinate clicked by user. It will be the x-coordinate of center after movement.y<integer>y-coordinate clicked by user. It will be the y-coordinate of center after movement.videosize<window size="">The resolution of streaming.stretch<boolean>0 indicates that it uses resolution (streaming size) as the range of coordinate system. 1 indicates system.focusautoAuto focus. far nearfocussetingsyncApplies the selected focus mode in camctrl_c&lt;0~(n-1)&gt;_focusm</br></br></boolean></window></integer></integer></integer>	speedfocus	-5 ~ 5	Set the focus speed.
patrolAuto patrol.stopStop camera.zoomwideZoom larger view with current speed.teleZoom further with current speed.stopStop zoom.zoomingwide or teleZoom without stopping for larger view or further view with zs sp used for joystick control.zs $0 \sim 8 < SD8362>$ Set the speed of zooming, "0" means stop.vx <integer ,="" 0="" excluding=""> (vinteger &gt;)The slope of movement = vy/vx, used for joystick control.vs<math>0 \sim 127</math>Set the speed of movement, "0" means stop.vs<math>0 \sim 127</math>Set the speed of movement, "0" means stop.x<integer>'coordinate clicked by user. It will be the x-coordinate of center after movement.y<integer>'coordinate clicked by user. It will be the y-coordinate of center after movement.videosize<window size="">The resolution of streaming.stretch<boolean>0 indicates that it uses resolution (streaming size) as the range of coordinate system. 1 indicates system.focusautoAuto focus. FarfocussetingsyncApplies the selected focus mode in camctrl_c&lt;0~(n-1)&gt;_focusm</boolean></window></integer></integer></integer>	speedapp	-5 ~ 5	Set the auto pan/patrol speed.
Stop camera.zoomwideZoom larger view with current speed.teleZoom further with current speed.stopStop zoom.zoomingwide or teleZoom without stopping for larger view or further view with zs sp used for joystick control.zs $0 \sim 8 < SD8362>$ Set the speed of zooming, "0" means stop.vx <integer ,="" 0="" excluding=""> (integer&gt;The slope of movement = vy/vx, used for joystick control.vs<math>0 \sim 127</math>Set the speed of movement, "0" means stop.x<integer>vs<math>0 \sim 127</math>Set the speed of movement, "0" means stop.x<integer>videosize<integer>y-coordinate clicked by user. It will be the x-coordinate of center after movement.y<integer>y-coordinate clicked by user. It will be the y-coordinate of center after movement.videosize<window size="">The size of plug-in (ActiveX) window in web pageresolution<window size="">The resolution of streaming.stretch<math>\begin{cases} boolean&gt;</math>0 indicates that it uses <b>resolution</b> (streaming size) as the range of coordinate system. 1 indicates that it uses <b>videosize</b> (plug-in size) as the range of coordinate system.focusautoAuto focus. FarfarFocus on further distance. Focus on closer distance.focussetingsyncApplies the selected focus mode in camctrl_c&lt;0~(n-1)&gt;_focusm</window></window></integer></integer></integer></integer></integer>	auto	pan	Auto pan.
vide         Zoom larger view with current speed.           tele         Zoom further with current speed.           stop         Stop zoom.           zooming         wide or tele         Zoom without stopping for larger view or further view with zs sp used for joystick control.           zs         0 ~ 8 <sd8362>         Set the speed of zooming, "0" means stop.           vx         <integer ,="" 0="" excluding=""> integer&gt;         The slope of movement = vy/vx, used for joystick control.           vy         <integer>         ×-coordinate clicked by user. It will be the x-coordinate of center after movement.           y         <integer>         y-coordinate clicked by user. It will be the y-coordinate of center after movement.           videosize         <window size="">         The size of plug-in (ActiveX) window in web page           resolution         <window size="">         The resolution of streaming.           stretch         <boolean>         0 indicates that it uses <b>resolution</b> (streaming size) as the range of coordinate system.           focus         auto         Auto focus. far         Focus on further distance. focus on closer distance.           focusseting         Sync         Applies the selected focus mode in camctrl_c&lt;0~(n-1)&gt;_focus</boolean></window></window></integer></integer></integer></sd8362>		patrol	Auto patrol.
tele         Zoom further with current speed.           stop         Stop zoom.           zooming         wide or tele         Zoom without stopping for larger view or further view with zs spused for joystick control.           zs         0 ~ 8 <sd8362>         Set the speed of zooming, "0" means stop.           vx         <integer ,="" 0="" excluding="">         The slope of movement = vy/vx, used for joystick control.           vy         <integer>         *-coordinate clicked by user.           x         <integer>         x-coordinate clicked by user.           x         <integer>         y-coordinate clicked by user.           y         <integer>         y-coordinate clicked by user.           it will be the y-coordinate of center after movement.           y         <integer>         y-coordinate of center after movement.           videosize         <window size="">         The size of plug-in (ActiveX) window in web page           resolution         <window size="">         The resolution of streaming.           stretch         <boolean>         0 indicates that it uses <b>resolution</b> (streaming size) as the range of coordinate system.           focus         auto         Auto focus.           far         Focus on further distance.           near         Focus on closer distance.           focus on closer distance.</boolean></window></window></integer></integer></integer></integer></integer></integer></sd8362>		stop	Stop camera.
stop         Stop zoom.           zooming         wide or tele         Zoom without stopping for larger view or further view with zs spused for joystick control.           zs         0 ~ 8 <sd8362>         Set the speed of zooming, "0" means stop.           vx         <integer ,="" 0="" excluding="">         The slope of movement = vy/vx, used for joystick control.           vy         <integer>          The slope of movement, "0" means stop.           vs         0 ~ 127         Set the speed of movement, "0" means stop.           x         <integer>         x-coordinate clicked by user. It will be the x-coordinate of center after movement.           y         <integer>         y-coordinate clicked by user. It will be the y-coordinate of center after movement.           videosize         <window size="">         The size of plug-in (ActiveX) window in web page           resolution         <window size="">         The resolution of streaming.           stretch         <boolean>         0 indicates that it uses <b>resolution</b> (streaming size) as the range of coordinate system. 1 indicates that it uses <b>videosize</b> (plug-in size) as the range of coordinate system.           focus         auto         Auto focus. far           far         Focus on further distance. near         Focus on closer distance.           focusseting         sync         Applies the selected focus mode in camctrl_c&lt;0~(n-1)&gt;_focusm  <td>zoom</td><td>wide</td><td>Zoom larger view with current speed.</td></boolean></window></window></integer></integer></integer></integer></sd8362>	zoom	wide	Zoom larger view with current speed.
zooming       wide or tele       Zoom without stopping for larger view or further view with zs spused for joystick control.         zs       0 ~ 8 <sd8362>       Set the speed of zooming, "0" means stop.         vx       <integer ,="" 0="" excluding="">       The slope of movement = vy/vx, used for joystick control.         vy       <integer>       0 ~ 127       Set the speed of movement, "0" means stop.         x       <integer>       x-coordinate clicked by user.         x       <integer>       y-coordinate clicked by user.         y       <integer>       y-coordinate clicked by user.         y       <integer>       y-coordinate of center after movement.         y       <integer>       twill be the x-coordinate of center after movement.         y       <integer>       The size of plug-in (ActiveX) window in web page         resolution       <window size="">       The resolution of streaming.         stretch       <boolean>       0 indicates that it uses <b>resolution</b> (streaming size) as the range of coordinate system.         focus       auto       Auto focus.         far       Focus on further distance.         near       Focus on closer distance.         focusseting       sync       Applies the selected focus mode in camctrl_c&lt;0~(n-1)&gt;_focusm</boolean></window></integer></integer></integer></integer></integer></integer></integer></integer></sd8362>		tele	Zoom further with current speed.
zs       0 ~ 8 <sd8362>       Set the speed of zooming, "0" means stop.         vx       <integer ,="" 0="" excluding="">       The slope of movement = vy/vx, used for joystick control.         vy       <integer>       The slope of movement, "0" means stop.         vs       0 ~ 127       Set the speed of novement, "0" means stop.         x       <integer>       x-coordinate clicked by user.         x       <integer>       y-coordinate clicked by user.         x timeger&gt;       y-coordinate clicked by user.         x window size&gt;       The size of plug-in (ActiveX) window in web page         resolution       <window size="">       The resolution of streaming.         stretch       <boolean>       0 indicates that it uses resolution (streaming size) as the range of coordinate system.         focus       auto       Auto focus.         far       Focus on further distance.         near       Focus on closer distance.         focusseting       sync       Applies the selected focus mode in camctrl_c&lt;0~(n-1)&gt;_focusm</boolean></window></integer></integer></integer></integer></sd8362>		stop	Stop zoom.
zs $0 \sim 8 < \text{SD8362>}$ Set the speed of zooming, "0" means stop.vx <integer ,="" 0="" excluding=""> (integer&gt;The slope of movement = vy/vx, used for joystick control.vy<integer>Set the speed of movement, "0" means stop.vs<math>0 \sim 127</math>Set the speed of movement, "0" means stop.x<integer>x-coordinate clicked by user. It will be the x-coordinate of center after movement.y<integer>y-coordinate clicked by user. It will be the y-coordinate of center after movement.videosize<window size="">The size of plug-in (ActiveX) window in web pageresolution<window size="">The resolution of streaming.stretch<boolean>0 indicates that it uses <b>resolution</b> (streaming size) as the range of coordinate system. 1 indicates that it uses <b>videosize</b> (plug-in size) as the range of coordinate system.focusautoAuto focus. far nearfocussetingsyncApplies the selected focus mode in camctrl_c&lt;0~(n-1)&gt;_focusm</boolean></window></window></integer></integer></integer></integer>	zooming	wide or tele	Zoom without stopping for larger view or further view with zs speed,
vx <integer, 0="" excluding="">       The slope of movement = vy/vx, used for joystick control.         vy       <integer>          vs       0 ~ 127       Set the speed of movement, "0" means stop.         x       <integer>       x-coordinate clicked by user. It will be the x-coordinate of center after movement.         y       <integer>       y-coordinate clicked by user. It will be the y-coordinate of center after movement.         videosize       <window size="">       The size of plug-in (ActiveX) window in web page         resolution       <window size="">       The resolution of streaming.         stretch       <boolean>       0 indicates that it uses <b>resolution</b> (streaming size) as the range of coordinate system. 1 indicates that it uses <b>videosize</b> (plug-in size) as the range of coordinate system.         focus       auto       Auto focus.         far       Focus on further distance. near       Focus on closer distance.         focusseting       sync       Applies the selected focus mode in camctrl_c&lt;0~(n-1)&gt;_focusm</boolean></window></window></integer></integer></integer></integer,>			used for joystick control.
vy <integer>         vs       0 ~ 127       Set the speed of movement, "0" means stop.         x       <integer>       x-coordinate clicked by user. It will be the x-coordinate of center after movement.         y       <integer>       y-coordinate clicked by user. It will be the y-coordinate of center after movement.         y       <integer>       y-coordinate clicked by user. It will be the y-coordinate of center after movement.         videosize       <window size="">       The size of plug-in (ActiveX) window in web page         resolution       <window size="">       The resolution of streaming.         stretch       <boolean>       0 indicates that it uses <b>resolution</b> (streaming size) as the range of coordinate system. 1 indicates that it uses <b>videosize</b> (plug-in size) as the range of coordinate system.         focus       auto       Auto focus.         far       Focus on further distance. near       Focus on closer distance.         focusseting       sync       Applies the selected focus mode in camctrl_c&lt;0~(n-1)&gt;_focusm</boolean></window></window></integer></integer></integer></integer>	zs	0~8 <sd8362></sd8362>	Set the speed of zooming, "0" means stop.
vs       0 ~ 127       Set the speed of movement, "0" means stop.         x <integer>       x-coordinate clicked by user. It will be the x-coordinate of center after movement.         y       <integer>       y-coordinate clicked by user. It will be the y-coordinate of center after movement.         videosize       <window size="">       The size of plug-in (ActiveX) window in web page         resolution       <window size="">       The resolution of streaming.         stretch       <boolean>       0 indicates that it uses <b>resolution</b> (streaming size) as the range of coordinate system. 1 indicates that it uses <b>videosize</b> (plug-in size) as the range of coordinate system.         focus       auto       Auto focus.         far       Focus on further distance. near       Focus on closer distance.         focusseting       sync       Applies the selected focus mode in camctrl_c&lt;0~(n-1)&gt;_focusm</boolean></window></window></integer></integer>	vx	<integer ,="" 0="" excluding=""></integer>	The slope of movement = $vy/vx$ , used for joystick control.
x <integer>       x-coordinate clicked by user. It will be the x-coordinate of center after movement.         y       <integer>       y-coordinate clicked by user. It will be the y-coordinate of center after movement.         videosize       <window size="">       The size of plug-in (ActiveX) window in web page         resolution       <window size="">       The resolution of streaming.         stretch       <boolean>       0 indicates that it uses resolution (streaming size) as the range of coordinate system. 1 indicates that it uses videosize (plug-in size) as the range of coordinate system.         focus       auto       Auto focus. far       Focus on further distance.         focusseting       sync       Applies the selected focus mode in camctrl_c&lt;0~(n-1)&gt;_focusm</boolean></window></window></integer></integer>	vy	<integer></integer>	
It will be the x-coordinate of center after movement.         y <integer>       y-coordinate clicked by user. It will be the y-coordinate of center after movement.         videosize       <window size="">       The size of plug-in (ActiveX) window in web page         resolution       <window size="">       The resolution of streaming.         stretch       <boolean>       0 indicates that it uses resolution (streaming size) as the range the coordinate system. 1 indicates that it uses videosize (plug-in size) as the range of coordinate system.         focus       auto       Auto focus. far       Focus on further distance. near         focusseting       sync       Applies the selected focus mode in camctrl_c&lt;0~(n-1)&gt;_focusm</boolean></window></window></integer>	vs	0 ~ 127	Set the speed of movement, "0" means stop.
y <integer>       y-coordinate clicked by user. It will be the y-coordinate of center after movement.         videosize       <window size="">       The size of plug-in (ActiveX) window in web page         resolution       <window size="">       The resolution of streaming.         stretch       <boolean>       0 indicates that it uses resolution (streaming size) as the range the coordinate system. 1 indicates that it uses videosize (plug-in size) as the range of coordinate system.         focus       auto       Auto focus.         far       Focus on further distance.         focusseting       sync       Applies the selected focus mode in camctrl_c&lt;0~(n-1)&gt;_focusm</boolean></window></window></integer>	x	<integer></integer>	x-coordinate clicked by user.
It will be the y-coordinate of center after movement.videosize <window size="">The size of plug-in (ActiveX) window in web pageresolution<window size="">The resolution of streaming.stretch<boolean>0 indicates that it uses <b>resolution</b> (streaming size) as the range the coordinate system. 1 indicates that it uses <b>videosize</b> (plug-in size) as the range of coordinate system.focusautoAuto focus. FarfocussetingsyncApplies the selected focus mode in camctrl_c&lt;0~(n-1)&gt;_focusm</boolean></window></window>			It will be the x-coordinate of center after movement.
videosize <window size="">       The size of plug-in (ActiveX) window in web page         resolution       <window size="">       The resolution of streaming.         stretch       <boolean>       0 indicates that it uses <b>resolution</b> (streaming size) as the range the coordinate system.         focus       auto       Auto focus.         far       Focus on further distance.         focusseting       sync       Applies the selected focus mode in camctrl_c&lt;0~(n-1)&gt;_focusm</boolean></window></window>	У	<integer></integer>	y-coordinate clicked by user.
resolution <window size="">       The resolution of streaming.         stretch       <boolean>       0 indicates that it uses resolution (streaming size) as the range the coordinate system.         1 indicates that it uses videosize (plug-in size) as the range of coordinate system.         focus       auto         far       Focus on further distance.         focusseting       sync         Applies the selected focus mode in camctrl_c&lt;0~(n-1)&gt;_focusm</boolean></window>			It will be the y-coordinate of center after movement.
stretch <boolean>       0 indicates that it uses resolution (streaming size) as the range the coordinate system.         1 indicates that it uses videosize (plug-in size) as the range of coordinate system.         focus       auto         far       Focus on further distance.         near       Focus on closer distance.         focusseting       sync         Applies the selected focus mode in camctrl_c&lt;0~(n-1)&gt;_focusm</boolean>	videosize	<window size=""></window>	The size of plug-in (ActiveX) window in web page
focus       auto       Auto focus.         far       Focus on further distance.         near       Focus on closer distance.         focusseting       sync	resolution	<window size=""></window>	The resolution of streaming.
the coordinate system. 1 indicates that it uses videosize (plug-in size) as the range of coordinate system.focusautoAuto focus.farFocus on further distance.nearFocus on closer distance.focussetingsyncApplies the selected focus mode in camctrl_c<0~(n-1)>_focusm	stretch	<boolean></boolean>	0 indicates that it uses <b>resolution</b> (streaming size) as the range of
1 indicates that it uses videosize (plug-in size) as the range of coordinate system.focusautoAuto focus.farFocus on further distance.nearFocus on closer distance.focussetingsyncApplies the selected focus mode in camctrl_c<0~(n-1)>_focusm			
focus       auto       Auto focus.         far       Focus on further distance.         near       Focus on closer distance.         focusseting       sync			
focus       auto       Auto focus.         far       Focus on further distance.         near       Focus on closer distance.         focusseting       sync         Applies the selected focus mode in camctrl_c<0~(n-1)>_focusm			
near       Focus on closer distance.         focusseting       sync         Applies the selected focus mode in camctrl_c<0~(n-1)>_focusm	focus	auto	
focusseting sync Applies the selected focus mode in camctrl_c<0~(n-1)>_focus		far	Focus on further distance.
		near	Focus on closer distance.
	focusseting	sync	Applies the selected focus mode in camctrl_c<0~(n-1)>_focusmode to this preset.
fixcurrent Applies the current focus position to this preset.		fixcurrent	Applies the current focus position to this preset.

	* We support this function when the version number of the PTZ control module is equal or greater than 5.0.0.20.	
cam		Adds a named preset at current position, and return the preset index. * We support this function when the version number of the PTZ control module is equal or greater than 5.0.0.20.
return		Redirect to the page <return page=""> after the parameter is assigned. The <return page=""> should be the relative path according to the root of camera. If you omit this parameter, it will redirect to an empty page. * If the <return page=""> is invalid path, it will ignore this parameter.</return></return></return>

### Syntax: (for querying API)

http://<*servername*>/cgi-bin/camctrl/camctrl.cgi?[<parameter>] [&<parameter>...]

Example:

http://myserver/cgi-bin/camctrl/camctrl.cgi?genpan

Response:

HTTP/1.0 200 OK\r\n

Cache-control: no-cache\r\n

Pragma: no-cache\r\n

\r\n

 $pan=4117\r\n$ 

PARAMETER	VALUE	DESCRIPTION
getversion	<string></string>	Get the version of the PTZ control module.
getaction	idle,	Get the current status of the camera.
	autopan,	
	tracking,	st We support this parameter when the version number (getversion) is
	tour,	equal or greater than 5.0.0.12
	patrol,	
getpan	0, <positive integer=""></positive>	Get the current pan position.
		*Only available when bit0 of
		"capability_camctrl_c<0~(n-1)>_buildinpt" is "1"
getpanangle	<integer></integer>	Get the current pan angle.
		*Only available when bit0 of
		"capability_camctrl_c<0~(n-1)>_buildinpt" is "1"
gettilt	0, <positive integer=""></positive>	Get the current tilt position.
		*Only available when bit1 of
		"capability_camctrl_c<0~(n-1)>_buildinpt" is "1"

gettiltangle	<integer></integer>	Get the current tilt angle.
		*Only available when bit1 of
		"capability_camctrl_c<0~(n-1)>_buildinpt" is "1"
getzoom	0, <positive integer=""></positive>	Get the current zoom position.
getratio	<decimal></decimal>	Get the current zoom ratio.
getfocus	0, <positive integer=""></positive>	Get the current focus position.
getminspeedlv	0, <positive integer=""></positive>	Get the minimum speed level of the PTZ control. Normally, the speed
		level is '0,' which denotes halting a continuous movement.
getmaxptspeedlv	0, <positive integer=""></positive>	Get the maximum speed level of pan/tilt moving.
		*Only available when "capability_camctrl_c<0~(n-1)>_buildinpt" > 0
getmaxzspeedlv	0, <positive integer=""></positive>	Get the maximum speed level of zoom moving.
getmaxfspeedlv	0, <positive integer=""></positive>	Get the maximum speed level of focus moving.
getminpan	0, <positive integer=""></positive>	Get the lower limit for pan position.
		*Only available when bit0 of
		"capability_camctrl_c<0~(n-1)>_buildinpt" is "1"
getmaxpan	0, <positive integer=""></positive>	Get the upper limit for pan position.
		*Only available when bit0 of
		"capability_camctrl_c<0~(n-1)>_buildinpt" is "1"
getminpanangle	<integer></integer>	Get the lower limit for pan angle.
		*Only available when bit0 of
		"capability_camctrl_c<0~(n-1)>_buildinpt" is "1"
getmaxpanangle	<integer></integer>	Get the upper limit for pan angle.
		*Only available when bit0 of
		"capability_camctrl_c<0~(n-1)>_buildinpt" is "1"
getmintilt	0, <positive integer=""></positive>	Get the lower limit for tilt position.
		*Only available when bit1 of
		"capability_camctrl_c<0~(n-1)>_buildinpt" is "1"
getmaxtilt	0, <positive integer=""></positive>	Get the upper limit for tilt position.
		*Only available when bit1 of
		"capability_camctrl_c<0~(n-1)>_buildinpt" is "1"
getmintiltangle	<integer></integer>	Get the lower limit for tilt angle.
		*Only available when bit1 of
		"capability_camctrl_c<0~(n-1)>_buildinpt" is "1"
getmaxtiltangle	<integer></integer>	Get the upper limit for tilt angle.
		*Only available when bit1 of
		"capability_camctrl_c<0~(n-1)>_buildinpt" is "1"
getminzoom	0, <positive integer=""></positive>	Get the lower limit for zoom position.
getmaxzoom	0, <positive integer=""></positive>	Get the upper limit for zoom position.
getmaxdzoom	0, <positive integer=""></positive>	Get the upper limit for digital zoom position.

getmaxratio	<decimal></decimal>	Get the maximum ratio of optical zoom.
		st We support this parameter when the version number (getversion) is
		equal or greater than 5.0.0.14
getmaxdratio	<decimal></decimal>	Get the maximum ratio of digital zoom.
		st We support this parameter when the version number (getversion) is
		equal or greater than 5.0.0.14
getminfocus	0, <positive integer=""></positive>	Get the lower limit for focus position.
getmaxfocus	0, <positive integer=""></positive>	Get the upper limit for focus position.

# 8.29 Recall (capability\_camctrl\_c<0~(n-1)>\_zoommodule = 1)

Note: This request requires Viewer privileges.

Method: GET

Syntax:

http://<*servername*>/cgi-bin/viewer/recall.cgi? recall=<value>[&channel=<value>][&return=<*return page*>]

PARAMETER	VALUE	DESCRIPTION
recall	string[30]	One of the present positions to recall.
channel	0~"	Channel of the video source.
	capability_nvideoin"-1	
return	<return page=""></return>	Redirect to the page <return page=""> after the parameter is assigned.</return>
		The <return page=""> should be the relative path according to the root of</return>
		camera. If you omit this parameter, it will redirect to an empty page.
		* If the <return page=""> is invalid path, it will ignore this parameter.</return>

## 8.30 Preset Locations

## (capability\_camctrl\_c<0~(n-1)>\_zoommodule = 1)

Note: This request requires Operator privileges.

Method: GET/POST

Syntax:

http://<servername>/cgi-bin/operator/preset.cgi?[channel=<value>]

[&addpos=<value>][&delpos=<value>][&return=<return page>]

PARAMETER	VALUE	DESCRIPTION
addpos	string[30]	Add one preset location to the preset list.
channel	0~"capability_nvideoin"-1	Channel of the video source.
delpos	string[30]	Delete preset location from preset list.
return	<return page=""></return>	Redirect to the page <return page=""> after the parameter is assigned.</return>
		The <return page=""> should be the relative path according to the root of camera. If you omit this parameter, it will redirect to an empty</return>
		page. * If the <return page=""> is invalid path, it will ignore this parameter.</return>

# 8.31 SmartSD (capability\_localstorage\_smartsd > 0)

**Note:** This request requires Administrator privileges.

#### Method: GET/POST

Syntax:

http://< <i>server</i>	<i>mame</i> >/cgi-bin/adm	in/smartsd.cgi?function= <value></value>
PARAMETER	VALUE	DESCRIPTION
function	getstatus	Function type
		getstauts : Information of smartSD internal status return value as
		below:
		smartsd_lifetime_num:
		Accumulated amount of data that has been written
		smartsd_lifetime_den:
		Card-guaranteed amount of data that can be written
		smartsd_lifetime_rate:
		The ratio of smartsd_lifetime_num to smartsd_lifetime_den.
		It means the accumulated percentage amount of flash block has been
		written. The range is from 0 to 100 (unit: %). The SD card is
		recommended to be replaced if the percentage reaches above 90%.
		smartsd_spare_block_rate:
		Usage rate of spare blocks.
		It means the usage percentage of total spare block. The range is from
		0 to 100 (unit: %). The SD card is recommended to be replaced if the
		percentage reaches above 90%.
		smartsd_data_size_per_unit:
		Size (in sectors) of data to be written when Life Information1 is
		updated.
		smartsd_num_of_sudden_power_failure:
		Indicates how many times power disconnection occurred during
		write/erase operations
		smartsd_operation_mode:
		Enables/disables power-off detection and write error notification
		smartsd_attached:
		Indicate the smartSD is attached or not.

# 8.32 Connect to AP (capability\_network\_wireless > 0)

**Note:** This request requires Administrator privileges. **Method:** GET/POST

Syntax:

http://<*servername*>/cgi-bin/admin/connect\_ap.cgi

PARAMETER	VALUE	DESCRIPTION
N/A	N/A	Apply the wireless settings and connect to AP.

## 8.33 Get wireless information (capability\_network\_wireless > 0)

Note: This request requires Administrator privileges.

Method: GET/POST

Syntax:

http://<servername>/cgi-bin/admin/getwirelessinfo.cgi

PARAMETER	VALUE	DESCRIPTION
N/A	N/A	Get wireless information. Camera will return following information.
		1. Wireless channel
		2. Link quality
		3. Signal level
		4. Noise level
		5. SNR
		6. TX Rate
		7. RX Rate

## 8.34 Get wireless signal strength (capability\_network\_wireless >

### 0)

**Note:** This request requires Administrator privileges. **Method:** GET/POST

Syntax:

http://<servername>/cgi-bin/admin/getwlsignalstrength.cgi

PARAMETER	VALUE	DESCRIPTION
N/A	N/A	Get wireless signal strength.

## 8.35 WPS transaction (capability\_network\_wireless > 0)

Note: This request requires Administrator privileges.

Method: GET/POST

Syntax:

http://<*servername*>/cgi-bin/admin/start\_wps.cgi

PARAMETER	VALUE	DESCRIPTION
N/A	N/A	Start WPS transaction.

# 8.36 Peripheral control (capability\_peripheral\_c<0~(n-1)>\_

## devicecontrol > 0)

**Note:** This request requires Administrator privileges. **Method:** GET/POST

Syntax: (for control API)

http://<servername>/cgi-bin/admin/peripheral.cgi?channel=<value>&operation=set [&washer\_mode=<value>] - Set washer mode [&washer\_status=<value>] - Set washer status [&washer\_dwelltime=<value>] - Set washer clean time [&heater\_status=<value>] - Set heater status

Example:

Response: HTTP/1.0 200 OK\r\n Cache-control: no-cache\r\n Pragma: no-cache\r\n \r\n "washer\_mode : OK\r\n" "washer\_status : FAIL\r\n"

PARAMETER	VALUE	DESCRIPTION
channel	0~"capability_nvideoin"-1	Channel of the video source.
washer_mode	wiper	Apply the wiper to the mode of washer control
		system.
		*Only available when
		capability_peripheral_c<0~(n-1)>_washer_supp
		ort=1
	washer	Apply the washer to the mode of washer control
		system.
		*Only available when
		capability_peripheral_c<0~(n-1)>_washer_supp
		ort=1
washer_status	on	Enable the functionality of washer control system.

		*Only available when
		capability_peripheral_c<0~(n-1)>_washer_supp
		ort=1
	off	Disable the functionality of washer control
		system.
		*Only available when
		capability_peripheral_c<0~(n-1)>_washer_supp
		ort=1
washer_dwelltime	15~999	Apply washer washer control system operation
		time (including the time when spraying and wiper
		actions take place).
		*Only available when
		capability_peripheral_c<0~(n-1)>_washer_supp
		ort=1
heater_status	auto	automatic control the heater component to keep
		the device in a workable environment.
		*Only available when
		capability_peripheral_c<0~(n-1)>_heater_suppo
		rt=1
	trigger	heater component is work in force heater once.
		*Only available when
		capability_peripheral_c<0~(n-1)>_heater_suppo
		rt=1

### Syntax: (for querying API)

http://<servername>/cgi-bin/admin/peripheral.cgi?channel=<value>&operation=get [&supportdevice] -Get support peripheral device [&washer\_supportmode] - Get washer support modes [&washer\_mode] - Get washer mode [&washer\_status] - Get washer status [&washer\_dwelltime] - Get washer clean time [&heater\_supportstatus] - Get heater support control status

[&heater\_status] – Get heater status

#### Example:

http://myserver/cgi-bin/admin/peripheral.cgi?channel=0&operation=get&supportdevice&washer\_status

Response: HTTP/1.0 200 OK\r\n Cache-control: no-cache\r\n

### Pragma: no-cache\r\n

\r\n
supportdevice=washer,heater\r\n
washer\_status=off\r\n

PARAMETER DESCRIPTION VALUE channel 0~"capability\_nvideoin"-1 Channel of the video source. supportdevice N/A Get support peripheral device. N/A washer\_supportmode Get the support mode of washer control system, its value is the same with "capability\_peripheral\_ c<0~(n-1)> washer mode". \*Only available when capability\_peripheral\_c<0~(n-1)>\_washer\_supp ort=1 N/A washer\_mode Get the current mode of washer control system. It return the value of "washer mode" \* Available values are listed in "capability\_peripheral\_c<0~(n-1)>\_washer\_mod e" N/A Get the current status of washer control module. washer\_status The status is 'off' as default, which means the washer is stopped; and the status 'on' means the washer is running. \*Only available when capability\_peripheral\_c<0~(n-1)>\_washer\_supp ort=1 N/A Get the current washer clean period of washer washer\_dwelltime control system. \*Only available when capability\_peripheral\_c<0~(n-1)>\_washer\_supp ort=1N/A Get the support status of heater control system. heater\_supportstatus \*Only available when capability\_peripheral\_c<0~(n-1)>\_heater\_suppo rt=1 heater\_status N/A Get the current heater status. Normally it will be 'auto', it means the heater device is control by internal algorithm to keep in a suitable environment; Otherwise is 'trigger', it means the heater device is force enable to heat to

	an internal condition.'trigger' status will be
	transfer to `auto' after reach the internal condition.
	*Only available when
	capability_peripheral_c<0~(n-1)>_heater_suppo
	rt=1

## 8.37 Optimized IR control

# (capability\_daynight\_c<0~(n-1)>\_optimizedir > 0)

Note: This request requires Administrator privileges.

Method: GET/POST

Syntax:

http://<servername>/cgi-bin/admin/optimizedir.cgi?function=<value>[&channel=<value>]

PARAMETER	VALUE	DESCRIPTION
channel	0~"capability_nvideoin"-1	Channel of the video source.
function	getstatus,	"onetimeauto": Camera will automatically adjust the IR zone one
	onetimeauto	time only.
		"getstatus": Information of optimized IR control status and return
		value as below:
		optimizedir_c<0~(n-1)>_irmode:
		Indicate the IR current mode, available value is "auto" and "manual"
		mode.
		optimizedir_c<0~(n-1)>_irnum:
		The number of IR that camera supports.
		optimizedir_c<0~(n-1)>_irstrength:
		Only available when irmode is set as manual. It's a set of integers,
		which indicate the strength of each IR LED (e.g. 23,45,100,100).
		optimizedir_c<0~(n-1)>_irstatus:
		Current IR status, normal / adjusting:
		"normal": the IR LED strength has been fixed.
		"adjusting": the IR LED strength is adjusting.

Example:

http://myserver/cgi-bin/admin/optimizedir.cgi?function=getstatus

Response: HTTP/1.0 200 OK\r\n Cache-control: no-cache\r\n Pragma: no-cache\r\n \r\n "optimizedir\_c0\_irmode='auto'" "optimizedir\_c0\_irstrength='1,97,100,100,100'" "optimizedir\_c0\_irstatus='normal'"

### Syntax: (for control API)

http://<servername>/cgi-bin/admin/optimizedir.cgi?channel=<value>&operation=<value>&irmode=manual [&strength=<value>] - Set IR strength

PARAMETER	VALUE	DESCRIPTION
channel	0~"capability_nvideoin"-1	Channel of the video source.
operation	set,	"set": set the strength of each IR LED separately
	settoall	"settoall": use fixed strength for all IR LED
irmode	manual	Irmode needs to be set as manual for adjusting IR LED
		strength.
strength	1~100	If the operation is set as "set", the number of strength
		values need to be the same as it of irnum. However, it
		needs only one value for strength when the operation is
		set as "settoall".

#### Example:

http://myserver/cgi-bin/admin/optimizedir.cgi?channel=0&operation=set&irmode=manual& strength=50,70,50,50,50\_

Response: HTTP/1.0 200 OK\r\n Cache-control: no-cache\r\n Pragma: no-cache\r\n \r\n "optimizedir\_c0\_irstrength='50,70,50,50,50'"

### "optimizedir\_c0\_irmode='manual'"

Example:

http://myserver/cgi-bin/admin/optimizedir.cgi?channel=0&operation=settoall&irmode=manual&strength=100\_\_\_\_

Response: HTTP/1.0 200 OK\r\n Cache-control: no-cache\r\n Pragma: no-cache\r\n \r\n "optimizedir\_c0\_irstrength='100,100,100,100,100'" "optimizedir\_c0\_irmode='manual'"

Example:

http://myserver/cgi-bin/admin/optimizedir.cgi?channel=0&operation=set&irmode=auto&strength=50,70,50,50, 50\_

Response: HTTP/1.0 200 OK\r\n Cache-control: no-cache\r\n Pragma: no-cache\r\n \r\n ERROR: Parameter "irmode" must be set as "manual"!

Example:

http://myserver/cgi-bin/admin/optimizedir.cgi?channel=0&operation=set&strength=50,70,50,50,50

Response: HTTP/1.0 200 OK\r\n Cache-control: no-cache\r\n Pragma: no-cache\r\n \r\n ERROR: Must have the "irmode=manual" argument!

#### Syntax: (for querying API)

http://<servername>/cgi-bin/admin/optimizedir.cgi?channel=<value>&operation=get [&support\_irmode] - list all adjustment mode that IR supports [&irmode] - Get current IR mode [&irnum] - Get the number of IR zone

PARAMETER	VALUE	DESCRIPTION
channel	0~"capability_nvideoin"-1	Channel of the video source.
support_irmode	N/A	List all adjustment mode that IR supports
irmode	N/A	Get the current IR control mode.
irnum	N/A	Get the number of IR that camera supports.

#### Example:

http://myserver/cgi-bin/admin/optimizedir.cgi?channel=0&operation=get&irmode

Response: HTTP/1.0 200 OK\r\n Cache-control: no-cache\r\n Pragma: no-cache\r\n \r\n "optimizedir\_c0\_irmode='auto'"

<End of document>

### Technical Specifications

Model	FE9191: 12MP 360° Panomorph Camera FE9391-EV: 12MP 360° Panomorph Camera, 360° 20M IR, IP66, IK10, EN50155		
System Information			
CPU	Multimedia SoC (System-on-Chip)		
Flash 256MB			
RAM	1GB		
Camera Features			
Image Sensor	1/1.7" Progressive CMOS in 4000x3000		
Maximum Resolution	2816x2816		
Lens Type	Fixed-focal		
Focal Length	f = 1.29 mm		
Aperture	F2.2		
Field of View	180° (horizontal) 180° (vertical) 180° (diagonal)		
Shutter Time	1/5 sec. to 1/16,000 sec.		
WDR Technology	WDR Pro		
Day/Night	Removable IR-cut filter for day & night function		
Minimum Illumination	0.18 Lux @ F2.2 (Color) <0.001 Lux @ F2.2 (B/W)		
Pan/Tilt/Zoom Functionalities	ePTZ: 12x digital zoom (12x on IE plug-in)		
IR Illuminators	FE9391-EV: Built-in IR illuminators, effective up to 20 meters with Smart IR II		
On-board Storage	Slot type: MicroSD/SDHC/SDXC card slot Seamless Recording		
Video			
Compression	H.265, H.264, MJPEG		
Maximum Frame Rate	30 fps @ 2816x2816		
Maximum Streams	4 Simultaneous Streams		
S/N Ratio	42.9 dB		
Dynamic Range	120 dB		
Video Streaming	Adjustable resolution, quality and bitrate, configurable video cropping for bandwidth saving, Smart Stream III		
Image Settings	Adjustable image size, quality and bit rate, time stamp, text overlay, flip & mirror, scheduled profile settings, configurable brightness/contrast/saturation/sharpness, pixel calculator, 3D-Noise reduction, white balance, exposure control, gain, backlight compensation, privacy masks, defog		
Audio			
Audio Capability	Two-way audio (full duplex)		
Compression	G.711, G.726		
279 110010 100			

Interface	Built-in microphone External microphone input External line output		
Effective Range	5 meters		
Network			
Users	Live viewing for up to 10 clients		
Protocols	IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/ RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPP0E, CoS, QoS, SNMP, 802.1X ,SSL/ TLS, ARP, CIFS/SMB		
Interface	10 Base-T/100 Base-TX/1000 Base-T Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard.		
ONVIF	Supported, specification available at www. onvif.org		
Intelligent Video			
Smart Motion Detection	Five-window video motion detection, people detection, time filter		
Smart 360 VCA	Intrusion detection, crowd detection, loitering detection		
VADP Package	Genetec Package, Trend Micro IoT Security, Smart Motion Detection, Amazon Kinesis Video Streams		
Alarm and Event			
Alarm Triggers	Motion detection, manual trigger, digital input, periodical trigger, system boot, recording notification, camera tampering detection, audio detection, MicroSD card life expectancy, cybersecurity events (block brute force attack, block cyber attack, quarantine event)		
Alarm Events	Event notification using digital output, HTTP, SMTP, FTP, NAS server and MicroSD card File upload via HTTP, SMTP, FTP, NAS server and MicroSD card		
General			
Connectors	RJ-45 cable connector for 10/100/1000Mpbs Network/PoE connection Audio input *1 Audio output *1 DC 12V Power input Digital input *1 Digital ouput *1		
LED Indicator	System power and status indicator		
Power Input	FE9191: DC12V, PoE 802.3af Class 2 FE9391-EV: DC12V, PoE 802.3at Class 4		
Power Consumption	FE9191: Max. 6.49 W FE9391-EV: Max. 25 W		
Dimensions	FE9191: Ø 139 x 37 mm FE9391-EV: Ø 160 x 62 mm		
Weight	FE9191: 345 g FE9391-EV: 846 g		
Casing	FE9391-EV: IP66, IK10		
Safety Certifications	FE9191: CE, LVD, VCCI, C-Tick, UL, FCC Class B FE9391-EV: CE, LVD, VCCI, C-Tick, UL, FCC Class A, EN50155		

378 - User's Manual

### **Technical Specifications**

	FE9191: Starting Temperature: 0°C ~ 50°C (32°F ~ 122°F)	Dimensions		
Operating Temperature	Working Temperature: -10°C ~ 50°C (14°F ~ 122°F) FE9391-EV: Starting Temperature: -25°C ~ 50°C (-13°F ~ 122°F) Working Temperature: -40°C ~ 50°C (-40°F ~ 122°F)	• FE9191	• FE	9391-EV
Humidity	90%	Ø139 m	nmI	Ø160 mm
Warranty	36 months		$ \longrightarrow $	
System Requirements			))	
Operating System	Microsoft Windows 8/7	ŀ		
Web Browser	Internet Explorer 10/11		-	
Other Players	VLC: 1.1.11 or above QuickTime: 7 or above			62 mm
Included Accessories				L
Others	Quick installation guide, warranty card, alignment sticker, desiccant bag, screw driver, screws pack, mounting bracket, I/ O cable (Cable not included in North America)			

### **Compatible Accessories**





All specifications are subject to change without notice. Copyright © VIVOTEK INC. All rights reserved. Ver. 18

### **Technology License Notice**



### Notices from HEVC Advance:

THIS PRODUCT IS SOLD WITH A LIMITED LICENSE AND IS AUTHORIZED TO BE USED ONLY IN CONNECTION WITH HEVC CONTENT THAT MEETS EACH OF THE THREE FOLLOWING QUALIFICATIONS: (1) HEVC CONTENT ONLY FOR PERSONAL USE; (2) HEVC CONTENT THAT IS NOT OFFERED FOR SALE; AND (3) HEVC CONTENT THAT IS CREATED BY THE OWNER OF THE PRODUCT. THIS PRODUCT MAY NOT BE USED IN CONNECTION WITH HEVC ENCODED CONTENT CREATED BY A THIRD PARTY, WHICH THE USER HAS ORDERED OR PURCHASED FROM A THIRD PARTY, UNLESS THE USER IS SEPARATELY GRANTED RIGHTS TO USE THE PRODUCT WITH SUCH CONTENT BY A LICENSED SELLER OF THE CONTENT. YOUR USE OF THIS PRODUCT IN CONNECTION WITH HEVC ENCODED CONTENT IS DEEMED ACCEPTANCE OF THE LIMITED AUTHORITY TO USE AS NOTED ABOVE.

### H.264

THIS PRODUCT IS LICENSED UNDER THE AVC PATENT PORTFOLIO LICENSE FOR THE PERSONAL AND NON-COMMERCIAL USE OF A CONSUMER TO (i) ENCODE VIDEO IN COMPLIANCE WITH THE AVC STANDARD ("AVC VIDEO") AND/OR (ii) DECODE AVC VIDEO THAT WAS ENCODED BY A CONSUMER ENGAGED IN A PERSONAL AND NON-COMMERCIAL ACTIVITY AND/OR WAS OBTAINED FROM A VIDEO PROVIDER LICENSED TO PROVIDE AVC VIDEO. NO LICENSE IS GRANTED OR SHALL BE IMPLIED FOR ANY OTHER USE. ADDITIONAL INFORMATION MAY BE OBTAINED FROM MPEG LA, L.L.C. SEE HTTP://WWW.MPEGLA.COM

### **AMR-NB Standard**

THIS PRODUCT IS LICENSED UNDER THE AMR-NB STANDARD PATENT LICENSE AGREEMENT. WITH RESPECT TO THE USE OF THIS PRODUCT, THE FOLLOWING LICENSORS' PATENTS MAY APPLY:

TELEFONAKIEBOLAGET ERICSSON AB: US PAT. 6192335; 6275798; 6029125; 6424938; 6058359. NOKIA CORPORATION: US PAT. 5946651; 6199035. VOICEAGE CORPORATION: AT PAT. 0516621; BE PAT. 0516621; CA PAT. 2010830; CH PAT. 0516621; DE PAT. 0516621; DK PAT. 0516621; ES PAT. 0516621; FR PAT. 0516621; GB PAT. 0516621; GR PAT. 0516621; IT PAT. 0516621; LI PAT. 0516621; LU PAT. 0516621; NL PAT. 0516621; SE PAT 0516621; US PAT 5444816; AT PAT. 819303/AT E 198805T1; AU PAT. 697256; BE PAT. 819303; BR PAT. 9604838-7; CA PAT. 2216315; CH PAT. 819303; CN PAT. ZL96193827.7; DE PAT. 819303/DE69611607T2; DK PAT. 819303; ES PAT. 819303; EP PAT. 819303; FR PAT. 819303; GB PAT. 819303; IT PAT. 819303; JP PAT. APP. 8-529817; NL PAT. 819303; SE PAT. 819303; US PAT. 5664053. THE LIST MAY BE UPDATED FROM TIME TO TIME BY LICENSORS AND A CURRENT VERSION OF WHICH IS AVAILABLE ON LICENSOR'S WEBSITE AT HTTP://WWW.VOICEAGE.COM.

### Support

Should you require any technical assistance, please contact your VIVOTEK reseller/distributor. VIVOTEK distributor contact information could be found on Where to Buy section at VIVOTEK website. To enhance customer satisfaction, your reseller/ distributor will reach us in a timely manner if the issue is not solved with first response.

We encourage you to take advantage of the many online resources VIVOTEK offers.

- VIVOTEK Downloads: With useful materials, such as brochure, firmware/software update.
- VIVOTEK Support: Including Top FAQ, Technical Videos, and Security Hardening Guide with efficient on-line assistance.
- VIVOTEK Customer Community: To obtain assistance from VIVOTEK technical support team, you can register and discuss problems in our on-line customer community and engage more with VIVOTEK's solutions, and service.

### Learning Center

Visit VIVOTEK Learning Center for advanced feature articles and white papers and enjoy VIVOTEK Warrior Academy global training program.

### **Contact Information**

VIVOTEK INC. 6F, No. 192, Lien-Cheng Rd., Chung-Ho Dist., New Taipei City, Taiwan. R.O.C. 23353 Tel: +886-2-8245-5282 Fax: +886-2-8245-5532 http://www.vivotek.com/ Email: technical@vivotek.com

### **Electromagnetic Compatibility (EMC)**

### **FCC Statement**

This device compiles with FCC Rules Part 15. Operation is subject to the following two conditions.

- This device may not cause harmful interference, and
- This device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the installation manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference, in which case the user will be required to correct the interference at his own expense.

### **CE Mark Warning**

This is a Class A product. In a domestic environment, this product may cause radio interference, in which case the user may be required to take adequate measures.

### **VCCI Warning**

この装置は、情報処理装置等電波障害自主規制協議会(VCCI)の基準にづくクラスB情報技術装置です。この 装置は、家庭環境で使用することを目的としていますが、この装置がラジオやテレビジョン受信機に近接して使 用されると、受信障害を引き起こすことがあります。

取扱説明書に従って正しい取り扱いをして下さい

### Liability

VIVOTEK Inc. cannot be held responsible for any technical or typographical errors and reserves the right to make changes to the product and manuals without prior notice. VIVOTEK Inc. makes no warranty of any kind with regard to the material contained within this document, including, but not limited to, the implied warranties of merchantability and fitness for any particular purpose.